

Queensland



Subordinate Legislation 1998 No. 21

Transport Operations (Marine Safety) Act 1994

TRANSPORT OPERATIONS (MARINE SAFETY—DESIGNING AND BUILDING COMMERCIAL AND FISHING SHIPS) STANDARD 1998

TABLE OF PROVISIONS

Section		Page
PART 1—PRELIMINARY		
1	Short title	4
2	Commencement	4
3	Definitions	4
4	Purposes of standard	5
5	How to understand this standard	5
PART 2—PERFORMANCE BASED APPROACH		
<i>Division 1—Designing ships</i>		
6	Stress	6
7	Verifying design	6
8	Components	7
9	Structure	7
10	Designing vision and access components	7
11	Designing for passenger comfort and protection	7
12	Designing for protection from fire	7
13	Designing propulsion machinery	8

14	Designing steering system	8
15	Designing machinery etc. to minimise fire risk	9
16	Designing bilge pumping system	9
17	Buoyancy and stability	9
18	Subdivision	9

Division 2—Building ships

19	Ship building facilities	10
20	Ship to be built as specified in design and specifications	10
21	Building vision and access components	10
22	Building for passenger comfort and protection	10
23	Other entry of water	10
24	Building to give protection from fire	10
25	Building propulsion machinery	11
26	Building steering system	11
27	Shielding hazardous machinery	12
28	Building machinery etc. to minimise fire risk	12
29	Building bilge pumping system	12
30	Identifying components of associated machinery	12

PART 3—PRESCRIPTIVE BASED APPROACH

Division 1—Designing ships

31	Designer should comply with Code or rule	12
----	--	----

Division 2—Building ships

32	Builder should comply with Code or rule	13
----	---	----

**PART 4—COMMON REQUIREMENTS FOR BOTH
APPROACHES FOR SHIP BUILDING**

33	Electrical work	13
34	Employees	14
35	Premises for building fibre reinforced plastic ships	14
36	Hull identification number (HIN)	14

PART 5—EXPIRY

37 Expiry 14

PART 1—PRELIMINARY

Short title

1. This standard may be cited as the *Transport Operations (Marine Safety—Designing and Building Commercial and Fishing Ships) Standard 1998*.

Commencement

2. This standard commences on 1 March 1998.

Definitions

3. In this standard—

“AC”, for electrical work, means alternating current.

“classification society” see schedule 11 of the regulation.

“Code” see schedule 11 of the regulation.¹

“commercial ship” see schedule 11 of the regulation.

“electrical work” see the *Electricity Act 1994*, section 16(1) to (3).²

“fishing ship” see schedule 11 of the regulation.

“HIN” means a hull identification number.

“licensed electrical contractor” means a person licensed as an electrical contractor under the *Electricity Act 1994*.

“part of a ship” means a section of the hull, bulkhead, deck, superstructure or machinery (including propulsion, associated systems and electrical) of a ship.

¹ The Code is the Uniform Shipping Laws Code adopted by Commonwealth, State and Territory Ministers.

² *Electricity Act 1994*, section 16 (Electrical work and electrical installation work)

“**regulation**” means the *Transport Operations (Marine Safety) Regulation 1995*.

“**rule**” includes a non-statutory code, regulation or standard issued by a classification society or other society or authority that specifies rules for specialised ships, for example, a hovercraft.

“**ship**” means a commercial or fishing ship, or part of a commercial or fishing ship.

“**ship builder**” means a person who builds a ship or part of a ship.

“**ship designer**” means a person who designs a ship or part of a ship.

Purposes of standard

4. The purposes of this standard are to—
- (a) set standards for designing and building ships; and
 - (b) help people to understand the general safety obligations imposed on them under part 4, division 1³ of the Act.

How to understand this standard

5.(1) This standard provides 2 approaches for designing and building ships.

- (2) The approaches are—
- (a) a performance based approach allowing for innovation in the way ships are designed and built; and
 - (b) a prescriptive based approach following the requirements of the Code, or a rule, about the way ships are designed and built.

³ Part 4 (General safety obligations and standards), division 1 (General safety obligations) of the Act

PART 2—PERFORMANCE BASED APPROACH

Division 1—Designing ships

Stress

6.(1) A ship designer should design a ship so that the calculated stress in any machinery component or member of the ship should not be greater than the maximum permissible stress derived from the minimum guaranteed mechanical properties of the material used in the component or member.

(2) The design should include an adequate safety factor for the ship.

Verifying design

7.(1) A ship designer should verify the sufficiency of the design of a ship including the specifications, details and calculations for the design.

(2) The material specifications and design details should—

(a) contain enough information and detail to allow a comparison to other design standards; and

(b) state the design is adequate for the intended service.

(3) The design calculations should take into account all foreseeable static and dynamic forces the ship may meet that may be induced by the sea, weather, motion and any stowed or wheeled cargo in the intended service.

(4) If design calculations are not provided, appropriate sections of the ship should be tested and analysed to determine the adequacy of the structural design and suitability for the intended service.

(5) If design calculations or test section results are not provided, full scale actual trials should be completed in all anticipated weather conditions to determine actual loadings to indicate the adequacy of the structural design and suitability for the intended service.

(6) The structural sufficiency of a ship may also be demonstrated by documented comparison with a similar ship of similar size, power and

displacement that has proven structural adequacy in commercial or fishing operations for 5 years.

Components

8. A ship designer should design all components contributing to the ship's structural strength to resist deformation from possible water pressure generated by the static and dynamic forces of the sea in all anticipated weather conditions.

Structure

9. A ship designer should design the ship's structure to—

- (a) resist deformation by impulse forces generated by engines and propellers; and
- (b) withstand structural failure under anticipated operational impact forces.

Designing vision and access components

10. A ship designer should design all vision and access components fitted to the ship to be of adequate strength to stop water entering the ship through the components in all anticipated weather conditions in the intended operating area.

Designing for passenger comfort and protection

11. A ship designer should design a ship's structure and accommodation to give reasonable comfort and protection from injury to everyone on the ship in all anticipated weather conditions in the intended operating area.

Designing for protection from fire

12.(1) A ship designer should design a ship to give protection from fire hazards.

- (2) The ship designer should have regard to the following—
- (a) the availability of the ship's main functions and safety systems including propulsion and control, fire detection, alarms and extinguishing capability through unaffected spaces in case of fire in any 1 compartment on board;
 - (b) the division of passenger accommodation areas in such a way that the occupants of a compartment can escape to an alternative safe area or compartment in case of fire;
 - (c) the subdivision of the ship by fire-resistant boundaries;
 - (d) the restricted use of combustible materials and materials generating smoke and toxic gases in a fire;
 - (e) the continuous detection of fire and its containment and extinguishment in the space of origin;
 - (f) the protection of the means of escape and access for fire fighting, and the immediate availability of fire extinguishing appliances.

Designing propulsion machinery

13. A ship designer should design a ship's propulsion machinery, components and associated systems to be—

- (a) adequate for the intended purpose; and
- (b) of robust design to operate reliably in all anticipated weather conditions in the intended operating area.

Designing steering system

14. A ship designer should design a ship's steering system to—

- (a) steer the ship in all sea and anticipated weather conditions; and
- (b) include another way of steering the ship if the main steering system fails.

Designing machinery etc. to minimise fire risk

15. A ship designer should design a ship's machinery and associated systems to minimise the risk of fire from a malfunction in the machinery or system in any anticipated operating condition.

Designing bilge pumping system

16.(1) A ship designer should design a ship to include a bilge pumping system capable of removing an accumulation of water in the ship affecting its safe operation.

(2) The system should enable stability to be achieved or maintained under reasonable conditions of list and trim.

Buoyancy and stability

17.(1) A ship designer should design a ship so the ship's form and structure gives an adequate reserve of intact buoyancy and stability in all anticipated loading conditions to prevent the ship from capsizing in all anticipated weather conditions in the intended operating area.

(2) If the ship is a class 1 commercial ship, the form and structure of the ship should give an adequate reserve of intact buoyancy and stability in all anticipated loading conditions necessary to maintain the safety of passengers and crew in all anticipated weather conditions in the intended operating area.

Subdivision

18. A ship designer should design a class 1 commercial ship so the ship's form and structure gives an adequate reserve of damaged stability in all anticipated conditions if any 1 compartment of the ship is open to the sea.

Division 2—Building ships

Ship building facilities

19. A ship builder should build ships with equipment, and in premises, appropriate for the ship being built to best industry practice.

Ship to be built as specified in design and specifications

20.(1) A ship builder should build a ship in accordance with the design and specifications for the ship.

(2) If there are no specifications for a ship, the ship builder should build the ship using good quality materials and best industry practice.

Building vision and access components

21. A ship builder should build all vision and access components fitted to the ship to be of adequate strength to stop water entering the ship through the components in all anticipated weather conditions in the intended operating area.

Building for passenger comfort and protection

22. A ship builder should build a ship's structure and accommodation to give reasonable comfort and protection from injury to everyone on the ship in all anticipated weather conditions in the intended operating area.

Other entry of water

23. A ship builder should build a ship to stop water entering the hull in all anticipated weather conditions in the intended operating area.

Building to give protection from fire

24.(1) A ship builder should build a ship's structure to give protection from fire hazards.

(2) The ship builder should have regard to the following—

- (a) the availability of the ship's main functions and safety systems including propulsion and control, fire detection, alarms and extinguishing capability through unaffected spaces in case of fire in any 1 compartment on board;
- (b) the division of passenger accommodation areas in such a way that the occupants of a compartment can escape to an alternative safe area or compartment in case of fire;
- (c) the subdivision of the ship by fire-resistant boundaries;
- (d) the restricted use of combustible materials and materials generating smoke and toxic gases in a fire;
- (e) the continuous detection of fire and its containment and extinguishment in the space of origin;
- (f) the protection of the means of escape and access for fire fighting, and the immediate availability of fire extinguishing appliances.

Building propulsion machinery

25. A ship builder should build a ship's propulsion machinery, components and associated systems to be—

- (a) adequate for the intended purpose; and
- (b) of robust design to operate reliably in all conditions in the intended operating area.

Building steering system

26. A ship builder should build a ship's steering system to—

- (a) steer the ship in all sea and weather conditions; and
- (b) include another way of steering the ship if the main steering system fails.

Shielding hazardous machinery

27. A ship builder should shield hazardous machinery on a ship to prevent the risk of injury.

Building machinery etc. to minimise fire risk

28. A ship builder should build a ship's machinery and associated systems to minimise the risk of fire from a malfunction in the machinery or system in any operating condition.

Building bilge pumping system

29.(1) A ship builder should build a ship to include a bilge pumping system capable of removing an accumulation of water in the ship affecting its safe operation.

(2) The system should enable stability to be achieved or maintained under reasonable conditions of list and trim.

Identifying components of associated machinery

30. A ship builder should provide an efficient and effective way to quickly identify and locate each component of the associated machinery system in normal and emergency operations.

PART 3—PRESCRIPTIVE BASED APPROACH

Division 1—Designing ships

Designer should comply with Code or rule

31.(1) A ship designer should design a ship to comply with—

- (a) the Code; or

- (b) a rule; or
- (c) a combination of them.

(2) However, a part of a ship should not be designed to comply with a combination of—

- (a) the Code and a rule; or
- (b) the rules.

Division 2—Building ships

Builder should comply with Code or rule

32.(1) A ship builder should build a ship to comply with—

- (a) the Code; or
- (b) a rule; or
- (c) a combination of them.

(2) However, a part of a ship should not be built to comply with a combination of—

- (a) the Code and a rule; or
- (b) the rules.

PART 4—COMMON REQUIREMENTS FOR BOTH APPROACHES FOR SHIP BUILDING

Electrical work

33.(1) A ship builder should ensure AC electrical work on a ship is done by a licensed electrical contractor.

(2) Subsection (1) does not apply to AC electrical work that is repair work if—

- (a) the repairs are done by the ship's chief engineer; and
- (b) the ship's chief engineer holds an engineer class 1 certificate of competency; and
- (c) the repairs are recorded in the ship's log.

Employees

34.(1) A ship builder should ensure the builder's employees are appropriately qualified and sufficiently trained for their ship building work.

(2) Without limiting subsection (1), welders working on aluminium ships should have the qualifications stated in AS 1665.

Premises for building fibre reinforced plastic ships

35. A ship builder who builds fibre reinforced plastic ships should ensure the premises where the ships are built conform with AS 4132.3.

Hull identification number (HIN)

36. A ship builder should provide a HIN as a means of identifying a ship.

PART 5—EXPIRY

Expiry

37. This standard expires 7 years after its commencement.

ENDNOTES

1. Made by the chief executive on 29 January 1998.
2. Approved by the Governor in Council on 26 February 1998.
3. Notified in the gazette on 27 February 1998.
4. Laid before the Legislative Assembly on . . .
5. The administering agency is the Department of Transport.