



Queensland

Workplace Health and Safety Act 1995

Workplace Health and Safety Regulation 1997

Reprinted as in force on 1 July 2008

Reprint No. 7E revised edition

This reprint is prepared by
the Office of the Queensland Parliamentary Counsel
Warning—This reprint is not an authorised copy

NOT FURTHER AMENDED
LAST REPRINT BEFORE REPEAL
See 2008 SL No. 283 s 358

Information about this reprint

This regulation is reprinted as at 1 July 2008. The reprint—

- shows the law as amended by all amendments that commenced on or before that day (Reprints Act 1992 s 5(c))
- incorporates all necessary consequential amendments, whether of punctuation, numbering or another kind (Reprints Act 1992 s 5(d)).

The reprint includes a reference to the law by which each amendment was made—see list of legislation and list of annotations in endnotes. Also see list of legislation for any uncommenced amendments.

This page is specific to this reprint. See previous reprints for information about earlier changes made under the Reprints Act 1992. A table of reprints is included in the endnotes.

Also see endnotes for information about—

- **when provisions commenced**
- **editorial changes made in earlier reprints.**

Spelling

The spelling of certain words or phrases may be inconsistent in this reprint or with other reprints because of changes made in various editions of the Macquarie Dictionary (for example, in the dictionary, ‘judgement’ has replaced ‘judgment’). Variations of spelling will be updated in the next authorised reprint.

Dates shown on reprints

Reprints dated at last amendment All reprints produced on or after 1 July 2002, authorised (that is, hard copy) and unauthorised (that is, electronic), are dated as at the last date of amendment. Previously reprints were dated as at the date of publication. If an authorised reprint is dated earlier than an unauthorised version published before 1 July 2002, it means the legislation was not further amended and the reprint date is the commencement of the last amendment.

If the date of an authorised reprint is the same as the date shown for an unauthorised version previously published, it merely means that the unauthorised version was published before the authorised version. Also, any revised edition of the previously published unauthorised version will have the same date as that version.

Replacement reprint date If the date of an authorised reprint is the same as the date shown on another authorised reprint it means that one is the replacement of the other.

Revised edition indicates further material has affected existing material. For example—

- a correction
- a retrospective provision
- other relevant information.



Queensland

Workplace Health and Safety Regulation 1997

Contents

		Page
Part 1	Preliminary	
1	Short title	23
2	Commencement	23
3	Definitions—the dictionary	23
3A	References to standards	23
3B	References to the doing of work by employer	23
3BA	References to the doing of work by person who conducts a business or undertaking	24
3C	Notes in text	24
4	Fees	24
Part 2	Registrable plant and registrable plant design	
Division 2	Registration of registrable plant	
10	Registrable plant not to be used before registration	24
11	Registration of registrable plant	25
12	Notification of change of ownership of registered plant	25
13	Cessation of registration of registered plant	25
14	Refund of fees because of change of ownership of registrable plant	25
Division 3	Registration of registrable plant design	
15	Application of div 3	26
16	Plant not to be installed or used unless certificate of registration is in force	26
16A	When certificate of registration is in force	27
16B	Certificate number to be given	28
16C	Certificate number to be marked on plant	28

Part 3	High risk work and operation of earthmoving equipment and particular crane	
Division 1A	Definitions	
16D	Meaning of assessment instrument	29
16E	Meaning of unit of competency	31
Division 1	Performing high risk work	
17	Authority to perform high risk work	31
18	Work incidental to high risk work	35
19	Application for licence to perform a class of high risk work or for variation of licence	35
20	Application for exemption from holding licence	36
21	Decision on application for exemption	37
22	Licence holder to notify change of address	37
23	Holder to make licence issued by recognised official available for inspection	37
Division 2	Performing work in an earthmoving or particular crane occupation	
24	Authority to perform work in an earthmoving or particular crane occupation	38
25	Work incidental to earthmoving or particular crane operation	41
27	Application for earthmoving or particular crane work certificate	41
28	Application for exemption from holding certificate	42
28A	Decision on application for exemption	42
28B	Holder to make certificate issued by recognised official available for inspection	43
Division 3	Training in work in an earthmoving or particular crane occupation or high risk work	
28C	Meaning of trainee	44
28CA	Employer's duties for training	44
28CB	What training plan must state	46
28D	Supervisor's duty for training	47
28E	Trainee's duty for training	47
28F	Supervisor to sign entry in training record	48
Division 3A	Employer's obligation if worker is undergoing assessment for suitability to perform work	
28FA	Supervision of worker and record keeping	48
Division 4	Other obligations	
28G	Employer must reasonably believe worker is competent	49

28H	Holder of certificate or licence must reasonably believe he or she is competent	49
28I	Holder of certificate or licence must take reasonable precautions and exercise proper diligence	50
Division 5	Revival of authority formerly conferred by certificate of competency for work in an occupation	
28J	Revival of authority	50
Division 6	Conversion of certificate of competency for work in an occupation to licence to perform a class of high risk work or other certificate	
28K	Conversion of certificates	52
Division 7	Expiry of licences to perform class of high risk work issued before July 2008 unless holder converts licence to a renewable licence	
28L	Pre-July 2008 licence to perform a class of high risk work will end unless converted to a renewable licence	53
28M	How to convert a pre-July 2008 licence to perform a class of high risk work to a renewable licence	54
29	Decision on application to convert to a renewable licence . . .	55
29A	Notice about ending of pre-July 2008 licence to perform a class of high risk work to be given to holder	56
Part 3A	Prescribed activities	
Division 1	Certificate to perform prescribed activity	
29B	Certificate to perform prescribed activity	57
29C	Application for certificate to perform prescribed activity	57
29D	Continuing to satisfy approved criteria	58
Division 2	Training and supervision in prescribed activities	
29E	Employer's duty for training in prescribed activity	59
29F	Supervision of performance of prescribed activity	59
Part 3B	Bonded asbestos removal certificate	
29G	Application of pt 3B	60
29H	Authority to perform work to remove bonded asbestos containing material	60
29I	Application for bonded asbestos removal certificate	61
29J	Term of certificate	62
29K	Certificate holder to notify change of address	62
Part 4	Workplace health and safety officers	
30	Workplaces requiring a workplace health and safety officer—Act, s 93	62
31	Application for certificate of authority of appointment	63
32	Approval of workplace health and safety officer course	64

Part 4A	Accredited providers, registered training organisations, approvals and related matters	
Division 1	Accredited providers	
33	Application for appointment as an accredited provider	64
33AA	Authorised accredited provider to make record of assessment and give a copy to applicant	65
33AB	Record of assessment by authorised accredited provider before 1 July 2007	65
Division 2	Duties, and monitoring, of registered training organisations	
33A	Registered training organisation's duty for assessing competency	66
33B	When registered training organisation must not make practical assessment	66
33C	Registered training organisation's duties before issuing statement of attainment	67
33D	Record of assessment by registered training organisation.	68
33E	Other duties of registered training organisation	68
33F	Monitoring of registered training organisation's compliance . . .	69
Division 3	False documents	
33G	Person must not sign false assessment summary	70
33H	Making available document purporting to be statement of attainment	70
Division 4	Approval of individual to provide training and assessment	
33I	Approval of individual to provide training and assessment	70
33J	Chief executive to decide application for training approval within 28 days	71
33K	Grant of approval	71
33L	Notice of refusal of application	72
Division 5	Suspension and cancellation of training approval	
33M	Grounds for suspension or cancellation of approval	72
33N	Procedure for suspension or cancellation	72
33O	Immediate suspension of approval.	74
33P	When immediate suspension has effect until	75
Part 5	Certificates and licences	
Division 1	Definitions	
34	Definitions for pt 5.	75

Division 1A	Applications for certificates, licences and variations of licences	
Subdivision 1	Certificates, licences and variations of licences generally	
35	How to apply for a certificate, other than an earthmoving or particular crane work certificate	76
36	How to apply for an earthmoving or particular crane work certificate	77
36A	Eligibility to obtain particular licence classes	78
37	How to apply for a licence or variation of a licence to endorse another class of high risk work	80
37A	If applicant for licence or variation of a licence holds a corresponding authority to licence or licence class	81
38	How to apply for a variation of a licence to remove a class of high risk work	81
38A	Refusal to grant licence or variation for applicant's misconduct . .	81
38B	Refusal to grant certificate, licence or variation—false assessment summary	82
38C	Refusal to grant earthmoving or particular crane work certificate for applicant's misconduct	82
38D	Refusal of application for lack of competence or for misconduct .	83
38E	Refusal of applications for particular certificates	83
38F	Chief executive to decide application within 28 days	84
38G	Grant of certificate, licence or variation of a licence	84
38H	Notice of refusal of application	84
38I	Grant of certificate, licence or variation of licence on conditions .	85
38J	Term of licence	85
Subdivision 1A	Renewal of licences	
38K	When licence may be renewed	85
38L	How to apply for renewal of a licence	86
38M	Renewal of licences	86
38N	Refusal to renew licence for lack of competence	86
39	Notice of refusal of application	86
Subdivision 2	Provisions about certificates of registration of registrable plant design	
39A	Application of sdiv 2	87
39B	Definitions for sdiv 2	87
39C	Application for certificate of registration of registrable plant design	88
39D	Prohibitions relating to design verification statements	88
39E	Chief executive may ask for additional information for registration	89

39F	Chief executive may require information from certificate holder. .	89
Subdivision 3	Provisions about certificates of registration of registrable plant that is mobile crane or tower crane	
39G	Application of sdiv 3	90
39H	Definitions for sdiv 3	90
39I	Application for certificate of registration of a mobile crane or tower crane	91
39J	Application under s 39I if engineer can not inspect because of unforeseeable circumstances.	91
Division 2	Renewal of certain certificates	
40	Definition for div 2.	92
41	Renewal of certificate.	92
42	Application for renewal before registration ends.	93
43	Div 1A applies to application for renewal	93
Division 3	Replacement and surrender of certificates and licences	
45	Replacement of certificate or licence	93
46	Surrender of certificate or licence	94
Division 4	Suspension and cancellation of certificates and licences	
46A	Grounds for suspension or cancellation	94
46B	Procedure for suspension or cancellation	96
46C	Immediate suspension of earthmoving or particular crane work certificate, licence or licence class	98
46D	Further provision about immediate suspension	100
46E	Suspension or cancellation of earthmoving or particular crane work certificate, licence or licence class on recommendation of recognised official.	100
46EA	Ending of licence if application for corresponding authority	101
46EB	Chief executive may advise recognised official of particular matters	101
46F	Requirement for retraining	102
46G	Certificate or licence to be returned	102
46H	Replacement licence to be issued for remaining licence class . .	102
Division 5	Obligation of relevant person	
46I	Way to prevent or minimise risk prescribed	103
Division 6	Miscellaneous	
46J	Giving information for administering Act.	103
46K	Particular work encompassed in licence classes	104
Part 6	Notifiable building and construction work	
47	Notification of building and construction work	104

48	Exemption from payment of fees	105
49	Recovering unpaid fees	107
50	Refund of fees	107
51	Start and finish of building and construction work	108
Part 7	Injuries, illnesses and dangerous events	
52	Notifying of particular workplace incidents	108
53	Recording particular workplace incidents	110
54	Scene not to be interfered with	112
Part 7A	Access—employers doing work that is not construction work	
54A	Employers—access	112
Part 10	Noise	
68	What is excessive noise	113
69	Preventing risk from exposure to excessive noise	113
Part 11	Asbestos removal and management	
Division 1	Interpretation	
69A	Definitions for pt 11	114
Division 2	Prohibitions relating to asbestos	
69B	Prohibited substances and prohibited ACM	114
69C	Performing work on ACM	115
69D	Removing ACM	115
69E	Cleaning ACM	115
Division 3	On-site management of ACM	
Subdivision 1	Particular buildings	
70	Application of sdiv 1	116
71	Compliance with asbestos management code	117
Subdivision 2	Particular structures	
72	Application of sdiv 2	117
73	Compliance with asbestos management code	117
Division 4	Asbestos removal work	
74	Performing asbestos removal work	118
Part 12	Underwater diving work	
Division 1	Definitions for part 12	
76	Meaning of underwater diving work	119
77	Meaning of construction diving work	119
Division 2	All underwater diving work—medical fitness to dive	
78	Requirements about certificate of medical fitness to dive	121

79	Contents of certificate of medical fitness to dive	122
Division 3	Underwater diving work other than conducting recreational diving or recreational technical diving	
Subdivision 1	Preliminary	
80	Application of div 3	123
81	Meaning of competent person for construction diving work	123
82	Meaning of competent person for other underwater diving work .	124
83	Competent person for s 82—holder of ADAS diving certificate for the diving	124
84	Competent person for s 82—holder of certification under Australian Qualifications Framework	124
85	Competent person for s 82—holder of certificate for AS 4005.2 subject areas	125
86	Competent person for s 82—person doing underwater diving work on no more than 28 days in the last 6 months	126
86AA	Competent person for s 82—someone who has spent at least 15 hours doing the same type of work as the underwater diving work	127
Subdivision 2	Proof of competency for underwater diving work other than construction diving work	
86AB	Proof of competency	128
Subdivision 3	Risk assessment and control measure process at particular stages	
86AC	Process to be carried out before work starts	129
86AD	Process to be carried out each time there is a significant change	130
86AE	Work not to start or restart unless diver has read, understood and signed record of process	130
86AF	Record to be kept for each time process is carried out	131
86AG	Control measure to be in place and monitored and reviewed . . .	132
Subdivision 4	Dive safety log	
86AH	Dive safety log—log must be kept	133
86AI	Dive safety log—required information about dives	133
86AJ	Dive safety log—diver must sign log	134
86AK	Dive safety log—further signing of log	135
86AL	Dive safety log—log to be kept for at least 1 year	135
Subdivision 5	Provisions relating only to construction diving work	
86AM	ADAS diving certificate for the diving is required	135
86AN	Dive supervisor	136
86AO	Stand-by diver	137
86AP	Recompression chamber and qualified operator	138

86AQ	Recompression chamber not to be operated without appropriate qualifications	140
86AR	When using open circuit scuba is prohibited	141
86AS	Work below 50m using SSBA supplying compressed air prohibited	141
Division 4	Conducting recreational diving or recreational technical diving	
86A	Ways to prevent or minimise risks prescribed	142
86B	Count of all persons on board to be made and recorded	142
86C	Medical conditions of resort divers	144
86D	Lookout and rescuer	145
86E	Supervision of resort divers	146
86F	Dive safety log	146
Part 12A	Conducting recreational snorkelling	
86G	Ways to prevent or minimise risks prescribed	149
86H	Count of all persons on board to be made and recorded	149
86I	Advice about medical conditions	151
86J	Lookout, guide and rescuer	151
Part 13	Hazardous substances	
Division 1	Interpretation	
87	Meaning of exposed	153
88	Meaning of hazardous substance	153
Division 2	Manufacturers and importers	
89	Who division applies to	154
90	Preparing, amending and reviewing MSDS	154
91	Providing MSDS	156
92	Notifying use of type 2 ingredient's generic name	157
93	Disclosing ingredient's chemical name	157
94	Providing NICNAS summary report and other information	158
Division 3	Suppliers	
95	Who division applies to	159
97	Providing MSDS	159
98	Labelling containers	160
Division 4	Relevant persons	
99	Who division applies to	161
100	Meaning of hazardous substance for division	161
101	Obtaining MSDS	161
102	Recording and displaying MSDS	162

103	Labelling containers	162
104	Hazardous substances in enclosed systems	163
105	Risk assessments	164
106	Risk assessment records	165
107	Controlling exposure.	165
108	Monitoring.	167
109	Health surveillance	167
110	Confidentiality of worker's medical record	169
111	Keeping register	169
112	Keeping records	170
113	Induction and training about hazardous substances	171
Division 5	Spray painting with hazardous substances	
115A	Ways to prevent or minimise risk prescribed	172
115B	Manufacturing or importing a spray painting booth	172
115C	Supplying a spray painting booth	173
115D	Protecting persons from spray painting	174
115E	Spray painting to be done in spray painting booth	174
115F	Controlling exposure from spray painting	175
115G	Maintaining a spray painting booth.	175
115H	Minimum air movement for booths	176
Part 14	Lead	
Division 1	Interpretation	
116	Meaning of exposed.	177
117	Meaning of lead hazardous substance.	177
Division 2	Manufacturers and importers	
118	Who division applies to.	178
119	Preparing, amending and reviewing MSDS	178
120	Providing MSDS	179
121	Providing NICNAS summary report and other information	180
Division 3	Suppliers	
122	Who division applies to.	181
123	Providing MSDS	181
124	Labelling containers	181
Division 4	Relevant persons	
125	Who division applies to.	182
126	Obtaining MSDS.	182
127	Keeping registers	183

128	Labelling containers	184
129	Risk assessment	184
130	Risk assessment records	187
131	Controlling exposure.	187
132	Atmospheric monitoring	189
133	Health surveillance	189
134	Reviewing control measures	192
135	Removal of worker from a lead-risk job	192
135A	Removal of relevant person from a lead-risk job	193
136	Return to a lead-risk job	193
137	Confidentiality of worker's medical record	194
138	Induction and training about lead	194
139	Keeping records	195
Division 5	Workers	
140	Who division applies to.	196
141	Health surveillance	196
142	Advising of pregnancy or breast feeding	197
Part 15	Confined spaces	
143	Designing, manufacturing or supplying a confined space	197
144	Modifying a confined space	198
145	Using a confined space	198
Part 16	Roll-over protective structures for wheeled tractors	
Division 1	Interpretation	
146	Definitions for pt 16.	199
147	Meaning of tractor	200
148	Demonstrator tractor is taken to be new.	200
Division 2	Ways to prevent or minimise risk from wheeled tractor rolling over	
149	Ways to prevent or minimise risk prescribed	201
150	Roll-over protective structure to be fitted to wheeled tractor used by relevant person	201
151	Roll-over protective structure to be fitted to wheeled tractor used by worker	201
153	Roll-over protective structure to be fitted to wheeled tractor hired, leased or borrowed.	202
Division 3	Obligation of prospective supplier of wheeled tractor not fitted with a roll-over protective structure	
154	Obligation of prospective supplier of wheeled tractor not fitted with a roll-over protective structure.	202

Part 17	Construction work	
Division 1	Interpretation	
155	Definitions for pt 17	204
156	Meaning of high risk construction activity	210
157	Meaning of work method statement for high risk construction activity other than prescribed activity	212
158	Meaning of work method statement for high risk construction activity that is prescribed activity	214
Division 2	Principal contractors	
Subdivision 1	Preliminary	
159	Application of div 2	215
Subdivision 2	Obligation to prepare construction safety plan	
160	Principal contractor must prepare construction safety plan	215
161	When principal contractor not to allow relevant person to start housing construction work	217
162	When principal contractor not to allow relevant person to start construction work, other than housing construction work	218
163	Availability of current construction safety plan	218
164	Amendment of construction safety plan	218
Subdivision 3	Principal contractor's obligation for work method statements	
165	Principal contractor not to allow relevant person to start high risk construction activity unless work method statement prepared	219
166	Work method statement or amended work method statement to be kept with construction safety plan	219
167	Principal contractor not to allow person to perform prescribed activity unless in compliance with work method statement	219
168	Principal contractor to monitor use of work method statement	220
Subdivision 4	Principal contractor's obligation to sight induction evidence and conduct site-specific workplace health and safety inductions	
169	Principal contractor to sight general induction evidence before construction work starts	220
170	Site-specific induction to be given	220
Subdivision 5	Principal contractor's obligation for others	
171	Authority to perform work for prescribed activities, work in an earthmoving or particular crane occupation or high risk work	222
Subdivision 6	Principal contractor's obligation to erect signs	
172	Signs	222

Subdivision 7	Principal contractor's obligation about safe housekeeping practices	
173	Purpose of sdiv 7	223
174	Safe housekeeping practices	224
Subdivision 8	Principal contractor's obligation for common plant	
175	Common plant	225
Subdivision 9	Principal contractor's obligation for hazardous substances	
176	Register of hazardous substances	225
Subdivision 10	Principal contractor's obligation for underground services	
177	Information about underground services	226
Subdivision 11	Principal contractor's obligation for falling objects	
178	Application of sdiv 11	227
179	What is mesh for sdiv 11	227
180	Risk assessment and control measures for civil construction work and housing construction work	228
181	Control measures for construction work that is not civil construction work or housing construction work	229
182	Additional control measures if measured angle is 75° or more, other than for demolition work or work erecting or dismantling formwork	231
183	Control measures for demolition work or work erecting or dismantling formwork	232
184	Perimeter containment screening as control measure	233
185	Catch platform as control measure	234
186	Gantry as control measure	234
187	Load lifted over adjoining area	235
188	Closure of part or all of adjoining area	236
Subdivision 12	Principal contractor's obligation for amenities	
189	Amenities	236
Division 3	Relevant persons	
Subdivision 1	Preliminary	
190	Application of div 3	237
Subdivision 2	Relevant person's obligation for work method statements	
191	Relevant person to prepare work method statement before starting high risk construction activity	237
192	When relevant person not to allow another relevant person to start prescribed activity	238
193	When relevant person who is employer not to allow worker to start high risk construction activity	239

194	High risk construction activity not to be performed unless in compliance with work method statement	239
195	Amendment of work method statement	239
196	Availability and review of work method statement	240
Subdivision 3	Relevant person's obligation for general induction evidence	
197	Definition for sdiv 3	240
198	Relevant person to hold general induction evidence before starting construction work	240
199	Relevant person who is employer to ensure worker holds general induction evidence before worker starts construction work	241
Subdivision 4	Relevant person's obligation for safe housekeeping practices	
200	Safe housekeeping practices	241
Subdivision 5	Relevant person's obligation for common plant	
201	Common plant	242
Subdivision 6	Relevant person's obligation for hazardous substances	
202	Relevant person to give principal contractor details of hazardous substances to be used	243
Subdivision 7	Relevant person's obligation for underground services	
203	Risk from contact with underground services—construction work for which there is principal contractor	243
204	Risk from contact with underground services—construction work for which there is no principal contractor	244
Subdivision 8	Relevant person's obligation for excavation work that could reduce the stability of a structure	
205	Obligation before excavation work starts	245
206	Obligation during excavation work	245
Subdivision 9	Relevant person's obligation for risk from excavations	
207	Meaning of competent person for sdiv 9	246
208	Risk from all excavations	247
209	Risk from working in trench at least 1m deep	248
210	Risk from working in trench more than 1.5m deep	249
211	Access by ladders to trench more than 1.5m deep	250
212	Events in trench more than 1.5m deep that is not shored, benched or battered	250
Subdivision 10	Relevant person's obligation for risk of a person falling	
213	Definition for sdiv 10	251
214	Risk of fall of less than 3m in housing construction work or less than 2m in other construction work or construction work on roof with slope not over 26°	252

215	Risk of fall of at least 3m in housing construction work or at least 2m in other construction work or construction work on roof with a slope over 26°	253
216	Edge protection as control measure.	254
217	Fall protection cover as control measure	256
217A	Travel restraint system as control measure	256
217B	Fall arresting platform as control measure	257
217C	Fall-arrest harness system as control measure	258
217D	Industrial safety net as control measure.	261
Subdivision 11	Relevant person's obligation for ladders	
217E	What work may be done from single or extension ladder.	262
217F	Work on a ladder	262
217G	Ladders generally.	264
Subdivision 12	Relevant person's obligation for platforms supported by trestle ladders	
217H	Work on platform supported by trestle ladders.	266
217I	Platform supported by trestle ladders.	267
Subdivision 13	Relevant person's obligation for scaffolding	
217J	Obligations before starting to erect or dismantle	268
217K	Erecting scaffolding	269
217L	Dismantling scaffolding.	270
Subdivision 14	Relevant person's obligation for falling objects	
217M	Application of sdiv 14	271
217N	Relevant person's obligation if no principal contractor	271
Subdivision 15	Relevant person's obligation for first aid	
217O	First aid.	272
Division 4	Workers	
217P	Application of div 4	272
217Q	Worker to hold general induction evidence before starting construction work	272
Division 5	General provisions about control measures and plant for pt 17	
217R	Control measure to be in place and monitored and reviewed . . .	273
217S	Plant not to be used as control measure unless it has been maintained	274
217T	Plant erected or installed after construction work starts.	274
217U	Written evidence about plant from engineer or competent person may be relied on.	275

Division 6	Chief executive may ask for information from Queensland Building Services Authority	
217V	Definitions for div 6	276
217W	Chief executive may ask general manager of Queensland Building Services Authority for relevant information	276
Part 21	Amenities—work that is not construction work	
218	Amenities for rural industry work	277
219	Amenities for work that is not construction work or rural industry work	277
220	Maintenance of amenities	277
Part 21A	Employers—requirements for building provided for worker to occupy when performing work that is not construction work or rural industry work	
221	Ventilation, lighting, floor area and air space for building	278
Part 21B	Employers—atmospheric contaminants	
222	Level of atmospheric contaminants	279
Part 21C	First aid	
223	Employers—work other than construction work	279
224	Employers—workers performing rural industry work	280
Part 21D	Workplace health and safety contributions	
226	Purpose of pt 21D	280
227	Amount of workplace health and safety contribution	280
Part 22	Miscellaneous	
229	Rural industry exemption	282
229A	Time for giving workplace health and safety undertaking	282
229B	Workplace health and safety representative training course	282
230	Appeal against decision of Authority	283
Part 23	Transitional provisions	
Division 1	Pc's workplace plan and pc's demolition work plan	
231	Transitional provision for pc's workplace plan and pc's demolition work plan.	283
Division 2	Induction for specified work	
232	Transitional provision for Workplace Health and Safety induction for specified work	284
Division 3	Certificates of registration of registrable plant design	
233	Transitional provision for Workplace Health and Safety Amendment Regulation (No. 1) 2004—applications for certificate of registration of registrable plant design	284

234	Transitional provision for Workplace Health and Safety Amendment Regulation (No. 1) 2004—certificates of registration of registrable plant design	285
Division 4	Certain amenities complying, or leased or acquired, immediately before 1 January 2005	
235	Definitions for div 4	286
236	Employers to whom this division applies	287
237	Lunch room	287
238	Dressing room	288
239	Toilets	289
Division 5	Transitional provisions for Workers' Compensation and Rehabilitation and Other Legislation Amendment Regulation (No. 1) 2005	
241	Construction work—construction safety plans	289
242	Construction work—general induction evidence before 1 January 2006	290
243	Construction work—general induction evidence from 1 January 2006	291
Division 6	Transitional provisions for Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2007, part 2, division 2	
Subdivision 1	Definition for division 6	
244	Definition for div 6	291
Subdivision 2	Assessments by authorised accredited providers	
245	Assessment for prescribed occupations made, but no application, before commencement	292
246	Application for certificate of authority of appointment of a workplace health and safety officer—assessment made but no application made before commencement.	292
247	Application for certificate of authority of appointment of a workplace health and safety officer—unfinished training or assessment	293
248	Application for certificate of authority of appointment of a workplace health and safety officer—undecided application made before commencement.	294
Subdivision 3	Other matters	
249	Changes in scope of prescribed occupations.	294
Division 7	Transitional provision for Workplace Health and Safety Legislation Amendment Regulation (No. 1) 2007	
250	Application for certificate of registration of mobile crane or tower crane	295

Division 8	Transitional provisions for Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2007, part 2, division 3	
251	Applications for certificates to work in a prescribed occupation . .	296
252	Unfinalised proposed action	296
Division 9	Transitional provision for Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2008	
253	Statement in assessment summary for unit of competency that person is competent	297
Schedule 1	Fees	298
Schedule 2	Accredited courses	306
Schedule 2A	Workplace health and safety representatives training course	307
Schedule 3	Registrable plant	308
Schedule 4	Registrable plant design	309
Schedule 5	Classes of high risk work and units of competency for the classes	311
Part 1	Scaffolding work	
1	Basic scaffolder	311
2	Intermediate scaffolder	311
3	Advanced scaffolder	311
Part 2	Rigging work	
4	Dogger	312
5	Basic rigger	312
6	Intermediate rigger	312
7	Advanced rigger	312
Part 3	Crane and hoist operation	
8	Tower crane	313
9	Self-erecting tower crane	313
10	Derrick crane	313
11	Portal boom crane	313
12	Bridge and gantry crane (open)	313
13	Vehicle loading crane	314
14	Non-slewing mobile crane	314
15	Slewing mobile crane with a capacity of 20t or less	314
16	Slewing mobile crane with a capacity of 60t or less	315
17	Slewing mobile crane with a capacity of 100t or less	315
18	Slewing mobile crane with a capacity of more than 100t . .	315
19	Materials hoist	315

20	Materials and personnel hoist	316
21	Boom-type elevating work platform	316
22	Mobile truck mounted concrete placing boom	316
Part 4	Forklift operation	
23	Forklift truck	316
24	Order picking forklift truck	317
Part 5	Pressure equipment operation	
25	Basic boiler operator	317
26	Intermediate boiler operator	317
27	Advanced boiler operator	317
28	Turbine operator	317
29	Reciprocating steam engine operator	318
Schedule 5A	Earthmoving or particular crane occupations and units of competency for the occupations	319
1	Bridge and gantry crane (remote control only)	319
2	Dozer	319
3	Excavator having an engine capacity of more than 2L	319
4	Front-end loader having an engine capacity of more than 2L	320
5	Front-end loader or backhoe having an engine capacity of more than 2L	320
6	Grader	320
7	Road roller having an engine capacity of more than 2L	320
8	Skid steer loader having an engine capacity of more than 2L	320
9	Scraper	321
Schedule 5B	Particular work encompassed in licence classes	322
Part 1	Work, under another licence class, encompassed in a licence class	
Schedule 6	Hazardous substances for which health surveillance must be supplied	326
Schedule 7	Prohibited substances, prohibited ACM and prohibited purposes	332
1	Amosite, crocidolite, fibrous anthophyllite, tremolite or actinolite	332
2	Chrysotile	332
Schedule 8	Lead hazardous substances	334
Schedule 8A	Principal contractors—particular amenities for construction work	335

Part 1	Definition for sch 8A	
1	Definition	335
Part 2	Toilets	
2	Toilets	335
3	When toilet must be connected toilet or portable toilet.	336
4	Privacy, ventilation and toilet paper	337
Part 3	Other amenities	
5	Room, or sheltered area, to eat meals in	338
6	Hands and face washing facilities	339
7	Drinking water	339
Schedule 8B	Employers—particular amenities for rural industry work . . .	341
Part 1	Toilets for workers and employer	
1	Toilets	341
Part 2	Other amenities for workers	
2	Application of pt 2.	342
3	Sheltered area to eat meals in	342
4	Hands washing facilities	342
5	Drinking water	342
Schedule 8C	Employers—particular amenities for work that is not construction work or rural industry work	344
Part 1	Application of sch 8C	
1	Application of sch 8C	344
Part 2	Explanation of applied BCA provisions or applied QDC provisions used for pt 3 or sch 8D	
2	Definitions for pt 2.	344
3	Purpose of applied BCA or applied QDC provisions	345
4	Changes to the text of BCA or QDC in modified provision.	346
5	Interpretation of applied BCA or applied QDC provisions	346
Part 3	If worker is at workplace where employer provides non-class 10 building for workers to occupy	
Division 1	Application of pt 3	
6	Application of pt 3.	348
Division 2	Toilets, and hands and face washing facilities	
Subdivision 1	If the building is a class 1b building or employer's domestic premises	
7	Toilets	349
8	Hands and face washing facilities	350

Subdivision 2	If the building is a particular class of building and not employer's domestic premises	
9	Application of sdiv 2	350
10	Toilets, and hands and face washing facilities	351
11	Performance requirements to be complied with	351
12	How to comply with performance requirements	352
13	Location of toilet	352
14	Toilet paper and disposal of female sanitary items.	353
15	Hands and face washing facilities to include soap, water and hands drying facilities.	353
Division 3	Dining facilities	
16	Dining facilities	353
17	Performance criteria to be complied with	354
18	How to comply with performance criteria mentioned in this part or sch 8D	354
19	If worker is able to eat in work area	355
Division 4	Dressing room facilities	
20	Dressing room facilities	356
21	Performance criteria to be complied with	356
Division 5	Drinking water	
22	Drinking water	356
23	Performance criteria that may be complied with.	357
Division 6	Other amenities	
24	Hands and face washing facilities	357
25	Showers	358
Part 4	If worker is not at workplace where employer provides non-class 10 building for workers to occupy	
26	Application of pt 4.	358
27	Toilets	359
28	Sheltered area to eat meals in	360
29	Drinking water	360
30	Hands washing facilities	360
31	Showers	361
Schedule 8D	Employers—requirements for building provided for worker to occupy when performing work that is not construction work or rural industry work	362
Part 1	Application of sch 8D	
1	Application of sch 8D	362

Part 2	Ventilation	
2	Ventilation	362
3	How to comply with performance requirements	363
Part 3	Lighting	
4	Lighting	364
Part 4	Floor area and air space	
5	Floor area and air space	365
Schedule 8E	Applied BCA provisions	366
Schedule 8F	Applied QDC provisions	388
Schedule 9	Dictionary	395
 Endnotes		
1	Index to endnotes	427
2	Date to which amendments incorporated	427
3	Key	428
4	Table of reprints	428
5	Tables in earlier reprints	430
6	List of legislation	430
7	List of annotations	435
8	Information about retrospectivity	487

Workplace Health and Safety Regulation 1997

[as amended by all amendments that commenced on or before 1 July 2008]

Part 1 Preliminary

1 Short title

This regulation may be cited as the *Workplace Health and Safety Regulation 1997*.

2 Commencement

This regulation commences on 1 February 1998.

3 Definitions—the dictionary

The dictionary in schedule 9 defines particular words used in this regulation.

3A References to standards

Unless otherwise stated, a reference in this regulation to an Australian Standard or to a standard published jointly by Standards Australia and Standards New Zealand is a reference to the standard as in force at 1 January 2006.

3B References to the doing of work by employer

A reference in this regulation to the doing or performing of work by an employer is taken to include the doing or performance of the work by a worker of the employer.

3BA References to the doing of work by person who conducts a business or undertaking

A reference in this regulation to the doing or performing of work by a person who conducts a business or undertaking is taken to include the doing or performance of the work by a work activity performer for the business or undertaking.

3C Notes in text

A note in the text of this regulation is part of the regulation.

4 Fees

- (1) The fees payable under the Act are in schedule 1.
- (2) The registration fee for a registrable plant that is first registered after 1 February in any year is adjusted on a proportional basis according to the number of whole months from the end of the month when the plant was first used and 31 January in the following year.
- (3) The chief executive may enter into an agreement with the Authority¹ or another agent for the collection of fees.
- (4) An agreement may provide for an agent to be paid.

Part 2 Registrable plant and registrable plant design**Division 2 Registration of registrable plant****10 Registrable plant not to be used before registration**

An owner of registrable plant must not use registrable plant, or allow it to be used, unless the plant is registered.

Maximum penalty—20 penalty units.

¹ Authority is a defined term—see schedule 9 (Dictionary).

11 Registration of registrable plant

- (1) The owner of registrable plant may apply to the chief executive, in accordance with part 5, division 1A, to register registrable plant.
- (2) Registration is valid—
 - (a) for the initial registration—from the date stated in the certificate until 31 January in the following year; and
 - (b) for the renewal of the certificate—from 1 February until 31 January in the following year.

12 Notification of change of ownership of registered plant

A holder of a certificate of registration of registered plant must give the chief executive notice of a change of ownership of the plant in the approved form within 28 days of the change.

Maximum penalty—20 penalty units.

13 Cessation of registration of registered plant

The registration of registered plant is taken to end on the day ownership of the plant changes if the holder of the certificate of registration does not notify the chief executive under section 12.

14 Refund of fees because of change of ownership of registrable plant

- (1) This section applies if the chief executive receives a notice under section 12.
- (2) The chief executive must cancel the registration and refund to the former holder of the certificate of registration the unexpired part of the registration fee.
- (3) The refund is to be worked out on a proportional basis according to the number of whole months from the end of the month when the change happened to 31 January in the following year.

Division 3 Registration of registrable plant design

15 Application of div 3

This division does not apply to manually powered plant.

16 Plant not to be installed or used unless certificate of registration is in force

- (1) A relevant person must not install or use plant mentioned in schedule 4² unless a certificate of registration of registrable plant design granted under part 5, division 1A for the design of the plant is in force.³

Maximum penalty—20 penalty units.

- (2) A relevant person who is an employer must not allow a worker of the employer to install or use plant mentioned in schedule 4 unless a certificate of registration of registrable plant design granted under part 5, division 1A for the design of the plant is in force.

Maximum penalty—20 penalty units.

- (3) The owner of any of the following specified high risk plant must not install or use, or allow anyone else to install or use, the plant unless a certificate of registration of registrable plant design granted under part 5, division 1A for the design of the plant is in force—

- (a) an escalator;⁴
- (b) an LP gas cylinder;
- (c) a lift;
- (d) a specified amusement device.

Maximum penalty—20 penalty units.

2 Schedule 4 (Registrable plant design)

3 For when the certificate is in force, see section 16A. See sections 233 and 234 for transitional provisions about certificates, or applications for certificates, of registration of registrable plant design.

4 *Escalator, LP gas cylinder and lift* are defined in schedule 2 of the Act.

- (4) A person does not commit an offence against subsection (1) or (2) in relation to plant mentioned in schedule 4 or against subsection (3) in relation to specified high risk plant mentioned in that subsection if—
 - (a) the person holds a certificate of registration, approval or notification of the design of the relevant plant in force under a corresponding law; and
 - (b) the design has not been changed in a way that requires new measures to control risk.⁵
- (5) The chief executive may give a person who relies under subsection (4) on a certificate in force under a corresponding law written notice—
 - (a) requiring the person to give the chief executive a copy of the certificate within 10 days after the day of the notice; and
 - (b) stating that it is an offence for the person to fail, without reasonable excuse, to comply with the requirement.
- (6) The person must comply with the requirement unless the person has a reasonable excuse.

Maximum penalty for subsection (6)—10 penalty units.

16A When certificate of registration is in force

- (1) A certificate of registration of registrable plant design continues in force until it stops having effect under this section.
- (2) A certificate of registration of registrable plant design for a design of plant stops having effect if the design is changed in a way that requires new measures to control risk.⁶

Example of a change in design causing certificate to stop having effect—

A certificate of registrable plant design is in force for the design of a mobile crane. The crane's reach is increased by fitting a longer boom, which increases the risk of the crane overturning. The certificate stops being in force because of the change.

⁵ See the examples in section 16A.

⁶ A fresh certificate will be needed if the plant is to be installed or used after the change.

Example of a change in design not causing certificate to stop having effect—

A certificate of registrable plant design is in force for the design of a fire tube boiler. The boiler's output is raised by increasing its firing rate, but the operating pressure and temperature of the boiler are unchanged. The certificate does not stop being in force because of the change.

- (3) In this section—

certificate of registration of registrable plant design includes a certificate, approval or notification in force under a corresponding law.

16B Certificate number to be given

- (1) The holder of a certificate of registration of registrable plant design for the design of plant must give the certificate number to—
- (a) each manufacturer of plant, manufactured according to the design, known to the holder; and
 - (b) each supplier of plant, manufactured according to the design, known to the holder.

Maximum penalty—20 penalty units.

- (2) The manufacturer or supplier must give the number to each person to whom the manufacturer or supplier supplies plant manufactured according to the design.

Maximum penalty—20 penalty units.

16C Certificate number to be marked on plant

- (1) A supplier of plant mentioned in schedule 4 must ensure that the number of the certificate of registration of registrable plant design for the design of the plant is permanently marked on the plant so as to be clearly visible.

Maximum penalty—20 penalty units.

- (2) A relevant person who installs or uses, or a relevant person who is an employer who allows a worker to install or use, plant mentioned in schedule 4 must ensure that the number of the certificate of registration of registrable plant design for the

design of the plant is permanently marked on the plant so as to be clearly visible.

Maximum penalty—20 penalty units.

- (3) Subsection (2) does not apply to the following specified high risk plant—
- (a) an escalator;
 - (b) an LP gas cylinder;
 - (c) a lift;
 - (d) a specified amusement device.
- (4) The owner of specified high risk plant mentioned in subsection (3) must ensure that the number of the certificate of registration of registrable plant design for the design of the plant is permanently marked on the plant so as to be clearly visible.

Maximum penalty—20 penalty units.

- (5) In this section—

certificate of registration of registrable plant design includes a certificate, approval or notification in force under a corresponding law.

Part 3 High risk work and operation of earthmoving equipment and particular crane

Division 1A Definitions

16D Meaning of *assessment instrument*

- (1) *Assessment instrument*, for a unit of competency for a class of high risk work, means—
- (a) before 1 July 2009—

- (i) if a national standard has been declared under the *Australian Workplace Safety Standards Act 2005* (Cwlth) stating an instrument, for the unit of competency, that relates to what is to be assessed for the unit of competency, how the assessment must be conducted and recording of the assessment results—
 - (A) the instrument; or
 - (B) the instrument for the unit of competency, issued by the chief executive, that relates to what is to be assessed for the unit of competency, how the assessment must be conducted and recording of the assessment results; or
- (ii) otherwise—the instrument mentioned in paragraph (a)(i)(B); or
- (b) on or after 1 July 2009—
 - (i) if a national standard has been declared under the *Australian Workplace Safety Standards Act 2005* (Cwlth) stating an instrument, for the unit of competency, that relates to what is to be assessed for the unit of competency, how the assessment must be conducted and recording of the assessment results—the instrument; or
 - (ii) otherwise—the instrument for the unit of competency, issued by the chief executive, that relates to what is to be assessed for the unit of competency, how the assessment must be conducted and recording of the assessment results.
- (2) **Assessment instrument**, for a unit of competency for an earthmoving or particular crane occupation, means an instrument for the unit of competency, issued by the chief executive, that relates to what is to be assessed for the unit of competency, how the assessment must be conducted and recording of the assessment results.

16E Meaning of *unit of competency*

- (1) ***Unit of competency***, for a class of high risk work, means—
- (a) before 1 July 2009—
 - (i) if a national standard has been declared under the *Australian Workplace Safety Standards Act 2005* (Cwlth) stating a unit of competency for a class of licence, or a class of work, that corresponds or substantially corresponds to the class of high risk work—
 - (A) the unit of competency; or
 - (B) the unit of competency stated in schedule 5 for the class of high risk work; or
 - (ii) otherwise—the unit of competency stated in schedule 5 for the class of high risk work; or
 - (b) on or after 1 July 2009—
 - (i) if a national standard has been declared under the *Australian Workplace Safety Standards Act 2005* (Cwlth) stating a unit of competency for a class of licence, or a class of work, that corresponds to the class of high risk work—the unit of competency; or
 - (ii) otherwise—the unit of competency stated in schedule 5 for the class of high risk work.
- (2) ***Unit of competency***, for an earthmoving or particular crane occupation, means the unit of competency stated in schedule 5A for the occupation.

Division 1 Performing high risk work**17 Authority to perform high risk work**

- (1) An employer must not employ or otherwise allow a worker to perform high risk work unless the worker has appropriate authority to perform the high risk work.

Maximum penalty—40 penalty units.

- (2) A person must not perform high risk work unless the person has appropriate authority to perform the high risk work.

Maximum penalty—40 penalty units.

- (3) A person has appropriate authority to perform high risk work for the class of high risk work that includes the high risk work if—

- (a) the person holds a licence to perform the class of high risk work; or
- (b) the person holds a document (however described), issued by a recognised official, authorising the performance of a class of work that is the same or substantially the same as the class of high risk work; or
- (c) the person is a trainee in the high risk work; or

- (ca) each of the following apply—

- (i) the person is a worker who is undergoing an assessment, conducted by the worker's employer, to decide the worker's suitability to perform the high risk work;
- (ii) the assessment has lasted for not more than 1 month;
- (iii) the person is being directly supervised during the assessment by someone who holds a licence to perform the class of high risk work that includes the high risk work;
- (iv) the date on which the assessment started and the date on which the assessment is expected to end is documented by the employer; or

- (d) the person holds an assessment summary under subsection (4) for the unit of competency for the class of high risk work, that was issued within 14 days before the day on which the work is to be performed; or
- (e) the person holds a statement of attainment for the unit of competency for the class of high risk work, that was issued within 60 days before the day on which the work is to be performed; or

- (f) the person has applied under section 19 for a licence, or a variation of a licence, to perform the class of high risk work, and has not received from the chief executive—
 - (i) the licence or the grant of the variation; or
 - (ii) notice of refusal for the application.
- (3A) However, high risk work may be performed only by a person who is at least 18 years, unless—
 - (a) the person is a trainee; or
 - (b) the person is a worker mentioned in subsection (3)(ca)(i).
- (4) An assessment summary for a person named in the summary must—
 - (a) be issued by a registered training organisation; and
 - (b) state the person who performed the assessment and be signed by that person; and
 - (c) state, for the unit of competency to which the assessment summary relates, that the person named in the summary—
 - (i) has a competent assessment result in the following assessments—
 - (A) written assessment;
 - (B) practical assessment;
 - (C) if an assignment is required to be assessed under the assessment instrument for the unit of competency, and was assessed—assignment assessment; and
 - (ii) demonstrated the appropriate underpinning knowledge; and
 - (d) be issued only if—
 - (i) the person who performed the assessment is nominated by the registered training organisation to provide training and assessment services for the registered training organisation; and

- (ii) the registered training organisation's scope of registration under the *Vocational Education, Training and Employment Act 2000* covers the assessment and training to which the assessment relates; and
 - (iii) for an assessment summary issued on or after 1 January 2009—the individual who performed the assessment—
 - (A) holds a training approval in relation to the unit of competency; or
 - (B) has complied with any criteria that must be complied with, under a corresponding law, to enable the individual to provide training and assessment for the unit of competency for a purpose that is the same as or similar to a purpose of this part.
- (5) Subsection (1) does not apply to a worker, and subsection (2) does not apply to a person, if the worker or person holds an exemption under section 21 in relation to performing the high risk work.
- (6) Subsection (1) does not apply to a worker, and subsection (2) does not apply to a person, in relation to high risk work that is the operation of a bridge and gantry crane by the worker or person, to the extent that the worker or person has authority to perform the work under an earthmoving or particular crane work certificate.
- (7) Subsection (1) applies to a worker, and subsection (2) applies to a person, in relation to high risk work that is the work of a dogger only if—
 - (a) the load being lifted is lifted, to or from the ground, outside the view of the worker or person and the worker or person holds the licence class operator of a vehicle loading crane with a capacity of 10 metre tonnes or more; or
 - (b) the load being lifted is lifted outside the view of the worker or person and the worker or person holds the licence class operator of a bridge and gantry crane; or

- (c) the load being lifted is lifted outside the view of the worker or person and the worker or person holds an earthmoving or particular crane certificate for the occupation operator of a bridge and gantry crane, if—
 - (i) the load being lifted by remote control is more than 5t; and
 - (ii) the crane has 3 or less powered operations.

18 Work incidental to high risk work

(1) This section applies to—

- (a) a person—
 - (i) whose work is primarily—
 - (A) the maintenance, servicing or repair of plant; or

Example—

a person who repairs the boom of a crane if the person does not lift a load with the crane

 - (B) the demonstration of plant for sale; and
- (ii) who performs work not involving use of the plant for the purpose for which it was designed; and

- (b) a person—
 - (i) whose work is primarily the maintenance, servicing or repair of plant; and

Example—

a person who, when repairing a pump, needs to lift the pump if it weighs no more than 1t

- (ii) who performs rigging work not involving lifting a load of more than 1t.

(2) The person is taken not to be performing high risk work.

19 Application for licence to perform a class of high risk work or for variation of licence

A person may apply to the chief executive, under part 5, division 1A, for—

- (a) a licence to perform a class of high risk work; or
- (b) a variation of a licence to perform a class of high risk work.

20 Application for exemption from holding licence

- (1) An employer may apply to the chief executive for an exemption from holding a licence to perform a class of high risk work for a worker of the employer.
- (2) A self-employed person may apply to the chief executive for an exemption from holding a licence to perform a class of high risk work.
- (3) An application under subsection (1) or (2) must be made in the approved form and state—
 - (a) the reasons for making the application; and
 - (b) the alternative measures to be used to ensure the high risk work for which the exemption is sought is performed safely.
- (4) The chief executive may grant the exemption if the chief executive is satisfied—
 - (a) the applicant proposes to use particular alternative measures to ensure the work is performed safely; and
 - (b) the alternative measures will ensure the work is performed safely.
- (5) The chief executive may require an applicant under subsection (1) or (2) to give the chief executive any further information the chief executive reasonably requires to decide the application.
- (6) A requirement under subsection (5) may state a reasonable period, of at least 28 days, by which the stated further information must be given to the chief executive.
- (7) If an exemption is granted, the chief executive may place restrictions on the performance of high risk work in the class of high risk work.

21 Decision on application for exemption

- (1) If the chief executive decides to grant an exemption under section 20, the chief executive must issue the exemption to the applicant.
- (2) If the chief executive decides to refuse an application under section 20, the chief executive must give written notice to the applicant about the decision within 10 days after making the decision.
- (3) The notice must state—
 - (a) the reasons for the refusal; and
 - (b) that the person may appeal against the decision under part 11⁷ of the Act.

22 Licence holder to notify change of address

The holder of a licence to perform a class of high risk work must notify the chief executive of a change of the licence holder's residential or postal address within 14 days after the change.

Maximum penalty—10 penalty units.

23 Holder to make licence issued by recognised official available for inspection

- (1) This section applies to a licence issued by a recognised official that has been or is to be relied on to authorise the performance of high risk work.
- (2) To enforce compliance with the Act, the chief executive may require the holder of the licence to make the licence available for inspection by the chief executive, or produce it to the chief executive for inspection, at a reasonable time and place stated by the chief executive.
- (3) To enforce compliance with the Act, an inspector may require the holder to make the licence available for inspection by an inspector, or produce it to an inspector for inspection, at a reasonable time and place stated by the inspector.

- (4) The holder must comply with a requirement under subsection (2) or (3), unless the holder has a reasonable excuse for not complying.

Maximum penalty—10 penalty units.

- (5) If the holder is an individual, it is a reasonable excuse for the holder not to comply with the requirement under subsection (2) or (3) if complying with the requirement might tend to incriminate the holder.

Division 2 Performing work in an earthmoving or particular crane occupation

24 Authority to perform work in an earthmoving or particular crane occupation

- (1) An employer must not employ or otherwise allow a worker to perform work in an earthmoving or particular crane occupation unless the worker has appropriate authority to perform work in the earthmoving or particular crane occupation.

Maximum penalty—40 penalty units.

- (2) A person must not perform work in an earthmoving or particular crane occupation unless the person has appropriate authority to perform work in the earthmoving or particular crane occupation.

Maximum penalty—40 penalty units.

- (3) A person has appropriate authority to perform work in an earthmoving or particular crane occupation if—
- (a) the person holds an earthmoving or particular crane work certificate for the occupation; or
 - (b) the person is a trainee in the occupation; or
 - (ba) each of the following apply—
 - (i) the person is a worker who is undergoing an assessment, conducted by the worker's employer, to decide the workers's suitability to perform the work;

Workplace Health and Safety Regulation 1997

- (ii) the assessment has lasted for not more than 2 weeks;
 - (iii) the person is being directly supervised during the assessment by someone who holds a certificate to work in the occupation;
 - (iv) the date on which the assessment started and the date on which the assessment is expected to end is documented by the employer; or
- (c) the person holds an assessment summary under subsection (4) for the unit of competency for the occupation, that was issued within 14 days before the day on which the work is to be performed; or
- (d) the person holds a statement of attainment for the unit of competency, that was issued within 60 days before the work is to be performed; or
- (e) the person has applied under section 27 for an earthmoving or particular crane work certificate for the occupation, and has not received from the chief executive—
 - (i) the certificate; or
 - (ii) notice of refusal for the application; or
- (f) the person holds a certificate, issued by a recognised official, authorising work in an occupation that is the same or substantially the same as the occupation; or
- (g) for an occupation mentioned in schedule 5A—the person holds evidence of competency that—
 - (i) is attained in another State; and
 - (ii) is required to be held under the corresponding law of that State; and
 - (iii) is equivalent to evidence of competency in the unit of competency.
- (4) An assessment summary for a person named in the summary must—
 - (a) be issued by a registered training organisation; and

- (b) state the person who performed the assessment and be signed by that person; and
- (c) state, for the unit of competency to which the assessment summary relates, that the person named in the summary—
 - (i) has a competent assessment result in the following assessments—
 - (A) written assessment;
 - (B) practical assessment;
 - (C) if an assignment is required to be assessed under the assessment instrument for the unit of competency, and was assessed—assignment assessment; and
 - (ii) demonstrated the appropriate underpinning knowledge; and
- (d) be issued only if—
 - (i) the person who performed the assessment is nominated by the registered training organisation to provide training and assessment services for the registered training organisation; and
 - (ii) the registered training organisation's scope of registration under the *Vocational Education, Training and Employment Act 2000* covers the assessment and training to which the assessment relates; and
 - (iii) for an assessment summary issued on or after 1 January 2009—the individual who performed the assessment—
 - (A) holds a training approval in relation to the unit of competency; or
 - (B) has complied with any criteria that must be complied with, under a corresponding law, to enable the individual to provide training and assessment for the unit of competency for a purpose that is the same as or similar to a purpose of this part.

- (5) Subsection (1) does not apply to a worker, and subsection (2) does not apply to a person, if the worker or person holds an exemption under section 28A in relation to performing work in the earthmoving or particular crane occupation.
- (6) Subsection (1) does not apply to a worker, and subsection (2) does not apply to a person, in relation to work mentioned in subsection (7), if the worker or person has authority to perform the work under a licence to perform a class of high risk work.
- (7) For subsection (6), the work is the operation of a bridge and gantry crane, if—
 - (a) the load being lifted by remote control is more than 5t; and
 - (b) the crane has 3 or less powered operations.

25 Work incidental to earthmoving or particular crane operation

- (1) This section applies to a person—
 - (a) whose work is primarily—
 - (i) the maintenance, servicing or repair of plant; or
 - (ii) the demonstration of plant for sale; and
 - (b) who performs work not involving use of the plant for the purpose for which it was designed.
- (2) The person is taken not to be performing work in an earthmoving or particular crane occupation.

27 Application for earthmoving or particular crane work certificate

A person may apply to the chief executive, under part 5, division 1A, for an earthmoving or particular crane work certificate.

28 Application for exemption from holding certificate

- (1) An employer may apply to the chief executive for an exemption from holding an earthmoving or particular crane work certificate for a worker of the employer.
- (2) A self-employed person may apply to the chief executive for an exemption from holding an earthmoving or particular crane work certificate.
- (3) An application under subsection (1) or (2) must be made in the approved form and state—
 - (a) the reasons for making the application; and
 - (b) the alternative measures to be used to ensure work in the earthmoving or particular crane occupation for which the exemption is sought is performed safely.
- (4) The chief executive may grant the exemption if the chief executive is satisfied—
 - (a) the applicant proposes to use particular alternative measures to ensure the work is performed safely; and
 - (b) the alternative measures will ensure the work is performed safely.
- (5) The chief executive may require an applicant under subsection (1) or (2) to give the chief executive any further information the chief executive reasonably requires to decide the application.
- (6) A requirement under subsection (5) may state a reasonable period, of at least 28 days, by which the stated further information must be given to the chief executive.
- (7) If an exemption is granted, the chief executive may place restrictions on the performance of the work in the earthmoving or particular crane occupation.

28A Decision on application for exemption

- (1) If the chief executive decides to grant an exemption under section 28, the chief executive must issue the exemption to the applicant.

- (2) If the chief executive decides to refuse an application under section 28, the chief executive must give written notice to the applicant about the decision within 10 days after making the decision.
- (3) The notice must state—
 - (a) the reasons for the refusal; and
 - (b) that the person may appeal against the decision under part 11⁸ of the Act.

28B Holder to make certificate issued by recognised official available for inspection

- (1) This section applies to a certificate issued by a recognised official that has been or is to be relied on to authorise the performance of work in an earthmoving or particular crane occupation.
- (2) To enforce compliance with the Act, the chief executive may require the holder of the certificate to make the certificate available for inspection by the chief executive, or produce it to the chief executive for inspection, at a reasonable time and place stated by the chief executive.
- (3) To enforce compliance with the Act, an inspector may require the holder to make the certificate available for inspection by an inspector, or produce it to an inspector for inspection, at a reasonable time and place stated by the inspector.
- (4) The holder must comply with a requirement under subsection (2) or (3), unless the certificate holder has a reasonable excuse for not complying.

Maximum penalty—10 penalty units.

- (5) If the holder is an individual, it is a reasonable excuse for the holder not to comply with the requirement under subsection (2) or (3) if complying with the requirement might tend to incriminate the holder.

Division 3 Training in work in an earthmoving or particular crane occupation or high risk work

28C Meaning of *trainee*

A person is a *trainee* if—

- (a) the person is receiving formal training and informal learning in an earthmoving or particular crane occupation, or in high risk work, under a training plan under section 28CB; and
- (b) the person is being supervised during the formal training or informal learning by someone who—
 - (i) if the training is in an earthmoving or particular crane occupation—holds a certificate to work in the occupation; or
 - (ii) if the training is in high risk work—holds a licence to perform the class of high risk work that includes the high risk work; and
- (c) the person's employer keeps an up-to-date record of the formal training or informal learning.

28CA Employer's duties for training

- (1) A trainee's employer must ensure the trainee—
 - (a) is being trained to achieve the standard set for the unit of competency for the earthmoving or particular crane occupation, or class of high risk work, in which the trainee is being trained; and
 - (b) is being supervised by a person who supervises the trainee as required under section 28D when the trainee performs work in the occupation or performs high risk work; and
 - (c) keeps the training record mentioned in section 28E.

Maximum penalty—20 penalty units.

Workplace Health and Safety Regulation 1997

- (2) A trainee's employer must keep a written record of the following in relation to the trainee's training given by the employer—
- (a) the formal training given to the trainee and the date on which it was given;
 - (b) the informal learning given to the trainee, including—
 - (i) the scope of work performed by the trainee that is work in an earthmoving or particular crane occupation or high risk work; and
 - (ii) the date on which the work was performed; and
 - (iii) the type of plant used or operated for the performance of the work, and the serial number of the plant; and
 - (iv) the name of the trainee's supervisor during the informal learning, and the number of the earthmoving or particular crane work certificate, or the licence to perform a class of high risk work, under which work to supervise the trainee was performed;
 - (c) the licensee's progress in the formal training and informal learning, that is kept up-to-date;
 - (d) the extent of the informal learning that the employer has decided is necessary for the trainee to receive, and the reasons for that decision;
 - (e) the name of the person who decided the level of formal training and informal learning, and the level of supervision of the trainee required during the training and learning, and the experience of the person that is relevant to making the decisions.

Maximum penalty—20 penalty units.

- (3) For workplace experience in the use or operation of plant to be treated as informal learning for a trainee, the trainee must have already received formal training in the use or operation of that plant.

28CB What training plan must state

For section 28C(a), a training plan for the formal training of and informal learning by a trainee (both of which are *the training*) must state the following—

- (a) the trainee's name and address;
- (b) the employer's name and address;
- (c) the unit of competency for the earthmoving or particular crane occupation, or the class of high risk work that includes the high risk work, in which the trainee is to be trained;
- (d) the scope of the training, including the topics to be covered;
- (e) the nominal hours for the training;
- (f) the day the training is to start;
- (g) the day the training is to end;
- (h) the primary training locations;
- (i) the plant to be used or operated by the trainee for the training;
- (j) the certificate or licence that must be held by the supervisor as mentioned in section 28C(b);
- (k) the name of the person who is the employer's contact in relation to the plan;
- (l) the arrangements for monitoring the training;
- (m) the arrangements for assessing the training;

Example for paragraph (m)—

A training plan may provide that a registered training organisation is to be engaged to—

- (a) evaluate the evidence of the training undertaken by the trainee; and
 - (b) assess the trainee's competence in the relevant competency.
- (n) the way the training must be recorded, including, for example, by keeping a training record as required under section 28CA(2) or 28E.

28D Supervisor's duty for training

The trainee's supervisor must directly supervise the trainee when the trainee performs high risk work or work in an earthmoving or particular crane occupation unless—

- (a) the nature or circumstances of a particular task make direct supervision impracticable or unnecessary; and
- (b) supervision is reduced only to a reasonable level having regard to the trainee's competence in performing the task; and
- (c) the reduced level of supervision will not place the health or safety of the trainee or someone else at risk.

Maximum penalty—20 penalty units.

28E Trainee's duty for training

The trainee must keep a written training record that identifies the trainee and includes the following—

- (a) the scope of work performed by the trainee that is high risk work or work in an earthmoving or particular crane occupation;
- (b) the date on which the work was performed;
- (c) the type of plant used or operated for the performance of the work;
- (d) the date the training was completed;
- (e) the name of the supervisor who supervised the training;
- (f) the number of the licence or certificate held by the supervisor—
 - (i) to perform work in the class of high risk work that includes the high risk work; or
 - (ii) to work in the earthmoving or particular crane occupation.

Maximum penalty—20 penalty units.

28F Supervisor to sign entry in training record

The trainee's supervisor must sign an entry in the trainee's training record if—

- (a) the supervisor supervised the training to which the entry relates; and
- (b) the supervisor is satisfied the entry is correct.

Maximum penalty—20 penalty units.

Division 3A Employer's obligation if worker is undergoing assessment for suitability to perform work**28FA Supervision of worker and record keeping**

- (1) This section applies if a worker is undergoing an assessment, conducted by the worker's employer, to decide the worker's suitability to perform work in an earthmoving or particular crane occupation or high risk work.
- (2) The employer must ensure the worker is being directly supervised during the assessment by someone who holds—
 - (a) if the work is in an earthmoving or particular crane occupation—an earthmoving or particular crane work certificate for the occupation; or
 - (b) if the work is high risk work—a licence to perform the class of high risk work that includes the high risk work.

Maximum penalty—20 penalty units.

- (3) The employer must make a written record that states the following—
 - (a) the worker's name and address;
 - (b) the employer's name and address;
 - (c) the unit of competency for the earthmoving or particular crane occupation, or the class of high risk work that includes the high risk work;
 - (d) the day the assessment is to start;

- (e) the day the assessment is to end;
- (f) the plant to be used or operated by the worker for the assessment;
- (g) the earthmoving or particular crane work certificate, or licence to perform a class of high risk work, under which work to directly supervise the worker was performed;
- (h) the worker's progress in the work to which the assessment relates, that is kept up-to-date.

Maximum penalty—20 penalty units.

- (4) The employer must keep the record for at least 5 years after the day the assessment ends.

Maximum penalty—20 penalty units.

Division 4 Other obligations

28G Employer must reasonably believe worker is competent

- (1) This section applies to an employer of a worker who holds—
 - (a) an earthmoving or particular crane work certificate; or
 - (b) a licence to perform a class of high risk work.
- (2) The employer must not allow the worker to perform work under the certificate or licence, that involves the use or operation of plant unless the employer reasonably believes the worker is competent to use or operate the plant.

Maximum penalty—40 penalty units.

28H Holder of certificate or licence must reasonably believe he or she is competent

- (1) This section applies to the holder of—
 - (a) an earthmoving or particular crane work certificate; or
 - (b) a licence to perform a class of high risk work.

- (2) The holder must not perform work under the certificate or licence, that involves the use or operation of plant unless the holder reasonably believes that he or she is competent to use or operate the plant.

Maximum penalty—40 penalty units.

28I Holder of certificate or licence must take reasonable precautions and exercise proper diligence

- (1) This section applies to the holder of—
- (a) an earthmoving or particular crane work certificate; or
 - (b) a licence to perform a class of high risk work.
- (2) The holder must take reasonable precautions and exercise proper diligence in performing the work in relation to which the certificate or licence was granted.

Maximum penalty—40 penalty units.

Division 5 Revival of authority formerly conferred by certificate of competency for work in an occupation

28J Revival of authority

- (1) This section applies if a person held any of the following certificates and the certificate ended at midnight on 30 June 2008—
- (a) a certificate of competency to work in, or in part of, an occupation prescribed under the repealed *Workplace Health and Safety Act 1989* and granted under that Act before 1 March 1992;
 - (b) a certificate of competency for an occupation issued under the repealed *Construction Safety Act 1971*, including a certificate of competency that was formerly a licence for an occupation issued under the repealed *Inspection of Scaffolding Act 1915*;

- (c) a certificate of competency authorising a person to take charge of particular machinery issued under the repealed *Inspection of Machinery Act 1951*.
- (2) The person may give notice, in a way mentioned in subsection (3), to the chief executive by midnight on 30 June 2009 of the following—
 - (a) that the person wants to revive the authority that was conferred by the certificate;
 - (b) the certificate number;
 - (c) the person's residential and postal address and date of birth.
- (3) The notice may be given by post, telephone, fax, internet or at an office of the department.
- (4) If a person gives notice under subsection (2) and the certificate that was held—
 - (a) related to work that corresponds or substantially corresponds to the work to which an earthmoving or particular crane occupation relates—the person is taken to hold an earthmoving or particular crane work certificate for the occupation; or
 - (b) related to work that corresponds less than substantially to the work to which an earthmoving or particular crane occupation relates—the person is taken to hold an earthmoving or particular crane work certificate that is limited in scope to the scope of the certificate that was held.

Example of work that corresponds less than substantially to the work to which an earthmoving or particular crane occupation relates—

the operation of a backhoe only in a particular mode corresponds less than substantially with the earthmoving or particular crane occupation operator of a front-end loader or backhoe having an engine capacity of more than 2L.
- (5) The person is taken to hold an earthmoving or particular crane work certificate under subsection (4) on and after the day the chief executive receives the notice.
- (6) If a person gives notice under subsection (2) but is not taken to hold a certificate under subsection (4), the person may make

an application under section 28M relating to the certificate mentioned in subsection (1).

- (7) For making an application under section 28M, the certificate is taken to be a current licence to perform a class of high risk work, issued before 1 July 2008, that is nearest in scope to the scope of the work to which the certificate relates.
- (8) Subsection (7) does not have the effect of licensing the person for any other purpose and does not have effect retrospectively.
- (9) In this section—
issue includes grant.

Division 6 Conversion of certificate of competency for work in an occupation to licence to perform a class of high risk work or other certificate

28K Conversion of certificates

- (1) This section applies to any of the following certificates in force at the commencement of this section—
 - (a) a certificate of competency to work in, or in a part of, an occupation prescribed under the repealed *Workplace Health and Safety Act 1989* and granted under that Act;
 - (b) a certificate of competency for an occupation issued under the repealed *Construction Safety Act 1971*, including a certificate of competency that was formerly a licence for an occupation issued under the repealed *Inspection of Scaffolding Act 1915*;
 - (c) a certificate of competency authorising a person to take charge of particular machinery issued under the repealed *Inspection of Machinery Act 1951*;
 - (d) a certificate to work in a prescribed occupation.
- (2) The certificate is taken to be—
 - (a) if the certificate related to work that corresponds or substantially corresponds to the work to which an

earthmoving or particular crane occupation relates—an earthmoving or particular crane work certificate for the occupation; or

- (aa) if the certificate related to work that corresponds less than substantially to the work to which an earthmoving or particular crane occupation relates—an earthmoving or particular crane work certificate that is limited in scope to the scope of the certificate;
 - (b) otherwise—a licence to perform the class of high risk work issued before 1 July 2008, that is nearest in scope to the scope of the work to which the relevant certificate relates, including, for example, for division 7 and part 5.
- (3) In this section—
issue includes grant.

Division 7 Expiry of licences to perform class of high risk work issued before July 2008 unless holder converts licence to a renewable licence

28L Pre-July 2008 licence to perform a class of high risk work will end unless converted to a renewable licence

- (1) A licence to perform a class of high risk work issued before 1 July 2008 ends as follows—
- (a) if the licence was issued before 1996—
 - (i) if the birthday of the holder of the licence first happens after 30 June 2008 and before 31 August 2008—at midnight on the day that is 56 days after that birthday; or
 - (ii) otherwise—at midnight on the birthday of the holder that first happens after 30 June 2008;
 - (b) if the licence was issued in 1996, 1997 or 1998—at midnight on the birthday of the holder that first happens after 30 June 2009;

- (c) if the licence was issued in 1999, 2000 or 2001—at midnight on the birthday of the holder that first happens after 30 June 2010;
 - (d) if the licence was issued in the 2002, 2003 or 2004—at midnight on the birthday of the holder that first happens after 30 June 2011;
 - (e) if the licence was issued in 2005, 2006, 2007 or in 2008 but before 1 July 2008—at midnight on the birthday of the holder that first happens after 30 June 2012.
- (2) Subsection (1) does not apply if—
- (a) the chief executive did not give notice under section 29A about the licence ending; or
 - (b) the licence is converted under section 28M to a renewable licence.
- (3) If the chief executive does not give notice under section 29A to the holder—
- (a) the licence does not end under subsection (1); but
 - (b) the chief executive may give to the holder written notice that the licence ends 6 months after the date of the notice.
- (4) If the chief executive gives notice under subsection (3)(b), the licence ends 6 months after the date of the notice.
- (5) Subsection (4) does not apply if the licence is converted to a renewable licence under section 28M.
- (6) In this section—
issue includes grant.

28M How to convert a pre-July 2008 licence to perform a class of high risk work to a renewable licence

- (1) A licence to perform a class of high risk work issued before 1 July 2008 may be converted to a renewable licence with a term of 5 years.

Note—

See sections 28J(7) and 28K(2)(b).

- (2) The holder of the licence may apply to the chief executive to convert the licence to a renewable licence.
- (3) The application must—
 - (a) be in the approved form; and
 - (b) state that the holder is competent to perform the class of high risk work to which the renewable licence relates; and
 - (c) be accompanied by—
 - (i) evidence, satisfactory to the chief executive, of the applicant's identity; and
 - (ii) the fee under schedule 1 for the application.
- (4) A single application must be made by a person for licences under subsection (1) held by the person.
- (5) If a person may apply under subsection (2) because of section 28J(6)—
 - (a) the application may only be made before 1 October 2009; and
 - (b) a renewable licence granted in relation to the application does not have the effect of retrospectively licensing the holder.
- (6) In this section—
issue includes grant.

29 Decision on application to convert to a renewable licence

- (1) If the chief executive decides to grant an application to convert a licence or licences to a single renewable licence, the chief executive must grant the renewable licence in the approved form as soon as practicable after making the decision.
- (2) The renewable licence is subject to the conditions, if any, to which the licence was subject.
- (3) If the chief executive decides to refuse an application to convert a licence to a renewable licence, the chief executive

must give written notice to the applicant about the decision within 10 days after making the decision.

- (4) The notice must state—
- (a) the reasons for the refusal; and
 - (b) that the person may appeal against the decision under part 11 of the Act.

29A Notice about ending of pre-July 2008 licence to perform a class of high risk work to be given to holder

- (1) The chief executive must give a notice under subsection (3) to each holder of a licence to perform a class of high risk work issued before 1 July 2008.
- (2) The notice must be given at least 6 weeks before the licence ends under section 28L(1).
- (3) The notice must state—
 - (a) that the holder's certificate of competency for work or work in an occupation is now a licence to perform a stated class of high risk work; and
 - (b) that the holder's licence to perform a class of high risk work will end at a stated time unless the licence is converted to a renewable licence by that time; and

Example of a stated time for paragraph (b)—

at midnight on the birthday of the holder that first happens after 30 June 2008

- (c) an application to convert the licence to a renewable licence—
 - (i) may be made to the chief executive; and
 - (ii) must be made under section 28M; and
 - (d) how the application may be made.
- (4) The stated time under subsection (3)(b) must be the time at which the licence to perform a class of high risk work will end under section 28L(1).
- (5) Subsection (3) does not prevent the notice stating other matters about workplace health or safety.

- (6) In this section—
issue includes grant.

Part 3A Prescribed activities

Division 1 Certificate to perform prescribed activity

29B Certificate to perform prescribed activity

- (1) A relevant person must not perform a prescribed activity unless—
- (a) if the prescribed activity is demolition work, and there is a principal contractor—the principal contractor or the relevant person holds a certificate to perform the activity issued by the chief executive; or
 - (b) if the prescribed activity is asbestos removal work—the relevant person holds a certificate to perform the activity issued by the chief executive.

Maximum penalty—40 penalty units.

- (2) However, subsection (1)(b) does not apply to the performance of work to remove 10m² or more of bonded asbestos containing material if the work activity performer, for the business or undertaking conducted by the relevant person, who performs the work holds a bonded asbestos removal certificate.

29C Application for certificate to perform prescribed activity

- (1) A person may apply to the chief executive, under part 5, division 1A, for a certificate to perform a prescribed activity.
- (2) The chief executive may grant the application only if the chief executive is satisfied that, within 60 days before the application was made, an authorised accredited provider or a registered training organisation has assessed the applicant,

under the approved criteria, as competent to perform the prescribed activity.

- (3) A certificate is valid for 2 years from the day it is granted unless suspended or cancelled.
- (4) In this section—

approved criteria means—

- (a) for demolition work—the criteria stated in Information Paper D1 (Approved criteria for a certificate to perform the prescribed activity of demolition work) issued by the chief executive; or
- (b) for asbestos removal work—the criteria stated in Information Paper AR1 (Approved criteria for a certificate to perform the prescribed activity of asbestos removal work) issued by the chief executive.⁹

authorised accredited provider means an accredited provider whose functions stated under section 178(2)¹⁰ of the Act include assessing a person's satisfaction of the approved criteria.

29D Continuing to satisfy approved criteria

In addition to any other condition imposed by the chief executive under section 39, a certificate held by a person to perform a prescribed activity is subject to the following conditions—

- (a) the person must take all reasonable steps to ensure that the person continues to satisfy the approved criteria;
- (b) if the prescribed activity to be performed under the certificate is demolition work—the performance of the prescribed activity must be restricted to the particular structures, or particular types of structures, stated in the certificate.

⁹ These information papers may be obtained at no cost from any office of the Department of Employment and Industrial Relations dealing with workplace health and safety, or at <www.deir.qld.gov.au> on the internet.

¹⁰ Section 178 (Functions of accredited providers) of the Act

Division 2 Training and supervision in prescribed activities

29E Employer's duty for training in prescribed activity

An employer who employs, or otherwise allows, a worker to perform a prescribed activity must ensure the person has received appropriate training in safe working methods for the performance of the prescribed activity.

Maximum penalty—30 penalty units.

29F Supervision of performance of prescribed activity

- (1) The holder of a certificate to perform a prescribed activity must ensure the performance of the prescribed activity is directly supervised by a competent person.

Maximum penalty—30 penalty units.

- (2) In this section—

competent person means—

- (a) for demolition work—a person who is competent under Information Paper D2 (Requirements to supervise demolition work) issued by the chief executive; or
- (b) for asbestos removal work—a person who is competent under Information Paper AR2 (Requirements for a competent person to supervise performance of the prescribed activity of asbestos removal work) issued by the chief executive.¹¹

¹¹ These information papers may be obtained at no cost from any office of the Department of Employment and Industrial Relations dealing with workplace health and safety, or at <www.deir.qld.gov.au> on the internet.

Part 3B Bonded asbestos removal certificate

29G Application of pt 3B

This part applies to a prescribed activity that is the performance of work to remove 10m² or more of bonded asbestos containing material.

29H Authority to perform work to remove bonded asbestos containing material

- (1) An employer must not employ or otherwise allow a worker to perform work to remove 10m² or more of bonded asbestos containing material unless the worker has appropriate authority to perform the work.

Maximum penalty—40 penalty units.

- (2) A person must not perform work to remove 10m² or more of bonded asbestos containing material unless the person has appropriate authority to perform the work.

Maximum penalty—40 penalty units.

- (3) A person has appropriate authority to perform work to remove 10m² or more of bonded asbestos containing material if—
- (a) the person holds a bonded asbestos removal certificate; or
 - (b) the person performs the work under a certificate that—
 - (i) is held by a relevant person to perform the prescribed activity of asbestos removal work; and
 - (ii) allows the firstmentioned person to perform the work; or
 - (c) the person holds an assessment summary under subsection (4) about the person's competence to perform work to remove bonded asbestos containing material, that was issued within 60 days before the day on which the work is to be performed; or

- (d) the person has applied under section 29I for a bonded asbestos removal certificate, and has not received from the chief executive—
 - (i) the certificate; or
 - (ii) notice of refusal for the application.
- (4) An assessment summary for a person named in the summary must—
 - (a) be issued by an authorised accredited provider or a registered training organisation; and
 - (b) state that—
 - (i) the person is competent to perform work to remove bonded asbestos containing material; and
 - (ii) the person demonstrated the appropriate underpinning knowledge for the competency assessed; and
 - (c) if—
 - (i) the assessment summary is issued by an authorised accredited provider, state the authorised accredited provider and be signed by the authorised accredited provider; or
 - (ii) the assessment summary is issued by a registered training organisation, state the person who performed the assessment and be signed by the person.
- (5) In this section—

authorised accredited provider means an accredited provider whose functions under section 178(2) of the Act include assessing a person's competence to perform work to remove bonded asbestos containing material.

29I Application for bonded asbestos removal certificate

A person may apply to the chief executive, under part 5, division 1A, for a bonded asbestos removal certificate.

29J Term of certificate

A bonded asbestos removal certificate is for a term of 5 years.

29K Certificate holder to notify change of address

The holder of a bonded asbestos removal certificate must notify the chief executive of a change of the certificate holder's residential or postal address within 14 days after the change.

Maximum penalty—10 penalty units.

Part 4 Workplace health and safety officers

30 Workplaces requiring a workplace health and safety officer—Act, s 93

For section 93¹² of the Act, workplaces (other than workplaces where construction work is performed and a principal contractor has not been appointed for the work) in the following industries are prescribed workplaces—

- (a) building and construction industry;
- (b) community services industry;
- (c) electricity, gas and water industry;
- (d) financial, property and business services industry;
- (e) manufacturing industry;
- (f) public administration industry;
- (g) recreational services, personal services and other services industry;

¹² Section 93 (Appointment of workplace health and safety officer by employer) of the Act. Section 94 (Appointment of workplace health and safety officer by principal contractor) of the Act provides for the appointment of a workplace health and safety officer for a construction workplace.

- (h) retail and wholesale trade industry;
- (i) transport and storage industry.

31 Application for certificate of authority of appointment

- (1) A person may apply to the chief executive, under part 5, division 1A, for a certificate of authority of appointment of a workplace health and safety officer.
- (2) The chief executive may grant the application only if the chief executive is satisfied that—
 - (a) within 3 months before the application is made—
 - (i) for an application for a certificate—a registered training organisation has assessed the applicant as competent to perform the functions of a workplace health and safety officer under the Act; or
 - (ii) for renewal of an application for a certificate—a registered training organisation has assessed the applicant as competent to continue to perform the functions of a workplace health and safety officer under the Act; or
 - (b) the applicant has other qualifications or experience that would enable the applicant to satisfactorily perform the functions of a workplace health and safety officer.
- (2A) The applicant may satisfy the chief executive for subsection (2) by giving the chief executive satisfactory evidence that the applicant has completed—
 - (a) for subsection (2)(a)(i)—an approved workplace health and safety officer course; or
 - (b) for subsection (2)(a)(ii)—an approved workplace health and safety officer recertification course.
- (3) A certificate is valid for the term (of a maximum of 5 years) stated in the certificate.
- (4) In this section—

approved workplace health and safety officer course means a course approved by the chief executive under section 32(1)(a).

approved workplace health and safety officer recertification course means a course approved by the chief executive under section 32(1)(b).

32 Approval of workplace health and safety officer course

- (1) The chief executive may approve—
 - (a) a workplace health and safety officer course; and
 - (b) a workplace health and safety officer recertification course.
- (2) The chief executive must not approve a workplace health and safety officer course or recertification course unless the chief executive is satisfied the course gives adequate instruction about the functions of a workplace health and safety officer under the Act.

Part 4A Accredited providers, registered training organisations, approvals and related matters

Division 1 Accredited providers

33 Application for appointment as an accredited provider

- (1) A person may apply to the chief executive, in accordance with part 5, division 1A, for a certificate of appointment as an accredited provider.
- (2) An appointment is valid for the term (of a maximum of 5 years) stated in the certificate.

Note—

See part 14, division 1 of the Act for further provisions about accredited providers.

33AA Authorised accredited provider to make record of assessment and give a copy to applicant

- (1) This section applies if an authorised accredited provider has assessed an applicant's competency for part 3A or 3B.
- (2) After assessing the applicant's competency, the authorised accredited provider must—

- (a) make a record of the assessment; and
- (b) give a copy of it to the applicant.

Maximum penalty—20 penalty units.

- (3) In this section—

authorised accredited provider—

- (a) if the assessment was made under part 3A—see section 29C; or
- (b) if the assessment was made under part 3B—see section 29H.

33AB Record of assessment by authorised accredited provider before 1 July 2007

- (1) This section applies if—

- (a) an authorised accredited provider has assessed an applicant's competency for part 3 or 4 as in force at any time before 1 July 2007; and
- (b) the authorised accredited provider holds a record of the assessment.

- (2) The authorised accredited provider must—

- (a) if required in writing by the chief executive—give the record of assessment to the chief executive in the way stated in writing by the chief executive; or
- (b) otherwise—keep the record of assessment for at least 5 years after the assessment is made.

Maximum penalty—40 penalty units.

(3) In this section—

authorised accredited provider means—

- (a) if the assessment was made under part 3 as in force at any time before 1 July 2007—an accredited provider whose functions under section 178(2) of the Act include assessing a person’s competency to perform work in the prescribed occupation involved; or
- (b) if the assessment was made under part 4 as in force at any time before 1 July 2007—an accredited provider whose functions under section 178(2) of the Act include the conduct of the course in relation to which the assessment is made.

Division 2 Duties, and monitoring, of registered training organisations

33A Registered training organisation’s duty for assessing competency

A registered training organisation must ensure that each person who trains or assesses the competency of an applicant for part 3, 3A, 3B or 4 complies with the requirements of—

- (a) the *Vocational Education, Training and Employment Act 2000* in relation to the training or assessment; and
- (b) any agreement entered into by the registered training organisation for the training or the assessment in the courses accredited under the *Vocational Education, Training and Employment Act 2000* that are listed in schedule 2.

Maximum penalty—40 penalty units.

33B When registered training organisation must not make practical assessment

A registered training organisation must not make a practical assessment of an applicant’s competency, in a unit of competency, for part 3, 3A, 3B or 4 unless—

- (a) either—
 - (i) the applicant has finished the formal training and informal learning for the unit of competency; or
 - (ii) the registered training organisation is satisfied, on reasonable grounds, that the applicant has acquired adequate skill and knowledge relevant to the unit of competency in a way other than by training; and
- (b) the applicant had a competent assessment result in—
 - (i) the written assessment in the unit of competency; and
 - (ii) if an assignment is required to be assessed under the assessment instrument for the unit of competency, and was assessed—assignment assessment in the unit of competency.

Maximum penalty—20 penalty units.

33C Registered training organisation's duties before issuing statement of attainment

- (1) This section applies if a registered training organisation provides training in a unit of competency for part 3, 3A, 3B or 4.
- (2) The registered training organisation must perform an assessment in the unit of competency in accordance with the assessment instrument for the unit of competency, before issuing a statement of attainment for the unit of competency.

Maximum penalty—20 penalty units.

- (3) Subsection (2) does not apply if, under a table of equivalent competencies issued by the chief executive, the registered training organisation has decided the person is eligible to receive recognition of competency as equivalent to competency in the unit of competency.
- (4) If subsection (3) does not apply, the registered training organisation must not issue a statement of attainment unless the person to whom the statement relates has a competent assessment result in the following assessments in the unit of competency—

- (a) written assessment;
- (b) practical assessment;
- (c) if an assignment is required to be assessed under the assessment instrument for the unit of competency, and was assessed—assignment assessment.

Maximum penalty—20 penalty units.

33D Record of assessment by registered training organisation

After a registered training organisation has assessed an applicant's competency for part 3, 3A, 3B or 4, the organisation must do each of the following—

- (a) make an assessment summary for the unit of competency to which the assessment relates;
- (b) if the registered training organisation decides that the applicant is competent in the unit of competency—issue a statement of attainment for the unit of competency;
- (c) give a copy of the assessment summary and statement of attainment to the applicant.

Maximum penalty—20 penalty units.

33E Other duties of registered training organisation

A registered training organisation that provides training in a unit of competency for part 3, 3A, 3B or 4 must—

- (a) provide the training in accordance with the unit of competency; and
- (b) for a unit of competency for part 3—allow an individual to assess an applicant's competency for the unit of competency, only if the individual, on or after 1 January 2009—
 - (i) holds a training approval in relation to the unit of competency; or
 - (ii) has complied with any criteria that must be complied with, under a corresponding law, to enable the individual to provide training and

assessment relating to the unit of competency for a purpose that is the same as or similar to a purpose of part 3; and

- (c) give a test for an assessment of an applicant's competency for part 3, 3A, 3B or 4, only in accordance with any tests and assessment instructions issued by the chief executive; and
- (d) not give the test to a trainee before the trainee does the test; and
- (e) keep, in a secure way, any model answers for the test until after the test is given to the trainee; and
- (f) not give any model answers for the test to a trainee until after the test is given to the trainee; and
- (g) keep the test papers and answers, and a copy of the assessment summary, for the assessment for at least 5 years from the day of the assessment; and
- (h) for part 3, recognise competency as equivalent to competency in a unit of competency, only in accordance with a table of equivalent competencies, issued by the chief executive.

Maximum penalty—20 penalty units.

33F Monitoring of registered training organisation's compliance

- (1) The chief executive may monitor a registered training organisation's compliance with this division.
- (2) The chief executive must report the results of the monitoring to the chief executive of the department within which the *Vocational Education, Training and Employment Act 2000* is administered.

Division 3 False documents

33G Person must not sign false assessment summary

A person must not sign an assessment summary that is relied on, or is likely to be relied on, under this regulation if the person knows the assessment summary is false.

Maximum penalty—40 penalty units.

33H Making available document purporting to be statement of attainment

A person must not make available to another person a document that—

- (a) purports to be a statement of attainment; and
- (b) is relied on, or likely to be relied on, under this regulation;

if the person knows the document is not a statement of attainment.

Maximum penalty—40 penalty units.

Division 4 Approval of individual to provide training and assessment

33I Approval of individual to provide training and assessment

- (1) An individual may apply to the chief executive for approval to provide training and assessment, for part 3 for either or both of the following, for a registered training organisation whose scope of registration under the *Vocational Education, Training and Employment Act 2000* covers the assessment and training—
 - (a) a unit of competency for a class of high risk work;
 - (b) a unit of competency for an earthmoving or particular crane occupation.

- (2) The chief executive may decide to grant the application only if the chief executive is satisfied the individual has the qualifications, training and experience to provide the training and assessment to the standard appropriate for part 3.
- (3) The application must—
 - (a) be made in writing; and
 - (b) be accompanied by advice by the registered training organisation to the chief executive that the registered training organisation supports the application; and
 - (c) be supported by enough information to enable the chief executive to decide the application.
- (4) The chief executive may require the applicant to give the chief executive any further information the chief executive reasonably requires to decide the application.
- (5) A requirement under subsection (4) may state a reasonable period, of at least 28 days, by which the stated further information must be given to the chief executive.

33J Chief executive to decide application for training approval within 28 days

- (1) The chief executive must decide the application for training approval within 28 days after the application is made.
- (2) However, if the chief executive requires the applicant to give the chief executive further information under section 33I(4), the chief executive must decide the application within a reasonable period, but within 28 days, after receiving the information.

33K Grant of approval

If the chief executive decides to grant the application for training approval, the chief executive must grant the approval, in the approved form, to the applicant within 10 days after making the decision.

33L Notice of refusal of application

- (1) If the chief executive decides to refuse the application for training approval, the chief executive must give written notice to the applicant of the decision within 10 days after making the decision.
- (2) The notice must state—
 - (a) the reasons for the refusal; and
 - (b) that the person may appeal against the decision under part 11 of the Act.

Division 5 Suspension and cancellation of training approval**33M Grounds for suspension or cancellation of approval**

- (1) The chief executive may, on the grounds mentioned in subsection (2), suspend or cancel a training approval.
- (2) The grounds are as follows—
 - (a) the holder of the training approval has contravened the Act or this regulation, whether or not the holder has been charged with, or convicted of, an offence;
 - (b) the approval was—
 - (i) issued in error; or
 - (ii) issued because of a false or misleading document or representation; or
 - (iii) obtained in another improper way.

33N Procedure for suspension or cancellation

- (1) Before taking action under section 33M(1), the chief executive must give the holder of the training approval a written notice that—
 - (a) states the action proposed to be taken under section 33M(1); and
 - (b) states the grounds for the proposed action; and

- (c) outlines the facts and circumstances forming the basis for the grounds; and
 - (d) if the proposed action is suspension of the training approval—states the proposed period of the suspension; and
 - (e) invites the holder to show, within a stated period of at least 28 days, why the proposed action should not be taken.
- (2) If, after considering all representations made within the stated period, the chief executive still considers grounds to take the proposed action exist, the chief executive may—
 - (a) if the notice stated a proposal to suspend the training approval—suspend the approval for a period no longer than the stated period; or
 - (b) if the notice stated a proposal to cancel the training approval—cancel or suspend the approval.
- (3) The chief executive must, by written notice, inform the holder about the decision.
- (4) A notice under subsection (3) must be given within 5 days after the chief executive makes the decision.
- (5) The chief executive must give a copy of the notice under subsection (3) to the registered training organisation for which the holder provides training and assessment.
- (6) If the chief executive decides to suspend or cancel the training approval, the notice under subsection (3) must state—
 - (a) the reasons for the decision; and
 - (b) that the holder may appeal against the decision under part 11 of the Act.
- (7) The decision takes effect on the later of the following—
 - (a) the day the notice under subsection (3) is given to the holder;
 - (b) the day stated in that notice.

330 Immediate suspension of approval

- (1) This section applies if the chief executive reasonably believes—
 - (a) a training approval was—
 - (i) issued in error or because of a false or misleading document or representation; or
 - (ii) obtained in another improper way; and
 - (b) a person may be exposed to substantial risks to his or her health or safety if urgent action to suspend the approval is not taken.
- (2) The chief executive may, by notice under subsection (3), (*immediate suspension notice*) immediately suspend the approval.
- (3) The immediate suspension notice must state the following—
 - (a) that the training approval is suspended;
 - (b) the grounds for the suspension;
 - (c) an outline of the facts and circumstances forming the basis of the grounds;
 - (d) the immediate suspension has effect until the later of the following—
 - (i) 14 days after the date of the immediate suspension notice; or
 - (ii) if, within that period of 14 days, a notice is given under section 33N(1) to the holder—when a decision of the chief executive relating to the proposed action to suspend or cancel the approval takes effect under section 33N(7);
 - (e) that the holder may appeal against the decision to immediately suspend the training approval under part 11 of the Act.
- (4) The chief executive must give a copy of the immediate suspension notice to the registered training organisation for which the holder provides training and assessment.

33P When immediate suspension has effect until

- (1) This section applies if an immediate suspension notice is given to the holder of a training approval.
- (2) The suspension has effect until the later of the following—
 - (a) 14 days after the immediate suspension notice is given; or
 - (b) if, within that period of 14 days, a notice under section 33N(1) is given to the holder—when a decision of the chief executive relating to the proposed action to suspend or cancel the approval takes effect under section 33N(7).

Part 5 Certificates and licences**Division 1 Definitions****34 Definitions for pt 5**

In this part—

certificate means any of the following—

- (a) a certificate of registration of registrable plant;
- (b) a certificate of registration of registrable plant design;
- (c) an earthmoving or particular crane work certificate;
- (d) a certificate of authority of appointment of a workplace health and safety officer;
- (e) a certificate of appointment as an accredited provider;
- (f) a bonded asbestos removal certificate;
- (g) a certificate to perform a prescribed activity.

licence means a licence to perform a class of high risk work.

variation of a licence means a variation of a licence—

- (a) to endorse another class of high risk work on the licence; or
- (b) to remove a class of high risk work from the licence.

Division 1A Applications for certificates, licences and variations of licences

Subdivision 1 Certificates, licences and variations of licences generally

35 How to apply for a certificate, other than an earthmoving or particular crane work certificate

- (1) An application for a certificate, other than an earthmoving or particular crane work certificate, must—
 - (a) be made to the chief executive in the approved form; and
 - (b) be supported by enough information to enable the chief executive to decide the application; and
 - (c) be accompanied by—
 - (i) the fee under schedule 1 for the application; and
 - (ii) evidence, satisfactory to the chief executive, of the applicant's identity, including date of birth; and
 - (iii) an assessment summary complying with section 24(4)(a) to (c) for the applicant for the unit of competency that relates to the application; and
 - (iv) a statement of attainment for the applicant for the unit of competency, issued by a registered training organisation within 60 days before the application is made.
- (2) Subsection (3) applies if an assessment summary is required to be included in an application for a bonded asbestos removal certificate.
- (3) The chief executive may, for the application, exempt the person from the requirement if the chief executive is satisfied the applicant—

- (a) is a competent person under section 29F(2); and
 - (b) has performed asbestos removal work in the last 5 years; and
 - (c) is competent to perform work to remove bonded asbestos containing material.
- (4) Subsection (5) applies if an assessment summary is required to be included in an application for a certificate of authority of appointment of a workplace health and safety officer.
- (5) The chief executive may, for the application, exempt the person from the requirement if the chief executive is satisfied the applicant has at least the level of competence required for the unit of competency to which the assessment summary relates.

36 How to apply for an earthmoving or particular crane work certificate

- (1) This section applies to an application for an earthmoving or particular crane work certificate for an earthmoving or particular crane occupation.

Note—

An earthmoving or particular crane work certificate is for a single earthmoving or particular crane occupation.

- (2) The applicant must not already hold an earthmoving or particular crane work certificate, or a corresponding authority to an earthmoving or particular crane work certificate, for the occupation, whether or not the certificate or corresponding authority has been suspended.
- (3) The application must—
 - (a) be made to the chief executive in the approved form; and
 - (b) be supported by enough information to enable the chief executive to decide the application; and
 - (c) be accompanied by—
 - (i) the fee under schedule 1 for the application; and
 - (ii) evidence, satisfactory to the chief executive, of the applicant's identity, including date of birth; and

- (iii) an assessment summary under section 24(4) for the applicant, in the unit of competency for the earthmoving or particular crane occupation to which the application relates; and
 - (iv) a statement of attainment for the unit of competency for the earthmoving or particular crane occupation issued by a registered training organisation within 60 days before the application is made.
- (4) If the chief executive is satisfied the applicant has at least the level of competence required for the unit of competency, the chief executive may, for the application, exempt the person from the requirements under subsection (3)(c)(iii) and (iv).
- (5) The chief executive may require the applicant to give the chief executive any further information the chief executive reasonably requires to decide the application.
- (6) A requirement under subsection (5) may state a reasonable period, of at least 28 days, by which the stated further information must be given to the chief executive.

36A Eligibility to obtain particular licence classes

- (1) To be eligible to obtain the licence class basic rigger, a person must hold—
 - (a) the licence class dogger or a corresponding authority to the licence class; or
 - (b) a summary, and statement of attainment, for the unit of competency for the class of high risk work dogger.
- (2) To be eligible to obtain the licence class intermediate rigger, a person must hold—
 - (a) the licence class basic rigger or a corresponding authority to the licence class; or
 - (b) a summary, and statement of attainment, for the unit of competency for the class of high risk work basic rigger.
- (3) To be eligible to obtain the licence class advanced rigger, a person must hold—

- (a) the licence class intermediate rigger or a corresponding authority to the licence class; or
 - (b) a summary, and statement of attainment, for the unit of competency for the class of high risk work intermediate rigger.
- (4) To be eligible to obtain the licence class intermediate scaffolder, a person must hold—
 - (a) the licence class basic scaffolder or a corresponding authority to the licence class; or
 - (b) a summary, and statement of attainment, for the unit of competency for the class of high risk work basic scaffolder.
- (5) To be eligible to obtain the licence class advanced scaffolder, a person must hold—
 - (a) the licence class intermediate scaffolder or a corresponding authority to the licence class; or
 - (b) a summary, and statement of attainment, for the unit of competency for the class of high risk work intermediate scaffolder.
- (6) To be eligible to obtain the licence class intermediate boiler operator, a person must hold—
 - (a) the licence class basic boiler operator or a corresponding authority to the licence class; or
 - (b) a summary for the unit of competency for the class of high risk work basic boiler operator.
- (7) To be eligible to obtain the licence class advanced boiler operator, a person must hold—
 - (a) the licence class intermediate boiler operator or a corresponding authority to the licence class; or
 - (b) a summary for the unit of competency for the class of high risk work intermediate boiler operator.
- (8) In this section—

summary means an assessment summary complying with section 17(4).

37 How to apply for a licence or variation of a licence to endorse another class of high risk work

- (1) This section applies to an application for—
 - (a) a licence; or
 - (b) a variation of a licence to endorse another class of high risk work on the licence.
- (2) The applicant must not already hold the licence or licence class to which the application relates or, subject to section 37A, a corresponding authority to the licence or licence class, whether or not the licence, licence class or corresponding authority has been suspended.
- (3) The application must—
 - (a) be made to the chief executive in the approved form; and
 - (b) be made by the applicant in person; and
 - (c) be supported by enough information to enable the chief executive to decide the application; and
 - (d) be accompanied by—
 - (i) the fee under schedule 1 for the application; and
 - (ii) evidence, satisfactory to the chief executive, of the applicant's identity, including date of birth; and
 - (iii) an assessment summary complying with section 17(4) for the applicant, in the unit of competency for the class of high risk work to which the application relates; and
 - (iv) a statement of attainment for the unit of competency for the class of high risk work issued by a registered training organisation within 60 days before the application is made.
- (4) If the chief executive is satisfied the applicant has at least the level of competence required for the unit of competency, the chief executive may, for the application, exempt the person from the requirements under subsection (3)(d)(iii) and (iv).
- (5) The chief executive may require the applicant to give the chief executive any further information the chief executive reasonably requires to decide the application.

- (6) A requirement under subsection (5) may state a reasonable period, of at least 28 days, by which the stated further information must be given to the chief executive.

37A If applicant for licence or variation of a licence holds a corresponding authority to licence or licence class

- (1) This section applies if an applicant for a licence or for a variation of a licence to endorse another class of high risk work on the licence holds a corresponding authority to the licence or to the licence class to which the application relates.
- (2) The chief executive must not issue the licence or licence class unless the recognised authority has advised the chief executive that the corresponding authority is validly held.
- (3) Without limiting the things that must accompany the application, the application must be accompanied by written authority given by the applicant to the recognised official who issued the corresponding authority to cancel or otherwise end the corresponding authority.

38 How to apply for a variation of a licence to remove a class of high risk work

An application for a variation of a licence to remove a class of high risk work from a licence must—

- (a) be made to the chief executive in the approved form; and
- (b) be supported by enough information to enable the chief executive to decide the application.

38A Refusal to grant licence or variation for applicant's misconduct

- (1) This section applies to an application for—
- (a) a licence; or
- (b) a variation of a licence to endorse another class of high risk work on the licence.
- (2) The chief executive may refuse to grant the application if, within the 2 years immediately before the application is made, the applicant had a licence or licence class to which the

application relates, or a corresponding authority to the licence or licence class, suspended or cancelled because the licence, licence class or corresponding authority was—

- (a) issued because of a document or representation made by or for the applicant that was false or misleading; or
- (b) obtained in another improper way by conduct of the applicant.

38B Refusal to grant certificate, licence or variation—false assessment summary

- (1) This section applies to an application for—
 - (a) a certificate; or
 - (b) a licence; or
 - (c) a variation of a licence to endorse another class of high risk work on the licence.
- (2) The chief executive may refuse to grant the certificate, licence or variation if a person who performed an assessment summary that is relied on for the application has, within 5 years immediately before the application is made, been charged with or convicted of an offence against section 33G.
- (3) Subsection (2) does not apply if the charge is withdrawn or dismissed.
- (4) Despite subsection (2), the chief executive may grant the certificate, licence or variation if the chief executive reasonably believes the assessment summary is satisfactory in the particular case.

38C Refusal to grant earthmoving or particular crane work certificate for applicant's misconduct

- (1) This section applies to an application for an earthmoving or particular crane work certificate.
- (2) The chief executive may refuse to grant the application if, within 2 years immediately before the application is made, the applicant had an earthmoving or particular crane work certificate, or a corresponding authority to an earthmoving or

particular crane work certificate, suspended or cancelled because the certificate or corresponding authority was—

- (a) issued because of a document or representation made by or for the applicant that was false or misleading; or
- (b) obtained in another improper way by conduct of the applicant.

38D Refusal of application for lack of competence or for misconduct

- (1) This section applies to an application for—
 - (a) a certificate, other than a certificate of registration of registrable plant or a certificate of registration of registrable plant design; or
 - (b) a licence; or
 - (c) a variation of a licence to endorse another class of high risk work on the licence.
- (2) The chief executive may refuse the application if the chief executive reasonably believes that—
 - (a) the applicant is not competent to perform the work or function that may be performed under the certificate or licence if the application were granted; or
 - (b) an assessment summary or statement of attainment relied on for the application was—
 - (i) issued in error or because of a representation that was false or misleading; or
 - (ii) obtained in another improper way.

38E Refusal of applications for particular certificates

- (1) This section applies to an application for—
 - (a) a certificate of appointment as an accredited provider; or
 - (b) a certificate of authority of appointment of a workplace health and safety officer; or
 - (c) a certificate to perform a prescribed activity; or

- (d) a bonded asbestos removal certificate.
- (2) The chief executive must refuse to grant the application if the applicant already holds a certificate of the same type.
- (3) The chief executive may refuse to grant the application if the chief executive has cancelled a certificate of the same type within 2 years immediately before the application is made because the certificate was—
 - (a) issued because of a document or representation made by or for the applicant that was false or misleading; or
 - (b) obtained in another improper way by conduct of the applicant.

38F Chief executive to decide application within 28 days

- (1) The chief executive must decide an application for a certificate, licence or variation of a licence within 28 days after the application is made.
- (2) However, if the chief executive requires the applicant to give the chief executive further information under section 36(5) or 37(5), the chief executive must decide the application within a reasonable period, but within 28 days, after receiving the information.

38G Grant of certificate, licence or variation of a licence

If the chief executive decides to grant an application for a certificate, licence or variation of a licence, the chief executive must grant the certificate, licence or variation in the approved form to the applicant within 10 days after making the decision.

38H Notice of refusal of application

- (1) If the chief executive decides to refuse an application for a certificate, licence or variation of a licence, the chief executive must give written notice to the applicant (*notice of refusal*) of the decision within 10 days after making the decision.

- (2) The notice of refusal must state—
 - (a) the reasons for the refusal; and
 - (b) that the person may appeal against the decision under part 11 of the Act.

38I Grant of certificate, licence or variation of licence on conditions

- (1) The chief executive may grant a certificate, licence or variation of a licence on conditions the chief executive considers appropriate.
- (2) This section does not apply to a variation of a licence to remove a class of high risk work from the licence.

38J Term of licence

- (1) A licence to perform a class of high risk work is for a term of 5 years.
- (2) For subsection (1), it is irrelevant that the licence is endorsed with another class of high risk work after the licence was granted.

Example—

A licence is granted on 1 January 2010. A variation of the licence is made on 1 March 2010. The licence ends at midnight on 1 January 2015.

Subdivision 1A Renewal of licences

38K When licence may be renewed

- (1) An application for renewal of a licence may only be made within 6 months before the licence ends and not more than 1 year after the licence ends.
- (2) The renewal of a licence, on an application made under subsection (1) after the licence ends, does not have the effect of retrospectively licensing the holder of the licence.

38L How to apply for renewal of a licence

- (1) An application for renewal of a licence must—
 - (a) be made to the chief executive in the approved form; and
 - (b) be made by the applicant in person; and
 - (c) be accompanied by—
 - (i) evidence, satisfactory to the chief executive, of the applicant's identity; and
 - (ii) the fee under schedule 1 for the application.
- (2) The chief executive may require the applicant to give the chief executive any further information the chief executive reasonably requires to decide the application.
- (3) A requirement under subsection (5) may state a reasonable period, of at least 28 days, by which the stated further information must be given to the chief executive.

38M Renewal of licences

If the chief executive is satisfied the applicant for renewal of a licence has complied with section 38L, the chief executive must renew the licence unless the chief executive must refuse the application under section 38N.

38N Refusal to renew licence for lack of competence

The chief executive must refuse an application for renewal of a licence if the chief executive considers the applicant is no longer competent to perform the class of high risk work to which the licence relates without exposing the applicant or someone else to risks to his or her health or safety.

39 Notice of refusal of application

- (1) If the chief executive decides to refuse an application for renewal of a licence, the chief executive must give written notice to the applicant about the decision within 10 days after making the decision.
- (2) The notice must state—

- (a) the reasons for the refusal; and
- (b) that the person may appeal against the decision under part 11 of the Act.

Subdivision 2 Provisions about certificates of registration of registrable plant design

39A Application of sdiv 2

This subdivision applies to certificates of registration of registrable plant design.

39B Definitions for sdiv 2

In this subdivision—

design verifier, for a design of plant, means a person who has acquired by qualifications or design experience the knowledge and skills to accurately state that the design, or the part of the design for which a design verification statement is to be made, complies with a particular technical standard or engineering principles.

engineering principles means principles, stated or outlined in an engineering, mathematical or scientific text, relevant to safe plant design, commonly used in professional engineering practice.

technical standard, for a design of plant, means a standard published by—

- (a) the chief executive; or
- (b) Standards Australia; or
- (c) another organisation that publishes standards about the design of plant.

Examples of paragraph (c)—

- American National Standards Institute
- American Society of Mechanical Engineers
- Canadian Standards Association

- International Standards Organisation
- Europäische Norm (European Standard)

39C Application for certificate of registration of registrable plant design

An application for a certificate of registration of registrable plant design must be accompanied by—

- (a) a statement in the approved form by a design verifier for the design stating (a *design verification statement*)—
 - (i) either—
 - (A) if the technical standard, or engineering principles, if any, complied with to produce the design or the part of the design for which the statement is made have a title—the title; or
 - (B) otherwise—a way of identifying the technical standard or engineering principles; and
 - (ii) that the design, or the part of the design, complies with the technical standard or engineering principles; and
- (b) representational drawings—
 - (i) on paper not larger than A3; or
 - (ii) in electronic form that when printed will be not larger than A3; and
- (c) the fee under schedule 1, section 3.

39D Prohibitions relating to design verification statements

- (1) An applicant for a certificate of registration of registrable plant design must not allow another person to make a design verification statement for any part of the design that the other person was involved in designing.

Maximum penalty—20 penalty units.

- (2) A person must not make a design verification statement for any part of a design of plant that the person was involved in designing.

Maximum penalty—20 penalty units.

39E Chief executive may ask for additional information for registration

- (1) The chief executive may, in writing, require an applicant for a certificate of registration of registrable plant design to give the chief executive any of the following additional information—
- (a) detailed drawings;
 - (b) design calculations;
 - (c) operating instructions;
 - (d) control system diagrams;
 - (e) the sequence of operation of the controls;
 - (f) maintenance requirements;
 - (g) a statement of the limits on the use of the plant;
 - (h) if the design was produced using a technical standard other than a Standards Australia standard—a copy of the standard;
 - (i) if the design was produced using engineering principles—a copy of the engineering principles.
- (2) The applicant must give the chief executive the information about the design, in English, within—
- (a) 10 days after the requirement is made; or
 - (b) any further time the chief executive allows.
- (3) The chief executive may refuse the application if the applicant does not comply with the requirement.

39F Chief executive may require information from certificate holder

- (1) The chief executive may, in writing, require the holder of a certificate of registration of registrable plant design to give the

chief executive any of the information mentioned in section 39E(1).

- (2) The holder must give the chief executive the information, in English, within 28 days after the requirement is made.
- (3) The holder must comply with the requirement unless the holder has a reasonable excuse.

Maximum penalty for subsection (3)—20 penalty units.

Subdivision 3 Provisions about certificates of registration of registrable plant that is mobile crane or tower crane

39G Application of sdiv 3

This subdivision applies to certificates of registration of registrable plant that is a mobile crane or tower crane specified in schedule 3.

39H Definitions for sdiv 3

In this subdivision—

certificate of registration of a mobile crane or tower crane means a certificate of registration of registrable plant that is a mobile crane or tower crane specified in schedule 3.

competent person—

- (a) for an inspection of a mobile crane or tower crane that is 10 years old or a multiple of 10 years—means an engineer; or
- (b) for any other inspection of a mobile crane or tower crane—means a person who—
 - (i) has a sound knowledge of relevant Australian Standards, relevant codes of practice and other relevant legislation; and
 - (ii) has a sound knowledge of, and competence in, the risk management process for the erection,

operation, maintenance, repair, alteration and dismantling of cranes; and

- (iii) has acquired, through training, qualifications or experience, the necessary skills to design procedures for the inspection, maintenance and repair of the crane.

39I Application for certificate of registration of a mobile crane or tower crane

An application for a certificate of registration of a mobile crane or tower crane must—

- (a) state the age of the mobile crane or tower crane; and
- (b) contain a statement by the owner of the crane that—
 - (i) during the period of 1 year before the application was made, the crane has been maintained in accordance with the instructions of the designer and manufacturer, and with relevant Australian Standards, relevant codes of practice and other relevant legislation; and
 - (ii) within 1 year before the application was made, the crane has been inspected by a competent person who has certified that—
 - (A) the crane has been maintained in accordance with the instructions of the designer and manufacturer, and with relevant Australian Standards, relevant codes of practice and other relevant legislation; and
 - (B) the crane is safe to use; and
- (c) state the name, address, contact details and qualifications of the competent person; and
- (d) state the date the competent person inspected the crane.

39J Application under s 39I if engineer can not inspect because of unforeseeable circumstances

- (1) This section applies, despite section 39I(b)(ii), if—

- (a) an application is made under that section for a certificate of registration of a mobile crane or tower crane; and
 - (b) the application should include a statement about a certification by an engineer in relation to an inspection of the crane but does not include the statement.
- (2) If the chief executive is satisfied the application can not contain the statement mentioned in subsection (1)(b) because the crane could not be inspected due to unforeseeable circumstances, the chief executive may, for the application, accept a statement under section 39I(b)(ii) that a competent person, other than an engineer, has certified to the matters mentioned in the subparagraph.

Example of unforeseeable circumstances—

A crane is used at a high rise construction site and the period for which the crane is required at the site extends beyond the time by which the inspection is due because of prolonged unseasonal wet weather that prevents the use of the crane.

- (3) This section expires on 31 January 2011.

Division 2 Renewal of certain certificates

40 Definition for div 2

In this division—

certificate means—

- (a) a certificate of registration of registrable plant; or
- (b) a certificate of authority for appointment as a workplace health and safety officer; or
- (c) a bonded asbestos removal certificate.

41 Renewal of certificate

- (1) The holder of a certificate may apply to the chief executive for its renewal.
- (2) The application must be—
 - (a) made in the approved form; and

- (b) supported by enough information to enable the chief executive to decide the application.

42 Application for renewal before registration ends

An application for renewal of a certificate, other than a certificate of authority of appointment of a workplace health and safety officer, must be made at least 14 days before the certificate ends.

43 Div 1A applies to application for renewal

- (1) Division 1A applies to an application for renewal of a certificate in the same way it applies to an application for a certificate.
- (2) However, the chief executive may refuse an application for renewal of a certificate if the certificate was—
 - (a) issued in error or because of a document or representation that is false, misleading or omits a material particular; or
 - (b) obtained or made in another improper way.

Division 3 Replacement and surrender of certificates and licences

45 Replacement of certificate or licence

- (1) The holder of a lost, damaged, destroyed or stolen certificate or licence may apply to the chief executive, in the approved form, for a replacement certificate or licence.
- (2) If the application relates to an earthmoving or particular crane work certificate, the application must be accompanied by—
 - (a) evidence, satisfactory to the chief executive, of the applicant's identity; and
 - (b) a statutory declaration stating the circumstances in which the certificate was lost, damaged, destroyed or stolen; and

- (c) the fee under schedule 1 for the application.
- (3) If the application relates to a licence, the application must—
 - (a) state the circumstances in which the licence was lost, damaged, destroyed or stolen; and
 - (b) be accompanied by—
 - (i) evidence, satisfactory to the chief executive, of the applicant's identity; and
 - (ii) the fee under schedule 1 for the application.
- (4) The chief executive may replace the certificate or licence if the chief executive is satisfied it has been lost, damaged, destroyed or stolen.

46 Surrender of certificate or licence

- (1) The holder of a certificate or licence may surrender it by notice, in the approved form, given to the chief executive.
- (2) The notice must be accompanied by the certificate or licence.
- (3) The surrender of the certificate or licence takes effect—
 - (a) on the day on which the notice is given; or
 - (b) if a later day is stated in the notice—on the later day.

Division 4 Suspension and cancellation of certificates and licences

46A Grounds for suspension or cancellation

- (1) The chief executive may, on any of the grounds mentioned in subsection (2)—
 - (a) suspend or cancel a certificate, licence or licence class; or
 - (b) for a corresponding authority to an earthmoving or particular crane work certificate, licence or licence class—recommend to the recognised official who issued the authority that the official suspend or cancel the authority.

- (2) The grounds are as follows—
- (a) the holder of the certificate, licence, licence class or corresponding authority—
 - (i) has contravened the Act or this regulation, whether or not the holder has been charged with, or convicted of, an offence; or
 - (ii) has not complied with a condition of the certificate, licence or licence class; or
 - (iii) has not taken reasonable precautions or exercised proper diligence in performing the work, activity or function for which the certificate, licence, licence class or corresponding authority was granted;
 - (b) the certificate, licence, licence class or corresponding authority was—
 - (i) issued in error; or
 - (ii) issued because of a document or representation that was false or misleading; or
 - (iii) obtained in another improper way;
 - (c) for a certificate to perform a prescribed activity—the person who is to supervise the prescribed activity is medically unfit to supervise the prescribed activity;
 - (d) for a bonded asbestos removal certificate, earthmoving or particular crane work certificate, licence, licence class, or corresponding authority to an earthmoving or particular crane work certificate, licence or licence class—
 - (i) the holder is medically unfit to perform work to which the certificate, licence, licence class or corresponding authority relates; or
 - (ii) the holder no longer has the competence to perform the work to which the certificate, licence, licence class or corresponding authority relates without exposing the holder or another person to risks to his or her health or safety;

- (e) for an earthmoving or particular crane work certificate, licence or licence class, if a statement of attainment for a unit of competency issued by a registered training organisation was given to the chief executive under section 36 or 37 for the application for the certificate or licence—
 - (i) the State has cancelled an agreement entered into by the registered training organisation for the training or the assessment in the accredited course for which the unit of competency is undertaken; or
 - (ii) the registered training organisation has, under the *Vocational Education, Training and Employment Act 2000*, section 32¹³—
 - (A) had its registration as a registered training organisation suspended or cancelled; or
 - (B) had a part of its scope of registration, that covers the statement of attainment, suspended; or
 - (C) had its scope of registration amended so that the scope no longer covers the statement of attainment.
- (3) However, subsection (2)(e)(ii) applies only if the suspension of registration, suspension of part of the scope of registration, or cancellation, was because of incorrect or misleading information.

46B Procedure for suspension or cancellation

- (1) Before taking action mentioned in section 46A(1) (***proposed action***), the chief executive must give the holder of the certificate, licence or corresponding authority a written notice (***show cause notice***) that—
 - (a) states the proposed action; and
 - (b) states the grounds for the proposed action; and

¹³ *Vocational Education, Training and Employment Act 2000*, section 32 (Amending, suspending or cancelling registration without application on particular grounds)

- (c) outlines the facts and circumstances forming the basis for the grounds; and
 - (d) if the proposed action is—
 - (i) suspension of an earthmoving or particular crane work certificate, licence or licence class—states the proposed period of suspension and whether or not retraining relating to the certificate, licence or licence class is to be a condition of the suspension ending; or
 - (ii) suspension of any other certificate or a recommendation that a recognised official suspend the corresponding authority—states the proposed period of the suspension; and
 - (e) invites the holder to show, within a stated period of at least 28 days, why the proposed action should not be taken.
- (2) If, after considering all representations made within the stated period, the chief executive still considers grounds to take the proposed action exist, the chief executive may—
- (a) if the show cause notice stated a proposal to suspend the certificate, licence or licence class—
 - (i) for a stated period with a requirement that retraining is to be undertaken as a condition of the suspension ending—state the condition about retraining and suspend the certificate, licence or licence class for a period no longer than the stated period; or
 - (ii) for a stated period but did not state retraining is to be undertaken as a condition of the suspension ending—suspend the certificate, licence or licence class for a period no longer than the stated period; or
 - (b) if the show cause notice stated a proposal to cancel the certificate, licence or licence class—
 - (i) cancel the certificate, licence or licence class; or
 - (ii) suspend the certificate, licence or licence class, with or without a requirement that retraining is to

be undertaken as a condition of the suspension ending; or

- (c) if the show cause notice stated matters relating to a corresponding authority to an earthmoving or particular crane work certificate, licence or licence class—recommend to the official who issued the corresponding authority that the official suspend or cancel the authority in accordance with the chief executive’s recommendation.
- (3) The chief executive must inform the holder of the decision by written notice.
- (4) The notice must be given within—
 - (a) if a notice was given to the holder under section 46C for the same reason as the show cause notice was given under subsection (1)—5 days after the chief executive makes the decision; or
 - (b) otherwise—10 days after the chief executive makes the decision.
- (5) If the chief executive decides to suspend or cancel the certificate, licence or licence class, or to recommend that a recognised official suspend or cancel the corresponding authority, the notice must state—
 - (a) the reasons for the decision; and
 - (b) that the holder may appeal against the decision under part 11 of the Act.
- (6) The decision takes effect on the later of the following—
 - (a) the day the notice is given to the holder;
 - (b) the day stated in the notice.

46C Immediate suspension of earthmoving or particular crane work certificate, licence or licence class

- (1) This section applies if the chief executive reasonably believes—
 - (a) an earthmoving or particular crane work certificate, licence or licence class was—

- (i) issued in error or because of a document or representation that was false or misleading; or
 - (ii) obtained in another improper way; and
- (b) the holder of the certificate, licence or licence class or someone else may be exposed to substantial risks to his or her health or safety if urgent action to suspend the certificate, licence or licence class is not taken.
- (2) The chief executive may, by notice under subsection (3), immediately suspend the certificate, licence or licence class.
- (3) The notice must state the following—
 - (a) that the certificate, licence or licence class is suspended;
 - (b) the grounds for the suspension;
 - (c) an outline of the facts and circumstances forming the basis of the grounds;
 - (d) the immediate suspension has effect until the later of the following—
 - (i) 14 days after the date of the notice; or
 - (ii) if a show cause notice is given to the holder, within 10 days after the notice is given, for proposed action to suspend or cancel the certificate, licence or licence class—
 - (A) the chief executive decides not to take the proposed action and gives written notice to the holder that the immediate suspension ends; or
 - (B) a decision of the chief executive, on the proposed action, to suspend or cancel the certificate, licence or licence class takes effect;
 - (e) that the holder may appeal against the decision to suspend the certificate, licence or licence class under part 11 of the Act.

46D Further provision about immediate suspension

- (1) This section applies if notice is given, under section 46C, to the holder of a certificate, licence or licence class.
- (2) The suspension has effect until the later of the following—
 - (a) 14 days after the notice is given; or
 - (b) if a show cause notice is given to the holder, within 10 days after the notice is given, to suspend or cancel the certificate, licence or licence class—
 - (i) the chief executive decides not to take the proposed action and gives written notice to the holder that the immediate suspension ends; or
 - (ii) a decision of the chief executive, on the proposed action, to suspend or cancel the certificate, licence or licence class takes effect.

46E Suspension or cancellation of earthmoving or particular crane work certificate, licence or licence class on recommendation of recognised official

- (1) This section applies to an earthmoving or particular crane work certificate, licence or licence class if—
 - (a) a recognised official recommends in writing to the chief executive that the chief executive suspend or cancel the certificate, licence or licence class; and
 - (b) the recommendation is made only after the official—
 - (i) has given the holder of the certificate, licence or licence class a reasonable opportunity to show cause why the certificate, licence or licence class should not be suspended or cancelled; and
 - (ii) has considered all written or oral submissions made by or for the holder to the official about why the proposed action should not be taken.
- (2) The chief executive may suspend or cancel the certificate, licence or licence class without complying with sections 46A and 46B.

- (3) If the chief executive decides to cancel or suspend the certificate, licence or licence class, the chief executive must give the holder written notice about the decision stating—
 - (a) the reasons for the decision; and
 - (b) that the holder may appeal against the decision under part 11 of the Act.
- (4) The suspension or cancellation of the certificate, licence or licence class takes effect on the day stated in the notice, but not earlier than 14 days after the day the notice is given.

46EA Ending of licence if application for corresponding authority

The chief executive may end a licence, or licence class, if the holder of the licence or licence class—

- (a) applied for a corresponding authority to the licence or licence class; and
- (b) authorised the chief executive, in writing, to end the licence or licence class.

46EB Chief executive may advise recognised official of particular matters

- (1) Subsection (2) applies if—
 - (a) a person has applied for—
 - (i) a licence; or
 - (ii) a variation of a licence to endorse another class of high risk work on the licence; and
 - (b) the person holds a corresponding authority to the licence or to the licence class to which the application relates; and
 - (c) the application was accompanied by written authority given by the person to the recognised official to cancel or otherwise end the corresponding authority.
- (2) The chief executive may advise the recognised official of the matters mentioned in subsection (1).

46F Requirement for retraining

- (1) The section applies in relation to a suspension under section 46A(1) of any of the following—
 - (a) an earthmoving or particular crane work certificate;
 - (b) a licence;
 - (c) a licence class.
- (2) If the suspension included a requirement for retraining in relation to the certificate, licence or licence class, the suspension does not end until the chief executive is satisfied the holder of the certificate, licence or licence class has undertaken the training as stated in the notice given to the holder under section 46B(3).

46G Certificate or licence to be returned

- (1) A person whose certificate, licence or licence class is suspended or cancelled must return the certificate or licence to which the suspension or cancellation relates to the chief executive within 14 days after the suspension or cancellation takes effect, unless the person has a reasonable excuse.

Maximum penalty—20 penalty units.

- (2) If a suspended certificate is returned to the chief executive, the chief executive must return the certificate to the holder of the certificate at the end of the period of the suspension.
- (3) If the licence to which a suspension of a licence or licence class relates is returned to the chief executive and the licence is only for 1 licence class, the chief executive must return the licence to the holder of the licence at the end of the period of the suspension.

46H Replacement licence to be issued for remaining licence class

If a licence for more than 1 licence class is not suspended or cancelled in relation to all licence classes, the chief executive must issue a replacement licence for the licence to which the suspension or cancellation relates, for the class or classes of high risk work that are not suspended or cancelled.

Division 5 Obligation of relevant person

46I Way to prevent or minimise risk prescribed

- (1) This section prescribes ways of preventing or minimising exposure to risk from lack of precautions or diligence.
- (2) If work is performed in conducting the business or undertaking of a relevant person under any of the following—
 - (a) a certificate other than—
 - (i) a certificate of registration of registrable plant; or
 - (ii) a certificate of registration of registrable plant design; or
 - (iii) a certificate of authority of appointment of a workplace health and safety officer;
 - (b) a licence;
 - (c) a corresponding authority to an earthmoving or particular crane work certificate, licence or licence class;

the relevant person must not induce the holder of the certificate, licence or authority not to take reasonable precautions or exercise proper diligence in performing the work, activity or function under the certificate, licence, licence class or authority was granted.

Division 6 Miscellaneous

46J Giving information for administering Act

- (1) This section applies if the chief executive reasonably believes—
 - (a) a relevant person is a worker's employer or prospective employer; and
 - (b) the relevant person asks for information mentioned in subsection (2) about the worker; and

- (c) giving the information to the relevant person is consistent with the administration of the Act.
- (2) The chief executive may give the following information to the relevant person—
 - (a) that the worker holds or does not hold a particular valid earthmoving or particular crane work certificate or licence to perform a class of high risk work; and
 - (b) the next action that must be taken by the worker to ensure the worker continues to hold a valid earthmoving or particular crane work certificate or licence to perform a class of high risk work, including, for example, a renewal of the certificate or licence; and
 - (c) the date by which the action must be taken.

46K Particular work encompassed in licence classes

- (1) For each licence class mentioned in schedule 5B, part 1, column 1, column 2 of that part states the work, under another licence class, that is encompassed in the licence class.
- (2) For the licence class mentioned in schedule 5B, part 2, column 1, column 2 of that part states the work, under an earthmoving or particular crane work certificate, that is encompassed in the licence class.

Part 6 Notifiable building and construction work

47 Notification of building and construction work

- (1) This section applies if—
 - (a) building and construction work is to be done; and
 - (b) the cost of the building and construction work is \$80000 or more.

- (2) The person who is mentioned in the *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 74¹⁴ must—
- (a) file an approved form with the Authority or its agent; and
 - (b) pay the appropriate fee (if any).¹⁵
- Maximum penalty—30 penalty units.
- (3) The form must be filed and the fee paid when a levy would be payable under that Act, whether or not a levy is actually payable.¹⁶
- (4) The approved form may be combined in the same document as the form required under the *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 67.¹⁷
- (5) In this section—
approved form includes a written notice containing the information required by the approved form.

48 Exemption from payment of fees

- (1) A person is not required to pay a fee for the notification of building and construction work—
- (c) if the work is to be done under an owner-builder permit; or
 - (d) for a voluntary component of the work to be done by, or for, a nonprofit organisation; or
 - (e) if the work, or part of the work, is to be done for a person who is not substantially engaged in the building

14 *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 74 (Liability for levy)

15 Fees are prescribed in schedule 1.

16 See the *Building and Construction Industry (Portable Long Service Leave) Act 1991*, sections 75 (When levy is payable) and 76 (Government entity to notify authority of building and construction work).

17 *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 67 (Notification of building and construction work)

and construction industry by the person or the person's workers—for the work or part of the work; or

- (f) if the work, or part of the work, is to be done for a government by its workers—for the work or part of the work.
- (2) The person must prove the entitlement to an exemption under subsection (1) to the Authority's satisfaction.
- (3) In this section—

government means a local government, a government entity, or a non-Queensland government entity.

government entity see the *Building and Construction Industry (Portable Long Service Leave) Act 1991*, schedule.¹⁸

nonprofit organisation see the *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 79.¹⁹

non-Queensland government entity see the *Building and Construction Industry (Portable Long Service Leave) Act 1991*, schedule.

owner-builder permit see the *Queensland Building Services Authority Act 1991*, schedule 2.²⁰

substantially engaged in the building and construction industry see the *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 4.²¹

voluntary component see the *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 79.

18 *Building and Construction Industry (Portable Long Service Leave) Act 1991*, schedule (Dictionary)

19 *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 79 (Voluntary performance of building and construction work)

20 *Queensland Building Services Authority Act 1991*, schedule 2 (Dictionary)

21 *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 4 (Meaning of *substantially engaged in the building and construction industry*)

49 Recovering unpaid fees

- (1) This section applies if the Authority reasonably suspects that someone is liable to pay a fee for building and construction work.
- (2) The Authority may, by written notice, require the person to give the information and documents about the work asked for in the notice within a stated reasonable time.
- (3) The person must comply with the notice, unless the person has a reasonable excuse.

Maximum penalty—30 penalty units.

- (4) If the Authority, after considering the information and documents, considers the fee payable for the work is more than the fee that has been paid, the Authority may (by written notice) require the person to pay the unpaid fee within a stated reasonable time.
- (5) The person must comply with the notice, unless the person has a reasonable excuse.

Maximum penalty—30 penalty units.

- (6) The Authority must waive the unpaid fee if satisfied—
 - (a) the cost of the work for which the fee has been paid was a reasonable estimate; and
 - (b) the correct fee for the cost of the work was paid; and
 - (c) the difference between the cost of the work for which the fee was paid and the actual cost of the work is \$20000 or less.

50 Refund of fees

- (1) A person who has paid the fee for building and construction work is entitled to a proportionate refund of the fee if the person satisfies the Authority that the work—
 - (a) has not been done; and
 - (b) is not to be done.
- (2) A person who has paid the fee for building and construction work is entitled to a proportionate refund of the fee if the person satisfies the Authority that—

- (a) the building and construction work for which the fee was paid is wholly or partly completed; and
- (b) the actual cost of the work is at least \$20000 less than the cost for which the fee was paid.
- (3) A person must apply to the Authority, in writing, for a refund within 1 year after the work is finished.
- (4) An application for a refund may be made on more than 1 occasion for the same work.

51 Start and finish of building and construction work

The Authority may decide, for this part, the day on which building and construction work starts and the day on which it finishes.

Part 7 Injuries, illnesses and dangerous events

52 Notifying of particular workplace incidents

- (1) This section applies if any of the following workplace incidents happen at a workplace—
 - (a) an incident resulting in a person suffering a work injury that is a serious bodily injury;
 - (b) a work caused illness;
 - (c) a dangerous event.
- (2) The following persons must give the chief executive notice of the workplace incident—
 - (a) for a workplace where construction work is being performed and a principal contractor has been appointed for the work—the principal contractor;
 - (b) for any other workplace—
 - (i) if the workplace incident does not cause a death—the relevant person; or

Workplace Health and Safety Regulation 1997

- (ii) if the workplace incident causes the death of—
 - (A) a relevant person—the person next in charge of the workplace; or
 - (B) any other person—the relevant person.

Maximum penalty—20 penalty units.

- (3) The person must give the notice—
 - (a) in the approved form within 24 hours after the person becomes aware of the workplace incident happening; or
 - (b) if the workplace incident causes a death—
 - (i) promptly after the person becomes aware of the death; and
 - (ii) in the approved form within 24 hours after the person becomes aware of the death.

Example of a prompt notification under paragraph (b)(i)—

a notification by phone or fax

- (4) If the workplace incident involves a relevant person, or a worker of a relevant person who is an employer, at a workplace where construction work is being performed and a principal contractor has been appointed for the work, the relevant person must—
 - (a) immediately notify the principal contractor that the workplace incident has happened; and
 - (b) give the principal contractor any help the principal contractor may reasonably require to complete an approved form under subsection (3) for the workplace incident.

Maximum penalty—20 penalty units.

- (5) A person required to notify the chief executive under this section does not commit an offence if—
 - (a) the person did not know, and could not reasonably be expected to know, of the workplace incident; or
 - (b) the person—
 - (i) was incapacitated by the work caused illness or work injury; and

- (ii) notifies the chief executive as soon as reasonably practicable after the person is no longer incapacitated.
- (6) A relevant person required to notify the principal contractor and give the principal contractor help under subsection (4) does not commit an offence if—
 - (a) the relevant person did not know, and could not reasonably be expected to know, of the workplace incident; or
 - (b) the relevant person—
 - (i) was incapacitated by the work caused illness or work injury; and
 - (ii) notifies the principal contractor as soon as reasonably practicable after the relevant person is no longer incapacitated.

53 Recording particular workplace incidents

- (1) This section applies if a workplace incident happens at a workplace.
- (2) If the workplace incident results in a person suffering a work injury or a work caused illness, the following persons must make a record of the workplace incident—
 - (a) if the workplace incident happens at a workplace where construction work is being performed and a principal contractor has been appointed for the work—the principal contractor;
 - (b) if the workplace incident happens at any other workplace—
 - (i) if the incident results in a worker suffering a work injury or a work caused illness—the relevant person who is the worker's employer; or
 - (ii) if the incident results in a relevant person suffering a work injury or a work caused illness—the relevant person.

Maximum penalty—20 penalty units.

- (3) If the workplace incident results in a dangerous event, the following persons must make a record of the workplace incident—
- (a) if the workplace incident happens at a workplace where construction work is being performed and a principal contractor has been appointed for the work—the principal contractor;
 - (b) if the workplace incident happens at any other workplace—the relevant person at the workplace.

Maximum penalty—20 penalty units.

- (4) A record under subsection (2) or (3) must be—
- (a) made in the approved form within 3 days after the person required to make the record becomes aware of the workplace incident happening; and
 - (b) kept by the person required to make the record for 1 year after it was made.
- (5) If the workplace incident involves a relevant person, or a worker of a relevant person who is an employer, at a workplace where construction work is being performed and a principal contractor has been appointed for the work, the relevant person must give the principal contractor for the construction work any help the principal contractor may reasonably require to complete a record under subsection (2) or (3) for the workplace incident.

Maximum penalty—20 penalty units.

- (6) A person required to make a record under this section does not commit an offence if—
- (a) the person did not know, and could not reasonably be expected to know, of the workplace incident; or
 - (b) the person—
 - (i) was incapacitated by the work caused illness or work injury; and
 - (ii) makes the record as soon as reasonably practicable after the person is no longer incapacitated.

54 Scene not to be interfered with

- (1) This section applies if—
 - (a) a person suffers serious bodily injury or a work caused illness at a workplace; or
 - (b) a dangerous event happens at a workplace.
- (2) A person must not move or otherwise interfere with any plant or other thing connected with the injury, illness or event without the permission of an inspector or, if an inspector is not available, a police officer.
Maximum penalty—20 penalty units.
- (3) A person does not commit an offence against subsection (2) if the movement or interference is necessary—
 - (a) to save life or relieve suffering; or
 - (b) to prevent injury to a person or property damage.

Part 7A Access—employers doing work that is not construction work**54A Employers—access**

- (1) This section applies to an employer doing²² work, that is not construction work, at a workplace.
- (2) The employer must ensure that—
 - (a) there is appropriate, safe and clear access to and from the workplace for each of the employer's workers working or about to work at the workplace; and
 - (b) all other means of access at the workplace are safe and clear.

Maximum penalty—20 penalty units.

22 See section 3B (References to the doing of work by employer).

Part 10 Noise

68 What is *excessive noise*

- (1) In this part—
excessive noise is a level of noise above—
 - (a) an 8 hour equivalent continuous A-weighted sound pressure level of 85dB(A), referenced to 20µPa;²³ or
 - (b) a C-weighted peak sound pressure level of 140dB(C), referenced to 20µPa.²⁴
- (2) For subsection (1), the sound pressure level is the level determined at the worker's ear without regard to the protection available to a worker wearing hearing protectors, and measured—
 - (a) for an 8 hour equivalent continuous A-weighted sound pressure level of 85dB(A)—under AS/NZS 1269.1;²⁵ or
 - (b) for a C-weighted peak sound pressure level of 140dB(C)—by a sound level meter with a peak detector indicator complying with AS IEC 61672.1.²⁶

69 Preventing risk from exposure to excessive noise

- (1) A relevant person who is an employer must not expose the employer's workers to excessive noise at work.
- (2) Subsection (1) is a workplace health and safety obligation for the Act.

23 The symbol for this sound pressure level is $L_{Aeq,8h}$ of 85dB(A). 'µPa' means micropascals.

24 The symbol for this sound pressure level is $L_{C,peak}$ 140dB. 'µPa' means micropascals.

25 AS/NZS 1269.1 (Occupational noise management—Measurement and assessment of noise immission and exposure)

26 AS IEC 61672.1 (Electroacoustics—Sound level meters—Specifications)

Part 11 Asbestos removal and management

Division 1 Interpretation

69A Definitions for pt 11

In this part—

asbestos management code means NOHSC's document entitled 'Code of Practice for the Management and Control of Asbestos in Workplaces [NOHSC:2018 (2005)]'.

asbestos removal code means NOHSC's document entitled 'Code of Practice for the Safe Removal of Asbestos [NOHSC:2002 (2005)]'.²⁷

Division 2 Prohibitions relating to asbestos

69B Prohibited substances and prohibited ACM

- (1) A relevant person must not use a prohibited substance or prohibited ACM mentioned in schedule 7²⁸ for a prohibited purpose mentioned in that schedule for the substance or material at the relevant person's workplace.
- (2) A relevant person who is an employer must not allow a worker of the employer to use a prohibited substance or prohibited ACM mentioned in schedule 7 for a prohibited purpose mentioned in that schedule for the substance or material at the relevant person's workplace.
- (3) Subsections (1) and (2) are workplace health and safety obligations for the Act.

²⁷ Copies of the codes are available on the department's website <www.deir.qld.gov.au>.

²⁸ Schedule 7 (Prohibited substances, prohibited ACM and prohibited purposes)

69C Performing work on ACM

- (1) A relevant person must not perform work on ACM other than in accordance with the asbestos management code.
- (2) A relevant person who is an employer must not allow a worker of the employer to perform work on ACM other than in accordance with the asbestos management code.
- (3) Subsections (1) and (2) are workplace health and safety obligations for the Act.

69D Removing ACM

- (1) A relevant person must not remove ACM other than in accordance with the asbestos removal code.
- (2) A relevant person who is an employer must not allow a worker of the employer to remove ACM other than in accordance with the asbestos removal code.
- (3) Subsections (1) and (2) are workplace health and safety obligations for the Act.

69E Cleaning ACM

- (1) A relevant person must not use—
 - (a) a power tool or power appliance to clean ACM; or
Examples of paragraph (a)—
 - using an electric sander to clean asbestos-cement sheeting before painting it
 - using an electric wire brush to remove an asbestos gasket from plant
 - (b) a high pressure water process to clean ACM; or
Examples of paragraph (b)—
 - using a water blaster to clean an asbestos-cement sheeting roof
 - using a water blaster to clean up debris left after removing an asbestos-cement sheeting roof
 - (c) compressed air or abrasive blasting to clean—
 - (i) ACM; or

Example of compliance with subparagraph (i)—

using a vacuum cleaner suitable for use with asbestos dust to clean vehicle brake or clutch systems fitted with parts containing asbestos rather than blowing the dust away with compressed air

- (ii) a surface where ACM is present.

Example of noncompliance with subparagraph (ii)—

using compressed air to blow dust from clothing after working with asbestos-cement sheeting

- (2) A relevant person who is an employer must not allow a worker of the employer to use—
 - (a) a power tool or power appliance to clean ACM; or
 - (b) a high pressure water process to clean ACM; or
 - (c) compressed air or abrasive blasting to clean—
 - (i) ACM; or
 - (ii) a surface where ACM is present.
- (3) Subsections (1) and (2) are workplace health and safety obligations for the Act.

Division 3 On-site management of ACM

Subdivision 1 Particular buildings

70 Application of sdiv 1

This subdivision applies to a building to which part 11, division 1,²⁹ as in force from time to time before 1 January 2006 (the *repealed division*), applied if—

- (a) the owner of the building had at any time an obligation to comply with the repealed division; and
- (b) the owner had not complied with the repealed division.

²⁹ The repealed division was part 11 (Asbestos), division 1 (On-site management of asbestos materials).

71 Compliance with asbestos management code

- (1) The owner of the building must comply with the asbestos management code.
- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Subdivision 2 Particular structures**72 Application of sdiv 2**

- (1) This subdivision applies to a structure or a part of a structure that is a workplace only if all or part of the structure was built under an approval given by a local government before 1 January 1990.

Examples for subsection (1)—

- a structure built in 1989
- a structure started in 1989 but completed in 1990
- a structure built in 1990 under an approval given in 1989

- (2) However, this division does not apply to a structure used for domestic residential purposes.

Examples of structures used for domestic residential purposes—

- house
- townhouse
- block of units

73 Compliance with asbestos management code

- (1) The owner of the structure or part must comply with the asbestos management code on or before 1 January 2008.
- (2) However, if a relevant event is proposed for the structure or part before 1 January 2008, the owner must comply with the asbestos management code before the relevant event happens.
- (3) If the relevant event is altering the structure or part or offering the structure or part for sale or lease, subsection (2) applies only to the first time the structure or part is offered for sale or lease.

- (4) Subsections (1) and (2) are workplace health and safety obligations for the Act.

- (5) In this section—

dismantle means systematically dismantle or remove a part of a structure for alteration, maintenance, remodelling, renovation or repair.

relevant event, for a structure or part of a structure, means the structure or part is to be—

- (a) offered for sale or lease; or
- (b) altered; or
- (c) dismantled; or
- (d) demolished.

Division 4 Asbestos removal work

74 Performing asbestos removal work

- (1) A person must not perform asbestos removal work other than in accordance with the asbestos removal code.
- (2) The owner of a structure or place where asbestos removal work is to be performed, or a person engaged by the owner to supervise or arrange for the work to be performed, must comply with the asbestos removal code, part 7.2³⁰ as if the owner or person were a client within the meaning of the asbestos removal code.
- (3) Subsections (1) and (2) are workplace health and safety obligations for the Act.

30 Asbestos removal code, part 7.2 (Responsibilities of clients)

Part 12 Underwater diving work

Division 1 Definitions for part 12

76 Meaning of *underwater diving work*

Underwater diving work means work conducted underwater while breathing compressed gas.

77 Meaning of *construction diving work*

- (1) *Construction diving work* means underwater diving work to assemble, construct, demolish, dismantle, install, clean, inspect, maintain, remove, repair, salvage, sample, search for, photograph, film, video or make a sound recording of a thing, or part of a thing, mentioned in subsection (2).
- (2) For subsection (1), the things are as follows—
 - (a) a building;
 - (b) a bridge;
 - (c) a pile or a structure supported by piles;
 - (d) a jetty, pontoon, wharf, mooring or slipway;
 - (e) a navigational aid;
 - (f) a pipe, cable or tunnel;
 - (g) scaffolding, whether or not for use with a building;
 - (h) a drilling rig;
 - (i) an oil or gas well platform;
 - (j) a weir or the structure or machinery of a dam or other artificial water storage, other than a swimming pool or aquarium;
 - (k) a craft or vehicle for use in, on or above water or land.
- (3) *Construction diving work* includes underwater diving work associated with dredging, reclamation of land or other earthworks.

(4) However, **construction diving work** does not include underwater diving work—

(a) for inspecting, sampling, photographing, filming, videoing or making a sound recording—

(i) for the entertainment or publishing industry; or

(ii) for tourism; or

(iii) for the print or electronic media; or

(iv) for art; or

(v) for genuine scientific research; or

(vi) for scientific management of natural resources; or

Example of subparagraph (vi)—

scientific management of the Great Barrier Reef or fish stocks

(b) for inspecting, sampling, photographing, filming, videoing or making a sound recording of—

(i) an artefact to decide its cultural heritage significance under the *Queensland Heritage Act 1992*;

(ii) an historic relic or historic shipwreck under the *Historic Shipwrecks Act 1976* (Cwlth); or

(c) for photographing, filming, videoing or making a sound recording while and for the purpose of conducting recreational diving or recreational technical diving, or training to go recreational diving or recreational technical diving; or

(d) for photographing, filming, videoing or making a sound recording of persons doing recreational diving or recreational technical diving if the photographing, filming, videoing or sound recording is to be used for a souvenir; or

(e) done in a marina or the ocean for cleaning, inspecting, maintaining or searching for a vessel or mooring solely or mainly used in the tourism industry.

Examples of vessels used in the tourism industry—

- glass bottom boats used for tours of a reef
 - boats used to transport tourists to a reef or island
 - yachts hired to sail around islands
 - fishing charter boats
- (5) It is immaterial whether or not a thing mentioned in subsection (2) is floating or wrecked.

Division 2 All underwater diving work—medical fitness to dive

78 Requirements about certificate of medical fitness to dive

- (1) An employer, self-employed person or other person who conducts a business or undertaking must not—
- (a) do underwater diving work as a work activity performer³¹ for the business or undertaking unless subsection (2) is complied with; or
 - (b) allow a work activity performer for the business or undertaking to do underwater diving work unless subsection (2) is complied with.
- (2) For subsection (1)—
- (a) the employer, self-employed person or other person must hold an original or copy of a certificate of medical fitness to dive³² for the work activity performer for the business or undertaking that appears to be current; and
 - (b) the work the work activity performer is to do must not be contrary to any limitations on diving stated in the certificate.
- (3) The employer, self-employed person or other person must keep the certificate or copy for at least 1 year after the certificate stops being current.

31 See schedule 9, definition *work activity performer*.

32 See schedule 9, definition *certificate of medical fitness to dive*.

- (4) Subsections (1) and (3) are workplace health and safety obligations for the Act.

Note—

See section 24³³ of the Act for the penalty for failing to discharge the obligations.

- (5) In this section—

current for a certificate of medical fitness to dive means—

- (a) the certificate is not replaced or revoked and has not expired; and
- (b) is not more than 1 year old.

79 Contents of certificate of medical fitness to dive

- (1) A certificate of medical fitness to dive must show its date of issue and the certificate holder's name.
- (2) If the certificate holder is at least 18, the certificate must also show that—
 - (a) the holder is medically fit to dive in accordance with the relevant fitness criteria; or
 - (b) subject to a limitation on diving stated in the certificate, the holder is medically fit to dive in accordance with the relevant fitness criteria.
- (3) If the certificate holder is under 18, and no limitations on diving are imposed on medical grounds, the certificate must also show that—
 - (a) apart from being under 18, the holder is medically fit to dive in accordance with the relevant fitness criteria; and
 - (b) no limitations on diving are needed even though the holder is under 18.
- (4) If the certificate holder is under 18, and limitations on diving are imposed on medical grounds, the certificate must also show—

33 Section 24 (Discharge of obligations) of the Act

- (a) that subject to the limitations on diving stated in the certificate, the holder is medically fit to dive in accordance with the relevant fitness criteria; and
 - (b) any limitations imposed because the holder is under 18.
- (5) In this section—

relevant fitness criteria means the fitness criteria stated in AS/NZS 2299, part 1, appendix K, paragraph K4³⁴ as published on 5 March 1999.

Division 3 Underwater diving work other than conducting recreational diving or recreational technical diving

Note—

See also division 2 (All underwater diving work—medical fitness to dive).

Subdivision 1 Preliminary

80 Application of div 3

This division does not apply to underwater diving work consisting of conducting recreational diving or recreational technical diving.

81 Meaning of *competent person* for construction diving work

A person is a *competent person* for construction diving work if the person holds an ADAS diving certificate under which the diving involved in the work may be done.

³⁴ AS/NZS 2299 (Occupational diving operations), part 1 (Standard operational practice), appendix K (Guidance for medical practitioners), paragraph K4 (Fitness criteria)

82 Meaning of *competent person* for other underwater diving work

- (1) A person described in any of the following sections is a ***competent person*** for underwater diving work other than construction diving work—
 - (a) section 83;
 - (b) section 84(1) or (2);
 - (c) section 85;
 - (d) section 86;
 - (e) section 86AA.
- (2) However, section 86 does not apply in relation to the use of the words ‘competent person’ in section 86AC(2) or 86AD(2)(b).³⁵
- (3) This subsection and subsection (1)(e) expire on 31 October 2008.

83 Competent person for s 82—holder of ADAS diving certificate for the diving

For section 82, the person is the holder of an ADAS diving certificate under which the diving involved in the underwater diving work may be done.

84 Competent person for s 82—holder of certification under Australian Qualifications Framework

- (1) For section 82, the person is the holder of a statement of attainment from a registered training organisation in relation to training that—
 - (a) is relevant in a substantial way to the work; and
 - (b) is provided within the registered training organisation’s scope of registration.

³⁵ Section 86AC (Process to be carried out before work starts) or 86AD (Process to be carried out each time there is a significant change)

- (2) For section 82, the person—
- (a) is the holder of a statement of attainment from a registered training organisation in relation to training in performing diver rescues—
 - (i) that includes the elements of competency mentioned in subsection (3); and
 - (ii) is provided within the registered training organisation's scope of registration; and
 - (b) has acquired through training, qualifications or experience, the knowledge and skills mentioned in the elements of competency and performance criteria in AS 2815, parts 1 to 4³⁶ relevant to the underwater diving work.
- (3) For subsection (2)(a)(i), the elements of competency are as follows—
- (a) demonstrate knowledge of diver physiology;
 - (b) demonstrate diver rescue skills;
 - (c) use supplemental oxygen.

85 Competent person for s 82—holder of certificate for AS 4005.2 subject areas

For section 82, the person—

- (a) is the holder of a certificate showing that the person has successfully finished training in the subject areas mentioned in AS 4005, part 2³⁷ from a recreational scuba training organisation; and
- (b) has acquired through training, qualifications or experience, the knowledge and skills mentioned in the elements of competency and performance criteria in AS 2815, parts 1 to 4 relevant to the underwater diving work.

36 AS 2815 (Training and certification of occupational divers), parts 1 (SCUBA diving to 30m), 2 (Air diving to 30m), 3 (Air diving to 50m) and 4 (Bell diving)

37 AS 4005 (Training and certification of recreational divers), part 2 (Recreational SCUBA dive supervisor)

86 Competent person for s 82—person doing underwater diving work on no more than 28 days in the last 6 months

- (1) For section 82, the person is someone who—
- (a) is a person mentioned in subsection (2) or (3); and
 - (b) is being personally supervised in the water by a person who—
 - (i) is a competent person for construction diving work; or
 - (ii) is described in section 83, 84(1) or (2) or 85; and
 - (c) has acquired, through training, qualifications or experience the knowledge and skills to do the work in a safe way, including a sound knowledge of the following—
 - (i) the application of diving physics;
 - (ii) the use of diving equipment, including emergency equipment;
 - (iii) the use of decompression tables or dive computers;
 - (iv) ways of communicating with a diver during underwater diving work;
 - (v) how to safely perform underwater diving work of the same type as the underwater diving work;
 - (vi) the use, inspection and maintenance of diving equipment and air supply of the same type that is being used for the underwater diving work;
 - (vii) diving physiology and first aid;
 - (viii) provisions of the Act, this regulation or AS/NZS 2299, part 1 relevant to the underwater diving work.
- (2) For subsection (1)(a)—
- (a) the person has done no underwater diving in the 6 months immediately before the underwater diving work is done; and
 - (b) before that 6 months, the person has spent at least 15 hours doing underwater diving, of which at least 8 hours

20 minutes were spent within a depth of 10m above or below the maximum depth at which the underwater diving work is being done.

- (3) Alternatively for subsection (1)(a)—
- (a) the person has done underwater diving work on no more than 28 days in the 6 months immediately before the underwater diving work is done; and
 - (b) at any time, the person has spent at least 15 hours doing underwater diving, of which at least 8 hours 20 minutes were spent within a depth of 10m above or below the maximum depth at which the underwater diving work is being done.

86AA Competent person for s 82—someone who has spent at least 15 hours doing the same type of work as the underwater diving work

- (1) For section 82, the person is someone who—
- (a) has spent at least 15 hours doing underwater diving work of the same type as the underwater diving work mentioned in section 82(1), of which at least 8 hours 20 minutes were spent within a depth of 10m above or below the maximum depth at which that underwater diving work is being or is to be done; and
 - (b) has acquired, through training, qualifications or experience the knowledge and skills to do the work in a safe way, including a sound knowledge of the matters mentioned in section 86(1)(c)(i) to (viii).
- (2) This section expires on 31 October 2008.

Subdivision 2 Proof of competency for underwater diving work other than construction diving work

86AB Proof of competency

- (1) This section applies to underwater diving work other than construction diving work.³⁸
- (2) An employer, self-employed person or other person who conducts a business or undertaking must not—
 - (a) do underwater diving work as a work activity performer for the business or undertaking unless subsection (3) is complied with; or
 - (b) allow a work activity performer for the business or undertaking to do underwater diving work unless subsection (3) is complied with.
- (3) For subsection (2)—
 - (a) the employer, self-employed person or other person must hold proof that the work activity performer for the business or undertaking is a competent person for the work; and
 - (b) the work the work activity performer is to do must not be contrary to any restrictions stated in the proof of competency.
- (4) The employer, self-employed person or other person must keep the proof of competency for at least 1 year after the work done under subsection (2) in reliance on the proof of competency ends.
- (5) Subsections (2) and (4) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligations.

³⁸ For qualifications required for construction diving work, see section 86AM (ADAS diving certificate for the diving is required).

Subdivision 3 Risk assessment and control measure process at particular stages

86AC Process to be carried out before work starts

- (1) This section applies to underwater diving work to be done by an employer, self-employed person or other person who conducts a business or undertaking.³⁹
- (2) Before the work starts, the employer, self-employed person or other person must ensure that the process set out in subsection (3) (the *process*) is carried out by a competent person for the underwater diving work.

Maximum penalty—30 penalty units.

- (3) The process is—
 - (a) identify the hazards associated with the work; and
 - (b) assess the risk of death, illness or injury that may result because of the hazards; and
 - (c) decide on and implement control measures to prevent, or minimise the level of, exposure to the risks.
- (4) The assessment of risk must take into account—
 - (a) the level of competence in underwater diving of the person who is to do the work; and
 - (b) each factor mentioned in AS/NZS 2299, part 1, appendix D, paragraph D2.4.⁴⁰
- (5) In deciding on the control measures, the hierarchy of control measures mentioned in AS/NZS 2299, part 1, appendix D, paragraph D3.2⁴¹ must be taken into account.

39 See section 3BA (References to the doing of work by person who conducts a business or undertaking).

40 AS/NZS 2299 (Occupational diving operations), part 1 (Standard operational practice), appendix D (Hazard identification, risk assessment and control), paragraph D2.4 (Factors for consideration)

41 AS/NZS 2299 (Occupational diving operations), part 1 (Standard operational practice), appendix D (Hazard identification, risk assessment and control), paragraph D3.2 (Control measures)

86AD Process to be carried out each time there is a significant change

- (1) This section applies if the process has been carried out under section 86AC(2).
- (2) Each time there is a change mentioned in subsection (3), the employer, self-employed person or other person who conducts a business or undertaking—
 - (a) if the work has started—must ensure that the work stops immediately; and
 - (b) must not start or restart the work, or allow the work to start or restart, unless a competent person for the underwater diving work, who is out of the water, has carried out the process again.

Maximum penalty—30 penalty units.

- (3) For subsection (2), the change is—
 - (a) a significant change in the way the work is to be done from the way the underwater diving work was to be done when the process was last carried out for the work; or
 - (b) a significant adverse change in the environmental conditions affecting the diving from the conditions prevailing when the process was last carried out for the work.

Examples of adverse changes in environmental conditions—

- reduced underwater visibility resulting from work tasks disturbing sediment
- increased current and surge action

86AE Work not to start or restart unless diver has read, understood and signed record of process

- (1) This section applies if the process has been carried out under section 86AC(2) or section 86AD(2).
- (2) The employer, self-employed person or other person who conducts a business or undertaking must not start or restart the underwater diving work as a work activity performer for the

business or undertaking unless the employer, self-employed person or other person—

- (a) has read and understood the record of the process made under section 86AF; and
- (b) signed an acknowledgement, on the record, that the employer, self-employed person or other person has read the record.

Maximum penalty—30 penalty units.

- (3) The employer, self-employed person or other person must not allow a work activity performer for the business or undertaking to start or restart the underwater diving work unless the work activity performer—
 - (a) has read and understood the record of the process made under section 86AF; and
 - (b) signed an acknowledgement, on the record, that the work activity performer has read the record.

Maximum penalty—30 penalty units.

86AF Record to be kept for each time process is carried out

- (1) This section applies if the process has been carried out under section 86AC(2) or section 86AD(2).
- (2) The employer, self-employed person or other person who conducts a business or undertaking must ensure that a written record is made of the following for the process before the underwater diving work is started or restarted or is allowed to start or restart—
 - (a) the date the process is carried out;
 - (b) the date the work is to start or restart and end;
 - (c) the work;
 - (d) the location of the dive site;
 - (e) the name of each person at the dive site who will be involved in the work;
 - (f) each hazard identified;

(g) for each hazard identified—the assessment of the risk of death, illness or injury that may result because of the hazard;

(h) each control measure decided on.

Maximum penalty—30 penalty units.

(3) The employer or self-employed person or other person who conducts a business or undertaking must—

(a) make the written record of the process available for inspection, out of the water at the dive site, by anyone involved in the work; and

(b) keep the record for at least 1 year after the last day it is used for the work.

Maximum penalty—30 penalty units.

86AG Control measure to be in place and monitored and reviewed

(1) This section applies if a control measure (an *original control measure*) is implemented under this subdivision for a risk.

(2) The employer, self-employed person or other person who conducts a business or undertaking and who implemented the original control measure must ensure that, while the risk exists—

(a) the original control measure is kept in place; or

(b) a different control measure necessary to prevent, or minimise the level of, exposure to the risk is implemented and kept in place.

Maximum penalty—30 penalty units.

(3) The employer, self-employed person or other person who conducts a business or undertaking and who implemented the original control measure must monitor and review the effectiveness of—

(a) the original control measure; or

(b) a different control measure implemented under subsection (2)(b).

Maximum penalty—30 penalty units.

Subdivision 4 Dive safety log

86AH Dive safety log—log must be kept

- (1) An employer, self-employed person or other person who conducts a business or undertaking must ensure that a dive safety log is kept about each dive, in doing underwater diving work, done by a work activity performer for the business or undertaking.

Examples of dives for which information must be recorded in a dive safety log kept by an employer who is an individual—

a dive by a worker or by the employer

Maximum penalty—30 penalty units.

- (2) The dive safety log must be written and comply with section 86AI.

86AI Dive safety log—required information about dives

- (1) The dive safety log must state the following information—
 - (a) the diver's name;
 - (b) the name of any co-diver with whom the dive is done;
 - (c) the name of any dive supervisor;
 - (d) the date and location of the dive;
 - (e) time in;
 - (f) time out;
 - (g) maximum depth of the dive;
 - (h) any incident, problem, discomfort or injury experienced or suffered by the diver;
 - (i) if the dive was done using a dive computer—the dive time;
 - (j) if the dive was done using dive tables—the repetitive dive group, if available, and either bottom time or dive time;

- (k) if the repetitive dive group and surface interval result in a repetitive factor—the surface interval and the repetitive factor.
- (2) If the underwater diving work is done using EANx, the dive safety log must also state the following information—
 - (a) oxygen content of the EANx;
 - (b) maximum operating depth for the EANx.
- (3) If the underwater diving work is done using mixed gas, the dive safety log must also state the following information—
 - (a) oxygen content and nitrogen content, if any, of the mixed gas;
 - (b) maximum operating depth for the mixed gas;
 - (c) minimum operating depth of the bottom mix.
- (4) The information mentioned in this section must be entered in the dive safety log as soon as practicable.

86AJ Dive safety log—diver must sign log

- (1) On completion of each dive in relation to which a dive safety log must be kept, the diver must verify the diver's return from the dive—
 - (a) by signing the dive safety log entry for the diver; or
 - (b) if the log is kept electronically—by entering in the log entry the name of, and a unique identifier for, the diver.

Example of a log kept electronically—

a record kept by computer

Maximum penalty—10 penalty units.

- (2) The signature or entry must be made as soon as practicable.

Example—

The diver's signature in the dive safety log is an important check on whether a diver has returned to the boat. Accordingly, the signature needs to be made as soon as the diver has removed necessary gear and dried the diver's hands. However, conditions in open boats, or numerous dives by the 1 diver in a single day, may make it impracticable to sign the dive safety log until the end of the diver's diving for the day.

86AK Dive safety log—further signing of log

- (1) The employer, self-employed person or other person who conducts a business or undertaking must ensure that a person verifies for the employer, self-employed person or other person, in the way stated in subsection (2), that—
 - (a) the dive safety log entry for the diver has been made as required under section 86AH; and
 - (b) the diver has complied with section 86AJ for the entry.Maximum penalty—20 penalty units.
- (2) The way is—
 - (a) by signing the log entry; or
 - (b) if the log is kept electronically—by entering in the log entry the name of, and a unique identifier for, the person.
- (3) The signature or entry must be made as soon as practicable.

86AL Dive safety log—log to be kept for at least 1 year

The employer or self-employed person or other person who conducts a business or undertaking must keep the dive safety log required under this subdivision for at least 1 year after the last entry in it is made.

Maximum penalty—20 penalty units.

Subdivision 5 Provisions relating only to construction diving work**86AM ADAS diving certificate for the diving is required**

- (1) An employer, self-employed person or other person who conducts a business or undertaking must not—
 - (a) do construction diving work as a work activity performer for the business or undertaking unless subsection (2) is complied with; or

- (b) allow a work activity performer for the business or undertaking to do construction diving work unless subsection (2) is complied with.
- (2) For subsection (1)—
 - (a) the employer, self-employed person or other person must hold an original or copy of an ADAS diving certificate, under which the diving involved in the work may be done, for the work activity performer for the business or undertaking; and
 - (b) the work the work activity performer is to do must not be contrary to any restrictions stated in the certificate.
- (3) The employer, self-employed person or other person must keep the certificate or copy for at least 1 year after the work done under subsection (1) in reliance on the certificate or copy ends.
- (4) Subsections (1) and (3) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligations.

86AN Dive supervisor

- (1) An employer, self-employed person or other person who conducts a business or undertaking must not—
 - (a) do construction diving work as a work activity performer for the business or undertaking unless subsection (2) is complied with; or
 - (b) allow a work activity performer for the business or undertaking to do construction diving work unless subsection (2) is complied with.
- (2) For subsection (1)—
 - (a) someone must have been appointed as the dive supervisor for the work or for the dive site where the work is to be done (the *dive supervisor*); and

- (b) the dive supervisor must—
 - (i) hold an ADAS diving certificate under which the diving involved in the work may be done; and
 - (ii) personally supervise the work from a position out of the water at the dive site; and
 - (iii) be able to communicate directly with each diver being supervised.
- (3) A dive supervisor may supervise more than 1 diver at the same time.
- (4) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

86AO Stand-by diver

- (1) An employer, self-employed person or other person who conducts a business or undertaking must not—
 - (a) do construction diving work as a work activity performer for the business or undertaking unless subsection (2) or (3) is complied with; or
 - (b) allow a work activity performer for the business or undertaking to do construction diving work unless subsection (2) or (3) is complied with.
- (2) For subsection (1)—
 - (a) someone must have been appointed as stand-by diver for the work or for the dive site where the work is to be done (the *stand-by diver*); and
 - (b) the stand-by diver must—
 - (i) be allowed under sections 78 and 86AM to make the dive; and
 - (ii) hold an ADAS diving certificate under which the diving involved in the work may be done; and
 - (iii) be out of the water; and

Workplace Health and Safety Regulation 1997

- (iv) be under the supervision of the dive supervisor; and
 - (v) be fully equipped and otherwise ready to dive to go to the rescue of the diver doing the work; and
 - (vi) be available to rescue the diver.
- (3) Alternatively for subsection (1)—
 - (a) the diver is 1 of only 2 divers who are under the water and under the supervision of the same dive supervisor; and
 - (b) each diver—
 - (i) can clearly see the other diver; and
 - (ii) can immediately go to the rescue of the other diver; and
 - (iii) must not be substantially obstructed from reaching the other diver; and
 - (iv) must be allowed under sections 78 and 86AM to make the dive.
- (4) A stand-by diver can not be the dive supervisor.
- (5) A stand-by diver may be the stand-by diver for some or all of the divers diving under the supervision of the same dive supervisor.
- (6) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

86AP Recompression chamber and qualified operator

- (1) An employer, self-employed person or other person who conducts a business or undertaking must not—
 - (a) do restricted diving work as a work activity performer for the business or undertaking unless subsection (2) is complied with; or

Workplace Health and Safety Regulation 1997

- (b) allow a work activity performer for the business or undertaking to do restricted diving work unless subsection (2) is complied with.
- (2) For subsection (1)—
 - (a) an operational recompression chamber must be at, or near, the dive site where the work is to be done; and
 - (b) a person must be at the dive site or chamber to operate the chamber; and
 - (c) the person must hold an ADAS diving certificate for the category—
 - (i) air diving to 50m (AS 2815, part 3); or
 - (ii) bell diving (AS 2815, part 4).
- (3) For subsection (2)(a), a recompression chamber is operational if—
 - (a) the chamber is fully operational and complies with AS/NZS 2299, part 1, clause 4.2⁴² as published on 5 March 1999, other than clause 4.2.2(f) or 4.2.8; and
 - (b) the equipment mentioned in clause 4.4,⁴³ other than clause 4.4.4, of that standard is available at the chamber.
- (4) For subsection (2)(a), a recompression chamber is near the dive site if a diver could be moved to the chamber in 5 minutes from where the diver doing the work enters the water, if the diver were unconscious when the diver leaves the water.
- (5) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

- (6) In this section—

restricted diving work means construction diving work—

42 AS/NZS 2299 (Occupational diving operations), part 1 (Standard operational practice), clause 4.2 (Chamber design, construction, fittings and services)

43 AS/NZS 2299 (Occupational diving operations), part 1 (Standard operational practice), clause 4.4 (Medical equipment)

- (a) at a depth of over 30m; or
- (b) requiring a decompression stop.

86AQ Recompression chamber not to be operated without appropriate qualifications

- (1) This section applies if an employer, self-employed person or other person who conducts a business or undertaking—
 - (a) is doing construction diving work; and
 - (b) has a recompression chamber under the control of the employer, self-employed person or other person.
- (2) The employer, self-employed person or other person must not—
 - (a) operate the recompression chamber as a work activity performer for the business or undertaking unless subsection (3) is complied with; or
 - (b) allow a work activity performer for the business or undertaking to operate the recompression chamber unless subsection (3) is complied with.
- (3) For subsection (2), the employer, self-employed person or other person must hold an original or copy of an ADAS diving certificate, for the person operating the chamber, for the category—
 - (a) air diving to 50m (AS 2815, part 3); or
 - (b) bell diving (AS 2815, part 4).
- (4) The employer, self-employed person or other person must keep the certificate or copy for at least 1 year after a recompression chamber is operated under subsection (2) in reliance on the certificate or copy.
- (5) Subsections (2) and (4) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligations.

86AR When using open circuit scuba is prohibited

- (1) An employer, self-employed person or other person who conducts a business or undertaking must not—
 - (a) do construction diving work using open circuit scuba as a work activity performer for the business or undertaking in any of the circumstances mentioned in subsection (2); or
 - (b) allow a work activity performer for the business or undertaking to do construction diving using open circuit scuba in any of the circumstances mentioned in subsection (2).
- (2) The circumstances are that the diver will—
 - (a) be at a depth of over 30m; or
 - (b) use a tool powered by anything other than a person; or
 - (c) be doing work requiring a decompression stop; or
 - (d) be at risk of being injured or trapped as a result of anyone's use of mechanical lifting equipment or a buoyancy lifting device; or
 - (e) be underneath something that would require the diver to move sideways, other than at an upwards angle, if the diver were to attempt to ascend.
- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

86AS Work below 50m using SSBA supplying compressed air prohibited

- (1) An employer, self-employed person or other person who conducts a business or undertaking must not—
 - (a) do construction diving work at a depth of over 50m using SSBA supplying compressed air as a work activity performer for the business or undertaking; or

- (b) allow a work activity performer for the business or undertaking to do construction diving work at a depth of over 50m using SSBA supplying compressed air.
- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

Division 4 Conducting recreational diving or recreational technical diving

86A Ways to prevent or minimise risks prescribed

- (1) This division prescribes ways of preventing or minimising exposure to the risk of death, illness or injury associated with conducting recreational diving or recreational technical diving as part of an employer's or self-employed person's undertaking in the circumstances mentioned in this division.
- (2) A person may discharge the person's workplace health and safety obligation for exposure to the risk in the circumstances mentioned in this division only by following the prescribed ways.⁴⁴
- (3) This division does not deal with all circumstances that may expose a person to a risk associated with conducting recreational diving or recreational technical diving as part of an employer's or self-employed person's undertaking.

86B Count of all persons on board to be made and recorded

- (1) This section applies if an employer or self-employed person uses a boat to transport persons to, or to the vicinity of, a recreational diving or recreational technical diving site.
- (2) Before the boat departs for the site, the employer or self-employed person must ensure a crew member—

⁴⁴ See the Act, section 24 (Discharge of obligations) for the penalty for failing to discharge the obligation.

- (a) counts all persons on board; and
- (b) makes a written⁴⁵ record of the count; and
- (c) verifies the count—
 - (i) by signing the record; or
 - (ii) if the record is made electronically—by entering in the record the name of, and a unique identifier for, the crew member.

Example of a record made electronically—

a record made on a computer

- (3) If anyone leaves the boat permanently for alternative transport to shore or another vessel, or if an additional person permanently joins the boat, the employer or self-employed person must ensure a crew member—
 - (a) counts the persons leaving the boat as they leave it; and
 - (b) counts the persons boarding the boat as they board it; and
 - (c) makes a written record of each of the counts; and
 - (d) makes a written record of the number of persons currently on board; and
 - (e) verifies the information recorded under paragraphs (c) and (d)—
 - (i) by signing the record; or
 - (ii) if the record is made electronically—by entering in the record the name of, and a unique identifier for, the crew member.
- (4) Before the boat departs from the site or its vicinity, the employer or self-employed person must ensure a crew member—
 - (a) counts the persons on board; and
 - (b) makes a written record of the count; and

⁴⁵ Under the *Acts Interpretation Act 1954*, *writing* includes any mode of representing or reproducing words in a visible form.

- (c) compares the count with the last count recorded under this section to ensure the counts agree; and
 - (d) makes a written record of the comparison; and
 - (e) verifies the information recorded under paragraph (b), and the comparison—
 - (i) by signing the record; or
 - (ii) if the record is made electronically—by entering in the record the name of, and a unique identifier for, the crew member.
- (5) The employer or self-employed person must keep each record made under this section for at least 1 year.

86C Medical conditions of resort divers

- (1) This section applies if an employer or self-employed person intends to conduct resort diving for a person.
- (2) The employer or self-employed person may allow the person to do resort diving only if—
 - (a) the person first gives the employer or self-employed person a medical declaration in the approved form about his or her medical fitness to dive; and
 - (b) the employer or self-employed person, or someone on his or her behalf—
 - (i) has read the declaration; and
 - (ii) does not know or suspect that the declaration is false or misleading; and
 - (iii) has assessed the person's fitness to dive, having regard to the declaration; and
 - (iv) decides it is reasonable to allow the person to dive.

Example of the process of assessment—

A declaration discloses a medical condition. The employer then seeks medical advice. In accordance with the medical advice, the employer decides that it is reasonable to allow the person to dive.

86D Lookout and rescuer

- (1) This section applies if an employer or self-employed person is conducting recreational diving or recreational technical diving for 1 or more persons.
- (2) The employer or self-employed person may allow the persons to do the diving only while there is at least 1 person acting as lookout for the diving.
- (3) The lookout must—
 - (a) be positioned out of the water where the lookout can see the whole area where the diving is taking place; and
 - (b) be solely engaged in being the lookout; and
 - (c) be able to recognise relevant hazards and divers in difficulty; and
 - (d) be able to either—
 - (i) rescue a diver; or
 - (ii) direct a person who is immediately available and capable of rescuing a diver to rescue a diver; and
 - (e) be able to either—
 - (i) provide first aid including expired air resuscitation, oxygen resuscitation and external cardiac compression; or
 - (ii) direct a person who is immediately available and capable of providing the first aid to provide the first aid.
- (4) A lookout is taken to be acting as lookout while occupied under subsection (3)(d) or (e) if—
 - (a) the employer or self-employed person, or someone on his or her behalf, has conducted a proper assessment of the risks involved in not having another person available to act as lookout while the lookout is occupied under subsection (3)(d) or (e); and
 - (b) it is reasonable having regard to those risks not to have another person available to act as lookout.

86E Supervision of resort divers

- (1) This section applies if an employer or self-employed person is conducting resort diving for 1 or more persons.
- (2) The employer or self-employed person must ensure that each person doing resort diving is supervised in the water by a dive instructor or a dive instructor assisted by a certified assistant.
- (3) A dive instructor must not supervise more than 4 resort divers at a time.
- (4) A dive instructor assisted by a certified assistant must not supervise more than 6 resort divers at a time.
- (5) In this section—

certified assistant means a person who holds a current qualification from a recreational scuba training organisation, designed to qualify the person to assist a dive instructor.

dive instructor means a person who holds a current qualification from a recreational scuba training organisation, designed to qualify the person as a scuba instructor.

86F Dive safety log

- (1) This section applies if an employer or self-employed person intends to conduct recreational diving or recreational technical diving for 1 or more persons.
- (2) The employer or self-employed person must ensure a written⁴⁶ dive safety log is kept.
- (3) The dive safety log must contain the required information about—
 - (a) each dive conducted by the employer or self-employed person; and
 - (b) each dive done by the employer, self-employed person or the employer's workers in conducting the dive.
- (4) Subject to subsections (5) and (6), the following is the required information—

⁴⁶ Under the *Acts Interpretation Act 1954*, *writing* includes any mode of representing or reproducing words in a visible form.

- (a) the diver's name;
 - (b) the name of any buddy with whom the dive is conducted;
 - (c) the dive supervisor's name;
 - (d) the date and location of the dive;
 - (e) time in;
 - (f) time out;
 - (g) maximum depth of the dive;
 - (h) any incident, problem, discomfort or injury experienced or suffered by the diver;
 - (i) if the dive was done using a dive computer—the dive time;
 - (j) if the dive was done using dive tables—the repetitive dive group and either bottom time or dive time;
 - (k) if the repetitive dive group and surface interval result in a repetitive factor—the surface interval and the repetitive factor.
- (5) The following is the additional information required if the recreational technical diving is intended to be done using EANx with scuba or an EANx rebreather—
- (a) oxygen content of the EANx;
 - (b) maximum operating depth for the gas being used.
- (6) The following is the additional information required if the recreational technical diving is intended to be done using mixed gas with scuba or a mixed gas rebreather—
- (a) oxygen content and nitrogen content (if any) of the mixed gas;
 - (b) maximum operating depth for the mixed gas;
 - (c) minimum operating depth of the bottom mix.
- (7) On completion of a recreational dive or a recreational technical dive, a diver must verify the diver's return from the dive—

Workplace Health and Safety Regulation 1997

- (a) by signing the dive safety log entry for the diver;⁴⁷ or
- (b) if the log is kept electronically—by entering in the log entry the name of, and a unique identifier for, the diver.

Example of a log kept electronically—

a record kept by computer

- (8) The dive supervisor, or a person authorised by the employer or self-employed person, must verify, in either of the following ways, that the dive safety log entry for the diver has been completed, and the diver's return from the dive has been verified by the diver, as required under subsections (2) to (7)—
 - (a) by signing the log entry;
 - (b) if the log is kept electronically—by entering in the log entry the name of, and a unique identifier for, the dive supervisor or authorised person.
- (9) The master of a boat used in connection with the diving, or a person authorised by the employer or self-employed person, must verify, in either of the following ways, that the dive safety log has been completed, and verified, as required under subsections (2) to (8)—
 - (a) by signing the log entry;
 - (b) if the log is kept electronically—by entering in the log entry the name of, and a unique identifier for, the master or authorised person.
- (10) Each entry and signature in the dive safety log must be made as soon as possible.

Example—

The signature of the diver in the dive safety log is an important check on whether a diver has returned to the boat. Accordingly, the signature needs to be made as soon as the diver has removed necessary gear and dried the diver's hands.

- (11) The employer or self-employed person must keep the dive safety log for at least 1 year.

⁴⁷ The entry may be only partially completed when the diver signs it or enters his or her name and identifier. See subsection (10).

Part 12A Conducting recreational snorkelling

86G Ways to prevent or minimise risks prescribed

- (1) This part prescribes ways of preventing or minimising exposure to the risk of death, illness or injury associated with conducting recreational snorkelling as part of an employer's or self-employed person's undertaking in the circumstances mentioned in this part.
- (2) A person may discharge the person's workplace health and safety obligation for exposure to the risk in the circumstances mentioned in this part only by following the prescribed ways.⁴⁸
- (3) This part does not deal with all circumstances that may expose a person to risks associated with conducting recreational snorkelling as part of an employer's or self-employed person's undertaking.

86H Count of all persons on board to be made and recorded

- (1) This section applies if an employer or self-employed person uses a boat to transport persons to, or to the vicinity of, a recreational snorkelling site.
- (2) Before the boat departs for the recreational snorkelling site, the employer or self-employed person must ensure a crew member—
 - (a) counts all persons on board; and
 - (b) makes a written⁴⁹ record of the count; and
 - (c) verifies the count—
 - (i) by signing the record; or

48 See the Act, section 24 (Discharge of obligations) for the penalty for failing to discharge the obligation.

49 Under the *Acts Interpretation Act 1954*, *writing* includes any mode of representing or reproducing words in a visible form.

Workplace Health and Safety Regulation 1997

- (ii) if the record is made electronically—by entering in the record the name of, and a unique identifier for, the crew member.

Example of a record made electronically—

a record made on a computer

- (3) If anyone leaves the boat permanently for alternative transport to shore or another vessel, or if an additional person permanently joins the boat, the employer or self-employed person must ensure a crew member—
 - (a) counts the persons leaving the boat as they leave it; and
 - (b) counts the persons boarding the boat as they board it; and
 - (c) makes a written record of each of the counts; and
 - (d) makes a written record of the number of persons currently on board; and
 - (e) verifies the information recorded under paragraphs (c) and (d)—
 - (i) by signing the record; or
 - (ii) if the record is made electronically—by entering in the record the name of, and a unique identifier for, the crew member.
- (4) Before the boat departs from the recreational snorkelling site or its vicinity, the employer or self-employed person must ensure a crew member—
 - (a) counts the persons on board; and
 - (b) makes a written record of the count; and
 - (c) compares the count with the last count recorded under this section to ensure the counts agree; and
 - (d) makes a written record of the comparison; and
 - (e) verifies the information recorded under paragraph (b), and the comparison—
 - (i) by signing the record; or

- (ii) if the record is made electronically—by entering in the record the name of, and a unique identifier for, the crew member.
- (5) The employer or self-employed person must keep each record made under this section for at least 1 year.

86I Advice about medical conditions

- (1) This section applies if an employer or self-employed person intends to conduct recreational snorkelling for 1 or more persons.
- (2) The employer or self-employed person must ensure that each person who intends to do the recreational snorkelling is advised that—
 - (a) snorkelling can be a strenuous physical activity and may increase the health and safety risks for persons suffering from—
 - (i) any medical condition that may be made worse by physical exertion, for example, heart disease, asthma and some lung complaints; or
 - (ii) any medical condition that can result in loss of consciousness, for example, some forms of epilepsy and some diabetic conditions; or
 - (iii) asthma that can be brought on by cold water or salt water mist; and
 - (b) the person should tell the lookout, snorkelling supervisor or snorkelling guide if the person has any concerns about a medical condition.

86J Lookout, guide and rescuer

- (1) This section applies if an employer or self-employed person is conducting recreational snorkelling for 1 or more persons.
- (2) The employer or self-employed person may allow the persons to do recreational snorkelling only if—
 - (a) there is at least 1 person acting as lookout for the snorkelling; or

- (b) the snorkelling is done with a guide and—
 - (i) the guide is guiding 10 snorkellers or less; and
 - (ii) the guide has conducted a proper assessment of the risks involved in not having a lookout; and
 - (iii) it is reasonable having regard to those risks not to have a lookout.
- (3) The lookout must—
 - (a) be positioned out of the water where the lookout can see the whole area where the snorkelling is taking place; and
 - (b) be solely engaged in being the lookout.
- (4) The lookout or guide must—
 - (a) be able to recognise relevant hazards and snorkellers in difficulty; and
 - (b) be able to either—
 - (i) rescue a snorkeller; or
 - (ii) direct a person who is immediately available and capable of rescuing a snorkeller to rescue a snorkeller; and
 - (c) be able to either—
 - (i) provide first aid including expired air resuscitation, oxygen resuscitation and external cardiac compression; or
 - (ii) direct a person who is immediately available and capable of providing the first aid to provide the first aid.
- (5) A lookout is taken to be acting as lookout and a guide is taken to be acting as a guide while occupied under subsection (4)(b) or (c) if—
 - (a) the employer or self-employed person, or someone on his or her behalf, has conducted a proper assessment of the risks involved in not having another person available to act as lookout or as a guide while the lookout or guide is occupied under subsection (4)(b) or (c); and

- (b) it is reasonable having regard to those risks not to have another person available to act as lookout or as a guide.

Part 13 Hazardous substances

Division 1 Interpretation

87 Meaning of *exposed*

A person is *exposed* to a hazardous substance if the person absorbs, or is likely to absorb, the substance—

- (a) by ingestion or inhalation; or
- (b) through the skin or mucous membrane.

88 Meaning of *hazardous substance*

- (1) In this part, other than division 4⁵⁰—

hazardous substance means—

- (a) a designated hazardous substance; or
 - (b) a substance that is not a designated hazardous substance but meets the approved criteria.
- (2) However, a hazardous substance does not include—
 - (a) lead within the meaning of part 14; or
 - (b) a substance containing a disease causing organism; or
 - (c) a radioactive substance; or
 - (d) a substance used at a workplace for personal or sanitary use not related to a work activity.

50 Division 4 (Relevant persons)

Example of subsection (2)(d)—

skin cream brought into the workplace by a worker for the worker's personal use, but not a skin cream supplied at the workplace for removing grease or other chemicals from the skin

Division 2 Manufacturers and importers

89 Who division applies to

This division applies to a manufacturer or importer of a hazardous substance for use at a workplace.⁵¹

90 Preparing, amending and reviewing MSDS

(1) A manufacturer or importer must—

- (a) prepare an MSDS for the substance—
 - (i) before first manufacturing or importing it; or
 - (ii) if that is not practicable—as soon as practicable after first manufacturing or importing it; and
- (b) amend the MSDS whenever necessary to ensure it contains current information; and
- (c) review the MSDS at least once in every 5 years to ensure it contains current information.

Example of paragraph (a)(ii)—

It may not be practicable to prepare an MSDS before first manufacturing a substance that is discovered through research.

(2) The MSDS must state—

- (a) the substance's product name; and
- (b) information about the substance's—
 - (i) chemical and physical properties; and
 - (ii) health hazards; and
 - (iii) safe use; and

51 See the Act, section 25 (Person may owe obligations in more than 1 capacity).

- (c) the importer's or manufacturer's name, Australian address and Australian telephone number;⁵² and
 - (d) for a substance containing a type 1 ingredient—the ingredient's chemical name; and
 - (e) for a substance containing a type 2 ingredient—
 - (i) the ingredient's chemical name; or
 - (ii) if the manufacturer or importer reasonably believes disclosure of the ingredient's chemical name gives insufficient commercial protection—the ingredient's generic name; and
 - (f) for a substance containing a type 3 ingredient—
 - (i) the ingredient's chemical name; or
 - (ii) the ingredient's generic name.
- (3) Despite subsection (2)(f), instead of stating a type 3 ingredient's chemical or generic name, the MSDS may state that the ingredient is not hazardous if—
- (a) the ingredient is not a hazardous substance with a known synergistic effect; and
 - (b) the manufacturer or importer reasonably believes disclosure of its chemical or generic name gives insufficient commercial protection.
- (4) The MSDS must be in English and contain—
- (a) unit measures commonly used in Australia; and
 - (b) the national exposure standard (if any) for the substance.
- (5) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

52 See NOHSC's document entitled 'National Code of Practice for the Preparation of Material Safety Data Sheets' for further information about the things mentioned in paragraphs (a) to (c).

91 Providing MSDS

- (1) A manufacturer or importer who prepares an MSDS must give a copy of it to—
- (a) the repository as soon as practicable after it is prepared; and
 - (b) each person to whom the manufacturer or importer supplies the substance when first supplying the substance to the person.

Maximum penalty for subsection (1)(a)—30 penalty units.

- (2) A manufacturer or importer who amends an MSDS by changing information mentioned in section 90(2)(a), (b) or (c) must give a copy of the amended MSDS to—
- (a) the repository within 1 month after amending it; and
 - (b) each person to whom the manufacturer or importer supplies the substance when first supplying the substance to the person after preparing the amended MSDS.

Maximum penalty for subsection (2)(a)—30 penalty units.

- (3) A manufacturer or importer must, on request, give a copy of a hazardous substance's current MSDS to—
- (a) a relevant person, worker or worker's representative at a workplace where the substance is, or is to be, used; or
 - (b) the chief executive.⁵³

Maximum penalty for subsection (3)—30 penalty units.

- (4) Subsections (1)(b) and (2)(b) do not apply to a manufacturer or importer if—
- (a) the manufacturer or importer supplies a substance to a retailer or retail warehouse operator; and
 - (b) the substance is contained in a consumer package that will not be opened on the retailer's or operator's premises.

⁵³ The chief executive means the chief executive of the department administering this part—see the *Acts Interpretation Act 1954*, sections 33 and 36.

- (5) Subsections (1)(b) and (2)(b) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

92 Notifying use of type 2 ingredient's generic name

- (1) A manufacturer or importer who states a type 2 ingredient's generic name in an MSDS must give NOHSC notice in the approved form of the use of the generic name.
- (2) The notice must be given as soon as practicable after the MSDS is prepared.

Maximum penalty—30 penalty units.

93 Disclosing ingredient's chemical name

- (1) This section applies despite section 90(3).
- (2) A manufacturer or importer must immediately give the chemical name of an ingredient contained in the substance to a designated doctor who—
- (a) believes a person has been exposed to the substance at a workplace and needs urgent medical treatment; and
 - (b) asks for the information for the person's treatment.
- (3) If an ingredient's chemical name is needed to give sufficient protection to the relevant person or a worker at a workplace against exposure—
- (a) the relevant person may, by written request, ask the substance's manufacturer or importer to give the person the ingredient's chemical name; or
 - (b) the worker or worker's representative may, by written request, ask the substance's manufacturer or importer to give the person the ingredient's chemical name.
- (4) A request under subsection (3) must contain—
- (a) the reason for the request; and

- (b) an undertaking to use the information only for the purpose mentioned in subsection (3).
- (5) The manufacturer or importer must not refuse the request unless the manufacturer or importer has a reasonable excuse.
Maximum penalty for subsection (5)—30 penalty units.
- (6) Without limiting subsection (5), it is a reasonable excuse to refuse the request if the manufacturer or importer—
 - (a) is not satisfied the ingredient's chemical name is needed; and
 - (b) gives the requester, within 30 days after receiving the request—
 - (i) written reasons for refusing the request;⁵⁴ and
 - (ii) information other than the ingredient's chemical name (if any) that may help protect the relevant person or worker from exposure.
- (7) Subsection (2) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

94 Providing NICNAS summary report and other information

- (1) A relevant person at a workplace where a hazardous substance is used may, by written request, ask the substance's manufacturer or importer for—
 - (a) information from the substance's NICNAS summary report (if any) that may help in the substance's safe use; and
 - (b) other information (if any), not contained in the substance's MSDS, that may help in the substance's safe use.

⁵⁴ The instrument giving the reasons must also refer to the evidence or other material on which those findings were based. See the *Acts Interpretation Act 1954*, section 27B (Content of statement of reasons for decision).

- (2) The manufacturer or importer must give the relevant person the information within 30 days after receiving the request, unless the manufacturer or importer has a reasonable excuse.

Maximum penalty for subsection (2)—30 penalty units.

Division 3 Suppliers

95 Who division applies to

This division applies to a supplier of a hazardous substance for use at a workplace.⁵⁵

97 Providing MSDS

- (1) A supplier must give a copy of a hazardous substance's current MSDS to the relevant person at a workplace—
- (a) when first supplying the substance to the relevant person; and
 - (b) when first supplying the substance to the relevant person after preparing or receiving an amended MSDS.⁵⁶
- (2) Subsection (1) does not apply to a retailer or retail warehouse operator who supplies a hazardous substance contained in a consumer package that will not be opened on the retailer's or operator's premises.
- (3) A supplier must, on request, give a copy of a hazardous substance's current MSDS to—
- (a) a relevant person, worker or worker's representative at a workplace where the substance is, or is to be, used; or
 - (b) the chief executive.

Maximum penalty for subsection (3)—30 penalty units.

- (4) Subsection (1) is a workplace health and safety obligation for the Act.

⁵⁵ See the Act, section 25 (Person may owe obligations in more than 1 capacity).

⁵⁶ Section 90 deals with the amendment of an MSDS.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

98 Labelling containers

- (1) A supplier must ensure a label is fixed to a hazardous substance's container when the substance is supplied.
- (2) The label—
 - (a) must be in English; and
 - (b) must state the substance's product name; and
 - (c) must state the substance's risk and safety phrases (other than a safety phrase giving information about a risk phrase); and
 - (d) if the substance contains a type 1 or type 2 ingredient—must state the ingredient's chemical name; and
 - (e) if the substance contains a type 2 ingredient and the substance's manufacturer or importer reasonably believes disclosure of the ingredient's chemical name gives insufficient commercial protection—may state the ingredient's generic name.

Example of a safety phrase giving information about a risk phrase in subsection (2)(c)—

a safety phrase stating 'Keep away from heat' if the risk phrase states 'Heating may cause an explosion'

- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

Division 4 Relevant persons

99 Who division applies to

This division applies to a relevant person at a workplace where a hazardous substance is used.⁵⁷

100 Meaning of *hazardous substance* for division

In this division—

hazardous substance means a substance for which its supplier must, under section 97, give a relevant person its current MSDS.

101 Obtaining MSDS

- (1) A relevant person who, when first supplied with a substance in a container labelled under section 98, does not receive an MSDS for the substance must—
 - (a) ask the supplier if the substance is a hazardous substance; and
 - (b) if it is—ask the supplier for a copy of its current MSDS.
- (2) This section does not apply to a retailer or retail warehouse operator if the substance—
 - (a) has been supplied to the retailer or operator for retail sale; and
 - (b) is contained in a consumer package that will not be opened on the retailer's or operator's premises.
- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

⁵⁷ See the Act, section 25 (Person may owe obligations in more than 1 capacity).

102 Recording and displaying MSDS

- (1) A relevant person must—
 - (a) put the copy of a hazardous substance's MSDS in the register immediately after the relevant person prepares or receives it; and
 - (b) take reasonable steps to ensure the contents of the MSDS are not changed other than in accordance with an amendment of the MSDS by the manufacturer or importer.
- (2) A relevant person who is an employer must also keep a copy of the MSDS close enough to where the substance is being used to allow a worker who may be exposed to the substance to refer to it easily.
- (3) This section does not apply to a retailer or retail warehouse operator if the substance—
 - (a) has been supplied to the retailer or operator for retail sale; and
 - (b) is contained in a consumer package that will not be opened on the retailer's or operator's premises.
- (4) Subsections (1) and (2) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

103 Labelling containers

- (1) A relevant person must—
 - (a) ensure a label complying with section 98 is fixed to the container of a hazardous substance used at the workplace; and
 - (b) take reasonable steps to ensure the label is not interfered with.
- (2) If a hazardous substance is transferred from 1 container into a second container and the second container's contents are not

entirely used immediately, the relevant person must ensure the second container is fixed with a label stating—

- (a) the substance's product name; and
- (b) the substance's risk and safety phrases (other than a safety phrase giving information about a risk phrase).

Example of a safety phrase giving information about a risk phrase in subsection (2)(b)—

a safety phrase stating 'Keep away from heat' if the risk phrase states 'Heating may cause an explosion'

- (3) Subsections (1) and (2) do not apply to a container if it has been cleaned of the hazardous substance.
- (4) Subsections (1) and (2) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

104 Hazardous substances in enclosed systems

- (1) A relevant person must ensure suitable warning of the presence and location of a hazardous substance in an enclosed system at a workplace is given to anyone who may be exposed to the substance if it escapes from the enclosed system.

Example of suitable warning—

a suitable warning stated in AS 1345⁵⁸

- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

58 AS 1345 (Identification of the contents of pipes, conduits and ducts)

105 Risk assessments

- (1) A relevant person must assess the risk to the health of the relevant person or a worker from a hazardous substance that is used, or is to be used, at the workplace.
- (2) The assessment must be done—
 - (a) as soon as is practicable after it is used; and
 - (b) within 5 years after the last assessment; and
 - (c) when any of the following happen at the workplace—
 - (i) a work practice involving the substance is significantly changed;
 - (ii) new information about the substance's hazards is available;
 - (iii) health surveillance⁵⁹ or monitoring⁶⁰ shows control measures need to be reviewed;
 - (iv) new or improved control measures are implemented.

Examples of significantly changed work practices in paragraph (c)(i)—

- the form of a catalyst for a chemical reaction is changed from liquid to a vaporised state
- the form of a substance used is changed from fine powder to pellets

Examples of control measures in paragraph (c)(iv)—

engineering controls, safe work practices and personal protective equipment

- (3) The assessment must include—
 - (a) an identification of the hazardous substance; and
 - (b) if the substance's MSDS is available—a review of the MSDS; and
 - (c) if the substance's MSDS is not available—a review of available equivalent information; and

⁵⁹ See section 109 (Health surveillance).

⁶⁰ See section 108 (Monitoring).

- (d) if the substance is contained in a consumer package—a review of the package’s label; and
 - (e) a decision whether any workers may be exposed to the substance; and
 - (f) a decision about the control measures, health surveillance and monitoring needed for the substance.
- (4) The assessment may be a generic assessment prepared for workplaces where the substance is used in the same or similar circumstances.

Example of generic assessment in subsection (4)—

an assessment prepared by an industry body or trade association about the use of brake fluid at service stations

Maximum penalty—30 penalty units.

106 Risk assessment records

The relevant person must, as soon as practicable after doing an assessment, record the following information—

- (a) the date when the assessment was done;
- (b) whether the degree of risk is assessed to be significant;⁶¹
- (c) the substance’s product name or other information;
- (d) the control measures for the use of the substance that were in place when the assessment was done;
- (e) the type of monitoring that is needed and the intervals at which the monitoring must be done;
- (f) the type of health surveillance that is needed and the intervals at which the health surveillance must be done.

Maximum penalty—30 penalty units.

107 Controlling exposure

- (1) If a risk assessment shows a relevant person or worker may be exposed to a hazardous substance, the relevant person must—

⁶¹ For guidance in deciding if the degree of risk is significant, see the Hazardous Substances Code of Practice 2003.

- (a) prevent the exposure; or
 - (b) if prevention is not practicable—reduce the exposure to as low a level as is practicable, but in any case the exposure must not be more than the relevant national exposure standard for the relevant period for the substance.
- (2) The relevant person must, as far as is practicable, prevent or reduce the exposure by ways other than the use of personal protective equipment.
- (3) However, if the exposure cannot be prevented or reduced other than by using personal protective equipment, the relevant person must ensure that anyone who may be exposed—
 - (a) is given personal protective equipment; and
 - (b) is properly instructed in the use of the personal protective equipment; and
 - (c) uses the equipment when there is a risk of being exposed to the substance.
- (4) The relevant person must also ensure the control measures decided under the risk assessment are—
 - (a) implemented as soon as practicable at the workplace; and
 - (b) effectively maintained.
- (5) Subsections (1) to (4) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

- (7) In this section—

relevant period means the exposure period stated in NOHSC's document entitled 'Exposure Standards for Atmospheric Contaminants in the Occupational Environment'.

108 Monitoring

- (1) This section applies if the risk assessment shows monitoring is needed.
- (2) The relevant person must ensure the monitoring is done at the workplace.
- (3) The relevant person must also ensure a record of the monitoring result is made as soon as practicable.
- (4) A relevant person who is an employer must—
 - (a) ensure a worker who may be exposed to a hazardous substance at the workplace is given a copy of the record; and
 - (b) allow a worker who may be exposed to inspect the record at any reasonable time.

Maximum penalty for subsections (3) and (4)—30 penalty units.

- (5) Subsection (2) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

109 Health surveillance

- (1) A relevant person must arrange for health surveillance of the relevant person or a worker who a risk assessment⁶² shows has been exposed to a hazardous substance if—
 - (a) the substance is listed in schedule 6, column 1 and the degree of risk to the health of the relevant person or worker is significant; or
 - (b) the relevant person reasonably believes, or ought to reasonably believe—
 - (i) an identifiable adverse health effect may be related to the exposure; and

62 See section 105 (Risk assessments).

- (ii) the health effect may happen under the work conditions of the relevant person or worker; and
- (iii) a valid technique capable of detecting signs of the health effect exists; or
- (c) the relevant person reasonably believes, or ought to reasonably believe—
 - (i) an identifiable adverse health effect may be related to the exposure; and
 - (ii) the health effect may happen under the work conditions of the relevant person or worker; and
 - (iii) a valid biological monitoring procedure is available to detect, in the relevant person or worker, changes from the current accepted values for the substance.

Examples of changes from current accepted values in paragraph (c)(iii)—

- lower than normal blood levels of acetylcholinesterase resulting from organophosphate pesticide exposure
 - raised urinary mercury levels in a laboratory technician exposed to mercury vapour
- (2) If the health surveillance relates to exposure to a hazardous substance mentioned in schedule 6, column 1, the surveillance must include the things stated in schedule 6, column 2 for the substance.
 - (3) The relevant person must—
 - (a) arrange for the health surveillance to be done by, or under, the supervision of a designated doctor; and
 - (b) ask the designated doctor to give—
 - (i) the relevant person a health surveillance report; and
 - (ii) the worker a health surveillance report and an explanation of the report; and
 - (c) keep the report as a record at the workplace.

- (4) If the health surveillance is of a worker, a relevant person who is an employer must consult the worker before choosing a designated doctor to do, or supervise, the surveillance.

Maximum penalty for subsection (4)—30 penalty units.

- (5) A relevant person who is an employer must pay for a worker's health surveillance.

Maximum penalty for subsection (5)—30 penalty units.

- (6) Subsections (1) and (3) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

- (8) In this section—

health surveillance report means information, other than a medical record, about—

- (a) the effects on a person's health related to the person's exposure to a hazardous substance at a workplace; and
- (b) the need (if any) for remedial action.

110 Confidentiality of worker's medical record

- (1) A relevant person who is an employer may only obtain a worker's medical record with the worker's written consent.
- (2) A relevant person who is an employer must not disclose to anyone (other than the worker or someone with the worker's written consent) the contents of the worker's medical record.

Example of someone with the worker's written consent—

the worker's representative at the workplace

Maximum penalty—30 penalty units.

111 Keeping register

- (1) A relevant person at a workplace must keep a register at the workplace containing—
- (a) a list of all hazardous substances used at the workplace; and

(b) the current MSDS for each substance.

Maximum penalty—30 penalty units.

- (2) A relevant person who is an employer must allow the employer's workers who may be exposed to a hazardous substance at the workplace to inspect the register at any reasonable time.

Maximum penalty—30 penalty units.

- (3) This section does not apply to a retailer or retail warehouse operator if the hazardous substance is contained in a consumer package that will not be opened on the retailer's or operator's premises.

112 Keeping records

- (1) If a risk assessment⁶³ shows a hazardous substance's use at a workplace causes a significant degree of risk to health, the relevant person must keep the following documents for 30 years from the day the particular document was made—
- (a) the risk assessment record;⁶⁴
 - (b) a monitoring result;⁶⁵
 - (c) a health surveillance report.⁶⁶
- (2) If a risk assessment shows a hazardous substance's use at a workplace does not cause a significant degree of risk to health, the relevant person must keep a record of the assessment for 5 years from the day it was made.
- (3) A relevant person who is an employer must allow a worker who may be exposed to a hazardous substance at the workplace to inspect a document mentioned in subsection (1) or (2) at any reasonable time.
- (4) If a person stops being a relevant person in the period a document is required to be kept under subsection (1) or (2),

63 See section 105 (Risk assessments).

64 See section 106 (Risk assessment records).

65 See section 108 (Monitoring).

66 See section 109 (Health surveillance).

the person must ask for, and comply with, the chief executive's directions about the document's storage.

Maximum penalty—30 penalty units.

113 Induction and training about hazardous substances

- (1) A relevant person who is an employer must give a worker who may be exposed to a hazardous substance at the workplace induction and ongoing training about the substance.
- (2) The induction and training must be appropriate having regard to—
 - (a) the level of risk identified in a risk assessment; and
 - (b) the workers who may be exposed to the substance.
- (3) The relevant person must keep a record of the induction and training given to a worker for 5 years from the date of the last entry in the record.

Maximum penalty for subsection (3)—30 penalty units.

- (4) The record must include the following information for each induction or training session—
 - (a) the date of the session;
 - (b) the topics dealt with at the session;
 - (c) the name of the person who conducted the session;
 - (d) the names of the workers who attended the session.
- (5) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

Division 5 Spray painting with hazardous substances

115A Ways to prevent or minimise risk prescribed

- (1) Sections 115B to 115H prescribe ways of preventing or minimising exposure to the risk of exposure to a hazardous substance used in or for spray painting in the circumstances mentioned in the sections.
- (2) However, the sections do not deal with all circumstances that expose someone to the risk of exposure to a hazardous substance from spray painting.
- (3) A person may discharge the person's workplace health and safety obligation for exposure to the risk in the circumstances mentioned in the sections only by following the prescribed ways.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

115B Manufacturing or importing a spray painting booth

- (1) This section applies to a manufacturer or importer of a spray painting booth—
 - (a) for use at a workplace; and
 - (b) in which a hazardous substance is likely to be used.

Examples of hazardous substances for subsection (1)(b)—

enamels, lacquers, powders, solvents, varnishes

- (2) The manufacturer or importer must ensure the booth—
 - (a) is constructed to be safe and without risk to health when used properly; and
 - (b) is able to prevent or control the escape of a hazardous substance that might be a risk to health; and
 - (c) undergoes appropriate testing and examination to ensure it complies with paragraphs (a) and (b).

- (3) The manufacturer or importer must ensure the booth is fitted with an effective ventilation system that incorporates—
 - (a) a filtration system to remove airborne residue produced during a spray painting process; and
 - (b) an exhaust capture system—
 - (i) to prevent the exposure of a person in an adjoining work area to a hazardous substance produced by a spray painting process; and
 - (ii) if prevention is not practicable—to reduce the exposure to as low a level as is practicable, but in any case the exposure must not be more than the relevant national exposure standard for the relevant period for the substance.

Example of airborne residue for subsection (3)(a)—

paint particles from overspray

- (4) In this section—

relevant period means the exposure period stated in NOHSC's document entitled 'Exposure Standards for Atmospheric Contaminants in the Occupational Environment'.

115C Supplying a spray painting booth

- (1) This section applies to a supplier of a spray painting booth—
 - (a) for use at a workplace; and
 - (b) in which a hazardous substance is likely to be used.

Examples of hazardous substances for subsection (1)(b)—

enamels, lacquers, powders, solvents, varnishes

- (2) The supplier must take all reasonable steps to ensure the person who is supplied with the booth is given the following information—
 - (a) the use for which the booth has been designed and tested;
 - (b) how the booth is to be used safely and without risk to health;

- (c) the maintenance procedures for the booth, including the maintenance procedures for any filters.

115D Protecting persons from spray painting

- (1) A relevant person must ensure that the risk of a person's exposure to a hazardous substance used in or for spray painting is—
 - (a) prevented; or
 - (b) if prevention is not practicable—minimised to as low a level as is practicable, but in any case the exposure must not be more than the relevant national exposure standard for the relevant period for the substance.
- (2) In this section—

relevant period means the exposure period stated in NOHSC's document entitled 'Exposure Standards for Atmospheric Contaminants in the Occupational Environment'.

115E Spray painting to be done in spray painting booth

- (1) A relevant person must ensure any spray painting using a hazardous substance is done in a spray painting booth.

Examples of hazardous substances for subsection (1)—

acrylic lacquers, 2 pack polyurethane paint, conventional epoxy paint, powders, solvents

- (2) However, a spray painting booth is not required if—
 - (a) it is not practical to do the painting in a booth; or
 - (b) the painting involves spotting, touching up or other minor work.

Examples for subsection (2)(a)—

- 1 painting a bridge, building or tower
- 2 painting a large boat that can not be easily placed in a booth because of its size

Example of spotting or touching up for subsection (2)(b)—

occasionally painting a scratch, small dent or stone chip on a car door

Example of what is minor work for subsection (2)(b)—

occasionally painting a car panel with an acrylic lacquer

Example of what is not minor work for subsection (2)(b)—

- 1 consecutively painting a number of car panels with an acrylic lacquer
- 2 painting a whole car panel with 2 pack polyurethane paint

115F Controlling exposure from spray painting

- (1) This section applies if a relevant person can not prevent or reduce someone's exposure to a hazardous substance used in or for spray painting other than by using personal protective equipment.
- (2) The relevant person must ensure that—
 - (a) anyone who may be exposed—
 - (i) is given the appropriate personal protective equipment; and
 - (ii) is properly instructed in how to use the equipment; and
 - (iii) uses the equipment when there is a risk of being exposed to the substance; and
 - (b) personal protective equipment given to someone is effectively maintained.

115G Maintaining a spray painting booth

- (1) This section applies if a spray painting booth is used by a relevant person for spray painting a hazardous substance.
- (2) The relevant person must ensure the booth is—
 - (a) regularly inspected by a competent person to ascertain whether the booth can be used safely and without risk to health; and
 - (b) appropriately maintained by a competent person.

Example of appropriately maintained for subsection (2)(b)—

maintained in accordance with the procedures supplied by the supplier of the booth

- (3) To work out how often to inspect the booth, the relevant person must consider the following things—
 - (a) the inspection intervals recommended by the manufacturer, importer, or supplier of the booth;
 - (b) the types of spray painting processes done in the booth;
 - (c) how often the booth is used;
 - (d) the types of substances, and the volumes of them, used in the booth.
- (4) In this section—

competent person means a person who has acquired, through training, qualification, experience, or a combination of these, the knowledge and skill enabling the person to inspect or maintain a spray painting booth for its safe use and proper air movement.

115H Minimum air movement for booths

- (1) This section applies if a spray painting booth is used by a relevant person for spray painting a hazardous substance.
- (2) The relevant person must ensure the booth's ventilation system can produce and keep an air movement of—
 - (a) for a full down draught booth—not less than 0.3 metres per second; or
 - (b) for a booth used only for electrostatic spray painting—not less than 0.4 metres per second; or
 - (c) for any other booth—not less than 0.5 metres per second;averaged over the area of the booth where the spray painting is done.
- (3) For subsection (2), the air movement must be measured—
 - (a) when the booth is empty; and
 - (b) during the booth's spray cycle; and
 - (c) in the area of the booth where the painting is done; and

- (d) for a booth that is not fully contained or enclosed—at the opening in the booth where the internal environment in the booth and the external environment meet.

Example of a booth that is not fully contained—

a tunnel booth that is not fitted with vapour barriers

Example of a booth that is not fully enclosed—

an open face booth

- (4) In this section—

spray cycle of a spray painting booth means the time during the booth's operation when the booth may be used for spray painting.

Part 14 Lead

Division 1 Interpretation

116 Meaning of ***exposed***

A person is ***exposed*** to lead if the person absorbs, or is likely to absorb, lead—

- (a) by ingestion or inhalation; or
- (b) through the skin or mucous membrane.

117 Meaning of ***lead hazardous substance***

A ***lead hazardous substance*** is—

- (a) a substance listed in schedule 8⁶⁷ in a concentration more than the concentration cut-off level stated for the substance in NOHSC's document entitled 'List of Designated Hazardous Substances'; or
- (b) a substance that meets the approved criteria.

67 Schedule 8 (Lead hazardous substances)

Division 2 Manufacturers and importers

118 Who division applies to

This division applies to a manufacturer or importer of lead for use at a workplace.⁶⁸

119 Preparing, amending and reviewing MSDS

- (1) A manufacturer or importer must—
 - (a) prepare an MSDS for the lead—
 - (i) before first manufacturing or importing it; or
 - (ii) if that is not practicable—as soon as reasonably practicable after first manufacturing or importing it; and
 - (b) amend the MSDS whenever necessary to ensure it contains current information; and
 - (c) review the MSDS at least once in every 5 years to ensure it contains current information.

Example of paragraph (a)(ii)—

It may not be practicable to prepare an MSDS before first manufacturing a lead hazardous substance that is discovered through research.

- (2) The MSDS must state—
 - (a) the lead's product name; and
 - (b) the lead's chemical name; and
 - (c) information about the lead's—
 - (i) chemical and physical properties; and
 - (ii) health hazards; and
 - (iii) safe use;⁶⁹ and

⁶⁸ See the Act, section 25 (Person may owe obligations in more than 1 capacity).

⁶⁹ See NOHSC's document entitled 'National Code of Practice for the Preparation of Material Safety Data Sheets' for further information about the things mentioned in paragraphs (a) to (c).

- (d) the importer's or manufacturer's name, Australian address and Australian telephone number.
- (3) The MSDS must be in English and contain—
 - (a) unit measures commonly used in Australia; and
 - (b) the national exposure standard (if any) for the lead.
- (4) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

120 Providing MSDS

- (1) A manufacturer or importer who prepares an MSDS must give a copy of it to—
 - (a) the repository as soon as practicable after it is prepared; and
 - (b) each person to whom the manufacturer or importer supplies the lead when first supplying the lead to the person.

Maximum penalty for subsection (1)(a)—30 penalty units.

- (2) A manufacturer or importer who amends an MSDS by changing information mentioned in section 119(2) must give a copy of the amended MSDS to—
 - (a) the repository within 1 month after amending it; and
 - (b) each person to whom the manufacturer or importer supplies the lead when first supplying the lead to the person after preparing the amended MSDS.

Maximum penalty for subsection (2)(a)—30 penalty units.

- (3) A manufacturer or importer must, on request, give a copy of the lead's current MSDS to—
 - (a) a relevant person, worker or workplace health and safety representative at a workplace where the lead is, or is to be, used; or

(b) the chief executive.⁷⁰

Maximum penalty for subsection (3)—30 penalty units.

- (4) Subsections (1)(b) and (2)(b) do not apply to a manufacturer or importer if—
- (a) the manufacturer or importer supplies lead to a retailer or retail warehouse operator; and
 - (b) the lead is contained in a consumer package that will not be opened on the retailer's or operator's premises.
- (5) Subsection (1)(b) and (2)(b) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

121 Providing NICNAS summary report and other information

- (1) A relevant person at a workplace where lead is used may, by written request, ask the lead's manufacturer or importer for—
- (a) information from the lead's NICNAS summary report (if any) that may help in the lead's safe use; and
 - (b) other information (if any), not contained in the lead's MSDS, that may help in the lead's safe use.
- (2) The manufacturer or importer must give the relevant person the information within 30 days after receiving the request, unless the manufacturer or importer has a reasonable excuse.

Maximum penalty for subsection (2)—30 penalty units.

⁷⁰ The chief executive means the chief executive of the department administering this part. See the *Acts Interpretation Act 1954*, sections 33 and 36.

Division 3 Suppliers

122 Who division applies to

This division applies to a supplier of lead for use at a workplace.⁷¹

123 Providing MSDS

- (1) A supplier must give a copy of the lead's current MSDS to the relevant person at a workplace—
 - (a) when first supplying the lead to the relevant person; and
 - (b) when first supplying the lead to the relevant person after preparing or receiving an amended MSDS.
- (2) A supplier must, on request, give a copy of the lead's current MSDS to—
 - (a) a relevant person, worker or workplace health and safety representative at a workplace where the lead is, or is to be, used; or
 - (b) the chief executive.

Maximum penalty for subsection (2)—30 penalty units.

- (3) Subsection (1) does not apply to a retailer or retail warehouse operator who supplies lead contained in a consumer package that will not be opened on the retailer's or operator's premises.
- (4) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

124 Labelling containers

- (1) A supplier must ensure a label is fixed to a container of lead when the lead is supplied.

⁷¹ See the Act, section 25 (Person may owe obligations in more than 1 capacity).

- (2) The label must be in English and state—
- (a) the lead's product name; and
 - (b) the lead's risk and safety phrases (other than a safety phrase giving information about a risk phrase); and
 - (c) the lead's chemical name.

Example of a safety phrase giving information about a risk phrase in subsection (2)(b)—

a safety phrase stating 'When using, do not eat or drink.' if the risk phrase states 'Harmful by inhalation and if swallowed.'

- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

Division 4 Relevant persons

125 Who division applies to

This division applies to a relevant person at a workplace where a lead process is carried out.⁷²

126 Obtaining MSDS

- (1) A relevant person who, when first supplied with a substance in a container labelled under section 124, does not receive an MSDS for the lead must—
- (a) ask the supplier if the substance is lead; and
 - (b) if it is—ask the supplier for a copy of its current MSDS.
- (2) This section does not apply to a retailer or retail warehouse operator if the lead—
- (a) has been supplied to the retailer or operator for retail sale; and

⁷² See the Act, section 25 (Person may owe obligations in more than 1 capacity).

- (b) is contained in a consumer package that will not be opened on the retailer's or operator's premises.
- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

127 Keeping registers

- (1) A relevant person at a workplace must—
 - (a) keep a register at the workplace containing—
 - (i) a list of the lead used in a lead process at the workplace; and
 - (ii) the MSDS for the lead used in a lead process at the workplace; and
 - (b) put the copy of the MSDS in the register immediately after the relevant person receives it; and
 - (c) keep a copy of the MSDS close to where the lead is being used; and
 - (d) take reasonable steps to ensure the contents of the MSDS are not changed other than in accordance with an amendment of the MSDS by the manufacturer or importer.

Maximum penalty—30 penalty units.

- (2) A relevant person who is an employer must allow the employer's workers to inspect the register at any reasonable time.

Maximum penalty—30 penalty units.

- (3) This section does not apply to a retailer or retail warehouse operator if the lead—
 - (a) has been supplied to the retailer or operator for retail sale; and
 - (b) is contained in a consumer package that will not be opened on the retailer's or operator's premises.

128 Labelling containers

- (1) A relevant person must—
 - (a) ensure a label complying with section 124⁷³ is fixed to the container of lead used at the workplace; and
 - (b) take reasonable steps to ensure the label is not changed.
- (2) If lead is transferred from a container into a second container and the second container's contents are not entirely used immediately, the relevant person must ensure the second container is fixed with a label stating—
 - (a) the lead's product name; and
 - (b) the lead's risk and safety phrases (other than a safety phrase giving information about a risk phrase).

Example of a safety phrase giving information about a risk phrase in subsection (2)(b)—

a safety phrase stating 'When using, do not eat or drink.' if the risk phrase states 'Harmful by inhalation and if swallowed.'

- (3) Subsection (2) does not apply to a container if it has been cleaned of the lead.
- (4) Subsections (1) and (2) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

129 Risk assessment

- (1) A relevant person must assess the risk to the health of the relevant person or a worker from a lead process at the workplace.

Maximum penalty for subsection (1)—30 penalty units.

- (2) The assessment must be done—
 - (a) when a new lead process starts at the workplace and again within 4 weeks after the process starts; and

73 Section 124 (Labelling containers)

- (b) if, in the last assessment, the process was assessed to include a lead-risk job—within 1 year after the last assessment; and
 - (c) if, in the last assessment, the process was assessed not to include a lead-risk job—within 5 years after the last assessment; and
 - (d) when any of the following happen at the workplace—
 - (i) if there is a significant change in the way a lead process is done at the workplace;
 - (ii) if there is a significant change in the amount of lead, or the amount of lead contained in a thing, used at the workplace.
- (3) The assessment must—
 - (a) identify the lead used at the workplace; and
 - (b) if the MSDS for the lead is available—review the MSDS; and
 - (c) if the MSDS for the lead is not available—review available equivalent information; and
 - (d) if the lead is contained in a consumer package—review the package’s label.
- (4) Having assessed the risk, the relevant person must decide whether a job in a lead-risk process is a lead-risk job.
- (5) If the process is assessed to include a lead-risk job, the relevant person must decide—
 - (a) the type of atmospheric monitoring needed;⁷⁴ and
 - (b) the control measures needed.

Example of a type of atmospheric monitoring in subsection (5)(a)—
monitoring a worker’s breathing zone

- (6) The assessment may be a generic assessment prepared for workplaces where lead is used in the same or similar circumstances.

74 See section 132 (Atmospheric monitoring).

Example—

where there are several soldering stations in a battery factory soldering the same kind of terminals under similar environmental conditions

- (7) After doing the assessment, the relevant person must—
- (a) if the process is assessed not to include a lead-risk job—develop a plan to ensure a job in the process does not become a lead-risk job; or
 - (b) if the process is assessed to include a lead-risk job—
 - (i) notify the chief executive, in the approved form within 28 days after the assessment, that the process includes a lead-risk job; and
 - (ii) if the process can be changed to a process that does not include a lead-risk job—develop a plan to do that; and
 - (iii) if the process can not be changed to a process that does not include a lead-risk job—develop a plan to minimise risk to health from the lead.

Maximum penalty for subsection (7)(b)(i)—20 penalty units.

- (8) The relevant person must ensure a plan under subsection (7)—
- (a) if the relevant person is an employer—is developed in consultation between the relevant person, worker and workplace health and safety representative; and
 - (b) contains specific aims and ways of deciding whether the aims are being achieved.
- (9) A relevant person who is an employer must not allow a person to start work in a lead-risk job if the relevant person knows the person—
- (a) has a medical condition that may be adversely affected by exposure to lead; or
 - (b) is pregnant or breast feeding.
- (10) Subsections (4), (5), (7)(a), (b)(ii) and (iii), (8) and (9) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

130 Risk assessment records

As soon as practicable after doing an assessment, the relevant person must record the following information—

- (a) the date when the assessment was done;
- (b) the results of atmospheric monitoring;
- (c) whether the process is assessed to include a lead-risk job;
- (d) if a process is assessed to include a lead-risk job—
 - (i) the lead's product name or other identification; and
 - (ii) the control measures that were in place when the assessment was done; and
 - (iii) the decision made about—
 - (A) the type of atmospheric monitoring needed; and
 - (B) the control measures needed.

Maximum penalty—30 penalty units.

131 Controlling exposure

- (1) If a risk assessment shows a relevant person or worker may be exposed to lead, the relevant person must—
 - (a) prevent the exposure; or
 - (b) if that is not practicable—reduce the exposure to as low a level as is necessary to minimise risk to health, but in any case the exposure must be less than the national exposure standard for the lead.
- (2) The relevant person must, as far as is practicable, prevent or reduce the exposure by ways other than the use of personal protective equipment.
- (3) However, if the exposure can not be prevented or reduced other than by using personal protective equipment, the relevant person must ensure that—
 - (a) anyone who may be exposed—

Workplace Health and Safety Regulation 1997

- (i) is given personal protective equipment, including suitable respiratory protective equipment; and
 - (ii) is properly instructed in the use of the personal protective equipment; and
 - (iii) uses the equipment when being exposed to the lead; and
 - (b) warning signs are erected showing the need to wear the personal protective equipment in the lead process area.
- (4) The relevant person must ensure—
- (a) the control measures decided, and plans developed, under the risk assessment are implemented at the workplace as soon as practicable; and
 - (b) the control measures, including all engineering controls, safe work practices and personal protective equipment, are effectively maintained.

Example of effective maintenance of personal protective equipment—

cleaning lead from respiratory equipment to maintain its effective use

- (5) A relevant person must also ensure—
- (a) lead used in a lead process area does not, as far as is practicable, contaminate other areas of the workplace; and
 - (b) workers are not exposed to the risk from lead in an area provided by the employer for eating and drinking; and
 - (c) before moving from a lead process area to an area used for eating and drinking, a worker washes the worker's forearms, hands and face at the washing facilities provided at the workplace; and
 - (d) no one eats, chews gum, smokes or carries anything used for smoking in a lead process area; and
 - (e) no one in a lead process area drinks from anything other than a drinking facility that is made free from lead contamination; and
 - (f) the workplace is, as far as is practicable, cleaned of lead; and

- (g) a lead process area is not cleaned by compressed air or another compressed gas or dry sweeping; and
 - (h) a worker does not take lead contaminated clothing home for laundering; and
 - (i) lead contaminated clothing is laundered.
- (6) Subsections (1) to (5) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

132 Atmospheric monitoring

- (1) If the risk assessment shows a process includes a lead-risk job, the relevant person must ensure—
- (a) atmospheric monitoring is done in a lead process area at the workplace; and
 - (b) the result of the monitoring is recorded as soon as practicable.

Maximum penalty for subsection (1)(b)—30 penalty units.

- (2) Subsection (1)(a) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

133 Health surveillance

- (1) If the risk assessment shows a process includes a lead-risk job, the relevant person must arrange for health surveillance of the relevant person or a worker who—
- (a) is to start work in the job; or
 - (b) works in the job.
- (2) For a relevant person or worker who is to start work in the lead-risk job, the relevant person must arrange for—

- (a) health surveillance of the relevant person or worker to be done before the relevant person or worker starts work;⁷⁵ and
 - (b) more biological monitoring of the relevant person or worker to be done within 1 month after the relevant person or worker starts work; and
 - (c) more health surveillance of the relevant person or worker to be done within 3 months after the relevant person or worker starts work; and
 - (d) more health surveillance of the relevant person or worker to be done within 6 months after the relevant person or worker starts work.
- (3) For a relevant person or worker who works in the lead-risk job, the relevant person must arrange for—
 - (a) health surveillance of the relevant person or worker to be done within 1 month after the risk assessment shows the job is a lead-risk job; and
 - (b) health surveillance or biological monitoring of the relevant person or worker to be done at any other time if requested by a designated doctor.
- (4) The relevant person must—
 - (a) arrange for health surveillance or biological monitoring to be done by a designated doctor; and
 - (b) give the designated doctor, on request, the risk assessment record; and
 - (c) when arranging for health surveillance or biological monitoring to be done, ask the designated doctor to, as soon as possible after it is done, give—
 - (i) the relevant person a health surveillance report; and
 - (ii) the worker—

⁷⁵ Note that *health surveillance* means monitoring by medical assessment and biological monitoring. See schedule 9 (Dictionary).

Workplace Health and Safety Regulation 1997

- (A) if health surveillance is done—a health surveillance report and an explanation of the report; and
 - (B) if biological monitoring is done—the results of biological monitoring; and
- (d) give the chief executive notice, in the approved form, of the results of the health surveillance within 6 months of receiving the report.

Maximum penalty for subsection (4)(d)—30 penalty units.

- (5) Anything that must be done by a designated doctor under subsection (4) may be done under the supervision of the designated doctor.
- (6) If the health surveillance is of a worker, a relevant person who is an employer must ensure the designated doctor is chosen after consultation between the relevant person, worker and workplace health and safety representative.

Maximum penalty for subsection (6)—30 penalty units.

- (7) If, after consultation, the relevant person, worker and workplace health and safety representative are unable to decide on a designated doctor, the designated doctor is to be chosen by the relevant person.
- (8) A relevant person who is an employer must pay for health surveillance of a worker under this section.

Maximum penalty for subsection (8)—30 penalty units.

- (9) Subsections (1) to (4)(c) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

- (11) In this section—

health surveillance report means information about—

- (a) the effects on a person's health related to the person's exposure to lead because of a lead-risk job; and
- (b) the need (if any) for remedial action; and
- (c) the type of remedial action needed.

134 Reviewing control measures

- (1) If the atmospheric monitoring shows the level of exposure is equal to or more than the national exposure standard for lead, the relevant person must review the control measures decided in the risk assessment.
- (2) If the designated doctor, in a health surveillance report, recommends the relevant person or worker must be removed from a lead-risk job, or that control measures must be reviewed, the relevant person must—
 - (a) identify how the relevant person or worker was exposed to the lead; and
 - (b) review the control measures; and
 - (c) control the exposure.
- (3) Subsections (1) and (2) are workplace health and safety obligations for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

135 Removal of worker from a lead-risk job

- (1) A relevant person who is an employer must immediately remove a worker from a lead-risk job to a job that is not a lead-risk job if—
 - (a) the designated doctor, in the health surveillance report, recommends the worker be removed from the lead-risk job because of the worker's confirmed blood lead level; or
 - (b) the worker tells the relevant person that the worker—
 - (i) has a medical condition that may be adversely affected by exposure to lead; or
 - (ii) is pregnant or breast feeding; or
 - (c) the relevant person, after consultation with the worker, considers the worker has been exposed to an excessive level of lead; or

- (d) the worker, after consultation with the relevant person, considers the worker has been exposed to an excessive level of lead.

Note—

In relation to taking action under this section or division, a person may also have obligations to comply with anti-discrimination or industrial laws.

- (2) If the relevant person or worker considers the worker has been exposed to an excessive level of lead, the relevant person must arrange for health surveillance of the worker to be done within 7 days after the worker is removed.
- (3) Subsections (1) and (2) are workplace health and safety obligations for the Act.

135A Removal of relevant person from a lead-risk job

- (1) A relevant person must remove himself or herself from a lead-risk job to a job that is not a lead-risk job if—
 - (a) the designated doctor, in the health surveillance report, recommends the relevant person be removed from the lead-risk job because of the person's confirmed blood lead level; or
 - (b) the relevant person—
 - (i) has a medical condition that may be adversely affected by exposure to lead; or
 - (ii) is pregnant or breast feeding.
- (2) If the relevant person considers he or she has been exposed to an excessive level of lead, the relevant person must arrange for health surveillance of himself or herself to be done within 7 days after the relevant person removes himself or herself.
- (3) Subsections (1) and (2) are workplace health and safety obligations for the Act.

136 Return to a lead-risk job

- (1) A relevant person who is an employer must not allow a worker to return to a lead-risk job from which the worker was removed under section 135 unless a designated doctor, after

determining the worker's confirmed blood lead level by health surveillance, advises the worker may return.

- (2) A relevant person must not return to a lead-risk job from which the relevant person removed himself or herself under section 135A unless a designated doctor, after determining the confirmed blood lead level of the relevant person by health surveillance, advises the relevant person may return.
- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

137 Confidentiality of worker's medical record

A relevant person who is an employer must not disclose to anyone (other than the worker or someone with the worker's written consent) the contents of a worker's medical record.

Maximum penalty—30 penalty units.

138 Induction and training about lead

- (1) A relevant person who is an employer must give a worker who may be exposed to lead at the workplace induction and, at least annually, information and ongoing training about lead, including about the worker's obligations under division 5.⁷⁶
- (2) The induction and training must be appropriate having regard to—
 - (a) the level of risk identified in a risk assessment; and
 - (b) the types of workers who may be exposed to the lead; and

Examples of subsection (2)(b)—

- 1 workers from a non-English speaking background
- 2 females of reproductive capacity

- (c) the potential health risks and toxic effects associated with lead absorption; and
- (d) the control measures being used to minimise the risk; and
- (e) the correct way to implement the control measures; and

Example 1 of paragraph (e)—

the correct care and use of personal protective equipment

Example 2 of paragraph (e)—

the correct way to do the work practices mentioned in section 131(5)⁷⁷

- (f) the health surveillance required under this part.
- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

139 Keeping records

- (1) If a risk assessment shows that a process includes a lead-risk job, the relevant person must keep the following documents for 30 years from the day the particular document was made—
- (a) a record of the person working in the lead-risk job, including the person's name, sex and the type of work carried out by the person;
 - (b) the risk assessment record;
 - (c) the results of atmospheric monitoring;
 - (d) the health surveillance report;
 - (e) a record of the date when a person was removed from, or returned to, the lead-risk job.

⁷⁷ Section 131 (Controlling exposure)

- (2) If a risk assessment shows that a process does not include a lead-risk job, the relevant person must keep the risk assessment record for 5 years from the day it was made.
- (3) A relevant person who is an employer must keep a record of the induction and training given to a worker for 5 years from the date of the last entry in the record.
- (4) The record must include the following information for each induction or training session—
 - (a) the date of the session;
 - (b) the topics dealt with at the session;
 - (c) the name of the person who conducted the session;
 - (d) the names of the workers who attended the session.
- (5) The relevant person must allow—
 - (a) a worker, or the workplace health and safety representative to inspect a document mentioned in subsection (1)(a), (b) or (c), (2) or (3) at any reasonable time; and
 - (b) a worker to copy the document.
- (6) If a person stops being a relevant person in the period a document is required to be kept under subsection (1), (2) or (3), the person must ask for, and comply with, the chief executive's directions about the documents storage.

Maximum penalty—30 penalty units.

Division 5 Workers

140 Who division applies to

This division applies to a worker at a workplace where a lead process is carried out.

141 Health surveillance

- (1) A worker must comply with the request of the worker's employer to undergo health surveillance.

- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

142 Advising of pregnancy or breast feeding

- (1) A worker must tell the worker's employer that the worker—
- (a) if the worker knows the worker has a medical condition that may be adversely affected by exposure to lead—has the medical condition; or
 - (b) if the worker knows the worker is pregnant—is pregnant; or
 - (c) is breast feeding.
- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

Part 15 Confined spaces

143 Designing, manufacturing or supplying a confined space

- (1) A designer, manufacturer or supplier of plant that is a confined space must comply with clauses 6.1 to 6.3 of AS/NZS 2865.⁷⁸
- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

78 AS/NZS 2865 (Safe working in a confined space)

144 Modifying a confined space

- (1) A person who modifies a confined space must comply with clause 6.4 of AS/NZS 2865.
- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

145 Using a confined space

- (1) A relevant person at a workplace at which a confined space is used, or is to be used, must comply with the following clauses of AS/NZS 2865—
 - (a) clause 8.1;
 - (b) clauses 9.1 and 9.2;
 - (c) clauses 10.1, 10.5, 10.11, 10.22, 10.30, 10.41 and 10.46 to 10.48;
 - (d) clauses 11.1, 11.3, 11.6 and 11.9;
 - (e) clauses 12.1 and 12.2;
 - (f) clause 13.⁷⁹

Maximum penalty for subsection (1)(a), (b) or (f)—30 penalty units.

- (1A) A risk assessment under subsection (1)(b) must be carried out by a person who has acquired through training, qualifications, or experience the knowledge and skill enabling the person to perform the assessment.
- (2) Subsection (1)(c) to (e) is a workplace health and safety obligation for the Act.

⁷⁹ AS/NZS 2865 (Safe working in a confined space)—clause 8.1 (Hazard identification), clauses 9.1 and 9.2 (Risk assessment), clauses 10.1, 10.5, 10.11, 10.22, 10.30, 10.41 and 10.46 to 10.48 (Control measures), clauses 11.1, 11.3, 11.6 and 11.9 (Training and competence), clauses 12.1 and 12.2 (Emergency response), and clause 13 (Record keeping)

Note—

See section 24 of the Act for the penalty for failing to discharge the obligation.

Part 16 **Roll-over protective structures for wheeled tractors**

Division 1 **Interpretation**

146 **Definitions for pt 16**

In this part—

exempt tractor means a tractor that—

- (a) weighs less than 560kg, or more than 15000kg, measured with a full fuel tank, coolant and lubricating oil; or
- (b) is being used in, or driven to or from, an orchard that would impede the operation of the tractor if a roll-over protective structure were to be fitted to the tractor; or
- (c) is being used in or near a building or other structure that would impede the operation of the tractor if a roll-over protective structure were to be fitted to the tractor; or
- (d) is being used in a stationary position; or
- (e) is being driven to or from a place where the tractor is to be used, or has been used, in a stationary position; or
- (f) is being maintained, modified, serviced or repaired if it is necessary to remove the tractor's roll-over protective structure to do the maintenance, modification, service or repair; or
- (g) is being used for a historical activity.

historical activity, in relation to the use of a tractor, includes an activity ancillary to a historical activity.

Example of a historical activity—

a historical display, parade, demonstration or re-enactment

Example of an activity ancillary to a historical activity—

restoring, maintaining, modifying, servicing, repairing or housing a tractor used, or to be used, for a historical activity

roll-over protective structure means a structure designed and constructed to prevent or minimise the risk of death or injury to the operator of a tractor because of the tractor rolling over in any direction.

tractor see section 147.

147 Meaning of *tractor*

- (1) In this part, ***tractor*** means a vehicle primarily designed to—
 - (a) haul agricultural machinery or implements; or
 - (b) provide power for agricultural machinery or implements by transmission shaft, belt or linkage system.
- (2) For subsection (1), it does not matter whether the vehicle—
 - (a) is used at an agricultural workplace; or
 - (b) can be converted temporarily into earthmoving machinery.
- (3) However, a vehicle primarily designed as earthmoving machinery is not a tractor under this part.

Example of earthmoving machinery—

a dozer or front-end loader

148 Demonstrator tractor is taken to be new

For this part, a tractor that is a demonstrator for new tractors is taken to be new.

Division 2 Ways to prevent or minimise risk from wheeled tractor rolling over

149 Ways to prevent or minimise risk prescribed

Sections 150 to 153 prescribe ways of preventing or minimising exposure of the operator of a wheeled tractor to the risk of death or injury from the tractor rolling over.

150 Roll-over protective structure to be fitted to wheeled tractor used by relevant person

- (1) This section does not apply to—
 - (a) an exempt tractor; or
 - (b) a tractor manufactured before 1 January 1981.
- (2) A relevant person must ensure that a wheeled tractor used by himself or herself, as the operator of the tractor, in the conduct of his or her business or undertaking is fitted with a roll-over protective structure.
- (3) However, until the end of 30 June 2007, subsection (2) applies only if the tractor was purchased new by the relevant person, or by persons who include the relevant person, after the commencement of this section.
- (4) Also, if the roll-over protective structure is first fitted to the tractor after the commencement of this section, the roll-over protective structure must comply with AS 1636.⁸⁰

151 Roll-over protective structure to be fitted to wheeled tractor used by worker

- (1) A relevant person who is an employer must ensure that a wheeled tractor, other than an exempt tractor, used by a worker of the employer as the operator of the tractor is fitted with a roll-over protective structure.
- (2) However, until the end of 30 June 2007, subsection (1) applies only if the tractor was purchased new by the relevant person,

80 AS 1636 (Tractors—Roll-over protective structures—Criteria and tests)

or by persons who include the relevant person, after the commencement of this section.

- (3) Also, if the roll-over protective structure is first fitted to the tractor after the commencement of this section, the roll-over protective structure must comply with AS 1636.

153 Roll-over protective structure to be fitted to wheeled tractor hired, leased or borrowed

- (1) Until the end of 30 June 2007, a relevant person must ensure that a tractor, other than an exempt tractor, is fitted with a roll-over protective structure if the tractor—
 - (a) is being hired, leased or borrowed by the relevant person or by persons who include the relevant person; and
 - (b) is used in the conduct of the relevant person's business or undertaking.
- (2) Until the end of 30 June 2007, a relevant person must ensure that a tractor, other than an exempt tractor, is fitted with a roll-over protective structure if the tractor—
 - (a) is being hired, leased or borrowed by the relevant person or by persons who include the relevant person; and
 - (b) is used for the purposes of the relevant person's business or undertaking.
- (3) Despite subsection (1) or (2), if the roll-over protective structure is first fitted to the tractor after the commencement of this section, the roll-over protective structure must comply with AS 1636.

Division 3 Obligation of prospective supplier of wheeled tractor not fitted with a roll-over protective structure

154 Obligation of prospective supplier of wheeled tractor not fitted with a roll-over protective structure

- (1) This section applies to a wheeled tractor that—

- (a) weighs at least 560kg, but not more than 15000kg, measured with a full fuel tank, coolant and lubricating oil; and
 - (b) is not fitted with a roll-over protective structure complying with AS 1636.
- (2) A person (the **prospective supplier**) must not supply the tractor or expose it for supply.
- (3) The prospective supplier does not contravene subsection (2) if the person to whom the tractor is supplied or exposed for supply tells, in general terms, the prospective supplier, or someone for the prospective supplier, that the person intends to use the tractor only in 1 or more of the following ways (the **stated way**)—
 - (a) in a stationary position;
 - (b) in an orchard that would impede the operation of the tractor if a roll-over protective structure were to be fitted to the tractor;
 - (c) in or near a building or other structure that would impede the operation of the tractor if a roll-over protective structure were to be fitted to the tractor;
 - (d) for a historical activity.
- (4) However, subsection (3) does not apply if the prospective supplier knows or suspects that the person intends to use the tractor in a way other than the stated way.
- (5) Subsection (2) is a workplace health and safety obligation for the Act.⁸¹
- (6) A person must not tell a prospective supplier, as mentioned in subsection (2), that the person intends to use a tractor only in 1 or more of the stated ways if the person does not have that intention at the time of the statement.

Maximum penalty—20 penalty units.

- (7) In this section—

supply includes sell, hire out, lease, auction, barter or supply.

81 See section 24 (Discharge of obligations) of the Act for the penalty for failing to discharge the obligation.

Part 17 Construction work

Division 1 Interpretation

155 Definitions for pt 17

In this part—

anchorage point means a device or thing by which a lanyard, static line or other line may be attached to a building or other structure, and includes the part of the building or structure to which the device or thing is attached.

Examples—

- a stainless steel eyebolt, set in a concrete floor, to which a lanyard may be attached
- a sling around a steel I beam, with padding under the sling, joined by a shackle or other joining device to which a lanyard may be attached
- a plate for a travel restraint system fixed by screws to a roof component to which a lanyard may be attached

barricade means a self-supporting fence, or a self-supporting series of continuous plastic, concrete or other solid barriers, usually temporary, erected or placed to restrict the entry of persons to a workplace.

Examples of fences—

- steel pickets joined by chain wire of appropriate height to restrict entry
- steel pickets joined by rows of wire at appropriate heights to restrict entry
- steel pickets joined by taut plastic webbing commonly known as para-webbing

caisson means a structure that provides an underground passageway or a passageway through water.

catch platform means a platform designed to provide overhead protection to persons by catching falling objects.

civil construction work means construction work in relation to any of the following structures—

- (a) a structure mentioned in schedule 3⁸² of the Act, definition *structure*, paragraph (b), (c) or (d);
- (b) a bridge;
- (c) a pumping station;
- (d) a refinery;
- (e) a telecommunications structure.

cofferdam means a temporary wall erected to exclude water from an area normally under water.

common plant means plant provided by the principal contractor for use by any person at the workplace for a purpose other than discharging the principal contractor's workplace health and safety obligations.

construction safety plan means a plan prepared by a principal contractor under section 160.

edge protection means a barrier to prevent a person falling erected along the edge of—

- (a) a building or other structure; or
- (b) an opening in a surface of a building or other structure; or
- (c) a fall arresting platform; or
- (d) the surface from which work is to be done.

excavation means a hole in the earth, or a face of earth, formed after rock, sand, soil or other material is removed.

Examples—

- a trench, ditch, shaft, well, tunnel, pier hole, cutting, caisson or cofferdam
- a hole drilled in the earth

excavation work means work to make, fill or partly fill an excavation.

fall-arrest harness system means a system that—

- (a) is designed to arrest the fall of a person using it and prevent or minimise the risk of injury to the person as the fall is arrested; and
- (b) consists of a harness attached to—
 - (i) a device to absorb the energy of the falling person attached to a lanyard that is attached to a static line or anchorage point; or
 - (ii) a line that—
 - (A) has a device that automatically locks the line, and absorbs the energy of the falling person; and
 - (B) is attached to a static line or anchorage point; or
 - (iii) a lanyard that—
 - (A) has a device that travels along a line or rail, automatically locks onto the line or rail, and absorbs the energy of the falling person; and
 - (B) is attached to a static line or anchorage point.

fall arresting platform means a platform installed to arrest the fall of a person who falls from a building or other structure.

fall protection cover means a structure that—

- (a) is placed over an opening in a surface of a building or other structure to prevent a person falling through the opening; and
- (b) consists of solid sheets of sturdy material.

Examples for paragraph (b)—

timber, plywood, metal, mesh

gantry means a structure that has—

- (a) an overhead platform; and
- (b) a hoarding, at least 1800mm high that is fully sheeted with timber, plywood, metal or sturdy synthetic sheets, running along its length.

geo-technical engineer means an engineer who holds an engineering qualification relevant to geo-technology.

high risk construction activity see section 156.

hoarding means a self-supporting structure, fully sheeted with timber, plywood, metal or sturdy synthetic sheets, or fully covered by chain wire or sturdy mesh, that is designed—

- (a) to prevent persons other than relevant persons or workers from entering a place where construction work is being performed; and
- (b) to provide protection to those persons against objects approaching them from the side.

housing construction work means construction work that is work to erect, construct, extend or structurally alter—

- (a) any of the following dwellings that is not located above or below another dwelling or another part of a building, other than a part that is a private garage—
 - (i) a detached house;
 - (ii) an attached dwelling, separated from the dwelling to which it is attached by a fire-resisting wall, including, for example, a terrace house or town house;
 - (iii) a boarding house, guest house, hostel or similar building with a floor area of not more than 300m²; or
- (b) a building that is not designed for habitation but is ancillary to a building to which paragraph (a) applies.

Example of an ancillary building—

a private garage, carport or shed

light work means work that is light having regard to the following—

- (a) the amount of physical exertion involved;
- (b) the physical capacity of the person doing the work;
- (c) the range of movement involved;
- (d) the weight or bulk of materials or equipment involved.

Workplace Health and Safety Regulation 1997

Examples of light work—

- painting
- installing a roof gutter, air-conditioning duct, metal fascia or lighting
- placing pine roof trusses in position on the roof of a low-set house
- performing inspections or tests
- installing an electrical connection

Examples of work that is not light work—

- fixing plaster board sheeting to an internal stairwell void
- fixing cladding to a gable end of a roof
- using a medium or heavy duty angle grinder or circular saw

object includes material.

overhead platform means a platform designed to provide overhead protection to persons against falling objects.

perimeter containment screening means a screen—

- (a) designed to stop objects falling on persons from a level of a building; or
- (b) to redirect a falling object onto a catch platform.

permitted work, in relation to work involving a ladder, means work in which—

- (a) the weight, size or shape of any equipment or material the person using the ladder is carrying is not likely to—
 - (i) restrict the person's movement while the person is climbing or descending the ladder; or
 - (ii) cause the person to lose balance on the ladder while doing the work; and
- (b) the person's trunk is approximately centred over the centre of the space between the sides of the ladder from when the person is fully on the ladder to when the person is leaving the ladder; and
- (c) any equipment being used by the person can be operated using 1 hand unless a control measure designed to support the person's body is being worn or used.

Example of a control measure—

a strap, commonly known as a pole strap, that fits around a pole and is attached to a harness worn by the person

prescribed information, about an underground service, means the information about the service necessary to safely do excavation work at or near the service, including—

- (a) the location of the service; and
- (b) the type of the service; and
- (c) the depth of the service; and
- (d) for an electrical service—whether the service is or is not live; and
- (e) the restrictions to be followed in doing the work.

site-specific induction, for construction work, means a workplace health and safety induction that is specific to the place where the construction work is to be performed.

static line means a flexible line, to which a lanyard is attached, supported by at least 2 anchorage points located so that the angle between the horizontal and an imaginary straight line between any anchorage point and the other or nearest anchorage point is—

- (a) if the manufacturer of the flexible line has specified the size of the angle—not more than the size specified; or
- (b) if the manufacturer has not specified the size of the angle—not more than 5°.

travel restraint system means a system that—

- (a) consists of a harness or belt, attached to 1 or more lanyards, each of which is attached to a static line or anchorage point; and
- (b) is designed to restrict the travelling range of a person wearing the harness or belt so that the person can not get into a position where the person could fall off an edge of a surface or through a surface.

trench means an excavation where the maximum depth is more than the minimum width.

underground service means a cable, pipe or other thing laid or installed underground for the transmission, transportation or storage of electricity or a substance.

Examples—

- underground electrical cables
- underground gas pipelines
- underground fuel tanks or pipes
- underground water pipes
- underground sewerage pipelines or services
- underground stormwater pipes or services

work method statement—

- (a) for a high risk construction activity other than a prescribed activity—see section 157; or
- (b) for a high risk construction activity that is a prescribed activity—see section 158.

156 Meaning of *high risk construction activity*

- (1) An activity is a ***high risk construction activity*** if the activity is part of construction work and—
 - (a) the activity involves a person—
 - (i) entering a trench that is more than 1.5m deep; or
 - (ii) using explosives; or
 - (iii) using a confined space;⁸³ or
 - (iv) using a hazardous substance; or
 - (b) during the activity, a person could fall—
 - (i) if the activity is housing construction work—at least 3m; or
 - (ii) if the activity is not housing construction work—at least 2m; or
 - (c) the activity is performed on a roof with a pitch of more than 26°; or

⁸³ Schedule 9 (Dictionary) defines *confined space*.

- (d) the activity is—
 - (i) a prescribed activity; or
 - (ii) demolition work that is not a prescribed activity; or
- (e) the activity consists of—
 - (i) tilt-up and precast construction work; or
 - (ii) structural alterations that require temporary support to prevent collapse; or
 - (iii) the movement of powered mobile plant at the workplace; or
 - Examples for subparagraph (iii)—*
 - the movement of forklifts at the workplace
 - the interaction of rollers with other powered mobile plant at the workplace
 - the interaction of graders with persons at the workplace
 - (iv) work on a telecommunications tower; or
 - (v) work in, over or adjacent to water where there is a risk of drowning; or
 - (vi) work on, or adjacent to, a road or railway; or
 - (vii) work on or near a pressurised gas distribution mains and consumer piping; or
 - (viii) work on or near a chemical, fuel or refrigerant line; or
 - (ix) work near an exposed energised electrical installation; or
 - (x) work in an area that may have a contaminated or flammable atmosphere; or
 - (xi) work in an area where there are artificial extremes of temperature; or
- (f) the principal contractor for the construction work reasonably believes the activity could result in death or bodily harm.

(2) In this section—

electrical installation see the *Electrical Safety Act 2002*, section 15.

energise see the *Electrical Safety Act 2002*, schedule 2.

exposed see the *Electrical Safety Act 2002*, schedule 2.

hazardous substance has the same meaning as in section 100.⁸⁴

powder-actuated hand-held fastening tool has the same meaning as in AS/NZ 1873.⁸⁵

using explosives does not include using powder-actuated hand-held fastening tools.

157 Meaning of *work method statement* for high risk construction activity other than prescribed activity

(1) A ***work method statement***, for a high risk construction activity, other than a prescribed activity, is a written statement for the activity prepared by or under the direction of a relevant person and stating—

- (a) the high risk construction activity; and
- (b) if the relevant person has an ABN, the ABN; and
- (c) the specific control measures the relevant person proposes to use to discharge the relevant person's workplace health and safety obligations for the activity; and
- (d) the way the relevant person proposes to perform the activity, including how the control measures are to be used; and

Example of a control measure to be used—

The relevant person will, when working on or near a road, comply with the Manual of Uniform Traffic Control Devices issued under the *Transport Operations (Road Use Management) Act 1995*.

84 Section 100 (Meaning of *hazardous substance* for division)

85 AS/NZ 1873 (Powder-actuated (PA) hand-held fastening tools)

- (e) how the effectiveness of the control measures will be monitored and reviewed; and

Example of how the effectiveness of a control measure may be monitored—

Before work starts each day, a competent person will check the shoring of a trench more than 1.5m deep to ensure the trench will not collapse.

- (f) if the activity is to be performed in an earthmoving or particular crane occupation—the occupation; and
 - (g) if the activity is high risk work—the class of high risk work that includes the work.
- (2) Control measures mentioned in subsection (1)(c) are control measures directed at—
 - (a) if the activity is a high risk construction activity because of section 156(1)(a)(i)—the trench collapsing; or
 - (b) if the activity is a high risk construction activity because of section 156(1)(a)(ii)—an explosion; or
 - (c) if the activity is a high risk construction activity because of section 156(1)(a)(iii)—working in the confined space; or
 - (d) if the activity is a high risk construction activity because of section 156(1)(a)(iv)—being exposed to the substance; or
 - (e) if the activity is a high risk construction activity because of section 156(1)(b) or (c)—falling; or
 - (f) if the activity is a high risk construction activity because of section 156(1)(f)—hazards the principal contractor identifies.
 - (3) A work method statement for a high risk construction activity, other than a prescribed activity, may be a generic work method statement prepared for workplaces where the activity is to be performed in the same way in the same or similar circumstances.

158 Meaning of *work method statement* for high risk construction activity that is prescribed activity

- (1) A *work method statement*, for a high risk construction activity that is a prescribed activity, is a written statement for the activity prepared by or under the direction of a relevant person who is the holder of a certificate prescribed in subsection (3) for the activity and stating—
 - (a) what prescribed activity is being performed; and
 - (b) if the holder has an ABN, the ABN; and
 - (c) the certificate number of the certificate; and
 - (d) the specific control measures the holder proposes to use to discharge the holder's workplace health and safety obligations for the activity; and
 - (e) the way the holder proposes to perform the activity, including how the control measures are to be used; and
 - (f) how the effectiveness of the control measures will be monitored and reviewed; and
 - (g) the arrangements for appropriate training under part 3A⁸⁶ of workers employed, or otherwise allowed, to perform the activity; and
 - (h) the arrangements for supervision under part 3A of the performance of the activity by a competent person within the meaning of section 29F(2).⁸⁷
- (2) A work method statement for a high risk construction activity that is a prescribed activity may be a generic work method statement prepared for workplaces where the activity is to be performed in the same way in the same or similar circumstances.
- (3) For subsection (1), the following are prescribed—
 - (a) if the activity is asbestos removal work, that is work to remove 10m² or more of bonded asbestos containing material—a bonded asbestos removal certificate;

86 Part 3A (Prescribed activities)

87 Section 29F (Supervision of performance of prescribed activity)

- (b) otherwise—a certificate under section 29B to perform the activity.

Division 2 Principal contractors

Subdivision 1 Preliminary

159 Application of div 2

- (1) This division applies only to a principal contractor performing construction work.
- (2) However, subsection (1) does not prevent a principal contractor from having obligations under division 3 if the principal contractor performs construction work as a relevant person.

Subdivision 2 Obligation to prepare construction safety plan

160 Principal contractor must prepare construction safety plan

- (1) A principal contractor must prepare a written construction safety plan complying with subsections (2) and (3) before construction work starts.

Maximum penalty—30 penalty units.

- (2) The construction safety plan must state—
 - (a) the address where the construction work is to be performed; and
 - (b) the name and address of the principal contractor for the construction work; and
 - (c) if the principal contractor has an ABN, the ABN; and

- (d) whether there is a workplace health and safety committee⁸⁸ for the workplace where the construction work is to be performed; and
- (e) whether there is a workplace health and safety officer appointed⁸⁹ for the workplace where the construction work is to be performed; and
- (f) when the construction work is expected to start; and
- (g) the principal contractor's estimate of how long the construction work will take; and
- (h) the type of construction work to be performed; and

Examples of the type of construction work to be performed—

- work to erect a town house
- work to construct a road
- work to demolish an office block
- (i) the risks of the construction work for which the principal contractor has a workplace health and safety obligation; and
- (j) the proposed control measures to prevent, or minimise the level of the risks; and
- (k) how the principal contractor proposes to ensure the proposed control measures are used; and
- (l) how the principal contractor proposes to monitor and review the effectiveness of the proposed control measures; and
- (m) the site rules; and

Examples of site rules—

- 1 All visitors to the site must report immediately to the site office.
- 2 Safety boots and goggles must be worn on the site.
- 3 A person must not consume alcohol on the site.

88 See part 7 (Workplace consultative arrangements), division 4 (Workplace health and safety committees) of the Act.

89 See part 8 (Workplace health and safety officers) of the Act.

- (n) the emergency procedures for the construction work; and

Examples of emergency procedures—

- 1 If there is an emergency evacuation, a siren will sound and all personnel must assemble on the corner of Green Street and Blue Street to await further instruction for returning to the site.
 - 2 The periodic testing of emergency lighting installations.
 - 3 The periodic testing of fire fighting equipment.
- (o) how the principal contractor proposes to discharge the principal contractor's obligation to persons using areas adjacent to the place where the construction work is being performed; and

Example—

A gantry with a hoarding will be provided over the footpath to protect persons from falling objects.

- (p) the common plant to be provided.

Examples of common plant—

- perimeter guard railing
- 1800mm hoarding

- (3) The construction safety plan must be—

- (a) written in a way likely to be understood by the persons likely to be performing the construction work; and
- (b) signed and dated by the principal contractor.

161 When principal contractor not to allow relevant person to start housing construction work

A principal contractor must not allow a relevant person to start construction work that is housing construction work unless the principal contractor, or someone acting for the principal contractor, has—

- (a) given the person a copy of the current construction safety plan; or

- (b) discussed with the person the aspects of the construction safety plan relevant to the person's work.

Maximum penalty—30 penalty units.

162 When principal contractor not to allow relevant person to start construction work, other than housing construction work

A principal contractor must not allow a relevant person to start construction work other than housing construction work unless the current construction safety plan—

- (a) is available for inspection at the workplace by any person performing or intending to perform the construction work; or
- (b) if the principal contractor, or someone acting for the principal contractor, is not present at the workplace—is readily available for inspection by any person performing or intending to perform the construction work.

Maximum penalty—30 penalty units.

163 Availability of current construction safety plan

A principal contractor must ensure the current construction safety plan and current work method statements held by the principal contractor are readily available for inspection while the construction work is being performed.

Maximum penalty—30 penalty units.

164 Amendment of construction safety plan

- (1) A principal contractor must ensure the construction safety plan is amended if there is a change in the information mentioned in section 160(2)(i) to (p).

Maximum penalty—30 penalty units.

- (2) If the construction safety plan is amended under subsection (1), the principal contractor must ensure each relevant person affected by the amendment is—

- (a) advised of the details of the amendment; or
- (b) given a copy of the amendment.

Maximum penalty—30 penalty units.

Subdivision 3 Principal contractor's obligation for work method statements

165 Principal contractor not to allow relevant person to start high risk construction activity unless work method statement prepared

A principal contractor must not allow a relevant person to start a high risk construction activity unless the relevant person has prepared a work method statement for the activity.

Maximum penalty—30 penalty units.

166 Work method statement or amended work method statement to be kept with construction safety plan

- (1) This section applies if a principal contractor is given a work method statement or amended work method statement for a high risk construction activity to be performed.
- (2) The principal contractor must—
 - (a) sign and date the work method statement or amended work method statement; and
 - (b) keep the statement or amended statement with the construction safety plan.

Maximum penalty—30 penalty units.

167 Principal contractor not to allow person to perform prescribed activity unless in compliance with work method statement

A principal contractor must not allow a person to perform a high risk construction activity that is a prescribed activity

unless the activity is performed in a way complying with the current work method statement for the activity.

Maximum penalty—30 penalty units.

168 Principal contractor to monitor use of work method statement

A principal contractor must monitor the use of any work method statement required under this regulation to ensure that all persons to whom the statement applies comply with the statement.

Maximum penalty—30 penalty units.

Subdivision 4 Principal contractor's obligation to sight induction evidence and conduct site-specific workplace health and safety inductions

169 Principal contractor to sight general induction evidence before construction work starts

- (1) A principal contractor must not allow a relevant person to start construction work unless the principal contractor has sighted general induction evidence for the person.

Maximum penalty—30 penalty units.

- (2) In this section—

construction work does not include work to repair a structure that is fixed plant, a ship or a submarine.

170 Site-specific induction to be given

- (1) This section does not apply to construction work that is housing construction work.
- (2) A principal contractor must ensure a person has been given a site-specific induction for the workplace before allowing the person to start construction work.

Maximum penalty—30 penalty units.

- (3) A principal contractor must ensure a person entering a part of the workplace where construction work is being performed—
- (a) has been given a site-specific induction for the workplace; or
 - (b) is accompanied by the principal contractor or someone who has been given a site-specific induction for the workplace.

Maximum penalty—30 penalty units.

- (4) The principal contractor must ensure that induction given to a person includes the following aspects of the construction safety plan for the workplace—
- (a) whether there is a health and safety committee for the workplace;
 - (b) if there is a workplace health and safety officer appointed—
 - (i) the officer's name and contact details; and
 - (ii) a description of the officer's role;
 - (c) the principal contractor's estimate of how long the construction work will take;
 - (d) how the principal contractor proposes to monitor and review the effectiveness of the control measures the principal contractor has used or will use;
 - (e) the site rules;
 - (f) emergency procedures, including the name and contact details of the first aid officer;
 - (g) the common plant and directions about how it is to be used at the workplace.

Maximum penalty—30 penalty units.

- (5) The principal contractor must ensure a record is made of—
- (a) the name of each person inducted; and
 - (b) the date the induction was given.

Maximum penalty—30 penalty units.

- (6) The principal contractor must keep the record made under subsection (5) until the construction work ends.

Maximum penalty—30 penalty units.

Subdivision 5 Principal contractor's obligation for others

171 Authority to perform work for prescribed activities, work in an earthmoving or particular crane occupation or high risk work

A principal contractor must not allow a person to perform the following—

- (a) high risk work unless the person has appropriate authority to perform the high risk work under section 17 or is exempted from the requirement to hold appropriate authority;
- (b) work in an earthmoving or particular crane occupation unless the person has appropriate authority to perform work in the occupation under section 24 or is exempted from the requirement to hold appropriate authority;
- (c) work that is a prescribed activity unless the person has authority under section 29B to perform the activity or section 29B does not apply to the performance of the work.

Maximum penalty—30 penalty units.

Subdivision 6 Principal contractor's obligation to erect signs

172 Signs

- (1) A principal contractor must, before construction work starts, ensure that adequate numbers of general safety signs, having regard to the size and complexity of the workplace, are erected at the workplace to adequately indicate to persons—
- (a) the nature of the workplace; and

Example of sign for paragraph (a)—

‘Construction site. No unauthorised entry.’

- (b) that unauthorised entry to the workplace is not allowed;
and

Example for paragraph (b)—

‘All persons must report to the site office.’

- (c) that they are not to use the workplace or any adjoining
area in stated circumstances.

Example of sign for paragraph (c)—

‘Do not proceed if light is flashing. Load is being lifted onto
site.’

Examples of general safety signs—

- signs, at each point of entry to the workplace, indicating that unauthorised entry to the workplace is not allowed
 - signs indicating the direction to the site office or site amenities
 - signs indicating where first aid equipment and facilities and fire extinguishing equipment are kept
 - signs indicating that a means of access must be kept clear
 - signs indicating where hazardous substances are kept
 - signs indicating who the principal contractor is
 - signs indicating that head and foot protection must be worn
- (2) The principal contractor must keep the signs in good condition.
- (3) Subsections (1) and (2) are workplace health and safety obligations for the Act.

Subdivision 7 Principal contractor’s obligation about safe housekeeping practices

173 Purpose of sdiv 7

The purpose of this subdivision is to establish and maintain an orderly workplace environment to prevent or minimise a person’s exposure to risk that may result because of hazards at

the workplace in relation to which the principal contractor owes a workplace health and safety obligation.

Examples of establishing and maintaining an orderly workplace environment—

- installing and maintaining adequate entry and exit lighting in accordance with AS/NZS 1680
- installing and maintaining emergency evacuation signage and lighting in accordance with AS/NZS 2293

174 Safe housekeeping practices

- (1) The principal contractor for construction work must ensure that—
 - (a) safe housekeeping practices are used for the construction work; and
 - (b) the effectiveness of the practices is monitored and reviewed; and
 - (c) the practices are kept up-to-date; and
 - (d) each relevant person performing the work is instructed to follow the practices to the extent they relate to the person.
- (2) For subsection (1), safe housekeeping practices include—
 - (a) ensuring there is appropriate, safe and clear entry to and exit from the workplace; and
 - (b) ensuring there is a safe system for collecting, storing and disposing of excess or waste materials; and
 - (c) ensuring there is enough area in which to safely store materials or plant for the construction work.
- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Subdivision 8 Principal contractor's obligation for common plant

175 Common plant

- (1) If a principal contractor provides common plant, the principal contractor must—
 - (a) ensure the plant is safe for the purpose for which it is provided when it is provided; and
 - (b) keep the plant effectively maintained while it is provided; and
 - (c) comply with the provisions of this regulation about plant of the same type as the common plant as if the provisions applied to the common plant.
- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Subdivision 9 Principal contractor's obligation for hazardous substances

176 Register of hazardous substances

- (1) A principal contractor must keep a register, containing the information mentioned in subsections (2) and (3), of all hazardous substances the principal contractor is aware are at, or are proposed to be used at, the workplace.

Maximum penalty—30 penalty units.

- (2) The register must contain the name of the relevant person (if any) the principal contractor knows is proposing to use the substance at the workplace.
- (3) The register must also contain a copy of the substance's current MSDS.
- (4) The information must be entered in the register as soon as reasonably practicable after the principal contractor becomes aware that the hazardous substance is at, or is proposed to be used at, the workplace.

Maximum penalty—30 penalty units.

- (5) The principal contractor must allow anyone working, or about to work, at the workplace to inspect the register at all reasonable times.

Maximum penalty—30 penalty units.

Subdivision 10 Principal contractor's obligation for underground services

177 Information about underground services

- (1) This section applies if a principal contractor intends to perform construction work that includes excavation work.
- (2) Before the excavation work starts the principal contractor must—
 - (a) find out from appropriate sources what underground services are at or near the location where the work is to be done that could create a risk if contacted or damaged; and
 - (b) obtain prescribed information about each underground service from an appropriate source; and
 - (c) ensure the information is recorded in writing; and
 - (d) give the information to each relevant person who is to do excavation work at or near the location of the service.
- (3) Subsection (2) is a workplace health and safety obligation for the Act.
- (4) The principal contractor must keep the information recorded until the construction work ends.

Maximum penalty—30 penalty units.

Subdivision 11 Principal contractor's obligation for falling objects

178 Application of sdiv 11

This subdivision applies to construction work if an object could fall on or otherwise hit persons during the work.

179 What is *mesh* for sdiv 11

- (1) **Mesh**, for this subdivision, is mesh that complies with this section.
- (2) The mesh must be made of at least 2.5mm diameter steel with a tensile strength of at least 380MPa.
- (3) If the pattern of the openings within the mesh are a square or other rectangle, the openings within the mesh must not be over—
 - (a) for mesh with prescribed lining securely attached to the inside of the mesh—50mm by 50mm; or
 - (b) otherwise—
 - (i) if the openings are square, 25mm by 25mm; or
 - (ii) if the openings are not square, 25mm by 50mm.
- (4) If the pattern of the openings within the mesh are not a square or other rectangle, the openings within the mesh must not be over—
 - (a) if the mesh has prescribed lining securely attached to the inside of the mesh—50mm in any direction; or
 - (b) otherwise—25mm in any direction.
- (5) In this section—

prescribed lining, in relation to mesh, means intact shade cloth, or another intact lining, that when tested, wet or dry, in accordance with method A in AS 2001.2.4⁹⁰ has a mean bursting pressure of at least 1000kPa.

90 AS 2001.2.4 (Methods of test for textiles—Physical tests—Determination of bursting pressure of textile fabrics—Hydraulic diaphragm method)

180 Risk assessment and control measures for civil construction work and housing construction work

- (1) This section applies to construction work that is—
 - (a) civil construction work; or
 - (b) housing construction work.
- (2) A principal contractor must, before the construction work starts—
 - (a) assess the risk of death or injury to persons that may result from objects that could fall on or otherwise hit persons during the work; and

Examples of objects that could fall—

- parts of a structure being built or demolished
- walls being demolished
- materials stored or stacked at the workplace
- construction material
- waste material
- debris
- plant
- tools
- scaffolding components
- pre-cast panels

- (b) ensure control measures are used to prevent, or minimise the level of, exposure to the risk.

Examples of control measures—

- a sign stating ‘Construction site. No unauthorised entry.’
- an 1800mm chain wire barricade, or an 1800mm hoarding, for work done beside a footpath near a school
- a gantry for work involving a multiple level domestic house that is beside a footpath
- perimeter containment screening
- a catch platform
- a catch net
- closure of the adjoining area
- a traffic control device

Workplace Health and Safety Regulation 1997

- a road diversion
 - a detour
 - traffic controllers to direct pedestrians or other traffic
 - working outside normal hours
- (3) However—
- (a) if the control measure is a hoarding—it must comply with the requirements for a hoarding under section 181(6)(a) and (b); or
 - (b) if the control measure is a gantry—it must comply with the requirements for a gantry under section 186; or
 - (c) if the control measure is a closure of the adjoining area—it must be used in compliance with the requirements for a closure under section 188; or
 - (d) if the control measure is perimeter containment screening—it must—
 - (i) comply with section 184; and
 - (ii) if it is designed to stop objects falling on persons from a level of a structure—be erected along each part of a structure from which an object could fall in the adjoining area during the work; or
 - (e) if the control measure is a catch platform—it must comply with section 185.
- (4) Subsections (2) and (3) are workplace health and safety obligations for the Act.

181 Control measures for construction work that is not civil construction work or housing construction work

- (1) This section applies to construction work that is not civil construction work or housing construction work.
- (2) A principal contractor must ensure that a relevant person—
 - (a) identifies and decides the line (the *proposed line*) along which any barricade or hoarding required under subsection (3) is to be erected; and
 - (b) measures the angle to the horizontal formed by an imaginary straight line drawn between—

- (i) the highest point at which work is being done on the structure involved in the work during which an object could fall on or otherwise hit a person; and
 - (ii) the point on the ground, along the proposed line, that is closest to the highest point.
- (3) Before the work starts, the principal contractor must ensure that—
 - (a) if the measured angle is not more than 15°—a barricade or hoarding at least 900mm high that surrounds the structure is erected along the proposed line; or
 - (b) if the measured angle is more than 15° but not more than 30°—a hoarding at least 1800mm high is erected along the proposed line; or
 - (c) if the measured angle is more than 30° but less than 75°—a hoarding at least 1800mm high that is fully sheeted with timber, plywood, metal or sturdy synthetic sheets is erected along the proposed line; or
 - (d) if the measured angle is 75° or more—
 - (i) a hoarding at least 1800mm high that is fully sheeted with timber, plywood, metal or sturdy synthetic sheets and that is not part of a gantry is erected along the proposed line; or
 - (ii) a gantry is erected under section 182(3)(a).
- (4) A hoarding under subsection (3)(b), (c) or (d) must be erected adjacent to the sides of each part of the structure from which an object could fall.
- (5) If subsection (3) or (4) does not require part of the structure to have a hoarding erected adjacent to the side of the part, the principal contractor must ensure that a barricade or hoarding at least 900mm high is erected along the proposed line adjacent to the sides of the part of the structure.
- (6) A hoarding under subsection (3) must—
 - (a) prevent an object that may reasonably be expected to hit it from entering the adjoining area; and
 - (b) be strong enough, and appropriately designed and erected, for the circumstances in which it is used,

including the location of the workplace and the type of work to be carried out near the hoarding.

- (7) A hoarding under subsection (3)(c) or (d)—
 - (a) must be able to withstand a horizontal force of—
 - (i) 500N per m² applied over 1m² at the top of the hoarding midway between any post and its nearest post without deforming permanently; and
 - (ii) 950N applied over 1500mm² at any point on the hoarding without fully penetrating the hoarding; and
 - (b) may have gaps to minimise wind resistance, if the gaps are no larger than are reasonably necessary; and
 - (c) if it is part of a gantry—must extend to the gantry's overhead platform.
- (8) Subsections (2) to (7) are workplace health and safety obligations for the Act.

182 Additional control measures if measured angle is 75° or more, other than for demolition work or work erecting or dismantling formwork

- (1) This section applies if the angle measured under section 181(2)(b) is 75° or more.
- (2) This section does not apply to—
 - (a) demolition work; or
 - (b) work erecting or dismantling formwork on or for a structure.
- (3) The principal contractor must ensure that at least 1 of the following control measures is used before construction work starts—
 - (a) a gantry is erected along the proposed line adjacent to the sides of each part of the structure from which an object could fall;
 - (b) the adjoining area is closed under section 188 at least to the extent necessary to prevent objects falling on or otherwise hitting persons;

- (c) a catch platform with perimeter containment screening complying with section 184 is installed—
 - (i) along the sides of each part of the structure from which an object could fall; and
 - (ii) not more than 1m below—
 - (A) if the structure has storeys—the storey of the structure from which an object could fall; or
 - (B) if the structure does not have storeys—the surface from which an object could fall.
- (4) Subsection (3) is a workplace health and safety obligation for the Act.
- (5) In this section—
formwork includes a structure installed to support formwork.

183 Control measures for demolition work or work erecting or dismantling formwork

- (1) This section applies to construction work that is—
 - (a) demolition work; or
 - (b) work erecting or dismantling formwork.
- (2) A principal contractor must ensure that, before the construction work starts—
 - (a) the adjoining area is closed under section 188 at least to the extent necessary to prevent objects falling on or otherwise hitting persons; or
 - (b) perimeter containment screening complying with section 184 is erected along each part of a structure from which an object could fall.
- (3) However, if the work is demolition work, the principal contractor must ensure that a control measure other than a control measure mentioned in subsection (2) is used before the work starts to prevent objects falling on or otherwise hitting persons if—
 - (a) the adjoining area can not be closed under subsection (2)(a) because the person who controls the area withholds written approval to close the area; and

- (b) perimeter containment screening can not be erected under subsection (2)(b).
- (4) If the principal contractor erects perimeter containment screening under subsection (2)(b), or extends or reduces perimeter containment screening erected under subsection (2)(b), the principal contractor must ensure that control measures are used to prevent a component of the screening falling on persons while the screening is being erected, extended or reduced.
- (5) Subsections (2), (3) and (4) are workplace health and safety obligations for the Act.
- (6) In this section—
formwork includes a structure installed to support formwork.

184 Perimeter containment screening as control measure

- (1) Each screen of perimeter containment screening used as a control measure, and its supporting framework, must comply with this section.
- (2) If the perimeter containment screening is used to redirect a falling object onto a catch platform, each screen must be fitted vertically to the top of, or flush with, the outer edge of the catch platform to redirect a falling object, that may reasonably be expected to hit the perimeter containment screening, onto the catch platform.
- (3) If the perimeter containment screening is not used to redirect a falling object onto a catch platform, each screen must be designed to prevent an object, that may reasonably be expected to hit the perimeter containment screening, from falling on persons from the level at which the work is to be done.
- (4) Each screen must be made of mesh or of timber, plywood or metal sheeting.
- (5) Each of the following gaps must be not over 25mm—
 - (a) the gap, measured horizontally, between—
 - (i) screens immediately beside each other; or
 - (ii) a screen and the framework supporting it;

- (b) the gap, measured vertically, between—
 - (i) a screen and another screen immediately above it; or
 - (ii) a screen and the framework supporting it.
- (6) The framework supporting a screen must be able to bear the load of the screen.

185 Catch platform as control measure

- (1) If a catch platform used or to be used as a control measure is installed, extended or reduced, the principal contractor must ensure that control measures are used to prevent a component of the platform falling on persons while the platform is being installed, extended or reduced.
- (2) Subsection (1) is a workplace health and safety obligation for the Act.

186 Gantry as control measure

- (1) A gantry used as a control measure must be designed by an engineer to withstand a downwards force of at least—
 - (a) if light work, or work other than light work at a height of not more than 10m above the ground, is to be done—5kPa applied on its overhead platform; or
 - (b) if work, other than light work, at a height of more than 10m above the ground is to be done—10kPa applied on its overhead platform.
- (2) The gantry must—
 - (a) be able to stop an object that may reasonably be expected to fall on it from falling; and
 - (b) have an overhead platform that is secured to prevent it lifting or coming apart; and
 - (c) have solid sheeting erected along the outer edge of its overhead platform to at least the higher of—
 - (i) 900mm above the platform; and
 - (ii) the height of any object stored on the platform; and

- (d) if it is used to store materials or has a shed erected on it—be designed by an engineer to take the additional load involved; and
- (e) be able to stop water or dust falling on persons; and
- (f) have natural or other lighting of at least 50 lux illuminating all of the area below it; and
- (g) not tip over or rotate if a force that could reasonably be expected to be applied to it is applied to it.

Example of a force mentioned in paragraph (g)—

the force of a truck backing into the gantry

187 Load lifted over adjoining area

- (1) This section applies to construction work that involves lifting a load over the adjoining area.
- (2) This section does not apply to construction work that is housing construction work.
- (3) A principal contractor must ensure that, before the work starts—
 - (a) the adjoining area is closed under section 188 at least to the extent necessary to prevent objects falling on or otherwise hitting persons in the adjoining area; or
 - (b) a gantry is erected that provides adequate protection to persons in the adjoining area against falling objects if the load were to fall.
- (4) Without limiting subsection (3)(b), the gantry must at least comply with section 186.

Example—

If a pallet of scaffolding components is to be lifted over an adjoining area, the downwards force that the gantry's overhead platform must be able to withstand is—

- (a) if the force applied by the pallet and components is less than or equal to 10kPa—10kPa; or
 - (b) if the force applied by the pallet and components is greater than 10kPa—the force applied by the pallet and components.
- (5) Subsection (3) is a workplace health and safety obligation for the Act.

188 Closure of part or all of adjoining area

- (1) If an adjoining area is to be closed, a principal contractor must, before construction work starts, do each of the following—

- (a) ensure that written approval to close the area is obtained from the authority or other person who controls the area;

Examples of an authority—

- a local government
- the Department of Main Roads
- the Queensland Police Service

- (b) if an authority controls the area, use any measures for the closure required by the authority.

Examples of measures for the closure—

- physical barriers to prevent use of a footpath or road
- signs about the closure
- signs directing pedestrians to use another footpath
- traffic controllers to direct pedestrians or other traffic

- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Subdivision 12 Principal contractor's obligation for amenities**189 Amenities**

- (1) Schedule 8A states particular duties of a principal contractor about amenities.
- (2) A principal contractor must ensure that an amenity provided under schedule 8A is maintained in a hygienic, safe and serviceable condition, including by ensuring that there is a system for—
- (a) inspecting and cleaning the amenity; and

- (b) if the amenity has facilities to dispose of sanitary items for females—the adequate and hygienic disposal of the sanitary items.

Maximum penalty—20 penalty units.

Division 3 Relevant persons

Subdivision 1 Preliminary

190 Application of div 3

- (1) This division applies only to a relevant person performing construction work.
- (2) However, subsection (1) does not prevent a relevant person from having obligations under division 2 if the relevant person performs construction work as a principal contractor.

Subdivision 2 Relevant person's obligation for work method statements

191 Relevant person to prepare work method statement before starting high risk construction activity

- (1) A relevant person must prepare a work method statement for a high risk construction activity, complying with subsection (2), before starting construction work for the activity.

Maximum penalty—30 penalty units.

- (2) The statement must—
 - (a) take into account—
 - (i) the current construction safety plan; and
 - (ii) if the activity is demolition work—the requirements of AS 2601;⁹¹ and

91 AS 2601 (Demolition of structures)

- (iii) circumstances at the workplace that will, or are likely to, affect the way the activity is performed; and
- (b) be written in a way likely to be understood by the persons working, or about to work, at the workplace who are likely to be affected by the activity; and
- (c) be signed and dated by the relevant person; and
- (d) if the relevant person is not also the principal contractor for the construction work—be copied and the copy given to the principal contractor.

192 When relevant person not to allow another relevant person to start prescribed activity

- (1) This section applies if—
 - (a) a relevant person is the holder of a certificate under section 29B⁹² to perform a prescribed activity; and
 - (b) the activity is to be performed by another relevant person.
- (2) The relevant person must not allow the other relevant person to perform the prescribed activity unless the relevant person who is the holder of the certificate—
 - (a) has given a copy of the work method statement for the activity to the other relevant person; and
 - (b) has discussed with the other relevant person the aspects of the work method statement relevant to the activity; and
 - (c) has ensured that the other relevant person understands and is able to comply with those aspects of the statement.

Maximum penalty—30 penalty units.

92 Section 29B (Certificate to perform prescribed activity)

193 When relevant person who is employer not to allow worker to start high risk construction activity

A relevant person who is an employer must not allow a worker of the employer to perform a high risk construction activity unless—

- (a) the employer, or someone acting for the employer, has discussed with the worker the aspects of the current work method statement for the activity relevant to the worker's work; and
- (b) the worker has satisfied the employer, or a person acting for the employer, that the worker understands and is able to comply with those aspects of the statement.

Maximum penalty—30 penalty units.

194 High risk construction activity not to be performed unless in compliance with work method statement

- (1) A relevant person must not perform a high risk construction activity unless the activity is performed in a way complying with the current work method statement for the activity.

Maximum penalty—30 penalty units.

- (2) A relevant person who is an employer must not allow a worker of the employer to perform a high risk construction activity unless the activity is performed in a way complying with the current work method statement for the activity.

Maximum penalty—30 penalty units.

195 Amendment of work method statement

- (1) This section applies if there is a change in the way the high risk construction activity is to be performed.

Example of a change—

a change in a control measure included in the statement or the insertion of a new control measure

- (2) A relevant person must—
 - (a) ensure a work method statement for the activity is amended as soon as possible after the change; and

- (b) if the relevant person is not also the principal contractor for the construction work—give the principal contractor a copy of the amended statement; and
- (c) ensure each person affected by the amendment is advised of the details of the amendment.

Maximum penalty—30 penalty units.

196 Availability and review of work method statement

- (1) A relevant person must ensure the current work method statement for the high risk construction activity is readily available for inspection while the activity is being performed.

Maximum penalty—30 penalty units.

- (2) The relevant person must review, and if necessary amend, the statement within 1 year after it is prepared and afterwards at intervals of not more than 1 year while the statement is required.

Maximum penalty—30 penalty units.

Subdivision 3 Relevant person's obligation for general induction evidence

197 Definition for sdiv 3

In this subdivision—

construction work does not include work to repair a structure that is fixed plant, a ship or a submarine.

198 Relevant person to hold general induction evidence before starting construction work

A relevant person must not start construction work unless the person—

- (a) holds general induction evidence; and

- (b) has shown the principal contractor the general induction evidence.

Maximum penalty—30 penalty units.

199 Relevant person who is employer to ensure worker holds general induction evidence before worker starts construction work

A relevant person who is an employer must not allow a worker of the employer to start construction work unless the employer has sighted general induction evidence for the worker.

Maximum penalty—30 penalty units.

Subdivision 4 Relevant person's obligation for safe housekeeping practices

200 Safe housekeeping practices

- (1) A relevant person performing construction work must ensure that—
 - (a) safe housekeeping practices are used for the construction work; and
 - (b) the effectiveness of the practices is monitored and reviewed; and
 - (c) the practices are kept up-to-date; and
 - (d) each of the person's workers at the workplace where the construction is being performed is instructed to follow the practices.⁹³
- (2) For subsection (1), safe housekeeping practices include the following, except to the extent of the obligations of a principal contractor for the construction work—
 - (a) establishing and maintaining an orderly workplace environment;

93 For workers' obligations see the Act, section 36.

- (b) ensuring there is safe and clear entry to, and exit from, the workplace;
- (c) erecting general safety signs and keeping them in good condition;

Examples of general safety signs—

- ‘Hazardous substances in use’
- ‘Hearing protection required’
- ‘Scaffolding incomplete’

- (d) ensuring there is a safe system for collecting, storing and disposing of excess or waste materials at the workplace;
- (e) ensuring there are safe storage areas for materials and plant;
- (f) making safe protruding objects that are a hazard;

Examples of safe housekeeping practices for paragraph (f)—

- bending over or removing exposed nails
- placing a cap over vertical reinforcing steel

- (g) supplying and maintaining lighting that is adequate for the work being done.

- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Subdivision 5 Relevant person’s obligation for common plant

201 Common plant

- (1) A relevant person who is not also the principal contractor—
 - (a) must not use common plant other than in accordance with the provisions of this regulation about plant of the same type as the common plant as if the provisions applied to the common plant; or
 - (b) must not alter or otherwise interfere with common plant without the approval of the principal contractor who provided the plant.

- (2) Subsection (1) is a workplace health and safety obligation for the Act.

Subdivision 6 Relevant person's obligation for hazardous substances

202 Relevant person to give principal contractor details of hazardous substances to be used

A relevant person may use, and a relevant person who is an employer may allow the employer's worker to use, a hazardous substance during construction work only if the principal contractor for the construction work has been given—

- (a) notice that the relevant person proposes to use the hazardous substance at the workplace; and
- (b) a copy of the substance's current MSDS.

Maximum penalty—30 penalty units.

Subdivision 7 Relevant person's obligation for underground services

203 Risk from contact with underground services—construction work for which there is principal contractor

- (1) This section applies if—
- (a) a relevant person intends to perform construction work that includes excavation work; and
 - (b) there is a principal contractor for the construction work.
- (2) The relevant person must not start the excavation work unless the principal contractor—
- (a) has advised the relevant person to the effect that the principal contractor's inquiries have shown there are no underground services at or near the location where the work is to be done; or

- (b) has given prescribed information about the underground services at the workplace to the relevant person.
- (3) The relevant person must—
 - (a) ensure information obtained under subsection (2) is considered in doing the work; and
 - (b) ensure any reasonable restrictions contained in the information that are to be followed in doing the work are followed in doing the work; and
 - (c) decide on and use any control measures necessary to prevent a person's exposure to the risk of death, illness or injury from contact with, or damage to, the service the information is about.
- (4) Subsections (2) and (3) are workplace health and safety obligations for the Act.

204 Risk from contact with underground services—construction work for which there is no principal contractor

- (1) This section applies if—
 - (a) a relevant person intends to perform construction work that includes excavation work; and
 - (b) there is no principal contractor for the construction work.
- (2) The relevant person must, before the excavation work starts—
 - (a) find out from appropriate sources what underground services are at or near the location where the work is to be done that could create a risk if contacted or damaged; and
 - (b) obtain prescribed information about each underground service from an appropriate source; and
 - (c) ensure the information is considered in planning the work; and
 - (d) ensure the information is recorded in writing.
- (3) The relevant person must—

- (a) ensure information obtained under subsection (2) is considered in doing the work; and
 - (b) ensure any reasonable restrictions contained in the information that are to be followed in doing the work are followed in doing the work; and
 - (c) decide on and use any control measures necessary to prevent a person's exposure to the risk of death, illness or injury from contact with, or damage to, the service the information is about; and
 - (d) keep the information recorded until the construction work ends.
- (4) Subsections (2) and (3) are workplace health and safety obligations for the Act.

Subdivision 8 Relevant person's obligation for excavation work that could reduce the stability of a structure

205 Obligation before excavation work starts

- (1) This section applies if a relevant person intends to do excavation work that could reduce the stability of part or all of a structure.
- (2) The relevant person must, before the work starts, use the control measures necessary to prevent a person's exposure to the risk of death, illness or injury from the collapse of part or all of the structure.
- (3) Subsection (2) is a workplace health and safety obligation for the Act.

206 Obligation during excavation work

- (1) This section applies if a relevant person is doing excavation work that could reduce the stability of part or all of a structure.
- (2) The relevant person must ensure the work proceeds only if the relevant person has used the control measures necessary to

prevent a person's exposure to the risk of death, illness or injury from the collapse of part or all of the structure.

Example of circumstances requiring control measures—

A large rock is encountered while performing excavation work. As a result, the excavation has to be performed closer to a structure than originally planned.

- (3) Subsection (2) is a workplace health and safety obligation for the Act.

Subdivision 9 Relevant person's obligation for risk from excavations

207 Meaning of *competent person* for sdiv 9

- (1) A person is a ***competent person*** for section 210(5) for work in relation to a trench if the person—
- (a) has at least 3 years experience in stabilising excavations that are trenches; and
 - (b) either—
 - (i) is a geo-technical engineer; or
 - (ii) holds a qualification, or statement of attainment, from a registered training organisation covering the knowledge and skills mentioned in subsection (2).
- (2) The following are knowledge and skills for subsection (1)—
- (a) knowledge of relevant Australian Standards, relevant codes of practice and other relevant legislation;
 - (b) knowledge of, and competence in, the following—
 - (i) hazard identification and risk assessment for trench stability;
 - (ii) measures to control exposure to risks from trench collapse;
 - (iii) safe work practices and procedures for installing control measures;
 - (iv) how to plan and prepare for working in a trench;

- (v) how to identify the location of underground services;
- (vi) how to identify soil types and other factors that affect the stability of a trench.

208 Risk from all excavations

- (1) This section applies if a relevant person intends to do—
 - (a) excavation work; or
 - (b) work in an excavation.
- (2) The relevant person must, before the work starts—
 - (a) for each of the following possible events that are relevant to the work, identify each hazard associated with the event—
 - (i) a person being trapped by the collapse of the excavation;
 - (ii) a person being struck by an object falling into the excavation;
 - (iii) a person falling into the excavation;
 - (iv) a person inhaling, or otherwise being exposed to, carbon monoxide or another impurity of the air in the excavation; and

Examples of hazards for paragraph (a)—

- unstable rock or soil
 - underground water tables
 - a previous trench
 - machinery being moved near the excavation
 - vibration and fumes from vehicles or other plant in or near the excavation
 - structures near the excavation
 - piles of excavated material beside the excavation
- (b) assess the risk that may result because of the hazards; and
 - (c) decide on the appropriate control measures for the work.

- (3) The relevant person must use and maintain the control measures for the work, including the control measures required under subsection (4) or (5), necessary to prevent, or minimise the level of, exposure to the risk.

Examples of control measures—

- plant fitted with suitable overhead protection against the collapse of the excavation
 - benching, battering or shoring the sides of the excavation
 - a hoarding to prevent access by persons
 - a secure cover over the excavation
 - filling the excavation as soon as possible
 - ensuring there is adequate ventilation to prevent exposure to carbon monoxide
- (4) The control measures must include a barricade or hoarding at least 900mm high erected to restrict access by persons to the excavation, unless—
- (a) the erection of the barricade or hoarding is impracticable; or
 - (b) no person is likely to be in the vicinity of the excavation.
- (5) If the work will involve a person entering a trench more than 1.5m deep, the control measures specified in section 210 must be used to prevent risks to the person from the collapse of the trench.
- (6) Subsections (2) and (3) are workplace health and safety obligations for the Act.

209 Risk from working in trench at least 1m deep

- (1) This section applies if a relevant person—
- (a) is doing work that involves a trench at least 1m deep; and
 - (b) is not already required to erect a barricade under section 208(4).
- (2) The relevant person must erect a barricade at least 900mm high to restrict access by a person to the trench unless—
- (a) the erection of the barricade is impracticable; or

- (b) the only persons likely to be in the vicinity of the trench are persons involved with the trench.
- (3) However, the relevant person need not erect a barricade around a part of the trench if there already is a barrier beside the part of the trench that restricts access to the trench.

Examples of a barrier—

a permanent fence, wall or pile of excavated material

- (4) Subsection (2) is a workplace health and safety obligation for the Act.

210 Risk from working in trench more than 1.5m deep

- (1) This section applies if a relevant person intends to do work that will involve a person entering a trench more than 1.5m deep.
- (2) The relevant person must use at least 1 of the following control measures, complying with this section, as a control measure under section 208(3) to prevent risk to the person from the collapse of the trench—
 - (a) shoring all sides of the trench by shielding or in another way;
 - (b) benching all sides of the trench;
 - (c) battering all sides of the trench;
 - (d) having a geo-technical engineer—
 - (i) approve in writing all sides of the trench as safe from collapse; and
 - (ii) state in writing how long the approval lasts if there is no stated natural occurrence that could affect adversely the stability of the trench; and
 - (iii) state in writing the natural occurrences that could affect adversely the stability of the trench.
- (3) However, the relevant person may use a combination of the control measures mentioned in subsection (2) if all sides of the trench are dealt with.
- (4) If shoring is used and it is commercially manufactured shielding, it must be—

- (a) designed by an engineer for the purpose for which it is intended to be used; and
 - (b) erected in accordance with the instructions, if any, of its manufacturer or supplier.
- (5) Sheeting or timber may only be used to shore the trench if a competent person has inspected the trench, assessed the shoring and approved the use of the shoring.
- (6) Each bench cut into the side of the trench must be no higher than it is wide, unless a geo-technical engineer has approved a greater height in writing.
- (7) The angle of each batter in the trench must not be more than 45° from the horizontal, unless a geo-technical engineer has approved a greater angle in writing.
- (8) The relevant person must ensure no vertical face of the side of a benched or battered trench is higher than 1.5m, unless a geo-technical engineer has approved a greater height in writing.
- (9) Subsection (2) is a workplace health and safety obligation for the Act.

211 Access by ladders to trench more than 1.5m deep

- (1) This section applies if access to and from a trench more than 1.5m deep is by ladders.
- (2) A relevant person must ensure that at least 1 ladder giving access to and from the trench is installed in every 9m of the length of the trench in the part of the trench where a person will be.
- (3) Subsection (2) is a workplace health and safety obligation for the Act.

212 Events in trench more than 1.5m deep that is not shored, benched or battered

- (1) This section applies if—
 - (a) a trench more than 1.5m deep is not shored, benched or battered; and

- (b) something happens that could affect the stability of the trench or place the safety of a person at risk because of the trench.

Examples of things that may happen that could affect the stability of the trench—

- water seeping from a side, or the base, of the trench
 - subsidence happening beside the trench
 - cracks appearing near, and parallel to, the edge of the trench
 - excavated or other material being piled beside the trench
- (2) A relevant person must ensure that work in the trench stops immediately and does not restart, other than work to shore, bench or batter the trench, until—
- (a) a geo-technical engineer has inspected the trench and approved, in writing, the trench as safe to enter; or
- (b) all sides of the trench have been—
- (i) shored by shielding or another way; or
 - (ii) benched; or
 - (iii) battered.
- (3) However, the relevant person may use a combination of the methods mentioned in subsection (2)(b) if all sides of the trench are dealt with.
- (4) Subsection (2) is a workplace health and safety obligation for the Act.

Subdivision 10 Relevant person's obligation for risk of a person falling

213 Definition for sdiv 10

In this subdivision—

ladder does not include a fixed ladder.

214 Risk of fall of less than 3m in housing construction work or less than 2m in other construction work or construction work on roof with slope not over 26°

- (1) This section applies to—
 - (a) construction work that is housing construction work during which a person could fall less than 3m; or
 - (b) construction work that is not housing construction work during which a person could fall less than 2m; or
 - (c) construction work on a roof, or partly completed roof, surface with a slope not over 26°.
- (2) However, this section does not apply to construction work where a person could fall from—
 - (a) a ladder or fixed ladder; or
 - (b) a platform supported by trestle ladders; or
 - (c) scaffolding that the person is erecting or dismantling; or
 - (d) an area near a ladder that the person needs to use to get on or off the ladder.
- (3) A relevant person who intends to do the construction work must, before the work starts—
 - (a) ensure each hazard that may result in a fall or cause death or injury if the person were to fall is identified; and

Examples of hazards—

- vertical reinforcing steel, or the edge of a rubbish skip, 1m below a surface from which the work is to be done
 - unsheathed floor bearers and joists 2m below a surface from which the work is to be done
 - an object, for example a picket fence or stack of bricks, that could cause injury if the person fell on it 2m below, or nearly below, a surface from which the work is to be done
 - a brittle roof on which the work is to be done 2m above a floor
- (b) ensure the risk of death or injury that may result because of the hazard is assessed; and
 - (c) ensure any control measures necessary to prevent, or minimise the level of, exposure to the risk are used.

- (4) If a control measure mentioned in this subdivision is used, the control measure and the use of the control measure must comply with this subdivision.
- (5) However, a fall arresting platform used under subsection (3)(c) need not comply with section 217B if the fall would be internal within formwork the person is erecting or dismantling.
- (6) Subsections (3) and (4) are workplace health and safety obligations for the Act.

215 Risk of fall of at least 3m in housing construction work or at least 2m in other construction work or construction work on roof with a slope over 26°

- (1) This section applies to—
 - (a) construction work that is housing construction work during which a person could fall at least 3m; or
 - (b) construction work that is not housing construction work during which a person could fall at least 2m; or
 - (c) construction work on a roof, or partly completed roof, surface with a slope over 26°.
- (2) However, this section does not apply to work where a person could fall from—
 - (a) a ladder or fixed ladder; or
 - (b) a platform supported by trestle ladders; or
 - (c) scaffolding which the person is erecting or dismantling; or
 - (d) an area near a ladder that the person needs to use to get on or off the ladder.
- (3) A relevant person who intends to do the construction work must, before the work starts, use control measures—
 - (a) to prevent the person falling any distance; or

Examples of control measures to prevent the person falling—

- edge protection

- a fall protection cover placed over an opening
 - a travel restraint system
- (b) if prevention is not practicable—
- (i) to arrest the person's fall; and
 - (ii) to prevent or minimise the risk of death or injury to the person when the fall is arrested.

Examples of control measures to arrest a person's fall—

- a fall arresting platform
 - a fall-arrest harness system
 - an industrial safety net
- (4) If a control measure mentioned in this subdivision is used, the control measure, and the use of the control measure, must comply with this subdivision.
- (5) However, a fall arresting platform used under subsection (3)(b) need not comply with section 217B if the fall would be internal within formwork the person is erecting or dismantling.
- (6) Subsections (3) and (4) are workplace health and safety obligations for the Act.

216 Edge protection as control measure

- (1) Edge protection used as a control measure must be erected in accordance with the instructions of—
- (a) if the edge protection's manufacturer or supplier has given instructions about its installation—the manufacturer or supplier; or
 - (b) otherwise—an engineer or competent person.
- (2) The edge protection must be designed to withstand the downwards or outwards force of the impact of a fall against it of any person who may reasonably be expected to fall against it to ensure that the person does not fall from the surface from which work is to be done.
- (3) The edge protection must—

- (a) have a rail, or another component that prevents the person from falling, fitted so that the top of the rail or component is at least—
 - (i) if the surface that is at the base of the edge protection is at least 1200mm wide—900mm higher than that surface; or
 - (ii) otherwise—
 - (A) if the surface from which work is to be done is sloped—900mm higher than where that surface, if extended downwards at that slope, would intersect with the edge protection; or
 - (B) if the surface from which work is to be done is not sloped—900mm higher than that surface; and
 - (b) have another rail or rails or sturdy mesh, sheeting or other material below the rail or component.
- (4) However, if the edge protection has rails, the edge protection must have—
- (a) either—
 - (i) a bottom rail fitted at least 150mm but not over 250mm higher than the surface that is at the base of the edge protection; or
 - (ii) a toe board, for the surface that is at the base of the edge protection, at least 150mm high and fitted below all rails of the edge protection; and
 - (b) another rail or rails fitted so that there is not over 450mm between any rail and its nearest rail or between the lowest rail and any toe board for the surface that is at the base of the edge protection; and
 - (c) if the slope of the surface from which work is to be done is over 26°—sturdy mesh, sheeting or other material that extends upwards at least 900mm from—
 - (i) the surface that is the at the base of the edge protection; or
 - (ii) the toe board.

- (5) A relevant person must not use, or allow another person to use, the edge protection unless it is used in accordance with the instructions of—
 - (a) if the edge protection's manufacturer or supplier has given instructions about its use—the manufacturer or supplier; or
 - (b) otherwise—an engineer or competent person.
- (6) In this section—

toe board for a surface means an upright timber or metal board securely fixed in place at an edge of the surface.

217 Fall protection cover as control measure

A fall protection cover used as a control measure must—

- (a) be able to withstand the impact of a fall onto it of any person who may reasonably be expected to fall onto it to ensure that the person does not fall; and
- (b) be securely fixed in place to prevent it being moved or removed accidentally.

217A Travel restraint system as control measure

- (1) A travel restraint system used as a control measure must—
 - (a) be installed by a competent person; and
 - (b) have an anchorage point with a capacity to withstand any load that could be exerted on it in the normal operation of the system to restrain any person who may reasonably be expected to use the system.
- (2) A relevant person must not use, or allow another person to use, the system unless the person who is to use the system has been trained in the safe and correct use of the system.
- (3) A relevant person must not use, or allow another person to use, a component of the system that shows evidence of wear or weakness to an extent that may affect the system's safety.
- (4) A relevant person must ensure that, at least once every 6 months, a competent person—

- (a) inspects the system; and
 - (b) gives the relevant person a written record of the inspection.
- (5) A relevant person must keep the record for the lesser of the following—
 - (a) 4 years;
 - (b) the life of the system.

217B Fall arresting platform as control measure

- (1) A fall arresting platform used as a control measure must be able to withstand the impact of a fall onto it of any person who may reasonably be expected to fall onto it.
- (2) The platform of the fall arresting platform must provide an unobstructed landing area, for a falling person, at least 675mm wide for the length of the platform.
- (3) If the slope of the surface from which construction work is to be performed is not over 26°, the fall arresting platform must be not over 1m lower than the surface.
- (4) If the slope of the surface from which construction work is to be performed is over 26°, the fall arresting platform must be not over 300mm lower than the surface.
- (5) The fall arresting platform must have edge protection complying with section 216⁹⁴ erected—
 - (a) along the outer edge of the length of the fall arresting platform; and
 - (b) along the edge of each end of the fall arresting platform.
- (6) Subsection (7) applies if the gap between the following is over 225mm—
 - (a) the inner edge of the length of the platform;
 - (b) the face of a structure that is immediately beside the fall arresting platform.

94 Section 216 (Edge protection as control measure)

- (7) A relevant person must, in complying with section 214 or 215, ensure that any control measures required to prevent or minimise the risk of a person falling off the inner edge are used.

217C Fall-arrest harness system as control measure

- (1) Each anchorage point of a fall-arrest harness system used as a control measure must be—
- (a) designed by an engineer for the purpose for which it is intended to be used; or
 - (b) inspected and approved by a competent person before the anchorage point is first used by any person.
- (2) Each anchorage point of the system, other than an anchorage point supporting a static line, must have a capacity of at least—
- (a) if only 1 person is using the anchorage point and the person could have a limited free fall—12kN; or
 - (b) if only 1 person is using the anchorage point and the person could have a free fall—15kN; or
 - (c) if 2 persons are using the anchorage point—21kN.
- (3) Each anchorage point of the system must be located so that a lanyard of the system can be attached to it before the person using the system moves into a position where the person could fall.
- (4) The system's device to absorb the energy of a falling person must limit the force applied to the person by a fall to not more than 6kN.
- (5) The system must be installed in accordance with the instructions of—
- (a) if the system's manufacturer or supplier has given instructions about its installation—the manufacturer or supplier; and
 - (b) to the extent the system's manufacturer or supplier has not given instructions—an engineer or competent person.

- (6) The system must be maintained in accordance with the instructions of—
- (a) if the system's manufacturer or supplier has given instructions about its maintenance—the manufacturer or supplier; and
 - (b) to the extent the system's manufacturer or supplier has not given instructions—an engineer or competent person.
- (7) A relevant person must ensure there is enough distance available for a person using the system to fall to prevent the person hitting an object, the ground or another surface, other than a vertical surface.
- (8) For subsection (7), whether there is enough distance available must be worked out by taking the following into account—
- (a) the person's height;
 - (b) the height and position of the anchorage point;
 - (c) the length of the lanyard;
 - (d) any slack in the static line;
 - (e) any stretching of the lanyard or static line when extended by a fall;
 - (f) the length of the energy absorber when extended by a fall;
 - (g) any other relevant factor.
- (9) A relevant person must ensure that—
- (a) no part of the system can come into contact with anything that could affect the safe use of the system; and
Examples of a thing that could affect the safe use of a system—
 - an edge of a platform or beam over which a lanyard would tighten if a fall were to happen
 - part of an anchorage point that is not adequately padded
 - (b) a person using the system is trained in the safe and correct use of the system; and
 - (c) there are written procedures about—

Workplace Health and Safety Regulation 1997

- (i) safely retrieving a person who has fallen, as soon as possible after the person has fallen; and
 - (ii) ensuring the safety of persons involved in the retrieval; and
 - (d) the persons to be involved in carrying out the procedures are familiar with the procedures.
- (10) A relevant person must ensure that—
- (a) a component of the system is not used if it shows evidence of wear or weakness to an extent that may affect the system's safety; and
 - (b) if a competent person considers that an anchorage point of the system is worn or that its load bearing capacity may be impaired—
 - (i) the anchorage point is not used; and
 - (ii) appropriate measures are taken to prevent its use while it is worn or its load bearing capacity may be impaired; and
 - (c) at least once every 6 months, a competent person inspects the components of the system, other than each anchorage point, and gives the relevant person a written record of the inspection; and
 - (d) the record is kept for the lesser of the following—
 - (i) 4 years;
 - (ii) the life of the system.
- (11) If the system has been used to arrest a fall, the system must not be used again unless its manufacturer or a competent person has inspected it and decided that it is fit for safe use.
- (12) A relevant person must not use, or allow another person to use, the system unless it is used in accordance with the instructions of—
- (a) if the system's manufacturer or supplier has given instructions about its use—the manufacturer or supplier; or
 - (b) otherwise—an engineer or competent person.

- (13) A relevant person must not use, or allow another person to use, the system while the person using the system is alone.
- (14) Subsection (7) is a workplace health and safety obligation for the Act.
- (15) In this section—

free fall means a fall in which the distance a person using a fall-arrest harness system falls vertically before the system starts to take loading is more than 600mm but not more than 2m.

limited free fall means a fall in which the distance a person using a fall-arrest harness system falls vertically before the system starts to take loading is not more than 600mm.

217D Industrial safety net as control measure

- (1) An industrial safety net used as a control measure must—
 - (a) be designed by an engineer or competent person for the purpose for which it is intended to be used; and
 - (b) be made of material designed to minimise injury to a person falling into the net; and
 - (c) have energy absorbing characteristics to reduce the shock or injury to a person falling into the net.
- (2) The net must be installed—
 - (a) so that a person falling into the net will not hit anything below the net; and
 - (b) as close as possible below the surface from which the person who is to be protected by the net is to work, but not more than the distance below the surface specified by—
 - (i) if the net's manufacturer or supplier has specified the distance—the manufacturer or supplier; or
 - (ii) otherwise—an engineer or competent person.
- (3) The net must, subject to anything specified under subsection (2), be installed in accordance with the instructions of—

- (a) if the net's manufacturer or supplier has given instructions about its installation—the manufacturer or supplier; or
 - (b) otherwise—an engineer or competent person.
- (4) A relevant person must not use, or allow another person to use, the net unless it is used in accordance with the instructions, if any, of the net's manufacturer or supplier, an engineer or a competent person.
- (5) A relevant person must ensure the net is inspected and maintained in accordance with the instructions, if any, of an engineer or competent person or the net's manufacturer or supplier.

Subdivision 11 Relevant person's obligation for ladders

217E What work may be done from single or extension ladder

- (1) This section applies if a relevant person intends to perform construction work that involves a single or extension ladder.
- (2) The relevant person must not use, or allow another person to use, the ladder—
 - (a) to gain access to a place, unless the person using the ladder has at least 2 hands and 1 foot, or 2 feet and 1 hand, on the ladder from when the person is fully on the ladder to when the person is leaving the ladder; or
 - (b) to do construction work, other than to gain access to a place under paragraph (a), unless the work is permitted work.
- (3) Subsection (2) is a workplace health and safety obligation for the Act.

217F Work on a ladder

- (1) This section applies if a relevant person intends to perform construction work that involves a ladder.
- (2) The relevant person must, before the work starts—

- (a) ensure that each hazard that may result in a fall by the person who is to use the ladder or cause death or injury if the person were to fall from the ladder is identified; and
 - (b) ensure that the risk of death or injury that may result because of the hazard is assessed; and
 - (c) ensure that any control measures required to prevent, or minimise the level of, exposure to the risk are used.
- (3) Subsection (4) applies if the construction work is permitted work, and, in doing the work, a person could fall—
- (a) for housing construction work—at least 3m; or
 - (b) otherwise—at least 2m.
- (4) The relevant person must not use, or allow another person to use, the ladder, if it is a single or extension ladder, unless—
- (a) the person using the ladder—

- (i) has at least 3 limbs holding, wrapped around or standing on the ladder in any combination; or

Example—

holding the ladder with 1 hand while standing on it with 2 feet

- (ii) is prevented from falling by a control measure, for example, a strap commonly known as a pole strap; or
 - (iii) is using a fall-arrest harness system that is not attached to the ladder; and
- (b) the ladder is secured—
 - (i) at or near the top to prevent it moving; or

Examples—

- tying the top of the ladder to a plate fixed to the top of a wall frame
 - clamping the top of the ladder to structural steel

- (ii) at or near the bottom to prevent it moving.

Examples—

- tying the bottom of the ladder to pegs in the ground

- a person, other than the person using the ladder, holding the ladder in position near the bottom of the ladder

- (5) Despite subsection (4)(a)(i), the person using the ladder may hold a stable object with 1 or both hands instead of holding the ladder with 1 or both hands.

Examples of stable objects—

- guttering
- a fascia board or timber stud
- a plate fixed to the top of a wall frame

- (6) The relevant person must ensure that the ladder, if it is a single or extension ladder, and is used against a pole to do construction work, has a device that—

- (a) is fitted at or near the top of the ladder between its sides; and
- (b) helps to ensure the ladder's stability by partly accepting the shape of the pole.

Example—

a steel rope or steel hoop

- (7) Subsections (2), (4) and (6) are workplace health and safety obligations for the Act.

217G Ladders generally

- (1) A relevant person performing construction work must ensure that a ladder, other than a trestle ladder, used for the work—
- (a) has a load rating of at least 120kg; and
 - (b) is manufactured for industrial use; and
 - (c) is used only for the purpose for which it is designed; and
 - (d) is not used to support a weight greater than that for which it is designed; and
 - (e) is no longer than—
 - (i) for a single ladder—6.1m; or
 - (ii) for an extension ladder used to do electrical work—9.2m; or

(iii) for another extension ladder—7.5m.

- (2) However, subsection (1)(e) does not apply if the ladder is used for work in a confined space.

Example of a confined space—

a well

- (3) A ladder may be taken to have a load rating of at least 120kg if it appears to be marked by its manufacturer to show it has a load rating of at least 120kg.
- (4) A ladder may be taken to be manufactured for industrial use if it appears to be marked by its manufacturer to show it is for industrial use.
- (5) However, subsection (3) or (4) does not apply if the relevant person knows or suspects that the marking is—
- (a) false; or
 - (b) not the manufacturer's marking.
- (6) The relevant person must ensure that—
- (a) the bottom of the ladder is on a stable surface; and
 - (b) the rungs of the ladder are approximately level.
- (7) The relevant person must not use, or allow another person to use, the ladder to support a platform.
- (8) The relevant person must not use, or allow another person to use, the ladder, if it is a single or extension ladder, unless—
- (a) it is placed so that the angle between the ladder and the horizontal is at least 70° but not more than 80° when in use; and
 - (b) if it is being used as a temporary means of access to or from a surface—the ladder extends at least 1m above the surface.
- (9) However, the ladder may be placed so that the angle between the ladder and the horizontal is more than 80° if—
- (a) a lesser angle is impractical because the ladder is being used in a confined space; and
 - (b) control measures are used to prevent the ladder moving when in use.

Example of a control measure—

securing the top and bottom of the ladder to prevent it moving

- (10) Subsection (8)(b) does not apply if—
- (a) it is impractical to comply with it, for example, because the work is being done from a surface attached to a pole; and
 - (b) the person using the ladder is attached to a fall-arrest harness system before the person moves from the ladder to the surface.
- (11) Subsections (1), (6), (7) and (8) are workplace health and safety obligations for the Act.

Subdivision 12 Relevant person's obligation for platforms supported by trestle ladders

217H Work on platform supported by trestle ladders

- (1) This section applies if a relevant person intends to perform construction work that involves a platform supported by trestle ladders.
- (2) The relevant person must, before the work starts—
 - (a) ensure that each hazard that may result in a fall by the person who is to use the platform, or cause death or injury if the person who is to use the platform were to fall from the platform, is identified; and
 - (b) ensure that the risk of death or injury that may result because of the hazard is assessed; and
 - (c) ensure that any control measures required to prevent, or minimise the level of, exposure to the risk are used.
- (3) Also, the relevant person must ensure subsections (4) to (6) are complied with before the work starts if the work is—
 - (a) housing construction work and the person could fall at least 3m from the platform; or

- (b) not housing construction work and the person could fall at least 2m from the platform.
- (4) Each trestle ladder must be secured to prevent it moving.
Examples of how a trestle ladder must be secured—
 - tying the ladder to a sturdy wall
 - bracing the ladder to the ground
 - applying weights to the bottom of the ladder
- (5) Edge protection complying with section 216⁹⁵ must be erected along the outer edge of the length of the platform.
- (6) Any control measures required to prevent, or minimise the level of, exposure to the following risks must be used—
 - (a) the risk of the person falling off the inner edge of the length of the platform, if the gap between that inner edge and the face of a building, or other structure, that is immediately beside the platform is over 225mm;
 - (b) the risk of the person falling off the edge of each end of the platform.
- (7) Subsections (2) and (3) are workplace health and safety obligations for the Act.

217I Platform supported by trestle ladders

- (1) This section applies if a relevant person is performing construction work on a platform supported by trestle ladders.
- (2) Subsection (3) applies if the construction work—
 - (a) is housing construction work and a person doing the work could fall less than 3m from the platform; or
 - (b) is not housing construction work and a person doing the work could fall less than 2m from the platform.
- (3) The relevant person must ensure the platform has an unobstructed surface that is—
 - (a) if the work is light work—at least 225mm wide along the length of the platform; or

95 Section 216 (Edge protection as control measure)

- (b) if the work is not light work—at least 450mm wide along the length of the platform.
- (4) Subsection (5) applies if the construction work—
 - (a) is housing construction work and a person doing the work could fall at least 3m from the platform; or
 - (b) is not housing construction work and a person doing the work could fall at least 2m from the platform.
- (5) The relevant person must ensure—
 - (a) the platform has an unobstructed surface at least 450mm wide along the length of the platform; and
 - (b) the platform is not higher than 5m.
- (6) Subsections (3) and (5) are workplace health and safety obligations for the Act.

Subdivision 13 Relevant person's obligation for scaffolding

217J Obligations before starting to erect or dismantle

- (1) A relevant person must, before construction work that is the erecting or dismantling of scaffolding starts—
 - (a) ensure each hazard that may result in a fall by the person who is to use the scaffolding, or cause death or injury if the person who is to use the scaffolding were to fall from the scaffolding, is identified; and
 - (b) ensure the risk of death or injury that may result because of the hazard is assessed; and
 - (c) ensure any control measures required to prevent, or minimise the level of, exposure to the risk are used.
- (2) Subsection (1) is a workplace health and safety obligation for the Act.

217K Erecting scaffolding

- (1) This section applies if a relevant person intends to perform construction work that is the erecting of scaffolding.
- (2) The relevant person must not erect, or allow another person to erect, the scaffolding if—
 - (a) the erection of the scaffolding is housing construction work and a person could fall at least 3m in erecting the scaffolding; or
 - (b) the erection of the scaffolding is not housing construction work and a person could fall at least 2m in erecting the scaffolding.
- (3) However, subsection (2) does not apply if—
 - (a) the person erecting the scaffolding—
 - (i) is prevented from falling from the scaffolding by a control measure; or
 - (ii) is using a fall-arrest harness system; or
 - (b) subsection (4) is complied with.
- (4) This subsection is complied with if—
 - (a) each of the following things is installed immediately after enough components of the scaffolding have been erected to support the thing—
 - (i) a platform at least 450mm wide along the full length of the section of scaffolding, designed to support the platform, at the level the scaffolding has reached;
 - (ii) edge protection across the space between the uprights forming the outer frame of the scaffolding at the level the scaffolding has reached;
 - (iii) a means of access to the level the scaffolding has reached; and

Example of a means of access—
temporary stairs or a ladder
 - (b) before the next level of the scaffolding is erected, a platform is installed below the level at a distance of not more than—

- (i) if the erection of the scaffolding is housing construction work—3m; or
 - (ii) otherwise—2m.
- (5) A platform under subsection (4)(b) must cover the full length and width of the section of scaffolding designed to support the platform at the level at which it is installed, other than a part of the section required to raise planks or other components of the scaffolding between levels.
- (6) Subsection (4)—
 - (a) does not require a platform to be installed on the bottom level of the scaffolding; and
 - (b) does not stop the relevant person removing a platform after the relevant person has started work 2 levels above the level from which the platform is to be removed.
- (7) Subsection (2) is a workplace health and safety obligation for the Act.

217L Dismantling scaffolding

- (1) This section applies if a relevant person intends to perform construction work that is the dismantling of scaffolding.
- (2) The relevant person must not dismantle, or allow another person to dismantle, the scaffolding if—
 - (a) the dismantling of the scaffolding is housing construction work and a person could fall at least 3m in dismantling the scaffolding; or
 - (b) the dismantling of the scaffolding is not housing construction work and a person could fall at least 2m in dismantling the scaffolding.
- (3) However, subsection (2) does not apply if—
 - (a) the person dismantling the scaffolding is—
 - (i) prevented from falling from the scaffolding by a control measure; or
 - (ii) using a fall-arrest harness system; or
 - (b) each of the following is complied with—

- (i) any edge protection for the scaffolding and any means of access to the level that the dismantling has reached are kept in place while it is practicable to do so;
 - (ii) there is in place while it is practicable a platform at least 450mm wide at the level the dismantling has reached;
 - (iii) there is in place a platform at a level (the ***lower level***) below the level the dismantling has reached at a distance of not more than—
 - (A) if the dismantling of the scaffolding is housing construction work—3m; or
 - (B) otherwise—2m.
- (4) The platform required under subsection (3)(b)(iii) must cover the full length and width of the section of scaffolding designed to support the platform at the lower level, other than a part of the section required to lower planks or other components of the scaffolding between levels.
- (5) Subsection (2) is a workplace health and safety obligation for the Act.

Subdivision 14 Relevant person's obligation for falling objects

217M Application of sdiv 14

This subdivision applies to construction work if—

- (a) an object could fall on or otherwise hit persons during the work; and
- (b) there is no principal contractor for the work.

217N Relevant person's obligation if no principal contractor

- (1) The relevant person has the obligations contained in division 2, subdivision 11 for the construction work if the relevant person is doing the work.

- (2) In applying the subdivision to the relevant person, a reference to a principal contractor in the subdivision is taken to be a reference to a relevant person.
- (3) Subsection (1) is a workplace health and safety obligation for the Act.

Subdivision 15 Relevant person's obligation for first aid

217O First aid

- (1) A relevant person performing construction work must ensure that first aid equipment is reasonably accessible to the person and, if the relevant person is an employer, to the person's workers.

Maximum penalty—20 penalty units.

- (2) The first aid equipment must be appropriate and adequate for the construction work and the relevant person or the person's workers.
- (3) The relevant person must ensure that all first aid equipment made available by the person is maintained in a hygienic, safe and serviceable condition.

Maximum penalty for subsection (3)—20 penalty units.

Division 4 Workers

217P Application of div 4

This division applies only to a worker performing construction work.

217Q Worker to hold general induction evidence before starting construction work

- (1) A worker must not start construction work unless the worker—
 - (a) holds general induction evidence; and

- (b) has shown the employer of the worker the general induction evidence.

Maximum penalty—30 penalty units.

- (2) In this section—

construction work does not include work to repair a structure that is fixed plant, a ship or a submarine.

Division 5 General provisions about control measures and plant for pt 17

217R Control measure to be in place and monitored and reviewed

- (1) This section applies if—
 - (a) a provision (the ***original provision***) of this part requires a principal contractor or relevant person to use a control measure for a risk before particular work starts; and
 - (b) a control measure (the ***original control measure***) is used in accordance with the original provision.
- (2) The principal contractor or relevant person must ensure that, while the risk exists, an effective control measure for the risk is used.
- (3) If the original control measure was chosen from a number of control measures that were available under this regulation to be used for the risk (the ***available control measures***), a control measure used for the risk is an effective control measure for the risk only if it was chosen from the available control measures.
- (4) If the original control measure is the only control measure that was available under this regulation to be used for the risk, only the original control measure is an effective control measure for the risk.
- (5) The principal contractor or relevant person must monitor and review the effectiveness of a control measure in place for the risk unless the control measure is an effective control measure because of subsection (3) or (4).

- (6) Subsections (2) and (5) are workplace health and safety obligations for the Act.
- (7) In this section—
effective control measure, for a risk, means a control measure that is effective to prevent, or minimise the level of, exposure to the risk.

217S Plant not to be used as control measure unless it has been maintained

- (1) A principal contractor for construction work must not use, or allow a person to use, plant provided by the principal contractor as a control measure under this part unless the plant has been maintained.
- (2) A relevant person must not use, or allow another person to use, plant provided by the relevant person as a control measure under this part unless the plant has been maintained.
- (3) Subsections (1) and (2) do not affect the requirement about the maintenance of an industrial safety net under section 217D(5).⁹⁶
- (4) Subsections (1) and (2) are workplace health and safety obligations for the Act.

217T Plant erected or installed after construction work starts

- (1) This section applies if—
 - (a) a provision of this part requires a principal contractor or relevant person to use control measures before particular construction work starts; and
 - (b) a provision of this part imposes a requirement in relation to an item of plant if it is used as a control measure; and

Example of a provision—

a provision about the design, specifications, inspection, maintenance or use of the plant

⁹⁶ Section 217D (Industrial safety net as control measure)

- (c) the principal contractor or relevant person erects or installs plant of the same type at a later time.
- (2) The principal contractor or relevant person must comply with the provision as if the plant were to be erected or installed before the construction work started.
- (3) Subsection (2) is a workplace health and safety obligation for the Act.

217U Written evidence about plant from engineer or competent person may be relied on

- (1) This section applies if a provision of this part imposes a requirement on a principal contractor or relevant person in relation to an item of plant.
- (2) If compliance with the requirement requires an engineer or competent person to have performed a task in relation to the plant, the principal contractor or relevant person may comply with the requirement by obtaining a document in original or copy form purporting to be by an engineer or competent person for the task evidencing the task has been performed by the engineer or competent person.
- (3) If the requirement is about the ability of the plant or a component of the plant to withstand a particular force or impact or bear a particular load, the principal contractor or relevant person may comply with the requirement by obtaining a document in original or copy form purporting to be by an engineer evidencing the plant or component can withstand the force or impact or bear the load.
- (4) Subsections (2) and (3) do not permit reliance on a document the principal contractor or relevant person knows or suspects to be false, or misleading, in a material particular.

Division 6**Chief executive may ask for information from Queensland Building Services Authority****217V Definitions for div 6**

In this division—

building contractor has the meaning given by the *Queensland Building Services Authority Act 1991*, schedule 2.

relevant information means the following information about residential construction work—

- (a) the name of the owner of the land on which the residential construction work is being carried out;
- (b) the address of the land;
- (c) the name of any building contractor or other person who will be carrying out the residential construction work.

residential construction work means—

- (a) residential construction work under the *Queensland Building Services Authority Act 1991* for which an insurance premium has been paid under section 68⁹⁷ of that Act; or
- (b) building work under the *Queensland Building Services Authority Act 1991* being carried out at a workplace under an owner-builder permit under that Act.

217W Chief executive may ask general manager of Queensland Building Services Authority for relevant information

- (1) For ensuring the workplace health and safety of persons who may be affected by residential construction work, the chief executive may ask the general manager of the Queensland Building Services Authority for relevant information.

⁹⁷ *Queensland Building Services Authority Act 1991*, section 68 (Payment of insurance premium for residential construction work)

- (2) If the chief executive asks the general manager for information under subsection (1), the general manager must comply with the request.
- (3) The general manager does not commit an offence merely by failing to comply with subsection (2).

Part 21 Amenities—work that is not construction work

218 Amenities for rural industry work

Section 220 and schedule 8B⁹⁸ state particular duties of an employer about amenities for work in a rural industry.⁹⁹

219 Amenities for work that is not construction work or rural industry work

Section 220 and schedule 8C¹⁰⁰ state particular duties of an employer about amenities for the employer's workers performing work that is not construction work or work in a rural industry.

220 Maintenance of amenities

- (1) An employer who makes an amenity available under schedule 8B or 8C must ensure that the amenity is maintained under subsection (2).

Maximum penalty—20 penalty units.

- (2) An amenity must be maintained in a hygienic, safe and serviceable condition, including by ensuring that there is a system for—

98 Schedule 8B (Employers—particular amenities for rural industry work)

99 *Rural industry* is defined in schedule 9 (Dictionary).

100 Schedule 8C (Employers—particular amenities for work that is not construction work or rural industry work)

- (a) inspecting and cleaning the amenity; and
- (b) if the amenity has facilities to dispose of sanitary items for females—the adequate and hygienic disposal of the sanitary items.

Part 21A Employers—requirements for building provided for worker to occupy when performing work that is not construction work or rural industry work

221 Ventilation, lighting, floor area and air space for building

- (1) Schedule 8D¹⁰¹ states particular duties of an employer—
 - (a) whose worker is at a workplace and performing work that is not construction work or work in a rural industry; and
 - (b) who provides a building¹⁰² at the workplace for the worker to occupy when performing work that is not construction work or work in a rural industry.
- (2) The duties are about ventilation, lighting, floor area and air space for the building.

101 Schedule 8D (Employers—requirements for building provided for worker to occupy when performing work that is not construction work or rural industry work)

102 *Building* is defined in schedule 9 (Dictionary).

Part 21B Employers—atmospheric contaminants

222 Level of atmospheric contaminants

- (1) This section applies to an atmospheric contaminant, other than a hazardous substance as defined in section 100,¹⁰³ for which the national exposure standard states an exposure level.
- (2) An employer must ensure that the level of the atmospheric contaminant generated from a process carried out in the conduct of the employer's business or undertaking is not more than the exposure standard stated for the atmospheric contaminant in the national exposure standard.

Maximum penalty—20 penalty units.

Part 21C First aid

223 Employers—work other than construction work

- (1A) This section does not apply to construction work.
 - (1) An employer must ensure that first aid equipment is reasonably accessible to each of the employer's workers.

Maximum penalty—20 penalty units.
 - (2) The first aid equipment must be appropriate and adequate for the worker and the worker's work.
 - (3) An employer must ensure that first aid equipment is reasonably accessible to the employer.

Maximum penalty—20 penalty units.
 - (4) The first aid equipment must be appropriate and adequate for the employer and the employer's work.

103 Section 100 (Meaning of *hazardous substance* for division)

- (5) An employer must ensure that the following first aid equipment is maintained in a hygienic, safe and serviceable condition—
- (a) all first aid equipment made available by the employer to a worker of the employer;
 - (b) all first aid equipment made available by the employer for his or her own use.

Maximum penalty for subsection (5)—20 penalty units.

224 Employers—workers performing rural industry work

The employer of a worker performing work in a rural industry must ensure that, if practicable, a person with first aid training is available to treat an injury suffered by the worker in performing the work.

Maximum penalty—20 penalty units.

Part 21D Workplace health and safety contributions

226 Purpose of pt 21D

The purpose of this part is to provide for the payment of workplace health and safety contributions by non-scheme employers for part 14, division 1B¹⁰⁴ of the Act.

227 Amount of workplace health and safety contribution

- (1) For section 182F(2)(a)¹⁰⁵ of the Act, the amount of the workplace health and safety contribution payable by a

104 Part 14 (General), division 1B (Workplace health and safety contributions) of the Act

105 Section 182F (Working out workplace health and safety contribution amounts) of the Act

non-scheme employer for a financial year is the amount worked out under the formula—

$$W = \left(\frac{A}{B} \times C \right) \times \frac{D}{E}$$

(2) In subsection (1)—

A means the total amount of payments for the financial year made by the Workers' Compensation Regulatory Authority under the Workers' Compensation Act, section 479(1)(b)¹⁰⁶ for the prevention or recognition of injury to workers.

B means the number of workers covered by the Queensland workers' compensation scheme in the financial year.

C means the number of workers employed by the non-scheme employer in Queensland in the financial year.

D means the rate for the financial year for the non-scheme employer's industry or business specified by industrial gazette notice under the Workers' Compensation Act, section 54.¹⁰⁷

E means the average rate of premium for the financial year of all employers under the Queensland workers' compensation scheme.

W means workplace health and safety contribution.

(3) However, no payment is required if an amount has been paid as annual levy under the Workers' Compensation Act, section 81¹⁰⁸ by or in relation to the non-scheme employer for the same financial year.

106 Workers' Compensation Act, section 479 (Amounts payable by Authority on Minister's instruction)

107 Workers' Compensation Act, section 54 (Setting of premium)

108 Workers' Compensation Act, section 81 (Annual levy payable)

Part 22 Miscellaneous

229 Rural industry exemption

- (1) A relevant person in rural industry is exempted from complying with the following provisions—
- part 2 in relation to plant that is a mobile elevating work platform with an elevation of 6m or less
 - part 3
 - part 3A, except in relation to a prescribed activity that is asbestos removal work
 - part 4
 - part 13
 - part 14
 - part 15
 - part 17, division 3, subdivision 9
 - part 21B.
- (2) A worker in rural industry is exempted from complying with part 3.

229A Time for giving workplace health and safety undertaking

For section 42DA(2)¹⁰⁹ of the Act, a workplace health and safety undertaking must be received by the chief executive within 90 days after the identified person for the undertaking is served with a summons in relation to the alleged contravention.

229B Workplace health and safety representative training course

For section 81(1)(o) of the Act, the training course accredited under the *Vocational Education, Training and Employment Act 2000*, mentioned in schedule 2A, is prescribed.

109 Section 42DA (Giving workplace health and safety undertaking) of the Act

230 Appeal against decision of Authority

The *Building and Construction Industry (Portable Long Service Leave) Act 1991*, part 9¹¹⁰ applies to a decision, determination, direction or notice made or given by the Authority under this regulation.

Part 23 Transitional provisions**Division 1 Pc's workplace plan and pc's demolition work plan****231 Transitional provision for pc's workplace plan and pc's demolition work plan**

- (1) If construction work under a pc's workplace plan for a construction workplace started before the commencement of this section, the pc's workplace plan, as in force under this regulation immediately before the commencement, may be taken to be the construction workplace plan for the construction workplace.
- (2) However, if the construction work includes demolition work, whether started before or after the commencement of this section, the pc's workplace plan, and the pc's demolition work plan for the demolition work as in force under this regulation immediately before the commencement, may together be taken to be the construction workplace plan for the construction workplace.

110 *Building and Construction Industry (Portable Long Service Leave) Act 1991*, part 9 (Appeals)

Division 2 Induction for specified work

232 Transitional provision for Workplace Health and Safety induction for specified work

- (1) Until the end of 31 December 2002, section 63 of this regulation, as in force immediately before the commencement of this section, is taken to continue in force as if it had not been repealed.
- (2) All provisions of this regulation, as in force immediately before the commencement of this section, that are necessary to support the continuing operation of section 63 under subsection (1) but that are amended or repealed on the commencement of this section, are taken to continue in force to support the continuing operation of section 63 until the end of 31 December 2002 as if they had not been amended or repealed.

Division 3 Certificates of registration of registrable plant design

233 Transitional provision for Workplace Health and Safety Amendment Regulation (No. 1) 2004—applications for certificate of registration of registrable plant design

- (1) This section applies to an application for a certificate of registration of registrable plant design, made under pre-amended section 35,¹¹¹ but not decided, before the commencement of this section.
- (2) The application must be decided as if the *Workplace Health and Safety Amendment Regulation (No. 1) 2004* had not commenced.
- (3) In this section—
pre-amended section 35 means section 35 as in force immediately before the commencement of this section.

111 Pre-amended section 35 (How to apply)

234 Transitional provision for Workplace Health and Safety Amendment Regulation (No. 1) 2004—certificates of registration of registrable plant design

- (1) Subsection (2) applies if, immediately before the commencement of this section—
 - (a) a certificate of registration of registrable plant design for the design of plant was in force; and
 - (b) repealed section 15(1)(a) and (b)¹¹² had been complied with for the design.
- (2) The certificate is taken to be a certificate of registration of registrable plant design for the design in force under part 5, division 1¹¹³ until the certificate stops having effect under section 16A.¹¹⁴
- (3) Subsection (4) applies if—
 - (a) a certificate of registration of registrable plant design for the design of plant is granted under section 233; and
 - (b) when the certificate is granted, repealed section 15(1)(a) and (b) is complied with for the design.
- (4) The certificate is taken to be a certificate of registration of registrable plant design for the design in force under part 5, division 1 until the certificate stops having effect under section 16A.
- (5) In this section—

repealed section 15(1)(a) and (b) means section 15(1)(a) and (b) as in force immediately before the commencement of this section.

112 Repealed section 15 (Use etc. of registrable plant design that is not approved or registered)

113 Part 5 (Certificates), division 1 (Interpretation)

114 Section 16A (When certificate of registration is in force)

Division 4 **Certain amenities complying, or leased or acquired, immediately before 1 January 2005**

235 **Definitions for div 4**

In this division—

agreement, in relation to a formerly complying amenity, includes—

- (a) a lease or arrangement; and
- (b) a variation of an agreement; and
- (c) an agreement under which the employer is not the only party to the agreement to whom the formerly complying amenity is to be made available.

formerly complying amenity means—

- (a) a lunch room, whether in or adjacent to the employer's workplace, complying with the repealed regulation, schedule 7, section 5¹¹⁵ (**formerly complying lunch room**); or
- (b) a dressing room complying with the repealed regulation, schedule 7, section 6¹¹⁶ (**formerly complying dressing room**); or
- (c) a toilet complying with the repealed regulation, schedule 7, section 7¹¹⁷ (**formerly complying toilet**).

repealed regulation means the repealed *Workplace Health and Safety (Miscellaneous) Regulation 1995* as in force immediately before 1 January 2005.¹¹⁸

115 Repealed regulation, schedule 7 (Workplace amenities (for workplaces other than construction workplaces)), section 5 (Lunch place)

116 Repealed regulation, schedule 7 (Workplace amenities (for workplaces other than construction workplaces)), section 6 (Dressing rooms)

117 Repealed regulation, schedule 7 (Workplace amenities (for workplaces other than construction workplaces)), section 7 (Toilets)

118 The *Workplace Health and Safety (Miscellaneous) Regulation 1995* expired on 31 December 2004.

236 Employers to whom this division applies

- (1) This division applies to an employer if, immediately before 1 January 2005, the employer's workplace had a formerly complying amenity.

Example—

a workplace had an amenity even if the amenity was temporarily closed for repairs or for another reason

- (2) This division also applies to an employer if—
- (a) before 1 January 2005, the employer entered into an agreement under which a formerly complying amenity is to be leased or acquired by, or otherwise made available to, the employer; and
 - (b) when entering into the agreement, the employer intended to make the formerly complying amenity available, as an employer, for the employer's workplace or future workplace; and
 - (c) the formerly complying amenity is made available to the employer on or after 1 January 2005 under the agreement.
- (3) An employer under subsection (2) need not have been an employer when subsection (2)(a), (b) or (c) happened.

237 Lunch room

- (1) This section applies if—
- (a) an employer to whom this division applies makes a dining room available for the purpose of complying with schedule 8C, section 17(3);¹¹⁹ and
 - (b) the dining room is a formerly complying lunch room; and
 - (c) the dining room is not being used to accommodate more workers at the one time than could reasonably be accommodated at the one time as a formerly complying lunch room.

119 Schedule 8C (Employers—particular amenities for work that is not construction work or rural industry work), section 17 (Performance criteria to be complied with)

- (2) For that purpose—
 - (a) the following provisions do not apply, in relation to the dining room, to the employer—
 - (i) schedule 8F, part 1, division 1,¹²⁰ acceptable solution A8;
 - (ii) schedule 8F, part 1, division 2,¹²¹ acceptable solution A9(i)(i) to the extent it requires an area to comply with A8; and
 - (b) the dining room need not be part of a building.
- (3) In this section—
dining room see schedule 8F, part 2,¹²² section headed ‘Definitions’.

238 Dressing room

- (1) This section applies if—
 - (a) an employer to whom this division applies makes a formerly complying dressing room available for the purpose of complying with schedule 8C, section 21(3);¹²³ and
 - (b) the formerly complying dressing room is not being used to accommodate more workers at the one time than could reasonably be accommodated at the one time as a formerly complying dressing room.
- (2) For that purpose, the following provisions of schedule 8F, part 1, division 2¹²⁴ do not apply, in relation to the formerly complying dressing room, to the employer—

120 Schedule 8F (Applied QDC provisions), part 1 (Performance criteria and acceptable solutions), division 1 (Dining facilities)

121 Schedule 8F (Applied QDC provisions), part 1 (Performance criteria and acceptable solutions), division 2 (Dressing room facilities)

122 Schedule 8F (Applied QDC provisions), part 2 (Other provisions for complying with performance criteria)

123 Schedule 8C (Employers—particular amenities for work that is not construction work or rural industry work), section 21 (Performance criteria to be complied with)

124 Schedule 8F (Applied QDC provisions), part 1 (Performance criteria and acceptable solutions), division 2 (Dressing room facilities)

- (a) acceptable solution A9(a), (b) or (d);
- (b) acceptable solution A9(i)(i) to the extent it requires an area to comply with A9(a), (b) or (d).
- (3) In this section—
dressings room see schedule 8F, part 2, section headed ‘Definitions’.

239 Toilets

- (1) This section applies if an employer to whom this division applies makes a formerly complying toilet, that is not portable, available for the purpose of complying with schedule 8C, section 10(1).¹²⁵
- (2) For that purpose, the following provisions do not apply, in relation to the formerly complying toilet, to the employer—
 - (a) schedule 8C, section 13;¹²⁶
 - (b) schedule 8E, part 1, division 1, section F2.5.¹²⁷
- (3) However, the formerly complying toilet must be in a cubicle, or room, that gives privacy.

Division 5 Transitional provisions for Workers’ Compensation and Rehabilitation and Other Legislation Amendment Regulation (No. 1) 2005

241 Construction work—construction safety plans

- (1) This section applies to construction work started before the commencement of this section.

125 Schedule 8C (Employers—particular amenities for work that is not construction work or rural industry work), section 10 (Toilets, and hands and face washing facilities)

126 Schedule 8C (Employers—particular amenities for work that is not construction work or rural industry work), section 13 (Location of toilet)

127 Schedule 8E (Applied BCA provisions), part 1 (Toilets, and hands and face washing facilities), division 1 (Performance requirements)

- (2) A construction workplace plan for construction work prepared under this regulation, as in force immediately before the commencement, is taken to be a construction safety plan for the construction work.
- (3) A work method statement for a high risk construction activity prepared under this regulation, as in force immediately before the commencement, is taken to be a work method statement for a high risk construction activity, other than a prescribed activity.
- (4) A work method statement for a prescribed activity that is demolition work prepared under this regulation, as in force immediately before the commencement, is taken to be a work method statement for a high risk construction activity that is a prescribed activity.

242 Construction work—general induction evidence before 1 January 2006

- (1) This section applies to—
 - (a) a principal contractor; or
 - (b) an existing construction person.
- (2) Sections 65J, 65S, 65T and 65U¹²⁸ do not apply in relation to a person to whom this section applies only because the person is required to sight, hold or show general induction evidence in relation to starting, or allowing an existing construction person to start, new construction work.
- (3) In this section—

existing construction person means an employer, self-employed person or worker who, at any time between 2 November 2005 and 31 December 2005 (both inclusive), was or is performing new construction work.

new construction work means work that—

¹²⁸ Sections 65J (Principal contractor must sight general induction evidence before work starts), 65S (Employer must ensure general induction evidence is held before work starts), 65T (Self-employed person must hold general induction evidence before work starts) and 65U (Worker must hold general induction evidence before work starts). These sections have been repealed by 2005 SL No. 308 s 44.

- (a) was not construction work before 2 November 2005; but
- (b) became construction work on 2 November 2005.

243 Construction work—general induction evidence from 1 January 2006

- (1) Sections 169, 198, 199 and 217Q¹²⁹ do not apply in relation to an existing construction person until 30 July 2007.
- (2) In this section—

existing construction person means a relevant person or worker who, at any time between 2 November 2005 and 31 December 2005 (both inclusive), was performing new construction work.

new construction work means work that—

- (a) was not construction work before 2 November 2005; but
- (b) became construction work on 2 November 2005.

Division 6 Transitional provisions for Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2007, part 2, division 2

Subdivision 1 Definition for division 6

244 Definition for div 6

In this division—

commencement means the commencement of this section.

¹²⁹ Sections 169 (Principal contractor to sight general induction evidence before construction work starts), 198 (Relevant person to hold general induction evidence before starting construction work), 199 (Relevant person who is employer to ensure worker holds general induction evidence before worker starts construction work) and 217Q (Worker to hold general induction evidence before starting construction work)

Subdivision 2 Assessments by authorised accredited providers

245 Assessment for prescribed occupations made, but no application, before commencement

- (1) This section applies if, before the commencement—
 - (a) an application for a certificate to work in a prescribed occupation has been made to the chief executive; and
 - (b) the application has not been approved by the chief executive and an appropriate certificate granted or the application has not been refused and notice of refusal given to the applicant; and
 - (c) an authorised accredited provider has, under old section 19, assessed the applicant for a certificate to work in the prescribed occupation.
- (2) The application must be decided and otherwise dealt with under this regulation as in force immediately before the commencement.
- (3) On and after the commencement, but no later than 60 days after the assessment is made, the applicant is taken, for section 17, to have appropriate authority to perform work in the prescribed occupation.
- (4) In this section—

authorised accredited provider see old section 19.

old section 19 means section 19 as in force immediately before the commencement.

246 Application for certificate of authority of appointment of a workplace health and safety officer—assessment made but no application made before commencement

- (1) This section applies if—
 - (a) before the commencement, an authorised accredited provider has, under old section 31, assessed a person as competent to perform the functions of a workplace health and safety officer under the Act; and

- (b) on or after the commencement but within 3 months after the assessment is made, the person applies under part 5 for, or for renewal of, a certificate of authority of appointment of a workplace health and safety officer.
- (2) Section 31(2)(a) does not apply to the application.
- (3) In this section—

authorised accredited provider see old section 31.

old section 31 means section 31 as in force immediately before the commencement.

247 Application for certificate of authority of appointment of a workplace health and safety officer—unfinished training or assessment

- (1) This section applies if—
 - (a) either—
 - (i) an authorised accredited provider started to train a person to achieve either of the following, but has not finished the training before the commencement—
 - (A) competence to perform the functions of a workplace health and safety officer under the Act;
 - (B) competence to continue to perform the functions of a workplace health and safety officer under the Act; or
 - (ii) an authorised accredited provider started to assess a person's—
 - (A) competence to perform the functions of a workplace health and safety officer under the Act; or
 - (B) competence to continue to perform the functions of a workplace health and safety officer under the Act; and
 - (b) on or after the commencement the person applies for, or for renewal of, a certificate of authority of appointment of a workplace health and safety officer.

- (2) If, on or after the commencement, the person is assessed by the authorised accredited provider as competent to perform those functions, section 31(2)(a)(i) is taken to be satisfied for the application.
- (3) If, on or after the commencement, the person is assessed by the authorised accredited provider as competent to continue to perform those functions, section 31(2)(a)(ii) is taken to be satisfied for the application.
- (3) In this section—

authorised accredited provider see old section 31.

old section 31 means section 31 as in force immediately before the commencement.

248 Application for certificate of authority of appointment of a workplace health and safety officer—undecided application made before commencement

- (1) This section applies to an application made before the commencement under this regulation for, or for renewal of, a certificate of authority of appointment of a workplace health and safety officer.
- (2) If, before the commencement, the application has not been decided, the application must be decided and otherwise dealt with under this regulation as in force immediately before the commencement.

Subdivision 3 Other matters

249 Changes in scope of prescribed occupations

- (1) A certificate to work in a prescribed occupation (*old prescribed occupation*) issued before the commencement is, after the commencement, taken to be a certificate to work in the prescribed occupation that is nearest in scope to the scope of the old prescribed occupation.

- (2) Subsection (3) applies if—
 - (a) an application for a certificate to work in a prescribed occupation was made but not decided before the commencement; and
 - (b) on the commencement, there is no prescribed occupation that has the same scope as the prescribed occupation.
- (3) The application is taken to be an application for a certificate to work in the prescribed occupation that is nearest in scope to the scope of the prescribed occupation.

Division 7 Transitional provision for Workplace Health and Safety Legislation Amendment Regulation (No. 1) 2007

250 Application for certificate of registration of mobile crane or tower crane

- (1) This section applies if—
 - (a) an application under section 39I was made before the commencement of this section; and
 - (b) a certificate of registration, or a renewal of a certificate of registration, had not been granted, and a decision to refuse the application had not been made, before the commencement.
- (2) Section 39I as in force immediately before the commencement continues to apply to the application.

Division 8**Transitional provisions for
Workplace Health and Safety and
Other Legislation Amendment
Regulation (No. 1) 2007, part 2,
division 3****251 Applications for certificates to work in a prescribed occupation**

- (1) This section applies to an application for a certificate to work in a prescribed occupation that—
 - (a) was made under this regulation before 1 July 2008; and
 - (b) has not been decided.
- (2) The application must be decided and otherwise dealt with under this regulation as in force immediately before 1 July 2008.
- (3) However, if the chief executive decides to grant the application, the chief executive must, instead of granting the certificate stated in the application, issue—
 - (a) if the proposed certificate relates to work that corresponds to the work to which an earthmoving or particular crane work occupation relates—an earthmoving or particular crane work certificate for the occupation; or
 - (b) otherwise—a licence to perform the class of high risk work, that corresponds to the work to which the proposed certificate relates.

252 Unfinalised proposed action

- (1) This section applies if proposed action stated in a show cause notice given to a person before 1 July 2008 has not been finalised.
- (2) The chief executive must decide whether to take the proposed action, and may otherwise finalise the proposed action, under section 46B as in force immediately before 1 July 2008.

Division 9**Transitional provision for Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2008****253 Statement in assessment summary for unit of competency that person is competent**

- (1) This section applies if—
 - (a) a person holds an assessment summary, issued before the commencement of this section, stating for the unit of competency to which the assessment summary relates that the person named in the assessment summary is competent; and
 - (b) the person has a competent assessment result in the following assessments in the unit of competency—
 - (i) written assessment;
 - (ii) practical assessment;
 - (iii) if an assignment is required to be assessed under the assessment instrument for the unit of competency, and was assessed—assignment assessment.
- (2) For sections 17(4)(c) and 24(4)(c), the person is taken to hold an assessment summary stating for the unit of competency to which the assessment summary relates that the person named in the assessment summary has a competent assessment result in the assessments mentioned in subsection (1)(b).

Schedule 1 Fees

section 4

\$

1 **Notification of building and construction work**

- (1) This section sets the fee, under section 47, for the notification of building and construction work.
- (2) The fee is 0.125% of the cost of the building and construction work.

2 **Registration, or renewal of certificate of registration, of registrable plant**

- (1) This section sets the fee for the following—
 - (a) registration, under section 11, of registrable plant;
 - (b) renewal, under section 41, of a certificate of registration of registrable plant.
- (2) The fee is—
 - (a) subject to subsection (3), for a boiler with a heating surface of—

(i) not more than 5m ²	61.50
(ii) more than 5m ² but 10m ² or less	147.25
(iii) more than 10m ² but 60m ² or less	231.30
(iv) more than 60m ² but 500m ² or less	443.10
(v) more than 500m ² but 2000m ² or less	784.00
(vi) more than 2000m ²	1 324.00
 - (b) for an unfired pressure vessel with a capacity of—

(i) more than 0.5m ³ but 5m ³ or less	66.60
(ii) more than 5m ³ but 15m ³ or less	113.80
(iii) more than 15m ³ but 30m ³ or less	171.40
(iv) more than 30m ³	225.50

Schedule 1 (continued)

	\$
(c) for a crane or hoist, other than a vehicle hoist, building maintenance unit or elevating work platform, with a safe working load of—	
(i) not more than 10t	124.20
(ii) more than 10t but 50t or less	261.30
(iii) more than 50t	326.85
(d) for a truck-mounted concrete placing unit with boom, other than manually powered	124.20
(e) for a building maintenance unit	67.85
(f) for a service lift	47.10
(g) for a lift other than a service lift	81.60
	plus 18.80 for each floor
(h) for an escalator	63.20
(i) for an airconditioning unit	154.15
(j) for a specified amusement device classified as—	
(i) a class 2 amusement device in AS 3533, part 1 as in force on 5 December 1997, other than a coin operated amusement device	124.20
(ii) a class 3 amusement device in that part	189.90
(iii) a class 4 amusement device in that part	261.30
(iv) a class 5 amusement device in that part	261.30
(3) If a boiler is heated electrically, the fee payable must be worked out on the basis that 1kW equals 0.08m ² of heating surface.	

Schedule 1 (continued)

		\$
3	Application for certificate of registration of registrable plant design	
	The fee, under section 39C, for an application for a certificate of registration of registrable plant design is	81.40
4	Certificates of authority of appointment of a workplace health and safety officer	
	(1) This section sets the fee relating to a certificate of authority of appointment of a workplace health and safety officer under part 4.	
	(2) The fee is—	
	(a) for an assessment of qualifications or experience for the certificate.	25.70
	(b) for an application, under section 31, for a certificate.	51.10
	(c) for an application, under section 45, to replace a lost, damaged, destroyed or stolen certificate.	25.70
4A	Earthmoving or particular crane work certificates	
	(1) This section sets the fee relating to an earthmoving or particular crane work certificate.	
	(2) The fee is—	
	(a) for an application, under section 36, for a certificate.	51.10
	(b) for an application, under section 45, to replace a lost, damaged, destroyed or stolen certificate.	25.70
4B	Licences to perform a class of high risk work	
	(1) This section sets the fee relating to a licence to perform a class of high risk work.	
	(2) The fee is—	

Schedule 1 (continued)

	\$
(a) for an application, under section 37, for a licence to perform a class of high risk work—	
(i) for each licence class that is mentioned in subsection (3) and endorsed on the licence—the amount stated in subsection (4) for the licence class; or	
(ii) for each licence class that is endorsed on the licence and not mentioned in subsection (3)	65.00
(b) for an application, under section 37, for a variation of a licence to perform a class of high risk work to endorse another class of high risk work on the licence—	
(i) for each additional licence class that is mentioned in subsection (3) and endorsed on the licence—the amount stated in subsection (4) for the licence class; or	
(ii) for each additional licence class that is not mentioned in subsection (3) and is endorsed on the licence.	65.00
(c) for an application, under section 38L, for renewal of a licence to perform a class of high risk work	60.00
(d) for an application, under section 45, to replace a lost, damaged, destroyed or stolen licence to perform a class of high risk work	25.70
(3) For subsection (2)(a)(i) and (b)(i), the licence classes are as follows—	
(a) basic rigger;	
(b) intermediate rigger;	
(c) advanced rigger;	
(d) intermediate scaffolder;	
(e) advanced scaffolder;	

Schedule 1 (continued)

	\$
(f) intermediate boiler operator;	
(e) advanced boiler operator.	
(4) For subsection (2)(a)(i) and (b)(i), the amount is as follows—	
(a) for the licence class basic rigger—	
(i) if the applicant for the licence holds the licence class dogger	65.00
(ii) otherwise	130.00
(b) for the licence class intermediate rigger—	
(i) if the applicant holds the licence class basic rigger	65.00
(ii) if the applicant holds the licence class dogger but not basic rigger	130.00
(iii) if the applicant does not hold the licence class dogger or basic rigger . .	195.00
(c) for the licence class advanced rigger—	
(i) if the applicant holds the licence class intermediate rigger	65.00
(ii) if the applicant holds the licence class basic rigger but not intermediate rigger	130.00
(iii) if the applicant holds the licence class dogger but not basic rigger or intermediate rigger	195.00
(iv) if the applicant does not hold any of the following licence classes—	
(A) dogger;	
(B) basic rigger;	
(C) intermediate rigger	260.00
(d) for the licence class intermediate scaffolder—	
(i) if the applicant holds the licence class basic scaffolder	65.00
(ii) otherwise	130.00
(e) for the licence class advanced scaffolder—	

Schedule 1 (continued)

	\$
(i) if the applicant holds the licence class intermediate scaffolder	65.00
(ii) if the applicant holds the licence class basic scaffolder but not intermediate scaffolder	130.00
(iii) if the applicant does not hold the licence class basic scaffolder or intermediate scaffolder	195.00
(f) for the licence class intermediate boiler operator—	
(i) if the applicant holds the licence class basic boiler operator	65.00
(ii) otherwise	130.00
(g) for the licence class advanced boiler operator—	
(i) if the applicant holds the licence class intermediate boiler operator . . .	65.00
(ii) if the applicant holds the licence class basic boiler operator but not intermediate boiler operator	130.00
(iii) if the applicant does not hold the licence class basic boiler operator or intermediate boiler operator	195.00
(5) A reference in subsection (4)—	
(a) to an applicant who holds a particular licence class includes a reference to an applicant who holds a corresponding authority to the licence class; or	
(b) to an applicant who does not hold a particular licence includes a reference to an applicant who does not hold a corresponding authority to that licence class.	

Schedule 1 (continued)

		\$
4C	Conversion to renewable licence to perform a class of high risk work	
(1)	This section sets the fee for an application, under section 28M, to convert a licence to perform a class of high risk work to a renewable licence.	
(2)	The fee, irrespective of the number of licences to be converted, is	60.00
5	Certificates—prescribed activities	
(1)	This section sets the fees relating to a certificate to perform a prescribed activity under part 3A.	
(2)	The fee is—	
(a)	for an application, under section 29C, for a certificate.	51.10
(b)	for an application, under section 45, to replace a lost, damaged or destroyed certificate.	25.70
6	Certificate of appointment as an accredited provider	
(1)	This section sets the fees relating to a certificate of appointment as an accredited provider under part 4A.	
(2)	The fee is—	
(a)	for an application, under section 33, for a certificate.	51.10
(b)	for an assessment of an application for a certificate, for each year or part of a year . .	146.50
(c)	for an application, under section 45, to replace a lost, damaged or destroyed certificate.	25.70
7	Bonded asbestos removal certificate	
(1)	This section sets the fee relating to a bonded asbestos removal certificate.	

Schedule 1 (continued)

		\$
(2)	The fee is—	
	(a) for an application, under section 29I, for a certificate.	51.10
	(b) for an application, under section 45, to replace a lost, damaged or destroyed certificate.	25.70
8	Report about occupational health and safety performance for Workers' Compensation Act	
(1)	This section sets the fee for the preparation, under part 14, division 1A of the Act, of a report about the occupational health and safety performance of a single employer or group employer for the issue or renewal of a licence to be a self-insurer under the Workers' Compensation Act, section 71 or 72.	
(2)	The fee is—	
	(a) for a single employer	921.10
	(b) for a group employer.	1 223.80

Schedule 2 Accredited courses

section 33A

Course code	Course name
30215QLD	Course in general safety induction (construction industry)
30494QLD	Course in self-erecting tower crane operation
30496QLD	Course in operating load shifting equipment
30497QLD	Course in operating crane, rigging and scaffolding equipment
30498QLD	Course in operating pressure equipment
30523QLD	Course in recertification to function as a workplace health and safety officer
30596QLD	Course in functioning as a workplace health and safety officer

Schedule 2A Workplace health and safety representatives training course

section 229B

Course code	Course name
30630QLD	Course in functioning as a workplace health and safety representative

Schedule 3 Registrable plant

section 39G and schedule 9, definition *registrable plant*

- 1 air conditioning units
- 2 specified amusement devices, other than coin operated amusement devices
- 3 boilers categorised as hazard level A, B or C under the criteria mentioned in AS 4343,¹³⁰ as in force on 1 July 2000
- 4 building maintenance units
- 5 cooling towers
- 6 lifts other than lifts installed in a private residence within the meaning given by AS 1735¹³¹
- 7 escalators
- 8 mobile cranes with a safe working load of more than 10t, other than those that are manually powered
- 9 pressure vessels categorised as hazard level A, B or C under the criteria mentioned in AS 4343, as in force on 1 July 2000, other than—
 - (a) refillable gas cylinders mentioned in AS 2030;¹³² and
 - (b) LP gas fuel vessels for automotive use mentioned in AS 3509;¹³³ and
 - (c) serial produced vessels mentioned in AS 2971¹³⁴
- 10 tower cranes, other than those that are manually powered
- 11 truck-mounted concrete placing units with booms, other than those that are manually powered

130 AS 4343 (Pressure equipment—Hazard levels)

131 AS 1735 (Lifts, escalators and moving walks)

132 AS 2030 (The verification, filling, inspection, testing and maintenance of cylinders for storage and transport of compressed gases)

133 AS 3509 (LP (liquefied petroleum) gas fuel vessels for automotive use)

134 AS 2971 (Serially produced pressure vessels)

Schedule 4 Registrable plant design

sections 16 and 16C and schedule 9, definition *registrable plant design*

- 1 boom-type elevating work platform
- 2 bridge crane with a safe working load of at least 10t
- 3 bridge crane or gantry crane designed to handle molten metal or dangerous goods
- 4 building maintenance unit
- 5 escalator¹³⁵
- 6 gantry crane with a safe working load of more than 5t
- 7 LP gas cylinder¹³⁶
- 8 personnel hoist
- 9 lift¹³⁷
- 10 mast climbing work platform
- 11 mobile crane with a safe working load of more than 10t
- 12 prefabricated scaffolding
- 13 pressure equipment with hazard level A, B, C or D, as worked out under the criteria stated in AS 4343¹³⁸ as in force on 1 July 2000, other than pressure piping
- 14 refillable gas cylinder
- 15 specified amusement device, other than—
 - (a) a coin operated amusement device; or

135 *Escalator* is defined in schedule 2 of the Act.

136 *LP gas cylinder* is defined in schedule 2 of the Act.

137 *Lift* is defined in schedule 2 of the Act.

138 AS 4343 (Pressure equipment—Hazard levels)

Schedule 4 (continued)

- (b) a specified amusement device manufactured before 30 July 2004 and classified as a class 2, 3, 4 or 5 amusement device in AS 3533-1997¹³⁹ that, if it had been manufactured before 5 December 1997, would have been classified as a class 1 amusement device in AS 3533-1988¹⁴⁰

- 16 tower crane
17 vehicle hoist
18 work box

139 AS 3533-1997 (Amusement rides and devices)

140 AS 3533-1988 (Amusement rides and devices)

Schedule 5 Classes of high risk work and units of competency for the classes

schedule 9, definitions *class of high risk work* and *unit of competency*

Part 1 Scaffolding work

1 Basic scaffolder

- (1) The class of work is basic scaffolder.
- (2) The unit of competency for the class is Perform basic scaffolding operations, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

2 Intermediate scaffolder

- (1) The class of work is intermediate scaffolder.
- (2) The unit of competency for the class is Perform intermediate scaffolding operations, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

3 Advanced scaffolder

- (1) The class of work is advanced scaffolder.
- (2) The unit of competency for the class is Perform advanced scaffolding operations, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

Schedule 5 (continued)

Part 2 Rigging work**4 Dogger**

- (1) The class of work is dogger.
- (2) The unit of competency for the class is Perform dogging operations, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

5 Basic rigger

- (1) The class of work is basic rigger.
- (2) The unit of competency for the class is Perform basic rigging operations, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

6 Intermediate rigger

- (1) The class of work is intermediate rigger.
- (2) The unit of competency for the class is Perform intermediate rigging operations, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

7 Advanced rigger

- (1) The class of work is advanced rigger.
- (2) The unit of competency for the class is Perform advanced rigging operations, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

Schedule 5 (continued)

Part 3 Crane and hoist operation**8 Tower crane**

- (1) The class of work is operator of a tower crane.
- (2) The unit of competency for the class is Operate a tower crane, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

9 Self-erecting tower crane

- (1) The class of work is operator of a self-erecting tower crane.
- (2) The unit of competency for the class is Operate a self-erecting tower crane, in accredited course 30494QLD—Course in self-erecting tower crane operation.

10 Derrick crane

- (1) The class of work is operator of a derrick crane.
- (2) The unit of competency for the class is Operate a derrick crane, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

11 Portal boom crane

- (1) The class of work is operator of a portal boom crane.
- (2) The unit of competency for the class is Operate a portal boom crane, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

12 Bridge and gantry crane (open)

- (1) The class of work is operator of a bridge and gantry crane.

Note—

See sections 17(6) and 24(6) and schedule 5A, section 1 (Bridge and gantry crane (remote control only)).

Schedule 5 (continued)

- (2) For subsection (1), each of the following is a single powered operation—
 - (a) raising and lowering a load;
 - (b) moving the crane along runways;
 - (c) traversing the hoisting mechanism across the bridge beam;
 - (d) rotating the hoisting mechanism.
- (3) The unit of competency for the class is Operate a bridge and gantry crane, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

13 Vehicle loading crane

- (1) The class of work is operator of a vehicle loading crane with a capacity of 10 metre tonnes or more.
- (2) The unit of competency for the class is Operate a vehicle loading crane, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

14 Non-slewing mobile crane

- (1) The class of work is operator of a non-slewing mobile crane with a capacity of more than 3t.
- (2) The unit of competency for the class is Operate non-slewing mobile cranes (less than 3 tonnes capacity), in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

15 Slewing mobile crane with a capacity of 20t or less

- (1) The class of work is operator of a slewing mobile crane with a capacity of 20t or less.
- (2) The unit of competency for the class is Operate slewing mobile crane (up to 20 tonnes), in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

Schedule 5 (continued)**16 Slewing mobile crane with a capacity of 60t or less**

- (1) The class of work is operator of a slewing mobile crane with a capacity of 60t or less.
- (2) The unit of competency for the class is Operate slewing mobile crane (up to 60 tonnes), in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

17 Slewing mobile crane with a capacity of 100t or less

- (1) The class of work is operator of a slewing mobile crane with a capacity of 100t or less.
- (2) The unit of competency for the class is Operate slewing mobile crane (up to 100 tonnes), in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

18 Slewing mobile crane with a capacity of more than 100t

- (1) The class of work is operator of a slewing mobile crane with a capacity of more than 100t.
- (2) The unit of competency for the class is Operate slewing mobile crane (open/over 100 tonnes), in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

19 Materials hoist

- (1) The class of work is operator of a materials hoist with a cantilever platform.
- (2) The unit of competency for the class is Operate material hoists (cantilever platform), in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

Schedule 5 (continued)**20 Materials and personnel hoist**

- (1) The class of work is operator of a materials and personnel hoist.
- (2) The unit of competency for the class is Operate a hoist (material or personnel) in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

21 Boom-type elevating work platform

- (1) The class of work is operator of a boom-type elevating work platform with a boom length of 11m or more.
- (2) The unit of competency for the class is Operate boom type elevating work platforms (boom length 11 metres or more), in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

22 Mobile truck mounted concrete placing boom

- (1) The class of work is operator of a mobile truck mounted concrete placing boom with a knuckle boom capable of power operated slewing and luffing.
- (2) The unit of competency for the class is Operate a vehicle loading crane, in accredited course 30497QLD—Course in operating crane, rigging and scaffolding.

Part 4 Forklift operation**23 Forklift truck**

- (1) The class of work is operator of a forklift truck, other than a pedestrian operated forklift truck.
- (2) The unit of competency for the class is Operate a forklift truck, in accredited course 30496QLD—Course in operating load shifting equipment.

Schedule 5 (continued)**24 Order picking forklift truck**

- (1) The class of work is operator of an order picking forklift truck.
- (2) The unit of competency for the class is Operate an order picking forklift truck, in accredited course 30496QLD—Course in operating load shifting equipment.

Part 5 Pressure equipment operation**25 Basic boiler operator**

- (1) The class of work is basic boiler operator.
- (2) The unit of competency for the class is Operate a boiler (basic), in accredited course 30498QLD—Course in operating pressure equipment.

26 Intermediate boiler operator

- (1) The class of work is intermediate boiler operator.
- (2) The unit of competency for the class is Operate a boiler (intermediate), in accredited course 30498QLD—Course in operating pressure equipment.

27 Advanced boiler operator

- (1) The class of work is advanced boiler operator.
- (2) The unit of competency for the class is Operate a boiler (advanced), in accredited course 30498QLD—Course in operating pressure equipment.

28 Turbine operator

- (1) The class of work is operator of a turbine with a power output of 500kW or more.

Schedule 5 (continued)

- (2) The unit of competency for the class is Operate a turbine, in accredited course 30498QLD—Course in operating pressure equipment.

29 Reciprocating steam engine operator

- (1) The class of work is operator of a reciprocating steam engine with a piston diameter of more than 250mm.
- (2) The unit of competency for the class is Operate a reciprocating steam engine, in accredited course 30498QLD—Course in operating pressure equipment.

Schedule 5A Earthmoving or particular crane occupations and units of competency for the occupations

schedule 9, definitions *earthmoving or particular crane occupation*
and *unit of competency*

1 Bridge and gantry crane (remote control only)

- (1) The occupation is operator of a bridge and gantry crane, if—
 - (a) the load being lifted by remote control is more than 5t; and
 - (b) the crane has the ability to perform 3 or less powered operations.

Note—

See sections 17(6) and 24(6) and schedule 5, section 12 (Bridge and gantry crane (open)).

- (2) The unit of competency for the occupation is Operate a bridge or gantry crane (remote operation only), in accredited course 30496QLD—Course in operating load shifting equipment.

2 Dozer

- (1) The occupation is operator of a dozer.
- (2) The unit of competency for the occupation is Operate a dozer (wheeled and tracked), in accredited course 30496QLD—Course in operating load shifting equipment.

3 Excavator having an engine capacity of more than 2L

- (1) The occupation is operator of an excavator having an engine capacity of more than 2L.
- (2) The unit of competency for the occupation is Operate an excavator, in accredited course 30496QLD—Course in operating load shifting equipment.

Schedule 5A (continued)

- 4 Front-end loader having an engine capacity of more than 2L**
- (1) The occupation is operator of a front-end loader having an engine capacity of more than 2L.
 - (2) The unit of competency for the occupation is Operate a front end loader, in accredited course 30496QLD—Course in operating load shifting equipment.
- 5 Front-end loader or backhoe having an engine capacity of more than 2L**
- (1) The occupation is operator of a front-end loader or backhoe having an engine capacity of more than 2L.
 - (2) The unit of competency for the occupation is Operate a front end loader/backhoe, in accredited course 30496QLD—Course in operating load shifting equipment.
- 6 Grader**
- (1) The occupation is operator of a grader.
 - (2) The unit of competency for the occupation is Operate a grader, in accredited course 30496QLD—Course in operating load shifting equipment.
- 7 Road roller having an engine capacity of more than 2L**
- (1) The occupation is operator of a road roller having an engine capacity of more than 2L.
 - (2) The unit of competency for the occupation is Operate a roller, in accredited course 30496QLD—Course in operating load shifting equipment.
- 8 Skid steer loader having an engine capacity of more than 2L**
- (1) The occupation is operator of a skid steer loader having an engine capacity of more than 2L.

Schedule 5A (continued)

- (2) The unit of competency for the occupation is Operate a front end loader skid steer type, in accredited course 30496QLD—Course in operating load shifting equipment.

9 Scraper

- (1) The occupation is operator of a scraper.
- (2) The unit of competency for the occupation is Operate a scraper, in accredited course 30496QLD—Course in operating load shifting equipment.

Schedule 5B Particular work encompassed in licence classes

section 46K

Part 1 Work, under another licence class, encompassed in a licence class

Column 1	Column 2
Licence class	Work, under another licence class, that is encompassed in the licence class
1 Basic rigger	1 Work of a dogger
2 Intermediate rigger	2 Work of a dogger or basic rigger
3 Advanced rigger	3 Work of a dogger, basic rigger or intermediate rigger
4 Intermediate scaffolder	4 Work of a basic scaffolder
5 Advanced scaffolder	5 Work of a basic scaffolder or intermediate scaffolder
6 Operator of a slewing mobile crane with a capacity of 20t or less	6 Operator of— (a) a non-slewing mobile crane with a capacity of more than 3t; or (b) a vehicle loading crane with a capacity of 10 metre tonnes or more

Schedule 5B (continued)

Column 1	Column 2
Licence class	Work, under another licence class, that is encompassed in the licence class
7 Operator of a slewing mobile crane with a capacity of 60t or less	7 Operator of— <ul style="list-style-type: none"> (a) a slewing mobile crane with a capacity of 20t or less; or (b) a non-slewing mobile crane with a capacity of more than 3t; or (c) a vehicle loading crane with a capacity of 10 metre tonnes or more
8 Operator of a slewing mobile crane with a capacity of 100t or less	8 Operator of— <ul style="list-style-type: none"> (a) a slewing mobile crane with a capacity of 20t or less; or (b) a slewing mobile crane with a capacity of 60t or less; or (c) a non-slewing mobile crane with a capacity of more than 3t; or (d) a vehicle loading crane with a capacity of 10 metre tonnes or more

Schedule 5B (continued)

Column 1	Column 2
Licence class	Work, under another licence class, that is encompassed in the licence class
9 Operator of a slewing mobile crane with a capacity of more than 100t	9 Operator of— <ul style="list-style-type: none"> (a) a slewing mobile crane with a capacity of 20t or less; or (b) a slewing mobile crane with a capacity of 60t or less; or (c) a slewing mobile crane with a capacity of 100t or less; or (d) a non-slewing mobile crane with a capacity of more than 3t; or (e) a vehicle loading crane with a capacity of 10 metre tonnes or more
10 Intermediate boiler operator	10 Work of a basic boiler operator
11 Advanced boiler operator	11 Work of a basic boiler operator or intermediate boiler operator

Schedule 5B (continued)

Part 2**Work, under earthmoving or particular crane work certificate, encompassed in licence class operator of a bridge and gantry crane****Column 1****Licence class****Column 2****Work, under an earthmoving or particular crane work certificate, that is encompassed in the licence class**

1 Operator of a bridge and gantry crane

1 Operation of a bridge and gantry crane, if —

- (a) the load being lifted by remote control is more than 5t; and
- (b) the crane has 3 or less powered operations.

Schedule 5B (continued)

Schedule 6 Hazardous substances for which health surveillance must be supplied

section 109

Column 1 Hazardous substance	Column 2 Health surveillance
4,4' Methylenebis (2-chloroaniline) (MOCA)	Demographic, medical and occupational history Dipstick analysis of urine for haematuria Health advice Urinary total MOCA Urine cytology
Acrylonitrile	Demographic, medical and occupational history Exposure record Health advice Physical examination if decided by the designated doctor supervising the health surveillance
Asbestos	Demographic, medical and occupational history Exposure record Health advice Physical examination if decided by the designated doctor supervising the health surveillance

Schedule 5B (continued)

Column 1 Hazardous substance	Column 2 Health surveillance
Benzene	<p>Baseline blood sample for haematological profile</p> <p>Demographic, medical and occupational history</p> <p>Exposure record</p> <p>Health advice</p>
Cadmium	<p>Demographic, medical and occupational history</p> <p>Exposure record</p> <p>Health advice including counselling about the effect of smoking on cadmium exposure</p> <p>Physical examination with emphasis on the respiratory system</p> <p>Standard respiratory function tests including, for example, FEV₁, FVC and FEV₁/FVC</p> <p>Standard respiratory questionnaire to be completed</p> <p>Urinary cadmium and β_2-microglobulin</p>
Creosote	<p>Demographic, medical and occupational history</p> <p>Exposure record including photosensitivity</p> <p>Health advice including recognition of photosensitivity and skin changes</p>

Schedule 5B (continued)

Column 1 Hazardous substance	Column 2 Health surveillance
Crystalline silica	Physical examination with emphasis on the neurological system and skin noting any abnormal lesions and evidence of skin sensitisation Chest X-ray, full size Pa view Demographic, medical and occupational history Exposure record Health advice Standard respiratory function test including, for example, FEV ₁ , FVC and FEV ₁ /FVC Standard respiratory questionnaire to be completed
Inorganic arsenic	Demographic, medical and occupational history Exposure record Health advice Physical examination with emphasis on the peripheral nervous system and skin Urinary total arsenic
Inorganic chromium	Demographic, medical and occupational history Health advice Physical examination with emphasis on the respiratory system and skin

Schedule 5B (continued)

Column 1 Hazardous substance	Column 2 Health surveillance
Inorganic mercury	<p>Weekly skin inspection of hands and forearms by a responsible person</p> <p>Demographic, medical and occupational history</p> <p>Health advice</p> <p>Physical examination with emphasis on gastrointestinal systems, neurological, renal systems and skin</p> <p>Urinary inorganic mercury</p>
Isocyanates	<p>Demographic, medical and occupational history</p> <p>Health advice</p> <p>Physical examination of respiratory system and skin</p> <p>Standard respiratory function tests including, for example, FEV₁, FVC and FEV₁/FVC</p> <p>Standard respiratory questionnaire to be completed</p>
Organophosphate pesticides	<p>Baseline examination of red cell and plasma cholinesterase activity levels by the Ellman method</p> <p>Demographic, medical and occupational history</p> <p>Estimate of red cell and plasma cholinesterase activity towards the end of a working day on which organophosphate pesticides have been used</p>

Schedule 5B (continued)

Column 1 Hazardous substance	Column 2 Health surveillance
Pentachlorophenol (PCP)	Health advice
	Physical examination
	Demographic, medical and occupational history
	Dipstick urinalysis for haematuria and proteinuria
	Exposure record
Polycyclic aromatic hydrocarbons (PAH)	Health advice
	Physical examination with emphasis on skin noting any abnormal lesions or effects of irritancy
	Urinary total pentachlorophenol
	Exposure including photosensitivity record
	Demographic, medical and occupational history
Thallium	Health advice including recognition of photosensitivity and skin changes
	Physical examination if decided by the designated doctor supervising the health surveillance
	Demographic, medical and occupational history
	Health advice
	Physical examination if decided by the designated doctor supervising the health surveillance
	Urinary thallium

Schedule 5B (continued)

Column 1
Hazardous substance

Vinyl chloride

Column 2
Health surveillanceDemographic, medical and
occupational history

Exposure record

Health advice

Physical examination if decided by
the designated doctor supervising the
health surveillance

Schedule 7 Prohibited substances, prohibited ACM and prohibited purposes

section 69B

1 Amosite, crocidolite, fibrous anthophyllite, tremolite or actinolite

- (1) Amosite, crocidolite, fibrous anthophyllite, tremolite and actinolite are prohibited substances.
- (2) A thing containing amosite, crocidolite, fibrous anthophyllite, tremolite or actinolite is a prohibited ACM.
- (3) The prohibited purpose for the prohibited substances or the prohibited ACM is a purpose other than any of the following—
 - (a) analysis, research or sampling;
 - (b) maintenance;
 - (c) removal or disposal;
 - (d) encapsulation or enclosure.

2 Chrysotile

- (1) Chrysotile is a prohibited substance.
- (2) A thing, other than a product or item exempted under the national model regulations, containing chrysotile is a prohibited ACM.
- (3) The prohibited purpose for chrysotile is a purpose other than—
 - (a) analysis, research or sampling; or
 - (b) removal or disposal.
- (4) The prohibited purpose for the prohibited ACM mentioned in subsection (2) is a purpose other than any of the following—
 - (a) analysis, research or sampling;

Schedule 7 (continued)

- (b) removal or disposal;
- (c) display of an artefact or other thing that is, or forms part of, the prohibited ACM, or work to prepare or maintain the artefact or thing for display;

Examples of an artefact or other thing for paragraph (c)—

- a locomotive, steam engine or vehicle in a museum or historical display
- an artefact that is an ornament

- (d) use of the prohibited ACM in the position where it was installed immediately before 31 December 2003.

Examples—

- use brake shoes, containing chrysotile, installed in a car before 31 December 2003
- paint, or cut a hole in, an asbestos-cement wall panel, containing chrysotile, installed before 31 December 2003

- (5) In this section—

national model regulations means NOHSC's document entitled 'National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC:1005]', schedule 2.

Schedule 8 Lead hazardous substances

section 117

lead acetate
lead arsenate
lead arsenates
lead arsenites
lead azide
lead chromate
lead cyanide
lead dioxide
lead hexafluorosilicate
lead nitrate
lead perchlorate
lead peroxide
lead phosphate
lead phosphite
lead styphnate
lead sulphate
lead trinitroresorcinate
other lead compounds

Schedule 8A Principal contractors—particular amenities for construction work

section 189

Part 1 Definition for sch 8A

1 Definition

In this schedule—

construction person means a relevant person or worker who is performing construction work.

Part 2 Toilets

2 Toilets

- (1) The principal contractor for construction work must ensure that toilets complying with this part are reasonably available to each construction person.

Examples of toilets that are reasonably available—

- toilets located within the site compound boundary
- toilets located within the boundary of the workplace where the construction work is being performed

Maximum penalty—20 penalty units.

- (2) There must be at least 1 toilet for each 15, or part of 15, construction persons.

Examples—

- for 1 to 15 construction persons, there must be at least 1 toilet

Schedule 8A (continued)

- for 20 construction persons, there must be at least 1 toilet for the first 15 construction persons plus at least 1 toilet for the other 5, making a total of at least 2 toilets
- (3) If the workplace includes at least 4 levels of a structure that is a building (not counting ground level), a toilet is, for schedule 9, definition *reasonably available*, paragraph (a), at a location reasonably convenient to each construction person only if there is at least 1 toilet on at least each of the following levels of the building—
- (a) ground level;
 - (b) the fourth level (not counting ground level);
 - (c) each third level after that fourth level.

Example—

For a workplace that includes ground level and levels 1 to 10 of a structure that is a building, there must be at least 1 toilet on ground level, level 4, level 7 and level 10.

- (4) Subsection (3) does not limit subsection (2).

3 When toilet must be connected toilet or portable toilet

- (1) If there are less than 15 construction persons, the toilet must be a connected toilet or a portable toilet.¹⁴¹
- (2) If there are at least 15 construction persons, each toilet must be—
- (a) if a sewerage or septic connection is available—a connected toilet; or
 - (b) otherwise—a portable toilet.
- (3) However, if—

¹⁴¹ For requirements for portable toilets see the *Environmental Protection (Waste Management) Regulation 2000*, section 67 (Prohibition on use of non-complying waste equipment) and the *Environmental Protection (Interim Waste) Regulation 1996*, sections 48 (Requirements for sanitary conveniences, pan cabinets and pans), 53 (Requirements for closets, pan cabinets and pans) and 55 (Requirements for cesspits).

Schedule 8A (continued)

- (a) a portable toilet is made available under subsection (1); and
 - (b) a sewerage or septic connection becomes available;
the portable toilet must be replaced by a connected toilet complying with this part within 2 weeks after the first time that there are at least 15 construction persons after the connection becomes available.
- (4) Despite subsection (2)(b), if—
- (a) a portable toilet is made available under subsection (2)(b); and
 - (b) a sewerage or septic connection becomes available;
the portable toilet must be replaced by a connected toilet complying with this part within 2 weeks after the connection becomes available.
- (5) In this section—
- connected toilet*** means a toilet that—
- (a) is connected to a sewerage or septic system; or
 - (b) is a pump-out holding tank storage type system.
- portable toilet*** means a toilet that can be moved, and provides for tanked waste.

4 Privacy, ventilation and toilet paper

- (1) Each toilet must be located—
- (a) in a position that gives privacy; and
 - (b) in a cubicle, or room, that—
 - (i) is fitted with a door that gives privacy and is lockable from inside the cubicle or room; and
 - (ii) is constantly supplied with fresh air from openings to the outside air or from mechanical ventilation.
- (2) Each toilet made available to a female construction person must—

Schedule 8A (continued)

- (a) have facilities to dispose of sanitary items for females; and
- (b) be separated from urinals so that no urinal can be seen by her.

Examples—

- locating a toilet for females in a separate room from urinals
 - putting a screen between urinals and a toilet for females
- (3) Each toilet may be a unisex toilet.
 - (4) Each toilet must have an adequate supply of toilet paper.

Part 3 Other amenities

5 Room, or sheltered area, to eat meals in

- (1) The principal contractor for construction work must ensure that a room, or sheltered area, to eat meals and take breaks in is reasonably available to each construction person.

Maximum penalty—20 penalty units.

- (2) The room or sheltered area must—
 - (a) be hygienic and separated from work activity that exposes or is likely to expose a construction person to a health or safety risk; and
 - (b) if there are at least 15 construction persons—
 - (i) have adequate space and seating for the maximum number of construction persons likely to use the room or sheltered area at the one time; and
 - (ii) have appropriate facilities for washing and storing utensils, boiling water, and storing food in a cool place.

Schedule 8A (continued)

6 Hands and face washing facilities

- (1) The principal contractor for construction work must ensure the following facilities are reasonably available to each construction person—

- (a) adequate clean water for washing the hands and face;
- (b) an appropriate facility for supplying the water.

Examples of an appropriate facility—

- a hose at a housing construction site
- a water container with a tap at a road construction site
- a washbasin included with a portable toilet or connected toilet at a high rise building construction site

Maximum penalty—20 penalty units.

- (2) However, the facilities must not be unisex facilities that are located inside a toilet block, room or cubicle (*toilets*), unless the toilets are unisex toilets.

7 Drinking water

- (1) The principal contractor for construction work must ensure that an adequate supply of potable, clean and cool drinking water is reasonably available to each construction person.

Examples of a supply of water that, for schedule 9, definition reasonably available, paragraph (a), is at a location reasonably convenient to the construction person—

- a supply located within 30m of where the construction person is working on a single level building
- a supply located on the ground level and then every second level of a high rise building being built

Maximum penalty—20 penalty units.

- (2) The supply of water must not be located in toilets.

Example of toilets—

a toilet block or a cubicle used as a toilet

Schedule 8A (continued)

- (3) If the water is made available in a container, the construction person must be able to drink the water without having to drink directly from the same container as someone else.
- (4) This section does not prevent the supply of water also being made available under section 6 for hands and face washing.

Schedule 8B Employers—particular amenities for rural industry work

section 218

Part 1 Toilets for workers and employer

1 Toilets

- (1) An employer must ensure that, to the greatest practicable extent, toilets complying with this section are reasonably available to each work person who is at a workplace and performing work in a rural industry.

Maximum penalty—20 penalty units.

- (2) Toilets located within a reasonable distance of the work person, using appropriate transport, are, for schedule 9, definition *reasonably available*, paragraph (a), at a location reasonably convenient to the work person.
- (3) There must be at least 1 toilet for each 15, or part of 15, work persons who are at the workplace and performing work in a rural industry.

Examples—

- For 1 to 15 work persons, there must be at least 1 toilet.
 - For 20 work persons, there must be at least 1 toilet for the first 15 work persons plus at least 1 toilet for the other 5, making a total of at least 2 toilets.
- (4) Each toilet made available to a female work person must have facilities to dispose of sanitary items for females.
- (5) Each toilet may be a unisex toilet.
- (6) Each toilet must have an adequate supply of toilet paper.
- (7) In this section—

work person means the employer or a worker of the employer.

Schedule 8B (continued)

Part 2 Other amenities for workers**2 Application of pt 2**

This part applies if a worker of an employer is performing work in a rural industry at a workplace.

3 Sheltered area to eat meals in

- (1) The employer must ensure that a sheltered area to eat meals and take breaks in is reasonably available to the worker.

Examples—

- a caravan
- a tent attached to a vehicle
- a tractor cabin or harvester cabin

Maximum penalty—20 penalty units.

- (2) The sheltered area must be separated from work activity that exposes or is likely to expose the worker to a health or safety risk.

4 Hands washing facilities

The employer must ensure the following are reasonably available to the worker—

- (a) adequate clean water, and soap or another suitable cleansing agent, for washing the worker's hands;
- (b) facilities to dry the worker's hands.

Example—

hand towels, paper towels or a mechanical hands dryer

Maximum penalty—20 penalty units.

5 Drinking water

- (1) The employer must ensure that an adequate supply of potable, clean drinking water is reasonably available to the worker.

Schedule 8B (continued)

Maximum penalty—20 penalty units.

- (2) The supply of water must not be located in toilets.

Example of toilets—

a toilet block or a cubicle used as a toilet

- (3) The water must not be at more than 15°C.
- (4) If the water is made available in a container, the worker must be able to drink the water without having to drink directly from the same container as someone else.
- (5) This section does not prevent the supply of water also being made available under section 4 for hands washing.

Schedule 8C Employers—particular amenities for work that is not construction work or rural industry work

section 219

Part 1 Application of sch 8C

1 Application of sch 8C

This schedule applies if a worker of an employer is performing work that is not construction work or work in a rural industry.

Part 2 Explanation of applied BCA provisions or applied QDC provisions used for pt 3 or sch 8D

2 Definitions for pt 2

In this part—

applied BCA provision see section 3(4).

applied QDC provision see section 3(4).

BCA means the edition of the Building Code of Australia¹⁴² as current on 1 May 2004.

¹⁴² The Building Code of Australia is a publication of the Australian Building Codes Board and the Board has consented to the use of the code. The logo of the Australian Building Codes Board appears at the end of schedule 8E. Also, the web address for the Board is <www.abcb.gov.au>.

Schedule 8C (continued)

Building Code of Australia see the *Building Act 1975*, section 12.

QDC means the Queensland Development Code as current on 23 August 2002.

Queensland Development Code see the *Building Act 1975*, section 13.

3 Purpose of applied BCA or applied QDC provisions

- (1) The BCA and QDC contain requirements, in relation to the design and construction of buildings, about—
 - (a) amenities that a building must be provided with; and
 - (b) requirements, for example, about ventilation or lighting, for a building.
- (2) Under certain provisions of part 3,¹⁴³ the amenity that an employer has a duty to make reasonably available to a worker while the worker is doing certain work is the same, with some modification, as a particular amenity required under the BCA or QDC.
- (3) Under certain provisions of schedule 8D,¹⁴⁴ the requirements for a building that an employer has a duty to ensure are complied with while the worker is doing certain work are the same, with some modification, as particular requirements for a building, under the BCA or QDC.
- (4) For the purpose of stating those duties, BCA or modified BCA provisions (***applied BCA provisions***) or modified QDC provisions (***applied QDC provisions***) are—

¹⁴³ Part 3 (If worker is at workplace where employer provides non-class 10 building for workers to occupy). The provisions are section 10 (Toilets, and hands and face washing facilities), 16 (Dining facilities) and 20 (Dressing room facilities) and the example in section 22(1) (Drinking water).

¹⁴⁴ Schedule 8D (Employers—requirements for building provided for worker to occupy when performing work that is not construction work or rural industry work). The provisions are sections 2 (Ventilation), 4 (Lighting) and 5 (Floor area and air space).

Schedule 8C (continued)

- (a) applied under part 3 or schedule 8D; and
- (b) set out in schedule 8E or 8F.¹⁴⁵

4 Changes to the text of BCA or QDC in modified provision

- (1) In the modified BCA or QDC provisions, changes to the text of the BCA or QDC are in italics and, for this purpose, italics or underlining in the text of the BCA or QDC are not reproduced.
- (2) Each modified BCA or QDC provision with a number keeps the same number as the BCA or QDC provision it modifies.

5 Interpretation of applied BCA or applied QDC provisions

- (1) It is intended that the applied BCA provisions and applied QDC provisions form part of a self-contained scheme all of which is set out in this regulation.
- (2) So, the BCA or QDC must not be referred to for the purpose of interpreting an applied BCA provision or applied QDC provision, and those provisions must be interpreted as if they were ordinary provisions of this regulation.

Notes—

- 1 Schedule 8E, part 3, section A1.1¹⁴⁶ contains definitions for applied BCA provisions.
- 2 Schedule 8F, part 2,¹⁴⁷ section headed ‘Definitions’ contains definitions for applied QDC provisions.
- 3 *Building*, and other particular words relevant to the applied BCA or applied QDC provisions, are defined in schedule 9.
- 4 The Act, and the *Acts Interpretation Act 1954*, also define particular words relevant to the applied BCA or applied QDC provisions.

145 Schedule 8E (Applied BCA provisions) or 8F (Applied QDC provisions)

146 Schedule 8E (Applied BCA provisions), part 3 (Further provisions for complying with performance requirements—definitions, classification of buildings and adoption of standards), section A1.1 (Definitions)

147 Schedule 8F (Applied QDC provisions), part 2 (Other provisions for complying with performance criteria)

Schedule 8C (continued)

- (3) However, the following definitions in schedule 3¹⁴⁸ of the Act do not apply in relation to an applied BCA provision or applied QDC provision—
- (a) board;
 - (b) lift,
 - (c) occupier;
 - (d) owner;
 - (e) place;
 - (f) plant;
 - (g) vehicle.
- (4) Also, the definition *Authority* in schedule 9¹⁴⁹ does not apply in relation to an applied BCA provision or applied QDC provision.
- (5) In an applied BCA provision or applied QDC provision relating to an amenity, a reference to workers is a reference to the employer's workers to whom the amenity must be available under part 3.

148 Schedule 3 (Dictionary) of the Act

149 Schedule 9 (Dictionary)

Schedule 8C (continued)

Part 3 **If worker is at workplace where employer provides non-class 10 building for workers to occupy****Division 1** **Application of pt 3****6** **Application of pt 3**

This part applies if—

- (a) the employer provides a building¹⁵⁰ at a workplace for the worker or any other worker of the employer to occupy when performing work that is not construction work or work in a rural industry; and
- (b) the building is not a class 10 building;¹⁵¹ and
- (c) the worker is at the workplace, whether or not the worker or other worker is actually occupying the building.

Examples of a building provided for the worker to occupy—

- an office building
- a building that is a walled or partly walled shed and used as a workshop
- a building, at a workplace that includes an outside storage yard, provided for the worker to occupy when not working in the yard

Example of a building not provided for the worker to occupy—

a building that the worker is in temporarily to repair equipment

150 *Building* is defined in schedule 9 (Dictionary).

151 *Class* is defined in schedule 9 (Dictionary).

Schedule 8C (continued)

**Division 2 Toilets, and hands and face
washing facilities****Subdivision 1 If the building is a class 1b building
or employer's domestic premises****7 Toilets**

- (1) If the building provided by the employer is a class 1b building or the employer's domestic premises, the employer must ensure that toilets complying with this section are reasonably available to the worker.

Maximum penalty—20 penalty units.

- (2) Each toilet must be adequate in all the circumstances, including the following—
- (a) the size and location of the workplace;
 - (b) the number of the employer's workers to whom a toilet must be made available under subsection (1).

Example—

the number of the workers may require more than 1 toilet to be made available

- (3) Each toilet must be in a cubicle, or room, that gives privacy.
- (4) If the worker is female, each toilet made available to her must—
- (a) have facilities to dispose of sanitary items for females; and
 - (b) be separated from urinals so that no urinal can be seen by her.

Examples—

- locating a toilet for females in a separate room from urinals
- putting a screen between urinals and a toilet for females

- (5) Each toilet may be a unisex toilet.
- (6) Each toilet must have an adequate supply of toilet paper.

Schedule 8C (continued)

8 Hands and face washing facilities

The employer must ensure the following facilities are reasonably available to the worker—

- (a) adequate clean water, and soap or another suitable cleansing agent, for washing the worker's hands and face;
- (b) facilities to dry the worker's hands.

Example—

hand towels, paper towels or a mechanical hands dryer

Maximum penalty—20 penalty units.

Subdivision 2 If the building is a particular class of building and not employer's domestic premises**9 Application of sdiv 2**

- (1) This subdivision applies if the building provided by the employer is not the employer's domestic premises and is—
 - (a) a class 3, 5, 6 or 9 building that is not part of a school; or
 - (b) a class 7 or 8 building; or
 - (c) a class 9b building that is part of a school.
- (2) In this section—

school see schedule 8E, part 3, section A1.1.¹⁵²

¹⁵² Schedule 8E (Applied BCA provisions), part 3 (Further provisions for complying with performance requirements—definitions, classification of buildings and adoption of standards), section A1.1 (Definitions)

Schedule 8C (continued)

10 Toilets, and hands and face washing facilities

- (1) The employer must ensure that toilets complying with this subdivision are reasonably available¹⁵³ to the worker.

Maximum penalty—20 penalty units.

- (2) The employer must ensure that hands and face washing facilities complying with this subdivision are reasonably available to the worker.

Maximum penalty—20 penalty units.

11 Performance requirements to be complied with

- (1) Schedule 8E, part 1, division 1¹⁵⁴ sets out the following applied BCA provisions—

- (a) FP2.1, which is a performance requirement for toilets and hands and face washing facilities;
- (b) FP2.5, which is a performance requirement for toilets.

- (2) Part 2¹⁵⁵ explains the purpose and interpretation of, and modification of the BCA for, applied BCA provisions used for this part.

- (3) Toilets must comply with the following performance requirements in the way stated in section 12—

- (a) FP2.1, in so far as it relates to toilets;
- (b) FP2.5.

- (4) Hands and face washing facilities must comply with performance requirement FP2.1, in so far as it relates to those facilities, in the way stated in section 12.

153 See schedule 9 (Dictionary), definition *reasonably available* and part 23 (Transitional provisions), division 4 (Certain amenities complying, or leased or acquired, immediately before 1 January 2005), section 239 (Toilets).

154 Schedule 8E (Applied BCA provisions), part 1 (Toilets, and hands and face washing facilities), division 1 (Performance requirements)

155 Part 2 (Explanation of applied BCA provisions or applied QDC provisions used for pt 3 or sch 8D)

Schedule 8C (continued)

12 How to comply with performance requirements

- (1) This section states the way to comply with the performance requirements.
- (2) The applied BCA provision that is section A0.5 (Meeting the Performance Requirements) in schedule 8E, part 1, division 2,¹⁵⁶ applies to the performance requirements.
- (3) Section A0.5 allows an employer to comply with the performance requirements in different ways.
- (4) However, an employer may use an alternative solution under section A0.5, to comply with part or all of the performance requirements, only if the chief executive has given the employer approval to use the alternative solution in the particular case.
- (5) The following applied BCA provisions, to the extent they are relevant to complying with the way chosen by the employer, must be applied to the performance requirements—
 - (a) the remaining provisions of schedule 8E, part 1, division 2;
 - (b) the provisions in schedule 8E, part 3.¹⁵⁷
- (6) However, each toilet, or hands and face washing facility need not be part of a building.

13 Location of toilet

If the toilet is not in the building provided by the employer, the toilet is, for schedule 9, definition *reasonably available*, paragraph (a), at a location reasonably convenient to the worker only if the toilet is—

156 Schedule 8E (Applied BCA provisions), part 1 (Toilets, and hands and face washing facilities), division 2 (Certain provisions for complying with performance requirements)

157 Schedule 8E (Applied BCA provisions), part 3 (Further provisions for complying with performance requirements—definitions, classification of buildings and adoption of standards)

Schedule 8C (continued)

- (a) within the boundary of the workplace containing the building provided by the employer; and

Example—

a toilet for a worker who is a school teacher must be within the school grounds

- (b) not more than 100m from the workplace if the building was built after 31 December 1991.

14 Toilet paper and disposal of female sanitary items

- (1) If the worker is female, each toilet made available to her must have facilities to dispose of sanitary items for females.
- (2) Each toilet must have an adequate supply of toilet paper.

15 Hands and face washing facilities to include soap, water and hands drying facilities

Hands and face washing facilities must include—

- (a) adequate clean water, and soap or another suitable cleansing agent, for washing the worker's hands; and
- (b) facilities to dry the worker's hands.

Example—

hand towels, paper towels or a mechanical hands dryer

Division 3 Dining facilities**16 Dining facilities**

- (1) The employer must ensure that dining facilities complying with this division are reasonably available to the worker, including for the purpose of taking breaks.¹⁵⁸

Maximum penalty—20 penalty units.

¹⁵⁸ See part 23 (Transitional provisions), division 4 (Certain amenities complying, or leased or acquired, immediately before 1 January 2005), section 237 (Lunch room).

Schedule 8C (continued)

- (2) However, a dining room or dining area made available for this division is taken not to be reasonably available to the worker while it is being used for a purpose that significantly interferes with the use of the dining room or dining area for dining or taking breaks in.

17 Performance criteria to be complied with

- (1) Schedule 8F, part 1, division 1¹⁵⁹ sets out the following applied QDC provisions—
 - (a) performance criteria for dining facilities;
 - (b) acceptable solutions for the performance criteria.
- (2) Part 2 explains the purpose and interpretation of, and modification of the QDC for, applied QDC provisions used for this part.
- (3) Dining facilities must comply with the performance criteria in the way stated in section 18.

18 How to comply with performance criteria mentioned in this part or sch 8D

- (1) This section states how to comply with performance criteria mentioned in this part or schedule 8D, section 4 or 5.¹⁶⁰
- (2) The applied QDC provision in schedule 8F, part 2,¹⁶¹ headed ‘Satisfying the performance *criteria*’ applies to the performance criteria.
- (3) That provision allows an employer to comply with the performance criteria in different ways.

159 Schedule 8F (Applied QDC provisions), part 1 (Performance criteria and acceptable solutions), division 1 (Dining facilities)

160 Schedule 8D (Employers—requirements for building provided for worker to occupy when performing work that is not construction work or rural industry work), section 4 (Lighting) or 5 (Floor area and air space)

161 Schedule 8F (Applied QDC provisions), part 2 (Other provisions for complying with performance criteria)

Schedule 8C (continued)

- (4) However, an employer may use an alternative solution under that provision, to comply with part or all of the performance criteria, only if the chief executive has given the employer approval to use the alternative solution in the particular case.
- (5) The following applied QDC provisions, to the extent they are relevant to complying with the way chosen by the employer, must be applied to the performance criteria—
 - (a) the acceptable solutions for the performance criteria;
 - (b) the section headed ‘Definitions’ in schedule 8F, part 2.
- (6) To remove any doubt, it is declared that—
 - (a) an amenity is required, under a performance criteria mentioned in this part, only in the circumstances mentioned in the performance criteria, whether or not the acceptable solutions for the performance criteria mention those circumstances; and
 - (b) a dining room or dining area required under this part must be part of building.
- (7) A dressing room required under this part need not be part of a building.

19 If worker is able to eat in work area

- (1) This section applies if the nature of work performed by the worker allows the worker to eat in the worker’s work area.
- (2) Sections 17 and 18 do not apply and dining facilities must consist of the following—
 - (a) a sink with a draining board and reticulated hot and cold water;
 - (b) cupboards for the storage of foodstuffs, free of dust and vermin;
 - (c) a chair or stool with back support;
 - (d) on or after 1 July 2005, a refrigerator of adequate capacity for the number of the employer’s workers to whom dining facilities must be available under this section.

Schedule 8C (continued)**Division 4 Dressing room facilities****20 Dressing room facilities**

The employer must ensure that dressing room facilities complying with this division are reasonably available to the worker.¹⁶²

Maximum penalty—20 penalty units.

21 Performance criteria to be complied with

- (1) Schedule 8F, part 1, division 2¹⁶³ sets out the following applied QDC provisions—
 - (a) performance criteria for dressing room facilities;
 - (b) acceptable solutions for the performance criteria.
- (2) Part 2 explains the purpose and interpretation of, and modification of the QDC for, applied QDC provisions used for this part.
- (3) Dressing room facilities must comply with the performance criteria in the way stated in section 18.

Division 5 Drinking water**22 Drinking water**

- (1) The employer must ensure that an adequate supply of potable, clean and cool drinking water is reasonably available to the worker.

162 See part 23 (Transitional provisions), division 4 (Certain amenities complying, or leased or acquired, immediately before 1 January 2005), section 238 (Dressing room).

163 Schedule 8F (Applied QDC provisions), part 1 (Performance criteria and acceptable solutions), division 2 (Dressing room facilities)

Schedule 8C (continued)

Example—

complying, in the way stated in section 18, with the performance criteria for drinking water set out in schedule 8F, part 1, division 3¹⁶⁴

Maximum penalty—20 penalty units.

- (2) The supply of water must not be located in toilets.

Example of toilets—

a toilet block or a cubicle used as a toilet

- (3) If the water is made available in a container, the worker must be able to drink the water without having to drink directly from the same container as someone else.
- (4) This section does not prevent the supply of water also being made available under section 24 for hands and face washing.

23 Performance criteria that may be complied with

- (1) Schedule 8F, part 1, division 3 sets out the following applied QDC provisions—
- (a) performance criteria for drinking water;
 - (b) acceptable solutions for the performance criteria.
- (2) Part 2 explains the purpose and interpretation of, and modification of the QDC for, applied QDC provisions used for this part.

Division 6 Other amenities**24 Hands and face washing facilities**

The employer must ensure the following facilities are reasonably available to the worker—

¹⁶⁴ Schedule 8F (Applied QDC provisions), part 1 (Performance criteria and acceptable solutions), division 3 (Drinking water)

Schedule 8C (continued)

- (a) adequate clean water, and soap or another suitable cleansing agent, for washing the worker's hands and face;
- (b) facilities to dry the worker's hands.

Example—

hand towels, paper towels or a mechanical hands dryer

Maximum penalty—20 penalty units.

25 Showers

- (1) This section applies if the worker is performing work likely to expose the worker to a health or safety risk if the worker can not shower at, or before, the end of the worker's shift.
- (2) The employer must ensure a shower is reasonably available to the worker to prevent the risk.

Maximum penalty—20 penalty units.

- (3) The shower may be a unisex shower only if—
 - (a) it is available to not more than 10 of the employer's workers to whom a shower must be available under subsection (2); and
 - (b) it is lockable from inside the shower; and
 - (c) it gives privacy. }

**Part 4 If worker is not at workplace
where employer provides
non-class 10 building for
workers to occupy****26 Application of pt 4**

- (1) This part applies if the worker is not at a workplace where the employer provides a building for the worker or any other

Schedule 8C (continued)

worker of the employer to occupy when performing work that is not construction work or work in a rural industry.

Note—

See the examples in section 6(c), which are also relevant to section 26(1).

(2) In this section—

building does not include a class 10 building.¹⁶⁵

27 Toilets

(1) The employer must ensure that, to the greatest practicable extent, toilets complying with this section are reasonably available to the worker.

Maximum penalty—20 penalty units.

(2) Toilets located within a reasonable distance of the worker, using appropriate transport, are, for schedule 9, definition *reasonably available*, paragraph (a), at a location reasonably convenient to the worker.

(3) There must be at least 1 toilet for each 15, or part of 15, of the employer's workers to whom a toilet must be available under subsection (1).

Examples—

- for 1 to 15 workers, there must be at least 1 toilet
- for 20 workers, there must be at least 1 toilet for the first 15 workers plus at least 1 toilet for the other 5, making a total of at least 2 toilets

(4) If the worker is female, each toilet made available to her must have facilities to dispose of sanitary items for females.

(5) Each toilet may be a unisex toilet.

(6) Each toilet must have an adequate supply of toilet paper.

¹⁶⁵ *Building* and *class* are defined in schedule 9 (Dictionary).

Schedule 8C (continued)

28 Sheltered area to eat meals in

- (1) The employer must ensure that a sheltered area to eat meals and take breaks in is reasonably available to the worker.

Examples—

- a caravan
- a tent attached to a vehicle

Maximum penalty—20 penalty units.

- (2) A sheltered area located within a reasonable distance of the worker, using appropriate transport, is, for schedule 9, definition *reasonably available*, paragraph (a), at a location reasonably convenient to the worker.
- (3) The sheltered area must be hygienic and separated from work activity that exposes or is likely to expose the worker to a health or safety risk.

29 Drinking water

- (1) The employer must ensure that an adequate supply of potable, clean and cool drinking water is reasonably available to the worker.

Maximum penalty—20 penalty units.

- (2) The supply of water must not be located in toilets.

Example of toilets—

a toilet block or a cubicle used as a toilet

- (3) If the water is made available in a container, the worker must be able to drink the water without having to drink directly from the same container as someone else.
- (4) This section does not prevent the supply of water also being made available under section 30 for hands washing.

30 Hands washing facilities

The employer must ensure the following facilities are reasonably available to the worker—

Schedule 8C (continued)

- (a) adequate clean water, and soap or another suitable cleansing agent, for washing the worker's hands;
- (b) facilities to dry the worker's hands.

Example—

hand towels, paper towels or a mechanical hands dryer

Maximum penalty—20 penalty units.

31 Showers

- (1) This section applies if the worker is performing work likely to expose the worker to a health or safety risk if the worker can not shower at, or before, the end of the worker's shift.
- (2) The employer must ensure a shower is reasonably available to the worker to prevent the risk.

Maximum penalty—20 penalty units.

- (3) The shower may be a unisex shower only if—
 - (a) it is available to not more than 10 of the employer's workers to whom a shower must be available under subsection (2); and
 - (b) it is lockable from inside the shower; and
 - (c) it gives privacy.

Schedule 8D Employers—requirements for building provided for worker to occupy when performing work that is not construction work or rural industry work

section 221

Part 1 Application of sch 8D

1 Application of sch 8D

This schedule applies if—

- (a) a worker is at a workplace and performing work that is not construction work or work in a rural industry; and
- (b) the worker's employer provides a building¹⁶⁶ at the workplace for the worker to occupy when performing work that is not construction work or work in a rural industry.

Note—

See the examples in schedule 8C, section 6(c), which are also relevant to section 1.

Part 2 Ventilation

2 Ventilation

- (1) Schedule 8E, part 2, division 1¹⁶⁷ sets out the applied BCA provisions that are performance requirements for ventilation.

¹⁶⁶ *Building* is defined in schedule 9 (Dictionary).

¹⁶⁷ Schedule 8E (Applied BCA provisions), part 2 (Ventilation), division 1 (Performance requirements)

Schedule 8D (continued)

- (2) Schedule 8C, part 2¹⁶⁸ explains the purpose and interpretation of, and modification of the BCA for, applied BCA provisions used for this schedule.
- (3) The employer must ensure that the building—
 - (a) complies with the performance requirements in the way stated in section 3; or
 - (b) is ventilated in a way that provides ventilation at least equivalent to the ventilation required under paragraph (a).

Maximum penalty—20 penalty units.

3 How to comply with performance requirements

- (1) This section states how to comply with the performance requirements.
- (2) The applied BCA provision that is section A0.5 (Meeting the Performance Requirements) in schedule 8E, part 1, division 2,¹⁶⁹ applies to the performance requirements.
- (3) Section A0.5 allows an employer to comply with the performance requirement in different ways.
- (4) However, an employer may use an alternative solution under section A0.5, to comply with part or all of the performance requirements, only if the chief executive has given the employer approval to use the alternative solution in the particular case.
- (5) The following applied BCA provisions, to the extent they are relevant to complying with the way chosen by the employer, must be applied to the performance requirement—

168 Schedule 8C (Employers—particular amenities for work that is not construction work or rural industry work), part 2 (Explanation of applied BCA provisions or applied QDC provisions used for pt 3 or sch 8D)

169 Schedule 8E (Applied BCA provisions), part 1 (Toilets, and hands and face washing facilities), division 2 (Certain provisions for complying with performance requirements)

Schedule 8D (continued)

- (a) the remaining provisions of schedule 8E, part 1, division 2;
- (b) the provisions in schedule 8E, part 3.¹⁷⁰

Part 3 Lighting

4 Lighting

- (1) Schedule 8F, part 1, division 4¹⁷¹ sets out the following applied QDC provisions—
 - (a) performance criteria for lighting;
 - (b) acceptable solutions for the performance criteria.
- (2) Schedule 8C, part 2 explains the purpose and interpretation of, and modification of the QDC for, applied QDC provisions used for this schedule.
- (3) The employer must ensure that—
 - (a) the building complies with the performance requirement in the way stated in schedule 8C, section 18;¹⁷² or
 - (b) the building is lit by lighting at least equivalent to the lighting required under paragraph (a).

Maximum penalty—20 penalty units.

170 Schedule 8E (Applied BCA provisions), part 3 (Further provisions for complying with performance requirements—definitions, classification of buildings and adoption of standards)

171 Schedule 8F (Applied QDC provisions), part 1 (Performance criteria and acceptable solutions), division 4 (Lighting)

172 Schedule 8C (Employers—particular amenities for work that is not construction work or rural industry work), section 18 (How to comply with performance criteria mentioned in this part or sch 8D)

Schedule 8D (continued)

Part 4 Floor area and air space**5 Floor area and air space**

- (1) Schedule 8F, part 1, division 5¹⁷³ sets out the following applied QDC provisions—
 - (a) performance criteria for floor area and air space;
 - (b) acceptable solutions for the performance criteria.
- (2) Schedule 8C, part 2 explains the purpose and interpretation of, and modification of the QDC for, applied QDC provisions used for this schedule.
- (3) The employer must ensure that the building complies with the performance criteria in the way stated in schedule 8C, section 18.

Maximum penalty—20 penalty units.

¹⁷³ Schedule 8F (Applied QDC provisions), part 1 (Performance criteria and acceptable solutions), division 5 (Floor area and air space)

Schedule 8E Applied BCA provisions

schedule 8C, section 3(4)(b)

Part 1 Toilets, and hands and face washing facilities

Division 1 Performance requirements

FP2.1

(1) Suitable sanitary facilities for personal hygiene, *consisting of toilets, and hands and face washing facilities, that are appropriate to the following*, must be made reasonably available—

(a) *for hands and face washing facilities—the nature of the work the worker is performing;*

Examples—

- *for an office worker—a washbasin*
- *for a worker performing greasy work in a workshop—a tub*

(b) the number and gender of the *workers*;

(c) *(omitted)*

(2) *In this section—*

hands and face washing facilities means an appropriate facility for supplying water for washing the hands and face.

FP2.5

A sanitary compartment must be constructed with sufficient space or other means to permit an unconscious *worker* to be removed from the compartment.

Schedule 8E (continued)

**Division 2 Certain provisions for complying
with performance requirements***Note—*

See also part 3 (Further provisions for complying with performance requirements—definitions, classification of buildings and adoption of standards).

A0.5 Meeting the Performance Requirements

Compliance with the Performance Requirements can only be achieved by—

- (a) complying with the Deemed-to-Satisfy Provisions; or
- (b) formulating an Alternative Solution which—
 - (i) complies with the Performance Requirements; or
 - (ii) is shown to be at least equivalent to the Deemed-to-Satisfy Provisions; or
- (c) a combination of (a) and (b).

F2.0 Deemed-to-Satisfy Provisions

- (a) Where a Building Solution is proposed to comply with the Deemed-to-Satisfy Provisions, Performance Requirements FP2.1 and FP2.5 are satisfied by complying with F2.3, including table F2.3, and F2.5.
- (b) *(omitted)*

F2.3 Facilities in Class 3 or 5 to 9 buildings

- (a) Sanitary facilities must be provided for Class 3, 5, 6, 7, 8 and 9 buildings in accordance with Table F2.3.
- (b) *(omitted)*

Table F2.3 SANITARY FACILITIES IN CLASS 3, 5, 6, 7, 8 AND 9 BUILDINGS

Class of building	User	Maximum Number Served By—								
		Closet pan(s)			Urinals			Washbasin(s)		
		1	2	Each Extra	1	2	Each Extra	1	2	Each Extra
3, 5, 6 or 9 that is not part of a school	Workers									
	Males	20	40	20	25	50	50	30	60	30
	Females	15	30	15				30	60	30
7 or 8	Workers									
	Males	20	40	20	25	50	50	20	40	20
	Females	15	30	15				20	40	20
(omitted)										
9b that is part of a school	Workers									
	Males	20	40	20	20	45	30	30	60	30
	Females	5	20	15				30	60	30
(omitted)										

Notes—

- Workers—a reference *in this table, including in these notes*, to *workers* includes a reference to the employer if the employer is at the workplace.
- Urinals—a urinal need not be provided if the number of *male workers* is less than 10.
- Unisex facility—instead of separate facilities for each sex, if not more than 10 persons are *workers*, a unisex facility *comprising 1 closet pan in a cubicle, or room, fitted with a door that gives privacy and is lockable from inside the cubicle or room, and 1 washbasin* may be provided.

Schedule 8E (continued)

4. Combined facilities—if the majority of <i>workers</i> are of one sex, not more than 2 <i>workers</i> of the other sex may share toilet facilities if—
(a) <i>(omitted)</i>
(b) the facilities are separated by means of walls, partitions and doors, <i>lockable from inside the facility</i> , to afford privacy.
5. Use of public facilities—sanitary facilities for <i>workers</i> need not be separate from those required for public use in a Class 6 or 9b building <i>that is not part of a school or early childhood centre</i> .
6. <i>(omitted)</i>
7. <i>(omitted)</i>

F2.5 Construction of sanitary compartments

- (a) Other than in an early childhood centre, sanitary compartments must have doors and partitions that separate adjacent compartments and extend—
 - (i) from floor level to the ceiling in the case of a unisex facility *mentioned in table F2.3, note 3*; or
 - (ii) *(omitted)*
 - (iii) 1.8m above the floor in all other cases.
- (b) The door to a fully enclosed sanitary compartment must—
 - (i) open outwards; or
 - (ii) slide; or
 - (iii) be readily removable from the outside of the sanitary compartment;

unless there is a clear space of at least 1.2m between the closet pan within the sanitary compartment and the nearest part of the doorway.

(omitted)

Schedule 8E (continued)

F2.6 Interpretation—Urinals and washbasins

- (a) A urinal may be—
 - (i) an individual stall or wall-hung urinal; or
 - (ii) a 600mm length of a continuous urinal trough; or
 - (iii) a closet pan used in place of a urinal.
- (b) A washbasin may be—
 - (i) an individual basin; or
 - (ii) a part of a hand washing trough served by a single water tap.

Part 2 Ventilation**Division 1 Performance requirements****FP4.3**

A space in *the* building, used by *the worker*, must be provided with means of ventilation with outdoor air which will maintain adequate air quality.

FP4.4

If a mechanical air-handling system *is* installed in *the* building, *the system* must control—

- (a) the circulation of objectionable odours; and
- (b) the accumulation of harmful contamination by micro-organisms, pathogens and toxins.

Schedule 8E (continued)**FP4.5**

Contaminated air must be disposed of in a manner which does not unduly create a nuisance or hazard to people in the building or other property.

Division 2 Certain provisions for complying with performance requirements

Note—

See also part 3 (Further provisions for complying with performance requirements—definitions, classification of buildings and adoption of standards).

A0.5 Meeting the Performance Requirements

Compliance with the Performance Requirements can only be achieved by—

- (a) complying with the Deemed-to-Satisfy Provisions; or
- (b) formulating an Alternative Solution which—
 - (i) complies with the Performance Requirements; or
 - (ii) is shown to be at least equivalent to the Deemed-to-Satisfy Provisions; or
- (c) a combination of (a) and (b).

F4.0 Deemed-to-Satisfy Provisions

- (a) Where a Building Solution is proposed to comply with the Deemed-to-Satisfy Provisions, Performance Requirements FP4.3 to FP4.5 are satisfied by complying with F4.5 to F4.9.
- (b) *(omitted)*

Schedule 8E (continued)**F4.5 Ventilation of rooms**

A habitable room, office, shop, factory, workroom, sanitary compartment, bathroom, shower room, laundry and any other room occupied by *the worker* must have—

- (a) natural ventilation complying with F4.6; or
- (b) a mechanical ventilation or air-conditioning system complying with AS 1668.2 and AS/NZS 3666.1.

(omitted)

F4.6 Natural ventilation

Natural ventilation provided in accordance with F4.5(a) must consist of permanent openings, windows, doors or other devices which can be opened—

- (a) with an aggregate opening or openable size not less than 5% of the floor area of the room required to be ventilated; and
- (b) open to—
 - (i) suitably sized court, or space open to the sky; or
 - (ii) an open verandah, carport, or the like; or
 - (iii) an adjoining room in accordance with F4.7.

F4.7 Ventilation borrowed from adjoining room

Natural ventilation to a room may come through a window, opening, ventilating door or other device from an adjoining room (including an enclosed verandah) if both rooms are within the same sole-occupancy unit or the enclosed verandah is common property, and—

- (a) in a Class 2 building, a sole-occupancy unit of a Class 3 building or Class 4 part of a building—
 - (i) the room to be ventilated is not a sanitary compartment; and

Schedule 8E (continued)

- (ii) the window, opening, door or other device has a ventilating area of not less than 5% of the floor area of the room to be ventilated; and
 - (iii) the adjoining room has a window, opening, door or other device with a ventilating area of not less than 5% of the combined floor areas of both rooms; and
- (b) in a Class 5, 6, 7, 8 or 9 building—
 - (i) the window, opening, door or other device has a ventilating area of not less than 10% of the floor area of the room to be ventilated, measured not more than 3.6 m above the floor; and
 - (ii) the adjoining room has a window, opening, door or other device with a ventilating area of not less than 10% of the combined floor areas of both rooms; and
- (c) the ventilating areas specified in (a) and (b) may be reduced as appropriate if direct natural ventilation is provided from another source.

F4.8 Restriction on position of water closets and urinals

A room containing a closet pan or urinal must not open directly into—

- (a) a kitchen or pantry; or
- (b) a public dining room or restaurant; or
- (c) a dormitory in a Class 3 building; or
- (d) a room used for public assembly (which is not an early childhood centre, primary school or open spectator stand); or
- (e) a workplace normally occupied by more than one person.

Schedule 8E (continued)

F4.9 Airlocks

If a room containing a closet pan or urinal is prohibited under F4.8 from opening directly to another room—

- (a) in a sole-occupancy unit in a Class 2 or 3 building or Class 4 part *of a building*—
 - (i) access must be by an airlock, hallway or other room; or
 - (ii) the room containing the closet pan or urinal must be provided with mechanical exhaust ventilation; and
- (b) in a Class 5, 6, 7, 8 or 9 building (which is not an early childhood centre, primary school or open spectator stand)—
 - (i) access must be by an airlock, hallway or other room with a floor area of not less than 1.1m² and fitted with self-closing doors at all access doorways; or
 - (ii) the room containing the closet pan or urinal must be provided with mechanical exhaust ventilation and the doorway to the room adequately screened from view.

Schedule 8E (continued)

Part 3**Further provisions for
complying with performance
requirements—definitions,
classification of buildings and
adoption of standards****A1.1 Definitions**

In an applied BCA provision, unless the contrary intention appears—

(omitted)

Aged care building means a Class 9c building for residential accommodation of aged persons who, due to varying degrees of incapacity associated with the ageing process, are provided with personal care services and 24 hour staff assistance to evacuate the building during an emergency.

(omitted)

Allotment see the *Standard Building Regulation 1993*, section 5.¹⁷⁴

(omitted)

Alternative Solution means a Building Solution which complies with the Performance Requirements other than by reason of satisfying the Deemed-to-Satisfy Provisions.

Assembly building means a building where people may assemble for—

- (a) civic, theatrical, social, political or religious purposes; or
- (b) educational purposes in a school, early childhood centre, preschool, or the like; or
- (c) entertainment, recreational or sporting purposes; or

¹⁷⁴ This regulation has been repealed, see 2006 SL No. 227 s 59.

Schedule 8E (continued)

(d) transit purposes.

(omitted)

Atrium means a space within a building that connects 2 or more storeys, and—

- (a) is wholly or substantially enclosed at the top by a floor or roof (including a glazed roof structure); and
- (b) includes any adjacent part of the building not separated by an appropriate barrier to fire; but
- (c) does not include a stairwell, rampwell or the space within a shaft.

Atrium well means a space in an atrium bounded by the perimeter of the openings in the floors or by the perimeter of the floors and the external walls.

(omitted)

Building Solution means a solution which complies with the Performance Requirements and is—

- (a) an Alternative Solution; or
- (b) a solution which complies with the Deemed-to-Satisfy Provisions; or
- (c) a combination of (a) and (b).

Carpark means a building that is used for the parking of motor vehicles but is neither a private garage nor used for the servicing of vehicles, other than washing, cleaning or polishing.

(omitted)

Common wall means a wall that is common to adjoining buildings.

(omitted)

Deemed-to-Satisfy Provisions means provisions which are deemed to satisfy the Performance Requirements.

(omitted)

Schedule 8E (continued)

Detention centre means a building in which persons are securely detained by means of the built structure including a prison, remand centre, juvenile detention centre, holding cells or psychiatric detention centre.

Early childhood centre means a kindergarten or child-minding centre.

(omitted)

Equivalent means equivalent to the level of health *and* safety *(words omitted)* provided by the Deemed-to-Satisfy Provisions.

(omitted)

External wall means an outer wall of a building which is not a common wall.

(omitted)

Floor area means—

(omitted)

- (c) in relation to a room—the area of the room measured within the finished surfaces of the walls, and includes the area occupied by any cupboard or other built-in furniture, fixture or fitting; and

(omitted)

Habitable room means a room used for normal domestic activities, and—

- (a) includes a bedroom, living room, lounge room, music room, television room, kitchen, dining room, sewing room, study, playroom, family room and sunroom; but
- (b) excludes a bathroom, laundry, water closet, pantry, walk-in wardrobe, corridor, hallway, lobby, photographic darkroom, clothes-drying room, and other spaces of a specialised nature occupied neither frequently nor for extended periods.

Health-care building means a building whose occupants or patients undergoing medical treatment generally need

Schedule 8E (continued)

physical assistance to evacuate the building during an emergency and includes—

- (a) a public or private hospital; *and*
- (b) a nursing home or similar facility for sick or disabled persons needing full-time care; *and*
- (c) a clinic, day surgery or procedure unit where the effects of the predominant treatment administered involve patients becoming non-ambulatory and requiring supervised medical care on the premises for some time after the treatment.

(omitted)

Mezzanine means an intermediate floor within a room.

(omitted)

Other property means all or any of the following—

- (a) any building on the same or an adjoining allotment; and
- (b) any adjoining allotment; and
- (c) a road.

Outdoor air means air outside the building.

(omitted)

Owner *see the Building Act 1975, schedule 2.*

(omitted)

Performance Requirement means a requirement which states the level of performance which a Building Solution must meet.

Personal care services means any of the following—

- (a) The provision of nursing care.
- (b) Assistance or supervision in—
 - (i) bathing, showering or personal hygiene; or
 - (ii) toileting or continence management; or

Schedule 8E (continued)

- (iii) dressing or undressing; or
- (iv) consuming food.
- (c) The provision of direct physical assistance to a person with mobility problems.
- (d) The management of medication.
- (e) The provision of substantial rehabilitation or development assistance.

(omitted)

Private garage means—

- (a) any garage associated with a Class 1 building; or
- (b) any single storey of a building of another Class capable of accommodating not more than 3 vehicles, if there is only one such storey in the building; or
- (c) any separate single storey garage associated with another building where such garage is capable of accommodating not more than 3 vehicles.

(omitted)

Required means required to satisfy a performance requirement or a Deemed-to-Satisfy Provision of the BCA as appropriate.

(omitted)

Road *see the Building Regulation 2006, schedule 4.*

(omitted)

Sanitary compartment means a room or space containing a closet pan or urinal.

(omitted)

School includes a primary or secondary school, college, university or similar educational establishment.

Self-closing, applied to a door, means equipped with a device which returns the door to the fully closed position immediately after each opening.

Schedule 8E (continued)

Service station means a garage which is not a private garage and is for the servicing of vehicles, other than only washing, cleaning or polishing.

Shaft means the walls and other parts of a building bounding—

- (a) a well, other than an atrium well; or
- (b) a vertical chute, duct or similar passage, but not a chimney or flue.

(omitted)

Sole-occupancy unit means a room or other part of a building for occupation by one or joint owner, lessee, tenant, or other occupier to the exclusion of any other owner, lessee, tenant, or other occupier and includes—

- (a) a dwelling; *and*
- (b) a room or suite of rooms in a Class 3 building which includes sleeping facilities; *and*
- (c) a room or suite of associated rooms in a Class 5, 6, 7, 8 or 9 building; *and*
- (d) a room or suite of associated rooms in a Class 9c aged care building, which includes sleeping facilities and any area for the exclusive use of a resident.

(omitted)

Storey means a space within a building which is situated between one floor level and the floor level next above, or if there is no floor above, the ceiling or roof above, but not—

- (a) a space that contains only—
 - (i) a lift shaft, stairway or meter room; or
 - (ii) a bathroom, shower room, laundry, water closet, or other sanitary compartment; or
 - (iii) accommodation intended for not more than 3 vehicles; or
 - (iv) a combination of the above; or

Schedule 8E (continued)

(b) a mezzanine.

(omitted)

Swimming pool means any excavation or structure containing water and used primarily for swimming, wading, paddling, or the like, including a bathing or wading pool, or spa.

(omitted)

Window includes a roof light, glass panel, glass block or brick, glass louvre, glazed sash, glazed door, or other device which transmits natural light directly from outside a building to the room concerned when in the closed position.

A1.2 Adoption of standards and other reference

Where a Deemed-to-Satisfy Provision adopts a Standard, rule, specification or provision included in any document issued by Standards Australia or other body, that adoption does not include a provision—

- (a) specifying or defining the respective rights, responsibilities or obligations as between themselves or any manufacturer, supplier or purchaser; or
- (b) specifying the responsibilities of any trades person or other building operative, architect, engineer, authority, or other person or body; or
- (c) requiring the submission for approval of any material, building component, form or method of construction, to any person, authority or body other than a person or body empowered under State or Territory legislation to give that approval; or
- (d) specifying that a material, building component, form or method of construction must be submitted to Standards Australia or a committee of Standards Australia for expression of opinion; or
- (e) permitting a departure from the code, rule, specification or provision at the sole discretion of the manufacturer or purchaser, or by arrangement or agreement between the manufacturer and purchaser.

Schedule 8E (continued)

A1.3 Referenced Standards, etc

- (a) A reference in a Deemed-to-Satisfy Provision to a document under A1.2 refers to the edition or issue, together with any amendment, listed in Specification A1.3 and only so much as is relevant in the context in which the document is quoted.
- (b) Any—
 - (i) reference in a document listed in Specification A1.3 (primary document) to another document (secondary document); and
 - (ii) subsequent references to other documents in secondary documents and those other documents;is a reference to the secondary and other documents as they existed at the time of publication of the primary document listed in Specification A1.3.

A1.4 Differences between referenced documents and *applied BCA provisions*

An *applied BCA provision* overrules in any difference arising between it and any Standard, rule, specification or provision in a document listed in Specification A1.3.

Schedule 8E (continued)

SPECIFICATION**DOCUMENTS ADOPTED BY****A1.3****REFERENCE**

1.

Schedule of referenced documents*(omitted)***Table 1: SCHEDULE OF REFERENCED DOCUMENTS**

	No.	Date	Title	BCA Clause(s)
<i>(omitted)</i>				
	AS 1668		The use of mechanical ventilation and airconditioning in buildings	
	Part 2	1991	Mechanical ventilation for acceptable indoor-air quality	F4.5 <i>(omitted)</i>
	<i>(omitted)</i>			
	AS/NZS 3666		Air-handling and water systems of buildings—Microbial control	
Amdt No. 11	Part 1	2002	Design, installation and commissioning	<i>(omitted)</i> F4.5
<i>(omitted)</i>				

Schedule 8E (continued)

A3.2 Classifications

Buildings are classified as follows—

Class 1—one or more buildings which in association constitute—

- (a) **Class 1a**—a single dwelling being—
 - (i) a detached house; or
 - (ii) one or more attached dwellings, each being a building, separated by a *wall that is fire resistant*, including a row house, terrace house, town house or villa unit; or
- (b) **Class 1b**—a boarding house, guest house, hostel or the like with a total floor area not exceeding 300 m² and in which not more than 12 persons would ordinarily be resident;

which is not located above or below another dwelling or another Class of building other than a private garage.

Class 2—a building containing 2 or more sole-occupancy units each being a separate dwelling.

Class 3—a residential building, other than a building of Class 1 or 2, which is a common place of long term or transient living for a number of unrelated persons, including—

- (a) a boarding-house, guest house, hostel, lodging-house or backpackers accommodation; or
- (b) a residential part of a hotel or motel; or
- (c) a residential part of a school; or
- (d) accommodation for the aged, children or people with disabilities; or
- (e) a residential part of a health-care building which accommodates members of staff; or
- (f) a residential part of a detention centre.

Class 4—a dwelling in a building that is Class 5, 6, 7, 8 or 9 if it is the only dwelling in the building.

Schedule 8E (continued)

Class 5—an office building used for professional or commercial purposes, excluding buildings of Class 6, 7, 8 or 9.

Class 6—a shop or other building for the sale of goods by retail or the supply of services direct to the public, including—

- (a) an eating room, cafe, restaurant, milk or soft-drink bar; or
- (b) a dining room, bar, shop or kiosk part of a hotel or motel; or
- (c) a hairdresser's or barber's shop, public laundry, or undertaker's establishment; or
- (d) market or sale room, showroom, or service station.

Class 7—a building which is—

- (a) **Class 7a**—a carpark; or
- (b) **Class 7b**—for storage, or display of goods or produce for sale by wholesale.

Class 8—a laboratory, or a building in which a handicraft or process for the production, assembling, altering, repairing, packing, finishing, or cleaning of goods or produce is carried on for trade, sale, or gain.

Class 9

(words omitted) **Class 9**—

a building of a public nature—

- (a) **Class 9a**—a health-care building, including those parts of the building set aside as a laboratory; or
- (b) **Class 9b**—an assembly building, including a trade workshop, laboratory or the like in a primary or secondary school, but excluding any other parts of the building that are of another Class; or
- (c) **Class 9c**—an aged care building.

Class 10—a non-habitable building or structure—

Schedule 8E (continued)

- (a) **Class 10a**—a non-habitable building being a private garage, carport, shed, or the like; or
- (b) **Class 10b**—a structure being a fence, mast, antenna, retaining or free-standing wall, swimming pool, or the like.

A3.3 Multiple classification

Each part of a building must be classified separately, and—


- (a)
 - (i) where parts have different purposes—if not more than 10% of the floor area of a storey, being the minor use, is used for a purpose which is a different classification, the classification applying to the major use may apply to the whole storey; and
 - (ii) the provisions of (i) do not apply when the minor use is a laboratory or Class 2, 3 or 4 part *of a building*; and
- (b) Classes 1a, 1b, 7a, 7b, 9a, 9b, 9c, 10a and 10b are separate classifications; and
- (c) a reference to—
 - (i) Class 1—is to Class 1a and 1b; and
 - (ii) Class 7—is to Class 7a and 7b; and
 - (iii) Class 9—is to Class 9a, 9b and 9c; and
 - (iv) Class 10—is to Class 10a and 10b; and
- (d) A plant room, machinery room, lift motor room, boiler room or the like must have the same classification as the part of the building in which it is situated.

A3.4 Parts with more than one classification

- (a) Notwithstanding A3.3, a building or part of a building may have more than one classification applying to the whole building or to the whole of that part of the building.

Schedule 8E (continued)

- (b) If a building or part of a building has more than one classification applying to the whole building or part in accordance with (a), that building or part must comply with all the relevant provisions of the *applied BCA provisions* for each classification.

Logo of the Australian Building Codes Board

Schedule 8F Applied QDC provisions

schedule 8C, section 3(4)(b)

Part 1 Performance criteria and acceptable solutions

Division 1 Dining facilities

PERFORMANCE CRITERIA	ACCEPTABLE SOLUTIONS
Dining Facilities	
<p>P6 Where the nature of work performed does not allow <i>the worker</i> to eat in <i>the worker's</i> work area, suitable dining facilities must be <i>made reasonably available</i> in safe and hygienic conditions.</p>	<p>A6 (a) A dining room is <i>made reasonably available</i>, except where there are five or less <i>workers</i>, a dining area may be <i>made reasonably available</i>; or</p> <p>(b) for shops situated in a shopping complex—</p> <p>(i) one dining room is used to satisfy the requirements of all the shops in the complex; and</p> <p>(ii) the dining room area is based on the total <i>persons</i>, to whom a dining room must be available under performance requirement <i>P6</i>, of all the shops in the complex.</p>

Schedule 8F (continued)

PERFORMANCE CRITERIA	ACCEPTABLE SOLUTIONS
<p>P7 A dining room <i>or dining area</i> must provide adequate facilities for eating, washing and cleaning of utensils, storage of food and utensils. Stored food and utensils must be kept free from contamination by dust and vermin.</p>	<p>A7 A dining room <i>or dining area</i> has the following facilities—</p> <ul style="list-style-type: none"> (a) a sink with a draining board and reticulated hot and cold water; and (b) cupboards for the storage of foodstuffs, free of dust and vermin; and (c) tables providing 600mm table length per <i>worker and a chair or stool with back support</i>; and (d) <i>on or after 1 July 2005</i>, a refrigerator of adequate capacity for the number of <i>workers</i>.
<p>P8 Dining rooms must be of an adequate area to provide a safe and comfortable environment, appropriate to the number of <i>workers</i> using it at any one time.</p>	<p>A8 (a) The minimum floor area of a dining room is—</p> <ul style="list-style-type: none"> (i) for 6-12 <i>workers</i>—11m²; and (ii) for additional <i>workers</i> up to 25—an additional 0.92m² for each <i>worker</i>; and (iii) for additional <i>workers</i> thereafter—an additional 0.75m² for each <i>worker</i>.

Schedule 8F (continued)

Division 2

Dressing room facilities

PERFORMANCE
CRITERIA

ACCEPTABLE SOLUTIONS

Dressing Room Facilities

- P9** *(words omitted) Where the nature of work requires the worker to change in and out of apparel, dressing rooms of adequate area, containing sufficient facilities and that provide adequate privacy must be made reasonably available.*
- A9** (a) The minimum unencumbered floor area of a dressing room is 1.8m² per worker; and
- (b) an additional unencumbered area is provided in the dressing room, dependant on the occupation of each worker as follows—
- (i) For sedentary or semi-sedentary occupations—0.37m² per worker;
- (ii) For light to medium and clean occupations—0.46m² per worker;
- (iii) For heavy, hot or dirty occupations—0.65m² per worker; and
- (c) *on or after 1 July 2005, the dressing room is provided with lockers that are not less than 300mm wide and 450mm deep and 900mm in height; and*
- (d) passage widths between facing lockers are—
- (i) at least 1500mm; or
- (ii) with lockers on one side only—at least 900mm; and
- (e) a dressing room is provided for each sex; and
- (f) dressing rooms are set apart from workrooms (*words omitted*); and
- (g) (*omitted*)

Schedule 8F (continued)

**PERFORMANCE
CRITERIA****ACCEPTABLE SOLUTIONS**

- (h) for fifteen or less *workers*, all of the same sex, a dining room may be combined with a dressing room; and
- (i) where a dressing room is combined with a dining room—
 - (i) the area complies with A7, A8 and A9; and
 - (ii) the dining room is provided with—
 - (A) *on or after 1 July 2005*, a locker for each *worker*; and
 - (B) *on or after 1 July 2005*, protective hanging space for clothing; and
 - (C) *omitted*
 - (D) *on or after 1 July 2005*, mirrors and shelving; and
 - (E) *(omitted)*

Division 3**Drinking water****PERFORMANCE
CRITERIA****ACCEPTABLE SOLUTIONS****Drinking water**

- P10** An adequate supply of clean, *cool and* potable drinking water must be *made reasonably available*.
- A10** (a) Drinking water is *made reasonably available* in *all of the worker's work situations (words omitted)*; and

Schedule 8F (continued)

**PERFORMANCE
CRITERIA****ACCEPTABLE SOLUTIONS***(omitted)*

(d) where there are more than 10 workers, drinking fountains are provided in the following numbers—

- (i) 11 to 40 workers—1 drinking fountain; and
- (ii) for each additional 40 workers (or part thereof)—1 additional drinking fountain.

Division 4 Lighting**PERFORMANCE
CRITERIA****ACCEPTABLE SOLUTIONS****Lighting**

- P4** Adequate lighting from natural and/or artificial sources must be provided to ensure healthy *(words omitted)* working conditions for *the worker*, appropriate to—
- (a) the nature of the work; and
 - (b) the location of the work; and
 - (c) the times at which the work is performed.
- A4** Lighting complies with AS 1680.^a

^a AS 1680 (Interior lighting)

Schedule 8F (continued)

Division 5 Floor area and air space**PERFORMANCE
CRITERIA****ACCEPTABLE SOLUTIONS****Work Areas**

- | | | | |
|-----------|---|-----------|---|
| P5 | Adequate work areas and air space must be <i>made reasonably available</i> to allow suitable standards of health and safety for <i>the worker</i> . | A5 | A workplace has a minimum unencumbered floor area of 2.3m ² for each <i>worker</i> . |
|-----------|---|-----------|---|

**Part 2 Other provisions for complying
with performance criteria****Satisfying the performance *criteria****(words omitted)*

Compliance with the performance criteria can only be achieved by—

- (a) complying with the acceptable solutions; or
- (b) formulating an alternative solution that satisfies the performance criteria or is shown to be at least equivalent to the acceptable solutions; or
- (c) a combination of (a) and (b).

*(omitted)***Definitions***(omitted)*

Dining area—*a sheltered area where workers may have lunch or take other breaks.*

Schedule 8F (continued)

Dining room—a room or sheltered place where workers may have lunch or take other breaks.

Dressing room—a room used for changing clothes.

Floor area—excludes the area of any item positioned on the floor.

(omitted)

Heavy, hot or dirty occupations—*work* in foundries, steel fabrication, sand blasting, spray painting and the like.

(omitted)

Light to medium and clean occupations—*work* in offices, retail stores, and the like.

(omitted)

Sedentary occupations—work requiring a sitting position.

Semi-sedentary occupations—work requiring a sitting or standing position eg retail store workers.

(omitted)

Unencumbered—clear circulation space with no fixtures or fittings intruding within the space.

(omitted).

Workrooms—means any part of a workplace contained in a building partitioned off by any means or set aside in which a worker is required to work.

Schedule 9 Dictionary

section 3

accredited course means a course accredited under the *Vocational Education, Training and Employment Act 2000*.

ACM means asbestos containing material.

ADAS diving certificate means an occupational diver certificate of competency or a commercial diver certificate that, on its face, is issued under the Australian Diver Accreditation Scheme associated with the *Petroleum (Submerged Lands) Act 1967* (Cwlth).

address of a workplace means—

- (a) a street or similar address; or
- (b) another description of the location of the workplace enabling the location to be identified.

ADG Code means the Australian Code for the Transport of Dangerous Goods by Road and Rail.¹⁷⁵

advanced boiler operator means a person who—

- (a) performs the work of an intermediate boiler operator; and
- (b) operates a boiler with multiple fuel types that may be fired simultaneously during normal operation (other than boilers changing fuel types during the start sequence).

advanced rigger means a person who performs—

- (a) the work of an intermediate rigger; and
- (b) rigging work associated with—
 - (i) gin poles and shearlegs; or
 - (ii) flying foxes and cable ways; or

¹⁷⁵ The ADG Code is prepared by the Australian Transport Safety Bureau of the Commonwealth Department of Transport and Regional Services.

Schedule 9 (continued)

- (iii) guyed derricks and structures; or
- (iv) suspended scaffolds and fabricated hung scaffolds.

advanced scaffolder means a person who performs—

- (a) the work of an intermediate scaffolder; and
- (b) scaffolding work, using scaffolding from which a person or object may fall more than 4m, associated with—
 - (i) hung scaffolds, including scaffolds hanging from tubes, wire ropes and chains; or
 - (ii) suspended scaffolds.

agreement, for part 23, division 4, see section 235.

an 8 hour equivalent continuous A-weighted sound pressure level of 85dB(A) means the actual energy of varying noise levels experienced over a period that is equivalent to an 8 hour continuous steady A-weighted sound pressure level of 85dB(A).

anchorage point, for part 17, see section 155.

application for training approval means an application under section 331.

applied BCA provision see schedule 8C, section 2.

applied QDC provision see schedule 8C, section 2.

approved criteria means—

- (a) until the end of 30 April 2001—the criteria stated in NOHSC’s document entitled ‘Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (1994)]’; and
- (b) from 1 May 2001—the criteria stated in NOHSC’s document entitled ‘Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (1999)]’.

asbestos management code, for part 11, see section 69A.

asbestos removal code, for part 11, see section 69A.

asbestos removalist, for part 11, see section 69A.

Schedule 9 (continued)

AS/NZS means a standard published jointly by Standards Australia and Standards New Zealand.

assessment means the process of collecting evidence and making judgments on whether competency has been achieved to decide whether a person can perform to the standard expected in the workplace.

assessment instrument, for a unit of competency for a class of high risk work or for a unit of competency for an earthmoving or particular crane occupation, see section 16D.

assessment summary means a document that records the result of an assessment.

atmospheric monitoring means determining the concentration of lead in the atmosphere.

Australian Qualifications Framework has the same meaning as AQF has under the *Vocational Education, Training and Employment Act 2000*, schedule 3.

Authority see the *Building and Construction Industry (Portable Long Service Leave) Act 1991*.

A-weighted means a standardised frequency response (in dB(A)) used in sound measuring instruments and corresponding approximately to the human ear response.

barricade, for part 17, see section 155.

basic boiler operator means a person who operates a boiler with—

- (a) a single fixed combustion air supply; and
- (b) a nonmodulating single heat source; and
- (c) a fixed firing rate.

basic rigger means a person who performs—

- (a) the work of a dogger; and
- (b) rigging work associated with—
 - (i) the movement of plant and equipment; or
 - (ii) the placement of precast concrete; or

Schedule 9 (continued)

- (iii) hoists other than hoists with jibs and self-climbing hoists; or
- (iv) steel erection; or
- (v) safety nets and static lines; or
- (vi) mast climbers; or
- (vii) perimeter safety screens and shutters; or
- (viii) cantilevered crane loading platforms.

basic scaffolder means a person who performs scaffolding work, using scaffolding from which a person or object may fall more than 4m, associated with—

- (a) prefabricated scaffolds; or
- (b) cantilevered materials hoists with a maximum working load of 500kg; or
- (c) ropes; or
- (d) gin wheels; or
- (e) safety nets and static lines; or
- (f) bracket scaffolds.

BCA see schedule 8C, section 2.

biological monitoring means—

- (a) for a hazardous substance—testing for the presence of a hazardous substance, its metabolites or a biochemical change in a person's body tissue, exhaled air or fluid; or
- (b) for lead—
 - (i) testing for the presence of lead in a person's tissue or fluid; or
 - (ii) testing for a biochemical change in a person's tissue or fluid.

blood lead level means the concentration of lead in capillary or venous whole blood.

Schedule 9 (continued)

boiler—

- (a) means a vessel or arrangement of vessels and interconnecting parts in which—
 - (i) steam or other vapour is generated; or
 - (ii) water or other liquid is heated at a pressure above that of the atmosphere;
by the application of fire, the products of combustion, electrical power, or similar high temperature means; and
- (b) includes superheaters, reheaters, economisers, boiler piping, supports, mountings, valves, gauges, fittings, controls, the boiler setting and directly associated equipment; and
- (c) does not include a fully flooded or pressurised system where water or other liquid is heated to a temperature lower than the normal atmospheric boiling temperature of the liquid.

boom-type elevating work platform means a telescoping, hinged or articulated device, or a combination of 2 or more devices of those types, used to support a lifting platform.

bottom mix means a gas mix that can be breathed at the deepest point of the dive.

bottom time means the time between a diver leaving the surface at the start of a dive and starting the final ascent.

bridge crane means a crane comprising a bridge beam, mounted at each end to an end carriage, capable of travelling along elevated runways and having 1 or more hoisting mechanisms arranged to traverse across the bridge beam.

building, for part 21A, part 23, division 4 and schedules 8C, 8D, 8E and 8F, see the *Building Act 1975*, schedule 2.

building and construction industry means—

- (a) that part of industry involved in the construction, erection, installation, addition to, alteration, repair, maintenance, cleaning, painting, renewal, removal,

Schedule 9 (continued)

dismantling or demolition of a building or other structure; or

- (b) the digging or filling of a structure; or
- (c) concreting, bricklaying or tiling; or
- (d) any part of industry involved in activities normally regarded as building or construction.

building and construction work see the *Building and Construction Industry (Portable Long Service Leave) Act 1991*.

Building Code of Australia see schedule 8C, section 2.

building maintenance unit means a power operated suspended platform, and associated equipment on a building, designed to provide permanent access to the faces of the building for maintenance.

caisson, for part 17, see section 155.

catch platform, for part 17, see section 155.

certificate, for part 5, see section 34.

certificate of medical fitness to dive means a certificate that—

- (a) on its face is issued by a doctor who has satisfactorily completed training in diving medicine approved by the Board of Censors of the South Pacific Underwater Medicine Society;¹⁷⁶ and
- (b) contains the information required under section 79.

certificate of registration of a mobile crane or tower crane see section 39H.

chemical name of a hazardous substance or lead means its scientific or technical name.

civil construction work, for part 17, see section 155.

¹⁷⁶ The society's address is c/- Australian and New Zealand College of Anaesthetists, 630 St Kilda Road, Melbourne 3004.

Schedule 9 (continued)

class, in relation to a building, means the class of the building under schedule 8E, part 3, sections A3.2, A3.3 and A3.4.

class of high risk work means a class of work stated in schedule 5.

cofferdam, for part 17, see section 155.

common plant, for part 17, see section 155.

community services industry means an industry involved in any of the following—

- (a) health or welfare services;
- (b) education services;
- (c) library services;
- (d) scientific research services;
- (e) meteorological services;
- (f) employment services;
- (g) prison services;
- (h) operating a museum;
- (i) nonprofit organisations that promote community or sectional aims.

competency means the ability to perform tasks or duties to the standard expected in employment.

competent person—

- (a) for construction diving work, see section 81; or
- (b) for underwater diving work other than construction diving work or conducting recreational diving or recreational technical diving, see section 82; or
- (c) for performing an inspection or other task for a control measure, means a person who has acquired, through training, qualifications or experience, the knowledge and skills to do the task in a safe way, including knowledge of—
 - (i) relevant Australian Standards; and

Schedule 9 (continued)

- (ii) relevant codes of practice; and
- (iii) other relevant legislation; or
- (d) for work in relation to a trench, see section 207; or
- (e) for inspecting a mobile crane or tower crane, see section 39H.

confined space means an enclosed or partially enclosed space that—

- (a) is at atmospheric pressure when anyone is in the space; and
- (b) is not intended or designed primarily as a workplace; and
- (c) could have restricted entry to, or exit from, the place; and
- (d) is, or is likely to be, entered by a person to work; and
- (e) at any time, contains, or is likely to contain, any of the following—
 - (i) an atmosphere that has potentially harmful levels of a contaminant;
 - (ii) an atmosphere that does not have a safe oxygen level;
 - (iii) anything that could cause engulfment.

Examples of a confined space—

- 1 storage tanks, tank cars, process vessels, pressure vessels, boilers, silos and other tank-like compartments
- 2 pits and degreasers
- 3 pipes, sewers, sewer pump stations including wet or dry wells, shafts and ducts
- 4 shipboard spaces entered through small hatchways or access points, cargo tanks, cellular double bottom tanks, duct keels, ballast or oil tanks and void spaces

confirmed blood lead level means the concentration of lead in venous whole blood.

construction diving work, for part 12, see section 77.

Schedule 9 (continued)

construction person, for schedule 8A, see schedule 8A, section 1.

construction safety plan, for part 17, see section 155.

consumer package means—

- (a) a single packaged item, holding less than 30kg or 30L, intended for retail sale; or
- (b) a package containing only identical packaged items mentioned in paragraph (a).

container means a thing (other than a bulk container, or tank, defined in the ADG Code) in which a hazardous substance or lead is, or has been, completely or partly cased, contained, covered, enclosed or packed, but does not include an enclosed system.

contaminant means anything that may be harmful to health and safety.

control measure means a measure to prevent, or minimise the level of, exposure to a risk.

corresponding authority—

- (a) to an earthmoving or particular crane work certificate—means a document (however described), issued by a recognised official, authorising work in an occupation that is the same or substantially the same as the earthmoving or particular crane occupation to which the certificate relates; or
- (b) to a licence or licence class—means a document (however described), issued by a recognised official, authorising the performance of a class of work that is the same or substantially the same as the class of high risk work to which the licence or licence class relates.

corresponding law means a law of the Commonwealth or another State about workplace health and safety.

cost of building and construction work see the *Building and Construction Industry (Portable Long Service Leave) Act 1991*, section 73(1) and (2).

Schedule 9 (continued)

crane means a machine for raising or lowering a load and moving it horizontally, including any supporting structure or foundation, but does not include—

- (a) an industrial lift truck, specified amusement device, tractor, industrial robot, conveyor, building maintenance unit, suspended scaffold or lift;¹⁷⁷ or
- (b) a backhoe, excavator, front-end loader, drag line, or other machine primarily designed for earthmoving purposes.

C-weighted means a standardised frequency response (in dB(C)) used in sound measuring instruments and corresponding approximately to the human ear response.

dangerous goods has the meaning given by the ADG Code.

dB(A) means A-weighted decibels.

dB(C) means C-weighted decibels.

decompression diving means diving that requires a diver to take a planned stop during the final ascent to decompress.

designated doctor means a doctor—

- (a) who is registered as a specialist registrant in the specialty of occupational medicine under the *Medical Practitioners Registration Act 2001*; or
- (b) who has satisfactorily completed a health surveillance training program supplied by the chief executive.

designated hazardous substance means—

- (a) until the end of 30 April 2001—a substance, listed as a designated hazardous substance in NOHSC's document entitled 'List of Designated Hazardous Substances [NOHSC:10005 (1994)]'; and
- (b) from 1 May 2001—a substance, listed as a designated hazardous substance in NOHSC's document entitled 'List of Designated Hazardous Substances [NOHSC:10005 (1999)]'.

¹⁷⁷ *Lift* is defined in schedule 2 of the Act.

Schedule 9 (continued)

design verification statement see section 39C(a).

design verifier, for part 5, division 1A, subdivision 2, see section 39B.

directly supervise, a trainee or a worker who is undergoing an assessment, conducted by the worker's employer, to decide the worker's suitability to perform high risk work, means overseeing the work of the trainee or worker for the purposes of—

- (a) directing, demonstrating, monitoring and checking the trainee's or worker's performance in a way that is appropriate to the trainee's or worker's competency level; and
- (b) ensuring a capacity to respond in an emergency situation.

dive supervisor, for part 12, division 3, see section 86AN.

dive time means the time between a diver leaving the surface at the start of a dive and surfacing at the end of the dive.

dogger means a person who—

- (a) uses techniques, including the selection or inspection of lifting gear, to safely sling a load; or
- (b) directs a crane or hoist operator in the movement of a load when the load is out of the operator's view.

domestic duplex means 2 single domestic dwellings with a common internal wall.

domestic house means a house that is a separate single domestic dwelling.

EANx means a mixture of oxygen and nitrogen in which the volume of oxygen in the mixture is at least 22%.

earthmoving or particular crane occupation means an occupation, or part of an occupation, stated in schedule 5A.

earthmoving or particular crane work certificate means a certificate to work in a single earthmoving or particular crane occupation.

Schedule 9 (continued)

edge protection, for part 17, see section 155.

electricity, gas and water industry means that part of industry involved in any of the following—

- (a) the generation, transmission or distribution of electricity;
- (b) the manufacture of town gas from coal or petroleum or coal and petroleum;
- (c) the distribution of town gas, natural gas or liquefied gas through a mains reticulation system;
- (d) the storage, purification or supply of water;
- (e) the operation of sewerage or stormwater drainage systems, including sewage treatment plants.

enclosed system includes a pipe or piping system and a process or reactor vessel.

engineer, in relation to the performance of a task, means a person who—

- (a) is a registered professional engineer under the *Professional Engineers Act 2002*; and
- (b) is competent to perform the task.

engineering principles, for part 5, division 1A, subdivision 2, see section 39B.

excavation, for part 17, see section 155.

excavation work, for part 17, see section 155.

excessive noise, for part 10, see section 68.

exempt tractor, for part 16, see section 146.

exposed—

- (a) for a hazardous substance—see section 87; or
- (b) for lead—see section 116; or
- (c) for an electrical installation—see section 156(2).

fall-arrest harness system, for part 17, see section 155.

fall arresting platform, for part 17, see section 155.

Schedule 9 (continued)

fall protection cover, for part 17, see section 155.

financial, property and business services industry means an industry involved in any of the following—

- (a) providing financial services;
- (b) investing in predominantly financial securities, including, for example, mortgages, patents and copyrights;
- (c) providing insurance services;
- (d) managing or valuing real estate, other than agricultural or pastoral properties;
- (e) selling, leasing or developing real estate;
- (f) providing architectural, surveying, legal, accountancy, or other professional services;
- (g) advertising, market research, management consultancy, data processing or other office services;
- (h) credit assessing or reporting;
- (i) cleaning, pest control or caretaking services;
- (j) security services;
- (k) packing of goods (other than agricultural produce, food, beverages and tobacco) or crating or packing goods for transport;
- (l) leasing or hiring machinery, plant or equipment, other than transport equipment.

fired heater means a pressure vessel in which—

- (a) a liquid is heated below its atmospheric boiling temperature; or
- (b) a process fluid is heated in tubes above or below its atmospheric boiling temperature;

by the application of fire, the products of combustion, electrical power, or similar high temperature means.

formal training means training involving theory and practical demonstration.

Schedule 9 (continued)

formerly complying amenity, for part 23, division 4, see section 235.

formerly complying dressing room, for part 23, division 4, see section 235.

formerly complying lunch room, for part 23, division 4, see section 235.

formerly complying toilet, for part 23, division 4, see section 235.

gantry, for part 17, see section 155.

gantry crane means a crane, comprising a bridge beam that is supported at 1 or both ends by legs mounted to end carriages, capable of travelling along runways and having 1 or more hoisting mechanisms.

general induction card means a document in the form of a card issued by the department evidencing a person's successful completion of the general induction training course and that includes—

- (a) the name of the registered training organisation that provided the general induction training course; and
- (b) the national provider code for the registered training organisation issued by the department that administers the *Vocational Education, Training and Employment Act 2000*; and
- (c) the course number and name; and
- (d) the name and signature of the person to whom the card was issued; and
- (e) the signature of—
 - (i) the person who conducted the general induction training course; or
 - (ii) a person signing for the person mentioned in subparagraph (i); and
- (f) the date the card was issued.

Schedule 9 (continued)

general induction evidence, for a person, means—

- (a) a statement of attainment for the general induction training course issued to the person by a registered training organisation under the *Vocational Education, Training and Employment Act 2000*; or
- (b) a general induction card issued to the person.

general induction training course means the course 30215 QLD—Course in General Safety Induction (Construction Industry) accredited under the *Vocational Education, Training and Employment Act 2000*.

generic name means the name of a chemical category or group, including, for example, ‘azo dyes’ and ‘halogenated aromatic amines’.

geo-technical engineer, for part 17, see section 155.

hazardous substance—

- (a) for part 13, other than division 4—see section 88; or
- (b) for part 13, division 4—see section 100.

health surveillance means the monitoring (including biological monitoring and medical assessment) of a person to identify changes in the person’s health because of exposure to a hazardous substance or lead.

health surveillance report—

- (a) for a hazardous substance—see section 109; or
- (b) for lead—see section 133.

high risk construction activity, for part 17, see section 155.

high risk work means work included in a class of high risk work.

historical activity, for part 16, see section 146.

hoarding, for part 17, see section 155.

holder of a certificate means the person in whose name the certificate is granted.

housing construction work, for part 17, see section 155.

Schedule 9 (continued)

impurity means any fumes, dust, smoke, gas, vapour or other thing that may endanger the workplace health and safety of a worker.

informal learning means workplace experience.

ingredient means a component (including an impurity) of a substance.

intermediate boiler operator means a person who performs—

- (a) the work of a basic boiler operator; and
- (b) operates a boiler with—
 - (i) a modulating combustion air supply; or
 - (ii) a modulating heat source; or
 - (iii) a superheater; or
 - (iv) an economiser.

intermediate rigger means a person who performs—

- (a) the work of a basic rigger; and
- (b) rigging work associated with—
 - (i) hoists; or
 - (ii) cranes, conveyors, dredges and excavators; or
 - (iii) tilt slabs; or
 - (iv) demolition work; or
 - (v) dual lifts.

intermediate scaffolder means a person who performs—

- (a) the work of a basic scaffolder; and
- (b) scaffolding work, using scaffolding from which a person or object may fall more than 4m, associated with—
 - (i) cantilevered crane loading platforms; or
 - (ii) cantilevered and spurred scaffolds; or
 - (iii) barrow ramps and sloping platforms; or
 - (iv) perimeter safety screens and shutters; or

Schedule 9 (continued)

- (v) mast climbers; or
- (vi) tube and coupler scaffolds, including tube and coupler covered ways and gantries.

ladder, for part 17, division 3, subdivision 10, see section 213.

lead means—

- (a) a lead metal; or
- (b) a mixture of 2 or more metals containing more than 0.5% lead by weight (***lead alloy***); or
- (c) a lead salt of an organic acid; or
- (d) a lead hazardous substance.

Example of a lead salt of organic acids—

lead acetate

lead compound means a substance, other than an organometallic compound of lead, in which lead is found in the substance's molecular structure.

lead hazardous substance see section 117.

lead process means any of the following carried out at a workplace—

- (a) work that exposes a person to lead dust, or lead fume, arising from the manufacture or handling of dry lead compounds;
- (b) work connected with the manufacture, assembly, handling or repair of electrical accumulators (batteries), or parts of electrical accumulators, that involves manipulating dry lead compounds, pasting, casting or soldering of lead;
- (c) breaking up, or dismantling, lead accumulators and the sorting, packing and handling of plates, or other parts of accumulators, that contain lead;
- (d) spraying molten lead, or alloys containing more than 5% by weight of lead;

Schedule 9 (continued)

- (e) melting or casting lead alloys containing more than 5% by weight of lead in which the temperature of the molten material is more than 450°C;
- (f) recovering lead from ore, oxides or other compounds by thermal reduction process;
- (g) using a power tool to dry grind, disc, buff, or cut lead or alloys containing more than 5% by weight of lead;
- (h) using a power tool to sand or buff surfaces coated with a substance containing more than 1% by dry weight of lead;
- (i) any process by which arc, oxyacetylene, oxy gas, plasma arc or a flame is applied (for the purposes of welding, cutting or cleaning) to—
 - (i) lead; or
 - (ii) metal coated with lead; or
 - (iii) a thing coated with paint containing more than 1% by dry weight of lead;
- (j) radiator repairs that generate lead dust or lead fume;
- (k) fire assay in which lead is used;
- (l) foundry work using alloys containing more than 2% by dry weight of lead;
- (m) spray painting with lead paint containing more than 1% by dry weight of lead.

lead process area means a workplace, or part of a workplace, where a lead process is carried out.

lead-risk job means a job in which—

- (a) a person may be exposed to lead; and
- (b) a person's blood lead level does, or may reasonably be expected to, equal or exceed—
 - (i) for a female who is pregnant or breast feeding—0.72µmol/L (15µg/dL); and

Schedule 9 (continued)

- (ii) for a female with a reproductive capacity— $0.97\mu\text{mol/L}$ ($20\mu\text{g/dL}$); and
- (iii) for anyone else— $1.45\mu\text{mol/L}$ ($30\mu\text{g/dL}$).

licence, for part 5, see section 34.

licence class means a class of high risk work endorsed on a licence to perform a class of high risk work.

licence to perform a class of high risk work means a licence authorising the holder of the licence to perform 1 or more classes of high risk work.

light work, for part 17, see section 155.

manufacturing industry means that part of industry involved in any of the following—

- (a) the physical or chemical transformation of materials or components into new products, whether the work is performed by power driven machinery or by hand;
- (b) the manufacturing of food, beverages, tobacco, textiles, clothing, footwear, wood, wood products, furniture, paper, paper products, printing and publishing materials, non-metallic mineral products, basic metal products, fabricated metal products, transport equipment and other machinery products and equipment.

mast climbing work platform means a hoist with a working platform used for temporary purposes to lift personnel or materials using a drive system mounted on an extendable mast that may be tied to a building.

master, of a boat, means the person having command or charge of the boat.

maximum operating depth, for a gas, means the maximum safe depth at which the gas can be used.

medical record of a person means personal medical results or clinical findings obtained from health surveillance of the person.

mesh, for part 17, division 2, subdivision 11, see section 179.

Schedule 9 (continued)

minimum operating depth, of a bottom mix, means the minimum safe depth at which the gas can be used.

mixed gas means an underwater breathing mixture other than compressed air or EANx.

mobile crane means a crane that—

- (a) is capable of travelling over a supporting surface without the need for fixed runways (including railway tracks); and
- (b) relies only on gravity for stability, that is, with no vertical restraining connection between itself and the supporting surface and no horizontal restraining connection (other than frictional forces at supporting surface level) that may act as an aid to stability.

monitoring means regularly checking, other than by biological monitoring—

- (a) a person's risk from, or level of exposure to, a hazardous substance; and
- (b) the effectiveness of hazardous substance control measures at a person's workplace.

MSDS, for a hazardous substance or lead, means a material safety data sheet for the substance or lead given to the person by the substance's or lead's supplier.

national exposure standard, for asbestos, a contaminant, a hazardous substance or lead, means the exposure standard for the asbestos, contaminant, hazardous substance or lead stated in the Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment contained in NOHSC's document entitled 'Exposure Standards for Atmospheric Contaminants in the Occupational Environment'.

Schedule 9 (continued)

NICNAS summary report means a summary report under the *Industrial Chemicals (Notification and Assessment) Act 1989* (Cwlth).¹⁷⁸

NOHSC means the National Occupational Health and Safety Commission under the *National Occupational Health and Safety Commission Act 1985* (Cwlth).

notice of refusal see section 38H(1).

object, for part 17, see section 155.

open circuit scuba means self-contained underwater breathing apparatus that does not recirculate, or partially recirculate, the breathing gas.

overhead platform, for part 17, see section 155.

people mover means plant designed and intended for use for the transportation of people by way of a vehicle supported and guided on a fixed structure, other than transportation by—

- (a) a people-mover system within the meaning of the *State Transport (People Movers) Act 1989*; or
- (b) a railway, or rail transport infrastructure within the meaning of the *Transport Infrastructure Act 1994*, owned or operated by Queensland Rail; or
- (c) a tram; or
- (d) an amusement device; or
- (e) an escalator; or
- (f) a lift, crane or hoist; or
- (g) an aerial funicular.

perform work includes use plant.

perimeter containment screening, for part 17, see section 155.

permitted work, for part 17, see section 155.

¹⁷⁸ NICNAS summary reports refer only to pure substances and are available from the NICNAS website, <www.nicnas.gov.au>.

Schedule 9 (continued)

personnel hoist means an appliance for lifting a person on a platform that can be raised more than 2m, but does not include a lift or building maintenance unit.

powered operation, in relation to a bridge and gantry crane, means—

- (a) raising and lowering a load; or
- (b) moving the crane along runways; or
- (c) traversing the crane's hoisting mechanism across a bridge beam; or
- (d) rotating the crane's hoisting mechanism.

prefabricated scaffolding means an integrated system of scaffolding components manufactured in a way that the assembled shape of the scaffolding is predetermined.

prescribed information, for part 17, see section 155.

pressure piping—

- (a) means an assembly of pipes, pipe fittings, valves and pipe accessories subject to internal or external pressure and used to contain or convey fluid or to transmit fluid pressure; and
- (b) includes distribution headers, bolting, gaskets, pipe supports and pressure retaining accessories; and
- (c) does not include a boiler, pressure vessel or a pipeline.

pressure vessel—

- (a) means a vessel subject to internal or external pressure; and
- (b) includes—
 - (i) interconnected parts and components, valves, gauges and other fittings up to the first point of connection to connecting piping; and
 - (ii) a fired heater; and
 - (iii) a refillable gas cylinder; and
- (c) does not include a boiler or pressure piping.

Schedule 9 (continued)

process, for part 12, division 3, see section 86AC(2).

product name of a hazardous substance or lead means the brand name, code name, trade name or code number given to the substance or lead by its manufacturer, importer or supplier.

proposed action see section 46B(1).

public administration industry means any of the following—

- (a) the Queensland Fire Service;
- (b) the Queensland Police Service;
- (c) judicial bodies;
- (d) political parties;
- (e) state or local governments.

QDC see schedule 8C, section 2.

Queensland Development Code see schedule 8C, section 2.

reasonably available, to a person, for schedules 8A, 8B, 8C, 8E and 8F in relation to an amenity, means—

- (a) available at a location reasonably convenient to the person; and
- (b) the person's use of the amenity is not unreasonably restricted.

rebreather means a semi-closed or closed circuit self-contained underwater breathing apparatus.

recognised official means a person who may issue a document (however described, including a certificate or licence) under a law of the Commonwealth, or another State, about occupational health and safety.

recreational diving means any of the following underwater diving for recreation using compressed air, other than diving in a swimming pool or decompression diving—

- (a) resort diving;

Schedule 9 (continued)

- (b) diving by a person undertaking training in diving for recreation, whether or not the person is being photographed, filmed or videoed while diving;
- (c) diving for recreation by a person with a qualification in underwater diving, whether or not the person is being photographed, filmed or videoed while diving.

recreational services, personal services and other services industry means an industry involved in any of the following—

- (a) entertaining services;
- (b) recreational or sporting services;
- (c) accommodation services;
- (d) catering services;
- (e) personal services, including, for example, babysitting, burial, gardening and photography.

recreational snorkelling does not include snorkelling in a swimming pool.

recreational technical diving means underwater diving for recreation, other than in a swimming pool—

- (a) using EANx or mixed gas; or
- (b) that is decompression diving using compressed air or other gas.

refillable gas cylinder means a rigid pressure vessel that—

- (a) has a water capacity of more than 0.1L but not more than 3000L; and
- (b) has no openings, or integral attachments, on the shell of the vessel other than at the ends of the vessel; and
- (c) is for the storage and transport of gas under pressure.

register means—

- (a) for part 13—the register mentioned in section 111; or
- (b) for part 14—the register mentioned in section 127.

Schedule 9 (continued)

registered means registered under this regulation.

registered training organisation see the *Vocational Education, Training and Employment Act 2000*, schedule 3.

registrable plant means the plant stated in schedule 3.

registrable plant design means the design of plant mentioned in schedule 4.

relevant authority means—

- (a) for an elevated electric line constructed by an electricity entity—the electricity entity; or
- (b) for an elevated electric line constructed and used by Queensland Rail under the *Transport Infrastructure Act 1994* as part of a system of electric traction or for signalling purposes on a railway—Queensland Rail.

relevant person see section 28(1) of the Act.

repetitive dive group means a letter of the alphabet, given by dive tables, that represents an estimate of the amount of residual nitrogen in a diver's tissues immediately on surfacing at the end of a dive.¹⁷⁹

repository means the Australian National Material Safety Data Sheet Repository kept by NOHSC.

representative of a worker includes a coworker elected by workers at the worker's workplace to represent the worker on workplace health and safety issues.

reproductive capacity means being physiologically capable of becoming pregnant.

Example—

A female using a contraceptive pill is of reproductive capacity if she would be physiologically capable of becoming pregnant were she not using the pill.

residual nitrogen means nitrogen, in excess of the amount normally present in a person's tissues, that is dissolved in the person's tissues.

179 Some dive tables refer to 'pressure group' instead of repetitive dive group.

Schedule 9 (continued)

resort diving means an introductory scuba experience, or introductory educational diving program, conducted according to a recreational scuba training organisation's program, or a recreational technical scuba training organisation's program, whether or not the person is being photographed, filmed or videoed while diving.

retail and wholesale trade industry means an industry involved in selling new or used goods.

retail warehouse operator means an operator of a warehouse where unopened packaged goods, intended for retail sale, are stored.

retraining means—

- (a) in relation to an earthmoving or particular crane work certificate—retraining in part or all of the unit of competency for the earthmoving or particular crane occupation to which the certificate relates; or
- (b) in relation to a licence or licence class—retraining in part or all of the unit of competency for the class of high risk work to which the licence or licence class relates.

rigging work means using mechanical load shifting equipment and associated gear—

- (a) to move, place or secure a load; or
- (b) to set up or dismantle a crane or hoist.

risk assessment means a risk assessment made under—

- (a) for part 13—section 105; or
- (b) for part 14—section 129.

risk phrase, for a hazardous substance or lead, means a phrase stated in NOHSC's document entitled 'National Code of Practice for the Labelling of Workplace Substances' that gives information about the substance's or lead's hazards.

roll-over protective structure, for part 16, see section 146.

rural industry means an industry in which persons are engaged primarily in work—

Schedule 9 (continued)

- (a) in the cultivation of any agricultural crop or product whether grown for food or not; or
- (b) in the rearing and management of livestock; or
- (c) in the classing, scouring, sorting or pressing of wool; or
- (d) in aquaculture; or
- (e) in flower or vegetable market gardens; or
- (f) at clearing, fencing, trenching, draining or otherwise preparing land for any purpose stated in paragraph (a), (b), (d) or (e).

safe oxygen level means an oxygen content in air under normal atmospheric pressure that—

- (a) is equal to or more than 19.5% by volume (equivalent to a partial pressure of oxygen of 19.8kPa); and
- (b) is equal to or less than 23.5% by volume (equivalent to a partial pressure of oxygen of 23.9kPa).

safety phrase, for a hazardous substance or lead, means a phrase stated in NOHSC's document entitled 'National Code of Practice for the Labelling of Workplace Substances' that gives information about—

- (a) the safe use of the substance or lead; or
- (b) the personal protective equipment for the substance or lead.

scaffolding means a temporary structure, not including a trestle ladder, supporting a platform used to perform work.

scaffolding work means the erection, alteration or dismantling of scaffolding.

scope of registration see the *Vocational Education, Training and Employment Act 2000*, schedule 3.

scuba means self-contained underwater breathing apparatus.

Schedule 9 (continued)

self-erecting tower crane means a tower crane that—

- (a) has a tower structure with a boom or jib that ordinarily remains fully assembled and part of the crane while being transported from one place to another; and
- (b) has erection and dismantling processes that are an inherent part of the crane's function.

show cause notice see section 46B(1).

site-specific induction, for part 17, see section 155.

specified amusement device means a device classified as a class 2, 3, 4 or 5 amusement device in AS 3533, part 1¹⁸⁰ as in force on 5 December 1997.

spray painting means—

- (a) the process in which either of the following are sprayed onto a surface to produce a film of required thickness and texture—
 - (i) a liquid coating substance that is converted into an aerosol or mist;
 - (ii) a powder coating substance; or
- (b) an activity directly related to the process mentioned in paragraph (a), whether carried out before, during or after the process.

Examples of paragraph (b)—

paint mixing, paint matching and cleaning a spray gun

spray painting booth means a room or enclosure designed solely for the purpose of spray painting.

SSBA means underwater breathing apparatus supplying the wearer with compressed breathing gas through a hose from a compressor or storage cylinder at the surface or from a submersible work chamber or habitat.

stand-by diver, for part 12, division 3, see section 86AO.

180 AS 3533 (Amusement rides and devices), part 1 (Design and construction)

Schedule 9 (continued)

statement of attainment see the *Vocational Education, Training and Employment Act 2000*, schedule 3.

static line, for part 17, see section 155.

substance does not include a thing (other than a fluid or particle)—

- (a) formed during production to a predetermined design or shape or to have a predetermined surface; and
- (b) used for a purpose depending completely or partly on its design, shape or surface; and
- (c) keeping its chemical composition and physical state during use.

technical standard, for part 5, division 1A, subdivision 2, see section 39B.

time in means the time a diver leaves the surface at the start of a dive.

time out means the time a diver surfaces at the end of a dive.

tower crane means a crane with a boom that is mounted on a tower structure.

tractor, for part 16, see section 146.

trainee see section 28C.

training approval means an approval granted under section 33K.

transport and storage industry means an industry involved in any of the following—

- (a) passenger or freight transport;
- (b) providing terminal facilities for passengers or freight;
- (c) operating airports;
- (d) selling or leasing aircraft or ships;
- (e) motor vehicle parking;
- (f) motor vehicle rental;
- (g) stevedoring;

Schedule 9 (continued)

- (h) harbour or navigation services;
- (i) booking, forwarding, crating, storage or custom agency services;
- (j) operating oil or gas pipelines.

travel restraint system, for part 17, see section 155.

trench, for part 17, see section 155.

truck-mounted concrete placing unit with boom means plant that—

- (a) is used to place concrete by way of pumping concrete through a pipeline attached to or forming part of the boom; and
- (b) is capable of travelling over a supporting surface without the need for fixed runways (including railway tracks); and
- (c) relies on gravity for stability, that is, with no vertical restraining connection between itself and the supporting surface and no horizontal restraining connection (other than frictional forces at supporting surface level) that may act as an aid to stability.

type 1 ingredient of a substance means an ingredient present in the substance in a concentration more than the ingredient's concentration cut-off level stated in the approved criteria and—

- (a) described in the approved criteria as—
 - (i) carcinogenic, corrosive, mutagenic, teratogenic, toxic or very toxic; or
 - (ii) a respiratory or skin sensitiser; or
 - (iii) a harmful substance capable of causing a person an irreversible adverse health effect after acute exposure; or
 - (iv) a harmful substance capable of causing serious damage to a person's health after repeated or prolonged exposure; or

Schedule 9 (continued)

- (b) listed, and having an exposure standard stated, in the Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment contained in NOHSC's document entitled 'Exposure Standards for Atmospheric Contaminants in the Occupational Environment'.

type 2 ingredient of a substance means an ingredient (other than an ingredient mentioned in the definition *type 1 ingredient*, paragraph (a)) present in the substance—

- (a) in a concentration more than the ingredient's concentration cut-off level stated in the approved criteria; and
- (b) described in the approved criteria as a harmful substance.

type 3 ingredient of a substance means an ingredient (other than a type 1 or type 2 ingredient) present in the substance.

underground service, for part 17, see section 155.

underwater diving does not include snorkelling or breath-hold diving.

underwater diving work, for part 12, see section 76.

unit of competency, for a class of high risk work or for an earthmoving or particular crane occupation, see section 16E.

use of a hazardous substance or lead includes handling, production, storage, movement and disposal of the substance or lead, but does not include the carriage of a substance covered by the ADG Code or the International Maritime Dangerous Goods Code.¹⁸¹

variation of a licence, for part 5, see section 34.

vehicle hoist means a vehicle hoisting device designed to give convenient under chassis access for work or examination.

181 The International Maritime Dangerous Goods Code is prepared by the International Maritime Organisation.

Schedule 9 (continued)

work activity performer, for a business or undertaking, means a person who performs a work activity for the purposes of the business or undertaking, whether or not the person works on a voluntary basis.

Examples of persons who may perform a work activity for the purposes of a business or undertaking—

- a worker
- an employer who is an individual
- an executive officer of an employer that is a corporation
- a self-employed person
- employees, of a supplier of labour, whose services have been obtained by the person conducting the business or undertaking under a contract

work box means a device designed to be suspended from a crane to provide a working area for a person.

Workers' Compensation Act means the *Workers' Compensation and Rehabilitation Act 2003*.

work method statement, for part 17, see section 155.

work requiring a decompression stop means diving, at a depth and for a time, that would require a decompression stop if the Standard Air Decompression Table (Decompression in the Water) as published in AS/NZS 2299, part 1, appendix F, Table F1(A) or F1(B)¹⁸² were being used for the dive.

182 AS 2299 (Occupational diving operations), part 1 (Standard operational practice)

Endnotes

1 Index to endnotes

	Page
2 Date to which amendments incorporated	427
3 Key	428
4 Table of reprints	428
5 Tables in earlier reprints	430
6 List of legislation	430
7 List of annotations	435
8 Information about retrospectivity	487

2 Date to which amendments incorporated

This is the reprint date mentioned in the Reprints Act 1992, section 5(c). Accordingly, this reprint includes all amendments that commenced operation on or before 1 July 2008. Future amendments of the Workplace Health and Safety Regulation 1997 may be made in accordance with this reprint under the Reprints Act 1992, section 49.

3 Key

Key to abbreviations in list of legislation and annotations

Key	Explanation	Key	Explanation
AIA	= Acts Interpretation Act 1954	(prev)	= previously
amd	= amended	proc	= proclamation
amdt	= amendment	prov	= provision
ch	= chapter	pt	= part
def	= definition	pubd	= published
div	= division	R[X]	= Reprint No. [X]
exp	= expires/expired	RA	= Reprints Act 1992
gaz	= gazette	reloc	= relocated
hdg	= heading	renum	= renumbered
ins	= inserted	rep	= repealed
lap	= lapsed	(retro)	= retrospectively
notfd	= notified	rv	= revised edition
num	= numbered	s	= section
o in c	= order in council	sch	= schedule
om	= omitted	sdiv	= subdivision
orig	= original	SIA	= Statutory Instruments Act 1992
p	= page	SIR	= Statutory Instruments Regulation 2002
para	= paragraph	SL	= subordinate legislation
prev	= previous		
prec	= preceding	sub	= substituted
pres	= present	unnum	= unnumbered

4 Table of reprints

Reprints are issued for both future and past effective dates. For the most up-to-date table of reprints, see the reprint with the latest effective date.

If a reprint number includes a letter of the alphabet, the reprint was released in unauthorised, electronic form only.

Reprint No.	Amendments to	Effective	Reprint date
1	none	1 February 1998	2 February 1998
1A	1998 SL No. 88	17 April 1998	7 May 1998
1B	1998 SL No. 318	1 January 1999	15 January 1999
1C	1999 SL No. 216	17 September 1999	15 October 1999
1D	1999 SL No. 276	1 February 2000	10 February 2000
2	2000 SL No. 249	22 September 2000	6 October 2000
2A	2000 SL No. 313	1 February 2001	15 February 2001
2B	2001 SL No. 219	29 June 2001	30 November 2001
2C	2001 SL No. 219	1 February 2002	1 February 2002
2D	2002 SL No. 31	1 March 2002	7 March 2002
2E	2002 SL No. 39	8 March 2002	22 March 2002
2F	2002 SL No. 80	1 May 2002	15 May 2002

Reprint No.	Amendments included	Effective	Notes
2G	2002 SL No. 182	12 July 2002	
2H	2002 SL No. 109	1 September 2002	
	2002 SL No. 232		
2I	2002 SL No. 201	2 September 2002	
2J	2002 SL No. 260	1 October 2002	
3	2002 SL No. 261	1 November 2002	
	2002 SL No. 290		
3A	2002 SL No. 109	1 January 2003	
	2002 SL No. 232		
3B	2002 SL No. 7	1 February 2003	
	2002 SL No. 313		
3C	2003 SL No. 102	1 June 2003	
3D	2003 SL No. 68	1 July 2003	
	2003 SL No. 119		
4	2003 SL No. 169	18 July 2003	
4A	2003 SL No. 235	31 December 2003	
4B	2003 SL No. 235	1 February 2004	
4C rv	2004 SL No. 142	30 July 2004	
4D rv	2004 SL No. 256	26 November 2004	
4E	2004 SL No. 289	17 December 2004	
4F	2004 SL No. 289	1 January 2005	
	2004 SL No. 290		
4G	2004 SL No. 289	1 February 2005	R4G withdrawn, see R5
5	—	1 February 2005	
5A	2005 SL No. 70	1 May 2005	
5B rv	2005 SL No. 308	16 December 2005	
5C	2005 SL No. 308	1 January 2006	
5D	2005 SL No. 308	1 February 2006	R5D withdrawn, see R6
6	—	1 February 2006	
6A	2006 SL No. 227	1 September 2006	
6B	2006 SL No. 312	15 December 2006	
6C rv	2006 SL No. 246	1 January 2007	
	2007 SL No. 12		
6D rv	2006 SL No. 312	1 February 2007	
6E	2007 SL No. 12	16 February 2007	
6F	2007 SL No. 12	1 April 2007	
6G	2007 SL No. 75	4 May 2007	
7 rv	2007 SL No. 115	1 July 2007	Revision notice issued for R7
7A	2007 SL No. 310	7 December 2007	
7B	2007 SL No. 310	1 February 2008	
7C	2008 SL No. 74	31 March 2008	
7D	2008 SL No. 189	at the end of 30 June 2008	
7Erv	2007 SL No. 115 (amd 2007 SL No. 310) 2008 SL No. 189	1 July 2008	

5 Tables in earlier reprints

Name of table	Reprint No.
Corrected minor errors	3, 5

6 List of legislation

Workplace Health and Safety Regulation 1997 SL No. 409

made by the Governor in Council on 27 November 1997

notfd gaz 28 November 1997 pp 1408–10

ss 1–2 commenced on date of notification

remaining provisions commenced 1 February 1998 (see s 2)

exp 1 September 2008 (see SIA s 54)

Note—The expiry date may have changed since this reprint was published. See the latest reprint of the SIR for any change.

amending legislation—

Workplace Health and Safety Amendment Regulation (No. 1) 1998 SL No. 88

notfd gaz 17 April 1998 pp 1616–18

commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 2) 1998 SL No. 318

notfd gaz 4 December 1998 pp 1270–1

ss 1–2 commenced on date of notification

remaining provisions commenced 1 January 1999 (see s 2)

Workplace Health and Safety Legislation Amendment Regulation (No. 1) 1999 SL No. 110 ss 1, 2(2)–(4), pt 3 (this regulation is amended, see amending legislation below)

notfd gaz 11 June 1999 pp 675–8

ss 1–2 commenced on date of notification

s 12(3)–(4) commenced 1 January 2000 (see s 2(2))

s 15 commenced 1 February 2000 (see s 2(4))

remaining provisions commenced 1 July 1999 (see s 2(4))

amending legislation—

Workplace Health and Safety Amendment Regulation (No. 3) 1999 SL No. 276 pts 1, 3 (amends 1999 SL No. 110 above)

notfd gaz 12 November 1999 pp 1007–9

commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 1) 1999 SL No. 216

notfd gaz 17 September 1999 pp 250–1

commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 2) 1999 SL No. 233

notfd gaz 15 October 1999 pp 630–1

commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 3) 1999 SL No. 276 pts 1–2

notfd gaz 12 November 1999 pp 1007–9
commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 1) 2000 SL No. 249

notfd gaz 22 September 2000 pp 313–14
commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 2) 2000 SL No. 288

notfd gaz 17 November 2000 pp 1093–5
pt 2 commenced 1 February 2001 (see s 2(1))
pt 3 commenced 1 February 2002 (see s 2(2))
remaining provisions commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 3) 2000 SL No. 313

notfd gaz 8 December 2000 pp 1374–7
ss 1–2 commenced on date of notification
remaining provisions commenced 1 February 2001 immediately after the commencement on that day of the Workplace Health and Safety Amendment Regulation (No. 2) 2000 pt 2 (see s 2)

Workplace Health and Safety Amendment Regulation (No. 1) 2001 SL No. 100

notfd gaz 29 June 2001 pp 822–5
commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 2) 2001 SL No. 166

notfd gaz 14 September 2001 pp 139–40
ss 1–2 commenced on date of notification
remaining provisions commenced 1 February 2002 (see s 2)

Workplace Health and Safety Amendment Regulation (No. 3) 2001 SL No. 219

notfd gaz 23 November 2001 pp 1088–91
ss 1–2 commenced on date of notification
remaining provisions commenced 1 February 2002 (see s 2)

Workplace Health and Safety Amendment Regulation (No. 1) 2002 SL No. 7

notfd gaz 1 February 2002 pp 338–9
ss 1–2 commenced on date of notification
remaining provisions commenced 1 February 2003 (see s 2)

Medical Practitioners Registration Regulation 2002 SL No. 31 ss 1–2, 16 sch 4

notfd gaz 1 March 2002 pp 850–2
ss 1–2 commenced on date of notification
remaining provisions commenced 1 March 2002 (see s 2)

Workplace Health and Safety Amendment Regulation (No. 2) 2002 SL No. 39

notfd gaz 8 March 2002 pp 936–7
commenced on date of notification

Podiatrists Registration Regulation 2002 SL No. 80 ss 1–2, 10 sch 3

notfd gaz 26 April 2002 pp 1540–3
ss 1–2 commenced on date of notification
remaining provisions commenced 1 May 2002 (see s 2)

Workplace Health and Safety Amendment Regulation (No. 3) 2002 SL No. 109

notfd gaz 17 May 2002 pp 235–6

ss 1–2 commenced on date of notification

ss 7 (to the extent it ins new s 65J and pt 8, div 3, sdiv 2 and div 4), 8 (to the extent it ins new pt 11, div 4, sdiv 2 and div 5) commenced 1 January 2003 (see s 2(2)–(3))

remaining provisions commenced 1 September 2002 (see s 2(1))

Note—A regulatory impact statement and explanatory note were prepared.

Workplace Health and Safety Amendment Regulation (No. 4) 2002 SL No. 182

notfd gaz 12 July 2002 pp 1064–5

commenced on date of notification

Workplace Health and Safety Legislation Amendment Regulation (No. 1) 2002 SL No. 201 pts 1–2

notfd gaz 16 August 2002 pp 1420–1

ss 1–2 commenced on date of notification

remaining provisions commenced 2 September 2002 (see s 2)

Workplace Health and Safety Amendment Regulation (No. 5) 2002 SL No. 232

notfd gaz 30 August 2002 pp 1557–61

ss 1–2 commenced on date of notification

ss 3, 4, 6–21 commenced 1 September 2002 immediately after the commencement of the Workplace Health and Safety Amendment Regulation (No. 3) 2002, s 3 (see s 2(1))

remaining provision commenced 1 January 2003 immediately after s 75K was ins into the Workplace Health and Safety Regulation 1997 by the Workplace Health and Safety Amendment Regulation (No. 3) 2002, s 8 (see s 2(2))

Electrical Safety Regulation 2002 SL No. 260 ss 1–2, 235 sch 7

notfd gaz 27 September 2002 pp 340–4

ss 1–2 commenced on date of notification

remaining provisions commenced 1 October 2002 (see s 2)

Note—A regulatory impact statement and explanatory note were prepared.

Workplace Health and Safety Amendment Regulation (No. 6) 2002 SL No. 261

notfd gaz 27 September 2002 pp 340–4

ss 1, 3 commenced on date of notification

remaining provisions commenced 1 November 2002 (see s 3)

Workplace Health and Safety Amendment Regulation (No. 7) 2002 SL No. 290

notfd gaz 1 November 2002 pp 759–62

commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 8) 2002 SL No. 313

notfd gaz 22 November 2002 pp 1018–21

ss 1–2 commenced on date of notification

remaining provisions commenced 1 February 2003 (see s 2)

Workplace Health and Safety Amendment Regulation (No. 1) 2003 SL No. 68

notfd gaz 17 April 2003 pp 1386–7

ss 1–2 commenced on date of notification

remaining provisions commenced 1 July 2003 (see s 2)

Note—A regulatory impact statement and explanatory note were prepared.

Workplace Health and Safety Amendment Regulation (No. 2) 2003 SL No. 102 pts 1–2

notfd gaz 30 May 2003 pp 371–6

ss 1–2 commenced on date of notification

remaining provisions commenced 1 June 2003 (see s 2)

Workers' Compensation and Rehabilitation Regulation 2003 SL No. 119 ss 1–2, 121 sch 7

notfd gaz 20 June 2003 pp 633–6

ss 1–2 commenced on date of notification

remaining provisions commenced 1 July 2003 (see s 2)

Workplace Health and Safety Amendment Regulation (No. 3) 2003 SL No. 169

notfd gaz 18 July 2003 pp 1016–17

commenced on date of notification

Workplace Health and Safety Amendment Regulation (No. 4) 2003 SL No. 235

notfd gaz 26 September 2003 pp 298–9

ss 1–2 commenced on date of notification

ss 3–7, 9 commenced 31 December 2003 (see s 2(1))

s 8 commenced 1 February 2004 (see s 2(2))

Note—A national regulatory impact statement was prepared.

Workplace Health and Safety Amendment Regulation (No. 1) 2004 SL No. 142 pts 1, 3

notfd gaz 30 July 2004 pp 1009–10

commenced on date of notification

Note—An explanatory note was prepared.

Workplace Health and Safety Amendment Regulation (No. 2) 2004 SL No. 256

notfd gaz 26 November 2004 pp 1040–2

commenced on date of notification

Workers' Compensation and Rehabilitation and Other Legislation Amendment Regulation (No. 1) 2004 SL No. 289 ss 1–2(1)–(2), pt 3

notfd gaz 17 December 2004 pp 1277–85

ss 1–2 commenced on date of notification

ss 21–23, 26–27, 31, 33 commenced 1 February 2005 (see s 2(2))

s 30 commenced 1 January 2005 (see s 2(1))

remaining provisions commenced on date of notification

Note—An explanatory note was prepared.

Workplace Health and Safety Amendment Regulation (No. 3) 2004 SL No. 290 pts 1–2

notfd gaz 17 December 2004 pp 1277–85

ss 1–2 commenced on date of notification

remaining provisions commenced 1 January 2005 (see s 2)

Workplace Health and Safety Amendment Regulation (No.1) 2005 SL No. 70

notfd gaz 29 April 2005 pp 1392–5

ss 1–2 commenced on date of notification

remaining provisions commenced 1 May 2005 (see s 2)

Note—A regulatory impact statement and explanatory note were prepared.

Workers' Compensation and Rehabilitation and Other Legislation Amendment Regulation (No. 1) 2005 SL No. 308 pts 1, 3, s 17 sch

notfd gaz 16 December 2005 pp 1490–6

ss 1–2, 17, 54, 56 (to the extent it ins pt 23 div 5 hdg, s 242), 59–60, 63(1), sch items 7–10, 13, 20, 23, 27–28, 40, 44, 52–53 commenced on date of notification

s 57 commenced 1 February 2006 (see s 2(2))

s 17 sch amdt 18 commenced 1 January 2006 (see s 2(1)) (amdt could not be given effect)

remaining provisions commenced 1 January 2006 (see s 2(1))

Note—Two regulatory impact statements and an explanatory note were prepared.

Building Regulation 2006 SL No. 227 ss 1–2, pt 16

notfd gaz 18 August 2006 pp 1821–5

ss 1–2 commenced on date of notification

remaining provisions commenced 1 September 2006 immediately after the commencement of s 5 of the Building and Other Legislation Amendment Act 2006 No. 36 (see s 2 and 2006 SL No. 226)

Education (General Provisions) Regulation 2006 SL No. 246 ss 1, 2(1), 90(2) sch 2

notfd gaz 6 October 2006 pp 577–80

ss 1–2 commenced on date of notification

remaining provisions commenced 1 January 2007 (see s 2(1))

Workplace Health and Safety Amendment Regulation 2006 SL No. 312

notfd gaz 15 December 2006 pp 1861–5

ss 1–2 commenced on date of notification

s 5 commenced 1 February 2007 (see s 2)

remaining provisions commenced on date of notification

Workers' Compensation and Rehabilitation and Another Regulation Amendment Regulation (No. 1) 2007 SL No. 12 pts 1, 3

notfd gaz 16 February 2007 pp 760–1

ss 1–2, 8(2) commenced on date of notification

s 8(1) commenced 1 April 2007 (see s 2(2))

remaining provisions commenced 1 January 2007 (see s 2(1))

Workplace Health and Safety Amendment Regulation (No. 1) 2007 SL No. 75

notfd gaz 4 May 2007 pp 116–17

commenced on date of notification

Note—A regulatory impact statement and an explanatory note were prepared.

Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2007 SL No. 115 pts 1–2 (this regulation is amended, see amending legislation below)

notfd gaz 15 June 2007 pp 892–5

ss 1–2 commenced on date of notification

pt 2 div 3 commenced 1 July 2008 (see s 2(2))

remaining provisions commenced 1 July 2007 (see s 2(1))

Note—A national regulatory impact statement and explanatory note were prepared.

amending legislation—

Workplace Health and Safety Legislation Amendment Regulation (No. 1)

2007 SL No. 310 pts 1, 3 (amends 2007 SL No. 115 above)

notfd gaz 7 December 2007 pp 1978–82

ss 1–2 commenced on date of notification

remaining provisions commenced 1 February 2008 (see s 2)

Workplace Health and Safety Legislation Amendment Regulation (No. 1) 2007 SL No. 310 pts 1–2

notfd gaz 7 December 2007 pp 1978–82

ss 1–2 commenced on date of notification

ss 5(3), 7–8 commenced 1 February 2008 (see s 2)

remaining provisions commenced on date of notification

Queensland Heritage and Other Legislation Amendment Regulation (No. 1) 2008 SL No. 74 pts 1, 5

notfd gaz 20 March 2008 pp 1598–9

ss 1–2 commenced on date of notification

remaining provisions commenced 31 March 2008 (see s 2)

Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2008 SL No. 189 pts 1–2

notfd gaz 27 June 2008 pp 1268–78

ss 1–2 commenced on date of notification

ss 3, 27 commenced at the end of 30 June 2008 (see s 2(1))

remaining provisions commenced 1 July 2008 immediately after the commencement of the Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2007 SL No. 115 pt 2 div 3 (see s 2(2))

Note—An explanatory note was prepared.

7 List of annotations

References to standards

s 3A ins 2001 SL No. 100 s 3

amd 2003 SL No. 169 s 3; 2005 SL No. 308 s 18

References to the doing of work by employer

s 3B ins 2002 SL No. 109 s 4

References to the doing of work by person who conducts a business or undertaking

s 3BA ins 2005 SL No. 70 s 4

References to person who conducts a business or undertaking

s 3BB ins 2005 SL No. 70 s 4

om 2005 SL No. 308 s 17 sch

Notes in text

s 3C ins 2004 SL No. 290 s 4

Fees

s 4 amd 2004 SL No. 289 s 21

PART 2—REGISTRABLE PLANT AND REGISTRABLE PLANT DESIGN**pt hdg** sub 2004 SL No. 289 s 22**Division 1—Registration of registrable workplaces****div 1 (ss 5–9)** om 2004 SL No. 289 s 23**Registration of registrable plant****s 11** amd 2005 SL No. 308 s 17 sch**Division 3—Registration of registrable plant design****div hdg** sub 2004 SL No. 142 s 5**Application of div 3****s 15** amd 2002 SL No. 260 s 235 sch 7
sub 2004 SL No. 142 s 5**Plant not to be installed or used unless certificate of registration is in force****s 16** sub 2004 SL No. 142 s 5
amd 2004 SL No. 289 s 24; 2005 SL No. 308 s 17 sch**When certificate of registration is in force****s 16A** ins 2004 SL No. 142 s 5**Certificate number to be given****s 16B** ins 2004 SL No. 142 s 5**Certificate number to be marked on plant****s 16C** ins 2004 SL No. 142 s 5
amd 2004 SL No. 289 s 25; 2005 SL No. 308 s 17 sch**PART 3—HIGH RISK WORK AND OPERATION OF EARTHMOVING
EQUIPMENT AND PARTICULAR CRANE****pt hdg** sub 2007 SL No. 115 s 43**Division 1A—Definitions****div hdg** ins 2008 SL No. 189 s 4**Meaning of “assessment instrument”****s 16D** ins 2008 SL No. 189 s 4**Meaning of “unit of competency”****s 16E** ins 2008 SL No. 189 s 4**Division 1—Performing high risk work****div hdg** amd 2000 SL No. 288 s 4
sub 2007 SL No. 115 s 43**Authority to perform high risk work****s 17** sub 2000 SL No. 288 s 5
amd 2005 SL No. 308 s 19; 2007 SL No. 115 s 4
sub 2007 SL No. 115 s 43
amd 2008 SL No. 189 s 5**Work incidental to high risk work****s 18** sub 2007 SL No. 115 s 43

Application for licence to perform a class of high risk work or for variation of licence

- s 19** amd 2000 SL No. 288 s 6; 2000 SL No. 288 s 16; 2005 SL No. 308 ss 20, 17
sch; 2007 SL No. 115 s 5
sub 2007 SL No. 115 s 43

Application for exemption from holding licence

- s 20** prev s 20 om 2000 SL No. 288 s 7
pres s 20 ins 2007 SL No. 115 s 6
sub 2007 SL No. 115 s 43

Decision on application for exemption

- s 20A** ins 2007 SL No. 115 s 6
om 2007 SL No. 115 s 43

Decision on application for exemption

- s 21** amd 2007 SL No. 115 s 7
sub 2007 SL No. 115 s 43

Licence holder to notify change of address

- s 22** sub 2007 SL No. 115 s 43

Holder to make licence issued by recognised official available for inspection

- s 23** prev s 23 om 2005 SL No. 308 s 21
pres s 23 ins 2007 SL No. 115 s 43

Division 2—Performing work in an earthmoving or particular crane occupation

- div hdg** sub 2007 SL No. 115 s 43

Authority to perform work in an earthmoving or particular crane occupation

- s 24** sub 2007 SL No. 115 s 43
amd 2008 SL No. 189 s 6

Work incidental to earthmoving or particular crane operation

- s 25** sub 2007 SL No. 115 s 43

Certificate holder to notify change of address

- s 26** prev s 26 om 2005 SL No. 308 s 22
pres s 26 ins 2007 SL No. 115 s 8
sub 2007 SL No. 115 s 43
om 2008 SL No. 189 s 7

Application for earthmoving or particular crane work certificate

- s 27** prev s 27 om 2005 SL No. 308 s 22
pres s 27 ins 2007 SL No. 115 s 8
sub 2007 SL No. 115 s 43

Application for exemption from holding certificate

- s 28** prev s 28 om 2005 SL No. 308 s 22
pres s 28 ins 2007 SL No. 115 s 8
sub 2007 SL No. 115 s 43

Decision on application for exemption

- s 28A** ins 2007 SL No. 115 s 43

Holder to make certificate issued by recognised official available for inspection

- s 28B** ins 2007 SL No. 115 s 43

Division 3—Training in work in an earthmoving or particular crane occupation or high risk work

div hdg prev div 3 hdg om 2005 SL No. 308 s 22
 pres div 3 hdg ins 2007 SL No. 115 s 8
 sub 2007 SL No. 115 s 43

Meaning of “trainee”

s 28C ins 2007 SL No. 115 s 43
 sub 2008 SL No. 189 s 8

Employer’s duties for training

s 28CA ins 2008 SL No. 189 s 8

What training plan must state

s 28CB ins 2008 SL No. 189 s 8

Supervisor’s duty for training

s 28D ins 2007 SL No. 115 s 43

Trainee’s duty for training

s 28E ins 2007 SL No. 115 s 43

Supervisor to sign entry in training record

s 28F ins 2007 SL No. 115 s 43

Division 3A—Employer’s obligation if worker is undergoing assessment for suitability to perform work

div 3A (s 28FA) ins 2008 SL No. 189 s 9

Division 4—Other obligations

div hdg ins 2007 SL No. 115 s 8
 sub 2007 SL No. 115 s 43

Employer must reasonably believe worker is competent

s 28G ins 2007 SL No. 115 s 43

Holder of certificate or licence must reasonably believe he or she is competent

s 28H ins 2007 SL No. 115 s 43

Holder of certificate or licence must take reasonable precautions and exercise proper diligence

s 28I ins 2007 SL No. 115 s 43

Division 5—Revival of authority formerly conferred by certificate of competency for work in an occupation

div hdg ins 2007 SL No. 115 s 43

Revival of authority

s 28J ins 2007 SL No. 115 s 43
 amd 2008 SL No. 189 s 10

Division 6—Conversion of certificate of competency for work in an occupation to licence to perform a class of high risk work or other certificate

div hdg ins 2007 SL No. 115 s 43

Conversion of certificates

s 28K ins 2007 SL No. 115 s 43
amd 2008 SL No. 189 s 11

Division 7—Expiry of licences to perform class of high risk work issued before July 2008 unless holder converts licence to a renewable licence

div hdg ins 2007 SL No. 115 s 43

Pre-July 2008 licence to perform a class of high risk work will end unless converted to a renewable licence

s 28L ins 2007 SL No. 115 s 43
amd 2008 SL No. 189 s 12

How to convert a pre-July 2008 licence to perform a class of high risk work to a renewable licence

s 28M ins 2007 SL No. 115 s 43

Decision on application to convert to a renewable licence

s 29 prev s 29 om 2005 SL No. 308 s 22
pres s 29 ins 2007 SL No. 115 s 8
sub 2007 SL No. 115 s 43

Notice about ending of pre-July 2008 licence to perform a class of high risk work to be given to holder

s 29A prev s 29A ins 2000 SL No. 288 s 8
om 2005 SL No. 308 s 17 sch
pres s 29A ins 2007 SL No. 115 s 43

PART 3A—PRESCRIBED ACTIVITIES**Division 1—Certificate to perform prescribed activity**

div hdg prev div 1 hdg ins 2000 SL No. 288 s 8
om 2005 SL No. 308 s 17 sch
pres div 1 hdg (prev div 2 hdg) renum 2005 SL No. 308 s 17 sch

Certificate to perform prescribed activity

s 29B ins 2000 SL No. 288 s 8
sub 2005 SL No. 308 s 23
amd 2007 SL No. 115 s 9

Application for certificate to perform prescribed activity

s 29C ins 2000 SL No. 288 s 8
amd 2005 SL No. 308 ss 24, 17 sch; 2007 SL No. 115 s 10

Continuing to satisfy approved criteria

s 29D ins 2000 SL No. 288 s 8
amd 2005 SL No. 308 s 17 sch

Division 2—Training and supervision in prescribed activities

div hdg (prev div 3 hdg) renum 2005 SL No. 308 s 17 sch

Employer's duty for training in prescribed activity

s 29E ins 2000 SL No. 288 s 8

Supervision of performance of prescribed activity

s 29F ins 2000 SL No. 288 s 8
amd 2005 SL No. 308 s 25; 2007 SL No. 115 s 11

Division 4—Suspension and cancellation of certificate

div hdg ins 2000 SL No. 288 s 8
om 2005 SL No. 308 s 26

PART 3B—BONDED ASBESTOS REMOVAL CERTIFICATE

pt hdg ins 2007 SL No. 115 s 12

Application of pt 3B

s 29G prev s 29G ins 2000 SL No. 288 s 8
om 2005 SL No. 308 s 26
pres s 29G ins 2007 SL No. 115 s 12

Authority to perform work to remove bonded asbestos containing material

s 29H prev s 29H ins 2000 SL No. 288 s 8
om 2005 SL No. 308 s 26
pres s 29H ins 2007 SL No. 115 s 12

Application for bonded asbestos removal certificate

s 29I prev s 29I ins 2000 SL No. 288 s 8
om 2005 SL No. 308 s 26
pres s 29I ins 2007 SL No. 115 s 12

Term of certificate

s 29J ins 2007 SL No. 115 s 12

Certificate holder to notify change of address

s 29K ins 2007 SL No. 115 s 12

PART 4—WORKPLACE HEALTH AND SAFETY OFFICERS

pt hdg sub 2005 SL No. 308 s 27

Division 1—Workplace health and safety officers

div hdg om 2005 SL No. 308 s 27

Workplaces requiring a workplace health and safety officer—Act, s 93

s 30 amd 2005 SL No. 308 s 28

Application for certificate of authority of appointment

prov hdg sub 2005 SL No. 308 s 29(1)
s 31 amd 2005 SL No. 308 ss 29(2)–(3), 17 sch; 2007 SL No. 115 s 13

Division 2—Accredited providers

div hdg om 2005 SL No. 308 s 30

PART 4A—ACCREDITED PROVIDERS, REGISTERED TRAINING ORGANISATIONS, APPROVALS AND RELATED MATTERS

pt hdg ins 2005 SL No. 308 s 30
sub 2007 SL No. 115 s 14; 2008 SL No. 189 s 13

Division 1—Accredited providers

div hdg ins 2008 SL No. 189 s 13

Application for appointment as an accredited provider**s 33** amd 2005 SL No. 308 ss 31, 17 sch**Authorised accredited provider to make record of assessment and give a copy to applicant****s 33AA** (prev s 33B) ins 2005 SL No. 308 s 32
sub 2007 SL No. 115 s 16
renum and reloc 2008 SL No. 189 s 14**Record of assessment by authorised accredited provider before 1 July 2007****s 33AB** (prev s 33C) ins 2007 SL No. 115 s 16
renum and reloc 2008 SL No. 189 s 14**Division 2—Duties, and monitoring, of registered training organisations****div hdg** ins 2008 SL No. 189 s 15**Registered training organisation's duty for assessing competency****s 33A** ins 2005 SL No. 308 s 32
amd 2007 SL No. 115 s 15**When registered training organisation must not make practical assessment****s 33B** ins 2008 SL No. 189 s 16**Registered training organisation's duties before issuing statement of attainment****s 33C** ins 2008 SL No. 189 s 16**Record of assessment by registered training organisation****s 33D** ins 2007 SL No. 115 s 16
amd 2008 SL No. 189 s 17**Other duties of registered training organisation****s 33E** ins 2008 SL No. 189 s 19**Monitoring of registered training organisation's compliance****s 33F** ins 2008 SL No. 189 s 19**Division 3—False documents****div hdg** ins 2008 SL No. 189 s 19**Person must not sign false assessment summary****s 33G** (prev s 33G) ins 2007 SL No. 115 s 16
renum 2008 SL No. 189 s 18**Making available document purporting to be statement of attainment****s 33H** ins 2008 SL No. 189 s 20**Division 4—Approval of individual to provide training and assessment****div 4 (ss 33I–33L)** ins 2008 SL No. 189 s 20**Division 5—Suspension and cancellation of training approval****div 5 (ss 33M–33P)** ins 2008 SL No. 189 s 20**PART 5—CERTIFICATES AND LICENCES****pt hdg** sub 2007 SL No. 115 s 44**Division 1—Definitions****div hdg** sub 2005 SL No. 308 s 33; 2007 SL No. 115 s 44

Definitions for pt 5

- prov hdg** sub 2005 SL No. 308 s 34(1)
s 34 amd 2005 SL No. 308 s 34(2)
 sub 2007 SL No. 115 s 44
 def “**certificate**” amd 2000 SL No. 288 s 9; 2004 SL No. 289 s 26; ; 2007 SL No. 115 s 17
 sub 2007 SL No. 115 s 44
 def “**licence**” ins 2007 SL No. 115 s 44
 def “**variation of licence**” ins 2007 SL No. 115 s 44

Division 1A—Applications for certificates, licences and variations of licences

- div hdg** ins 2005 SL No. 308 s 35
 sub 2007 SL No. 115 s 44

Subdivision 1—Certificates, licences and variations of licences generally

- sdiv hdg** ins 2005 SL No. 308 s 35
 sub 2007 SL No. 115 s 44

How to apply for a certificate, other than an earthmoving or particular crane work certificate

- s 35** amd 2004 SL No. 142 s 6; 2005 SL No. 308 s 36; 2007 SL No. 115 s 18
 sub 2007 SL No. 115 s 44
 amd 2008 SL No. 189 s 21

Prohibitions relating to design verification statements

- s 35A** ins 2004 SL No. 142 s 7
 om 2005 SL No. 308 s 37

Chief executive may ask for additional information for registration

- s 35B** ins 2004 SL No. 142 s 7
 om 2005 SL No. 308 s 37

Chief executive may require information from certificate holder

- s 35C** ins 2004 SL No. 142 s 7
 om 2005 SL No. 308 s 37

How to apply for an earthmoving or particular crane work certificate

- s 36** sub 2007 SL No. 115 s 44

Eligibility to obtain particular licence classes

- s 36A** prev s 36A ins 2005 SL No. 308 s 38
 prev s 36A om 2007 SL No. 115 s 44
 pres s 36A ins 2008 SL No. 189 s 22

Refusal to grant certificate—false assessment summary

- s 36B** ins 2007 SL No. 115 s 19
 om 2007 SL No. 115 s 44

How to apply for a licence or variation of a licence to endorse another class of high risk work

- s 37** sub 2007 SL No. 115 s 44
 amd 2008 SL No. 189 s 23

If applicant for licence or variation of a licence holds a corresponding authority to licence or licence class**s 37A** ins 2008 SL No. 189 s 24**How to apply for a variation of a licence to remove a class of high risk work****s 38** amd 2007 SL No. 115 s 20

sub 2007 SL No. 115 s 44

Refusal to grant licence or variation for applicant's misconduct**s 38A** ins 2007 SL No. 115 s 44**Refusal to grant certificate, licence or variation—false assessment summary****s 38B** ins 2007 SL No. 115 s 44

amd 2008 SL No. 189 s 25

Refusal to grant earthmoving or particular crane work certificate for applicant's misconduct**s 38C** ins 2007 SL No. 115 s 44**Refusal of application for lack of competence or for misconduct****s 38D** ins 2007 SL No. 115 s 44**Refusal of applications for particular certificates****s 38E** ins 2007 SL No. 115 s 44**Chief executive to decide application within 28 days****s 38F** ins 2007 SL No. 115 s 44**Grant of certificate, licence or variation of a licence****s 38G** ins 2007 SL No. 115 s 44**Notice of refusal of application****s 38H** ins 2007 SL No. 115 s 44**Grant of certificate, licence or variation of licence on conditions****s 38I** ins 2007 SL No. 115 s 44**Term of licence****s 38J** ins 2007 SL No. 115 s 44**Subdivision 1A—Renewal of licences****sdiv hdg** ins 2007 SL No. 115 s 44**When licence may be renewed****s 38K** ins 2007 SL No. 115 s 44**How to apply for renewal of a licence****s 38L** ins 2007 SL No. 115 s 44**Renewal of licences****s 38M** ins 2007 SL No. 115 s 44**Refusal to renew licence for lack of competence****s 38N** ins 2007 SL No. 115 s 44**Notice of refusal of application****s 39** sub 2007 SL No. 115 s 44

Subdivision 2—Provisions about certificates of registration of registrable plant design**sdiv 2** (ss 39A–39F) ins 2005 SL No. 308 s 39**Subdivision 3—Provisions about certificates of registration of registrable plant that is mobile crane or tower crane****sdiv hdg** ins 2005 SL No. 308 s 39**Application of sdiv 3****s 39G** ins 2005 SL No. 308 s 39**Definitions for sdiv 3****s 39H** ins 2005 SL No. 308 s 39def “**certificate of registration of a mobile crane or tower crane**” ins 2007 SL No. 310 s 4(2)def “**competent person**” amd 2007 SL No. 310 s 4(1)**Application for certificate of registration of a mobile crane or tower crane****prov hdg** amd 2007 SL No. 310 s 5(1)**s 39I** ins 2005 SL No. 308 s 39
amd 2007 SL No. 310 s 5(2)–(3)**Application under s 39I if engineer can not inspect because of unforeseeable circumstances****s 39J** ins 2007 SL No. 310 s 6
exp 31 January 2011 (see s 39J(3))**Definition for div 2****s 40** amd 2000 SL No. 288 s 10
sub 2004 SL No. 289 s 27
def “**certificate**” amd 2007 SL No. 115 s 21**Application for renewal before registration ends****s 42** amd 2005 SL No. 308 s 17 sch**Div 1A applies to application for renewal****prov hdg** amd 2005 SL No. 308 s 40(1)
s 43 amd 2005 SL No. 308 s 40(2)–(4)**Definition****s 44** om 2005 SL No. 308 s 17 sch**Division 3—Replacement and surrender of certificates and licences****div hdg** sub 2007 SL No. 115 s 45**Replacement of certificate or licence****s 45** sub 2007 SL No. 115 s 45
amd 2008 SL No. 189 s 26**Surrender of certificate or licence****s 46** amd 2007 SL No. 115 s 22
sub 2007 SL No. 115 s 45**Division 4—Suspension and cancellation of certificates and licences****div hdg** ins 2005 SL No. 308 s 41
sub 2007 SL No. 115 s 45

Grounds for suspension or cancellation

s 46A ins 2005 SL No. 308 s 41
sub 2007 SL No. 115 s 45

Procedure for suspension or cancellation

s 46B ins 2005 SL No. 308 s 41
sub 2007 SL No. 115 s 45

Immediate suspension of earthmoving or particular crane work certificate, licence or licence class

s 46C ins 2005 SL No. 308 s 41
sub 2007 SL No. 115 s 45

Further provision about immediate suspension

s 46D ins 2005 SL No. 308 s 41
sub 2007 SL No. 115 s 45

Suspension or cancellation of earthmoving or particular crane work certificate, licence or licence class on recommendation of recognised official

s 46E prev s 46E ins 2007 SL No. 115 s 23
om 2008 SL No. 189 s 27
pres s 46E ins 2007 SL No. 115 s 45

Ending of licence if application for corresponding authority

s 46EA ins 2008 SL No. 189 s 28

Chief executive may advise recognised official of particular matters

s 46EB ins 2008 SL No. 189 s 28

Requirement for retraining

s 46F ins 2007 SL No. 115 s 45

Certificate or licence to be returned

s 46G ins 2007 SL no. 115 s 45

Replacement licence to be issued for remaining licence class

s 46H ins 2007 SL No. 115 s 45

Division 5—Obligation of relevant person

div hdg prev div 5 hdg ins 2007 SL No. 115 s 23
om 2008 SL No. 189 s 27
pres div 5 hdg ins 2007 SL No. 115 s 45

Way to prevent or minimise risk prescribed

s 46I ins 2007 SL No. 115 s 45

Division 6—Miscellaneous

div 6 (ss 46J–46K) ins 2008 SL No. 189 s 29

Notification of building and construction work

s 47 amd 1998 SL No. 318 s 4

Exemption from payment of fees

s 48 amd 1998 SL No. 318 s 5; 2007 SL No. 115 s 24

Start and finish of building and construction work

s 51 amd 2007 SL No. 115 s 25

Notifying of particular workplace incidents**prov hdg** sub 2003 SL No. 102 s 4(1)**s 52** amd 2002 SL No. 109 s 5; 2003 SL No. 102 s 4(2)–(4); 2005 SL No. 308 s 42**Recording particular workplace incidents****prov hdg** sub 2003 SL No. 102 s 5(1)**s 53** amd 2002 SL No. 109 s 6; 2003 SL No. 102 s 5(2)–(4); 2005 SL No. 308 s 43**PART 7A—ACCESS—EMPLOYERS DOING WORK THAT IS NOT CONSTRUCTION WORK****pt 7A (s 54A)** ins 2004 SL No. 290 s 5**PART 8—CONSTRUCTION WORKPLACE PLANS, WORK METHOD STATEMENTS AND INDUCTIONS****pt hdg** sub 2002 SL No. 109 s 7

om 2005 SL No. 308 s 44

Division 1—Interpretation**div hdg** sub 2002 SL No. 109 s 7

om 2005 SL No. 308 s 44

Definitions for pt 8**s 55** amd 2000 SL No. 288 s 17

sub 2002 SL No. 109 s 7

om 2005 SL No. 308 s 44

Meaning of “construction workplace plan”**s 56** amd 1998 SL No. 88 s 3; 2000 SL No. 288 s 11

sub 2002 SL No. 109 s 7

om 2005 SL No. 308 s 44

Meaning of “high risk construction activity”**s 57** sub 2002 SL No. 109 s 7

amd 2003 SL No. 102 s 6

om 2005 SL No. 308 s 44

Meaning of “work method statement” for a high risk construction activity**s 58** sub 2002 SL No. 109 s 7

om 2005 SL No. 308 s 44

Meaning of “work method statement” for a prescribed activity that is demolition work**s 59** sub 2002 SL No. 109 s 7

om 2005 SL No. 308 s 44

Work method statements may be generic**s 60** sub 2002 SL No. 109 s 7

om 2005 SL No. 308 s 44

Division 2—Principal contractors**div hdg** sub 2002 SL No. 109 s 7

om 2005 SL No. 308 s 44

Subdivision 1—Construction workplace plans and work method statements for construction workplaces

sdiv hdg ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Application of sdiv 1

s 61 sub 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Principal contractor must ensure construction workplace plan is prepared

s 62 amd 2000 SL No. 288 s 18
sub 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Work method statements or amended work method statements to be kept with construction workplace plan

s 63 sub 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Principal contractor must not allow work to start unless particular things have been done

s 64 sub 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 7
om 2005 SL No. 308 s 44

Principal contractor to monitor implementation of work method statement

s 65 sub 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Current construction workplace plan to be available for inspection

s 65A ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 8
om 2005 SL No. 308 s 44

Amendment of construction workplace plan

s 65B ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Subdivision 2—Work method statements for a prescribed activity that is demolition work

sdiv hdg ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Application of sdiv 2

s 65C ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Work method statement to be prepared and given

s 65D ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Activity must not be allowed to start unless particular things have been done

s 65E ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Activity not to be performed unless in compliance with work method statement

s 65F ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Amendment of work method statement

s 65G ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Availability and review of work method statement

s 65H ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 9
om 2005 SL No. 308 s 44

Subdivision 3—Workplace health and safety inductions

sdiv hdg ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Application of sdiv 3

s 65I ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Principal contractor must sight general induction evidence before work starts

s 65J ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 10
om 2005 SL No. 308 s 44

Site-specific induction to be given

s 65K ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 11
om 2005 SL No. 308 s 44

Division 3—Employers and self-employed persons

div hdg sub 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Subdivision 1—Work method statements

sdiv hdg ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Application of sdiv 1

s 65L ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Work method statement to be prepared and given

s 65M ins 2002 SL No. 109 s 7
amd 2002 SL No. 232 s 4
om 2005 SL No. 308 s 44

Activity must not be allowed to start unless particular things have been done

s 65N ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Activity not to be performed unless in compliance with work method statement

s 65O ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Amendment of work method statement

s 65P ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Availability and review of work method statement

s 65Q ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 12
om 2005 SL No. 308 s 44

Subdivision 2—Workplace health and safety inductions

sdiv hdg ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Application of sdiv 2

s 65R ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 13
om 2005 SL No. 308 s 44

Employer must ensure general induction evidence is held before work starts

s 65S ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 14
om 2005 SL No. 308 s 44

Self-employed person must hold general induction evidence before work starts

s 65T ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 15
om 2005 SL No. 308 s 44

Division 4—Workers

div hdg sub 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Worker must hold general induction evidence before work starts

s 65U ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 16
om 2005 SL No. 308 s 44

PART 8A—SAFE HOUSEKEEPING PRACTICES FOR CONSTRUCTION WORK

pt hdg ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 17
om 2005 SL No. 308 s 44

Division 1—Principal contractors

div 1 (ss 65V–65W) ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

Division 2—Employers or self-employed persons

div hdg ins 2002 SL No. 109 s 7
om 2005 SL No. 308 s 44

What are safe housekeeping practices for an employer or self-employed person

s 65X ins 2002 SL No. 109 s 7
amd 2003 SL No. 102 s 18
om 2005 SL No. 308 s 44

Employer's or self-employed person's obligation about safe housekeeping practices

s 65Y ins 2002 SL No. 109 s 7
 amd 2003 SL No. 102 s 19
 om 2005 SL No. 308 s 44

PART 8B—COMMON PLANT AT A CONSTRUCTION WORKPLACE

pt hdg ins 2002 SL No. 109 s 7
 om 2005 SL No. 308 s 44

Division 1—Interpretation

div 1 (s 65Z) ins 2002 SL No. 109 s 7
 om 2005 SL No. 308 s 44

Division 2—Principal contractors

div 2 (s 65ZA) ins 2002 SL No. 109 s 7
 om 2005 SL No. 308 s 44

Division 3—Employers or self-employed persons

div 3 (s 65ZB) ins 2002 SL No. 109 s 7
 om 2005 SL No. 308 s 44

PART 9—HAZARDOUS SUBSTANCES AT CONSTRUCTION WORKPLACES

pt 9 (ss 66–67) om 2005 SL No. 308 s 44

What is “excessive noise”

s 68 amd 2001 SL No. 100 s 4; 2002 SL No. 7 s 4; 2003 SL No. 169 s 4; 2005 SL No. 308 s 45

Preventing risk from exposure to excessive noise

s 69 sub 2005 SL No. 308 s 46

PART 11—ASBESTOS REMOVAL AND MANAGEMENT

pt hdg amd 2000 SL No. 249 s 3
 sub 2005 SL No. 308 s 47; 2007 SL No. 115 s 26

Division 1—Interpretation

div hdg sub 2000 SL No. 249 s 4; 2005 SL No. 308 s 47

Definitions for pt 11

s 69A ins 2000 SL No. 249 s 4
 amd 2002 SL No. 290 s 3
 sub 2005 SL No. 308 s 47
 def “**asbestos removalist**” om 2007 SL No. 115 s 27

Division 2—Prohibitions relating to asbestos

div hdg sub 2000 SL No. 249 ss 4–5; 2005 SL No. 308 s 47

Prohibited substances and prohibited ACM

s 69B ins 2000 SL No. 249 s 4
 sub 2005 SL No. 308 s 47

Performing work on ACM

s 69C ins 2000 SL No. 249 s 4
 sub 2005 SL No. 308 s 47

Removing ACM

s 69D ins 2000 SL No. 249 s 4
 sub 2005 SL No. 308 s 47
 amd 2007 SL No. 115 s 28

Cleaning ACM

s 69E ins 2000 SL No. 249 s 4
 amd 2004 SL No. 142 s 8
 sub 2005 SL No. 308 s 47

Asbestos materials register

s 69F ins 2000 SL No. 249 s 4
 om 2005 SL No. 308 s 47

Controlling exposure to asbestos

s 69G ins 2000 SL No. 249 s 4
 om 2005 SL No. 308 s 47

Division 3—On-site management of ACM

div hdg sub 2000 SL No. 249 ss 6–7; 2003 SL No. 235 s 4; 2005 SL No. 308 s 47

Subdivision 1—Particular buildings

sdiv hdg ins 2005 SL No. 308 s 47

Application of sdiv 1

s 70 sub 2005 SL No. 308 s 47

Compliance with asbestos management code

s 71 sub 2005 SL No. 308 s 47

Subdivision 2—Particular structures

sdiv hdg ins 2005 SL No. 308 s 47

Application of sdiv 2

s 72 sub 2005 SL No. 308 s 47

Compliance with asbestos management code

s 73 sub 2005 SL No. 308 s 47

Division 4—Asbestos removal work

div hdg ins 2002 SL No. 109 s 8
 sub 2005 SL No. 308 s 47

Performing asbestos removal work

s 74 sub 2005 SL No. 308 s 47
 amd 2007 SL No. 115 s 29

Dismantling containment barrier

s 75 om 2005 SL No. 308 s 47

Prohibition for employers—particular activities involving asbestos

prov hdg amd 2000 SL No. 249 s 8(1)
s 75A (prev s 96) amd 2000 SL No. 249 s 8(2)
 reloc and renum 2000 SL No. 249 s 8(3)
 sub 2003 SL No. 235 s 5
 om 2005 SL No. 308 s 47

Prohibition for self-employed persons—particular activities involving asbestos

- s 75B** (prev s 115) reloc and renum 2000 SL No. 249 s 9
 sub 2003 SL No. 235 s 5
 om 2005 SL No. 308 s 47

Subdivision 1—Work method statements

- sdiv hdg** ins 2002 SL No. 109 s 8
 om 2005 SL No. 308 s 47

Meaning of “work method statement” for prescribed activity that is the removal of asbestos materials

- s 75C** ins 2002 SL No. 109 s 8
 om 2005 SL No. 308 s 47

Work method statement may be generic

- s 75D** ins 2002 SL No. 109 s 8
 om 2005 SL No. 308 s 47

Application of sdiv 1

- s 75E** ins 2002 SL No. 109 s 8
 amd 2003 SL No. 102 s 20
 om 2005 SL No. 308 s 47

Work method statement must be prepared

- s 75F** ins 2002 SL No. 109 s 8
 om 2005 SL No. 308 s 47

Activity must not be allowed to start unless particular things have been done

- s 75G** ins 2002 SL No. 109 s 8
 om 2005 SL No. 308 s 47

Activity not to be performed unless in compliance with work method statement

- s 75H** ins 2002 SL No. 109 s 8
 om 2005 SL No. 308 s 47

Amendment of work method statement

- s 75I** ins 2002 SL No. 109 s 8
 amd 2003 SL No. 169 s 5
 om 2005 SL No. 308 s 47

Availability and review of work method statement

- s 75J** ins 2002 SL No. 109 s 8
 amd 2003 SL No. 102 s 21
 om 2005 SL No. 308 s 47

Subdivision 2—Workplace health and safety inductions

- sdiv hdg** ins 2002 SL No. 109 s 8
 om 2005 SL No. 308 s 47

General induction evidence must be held before work starts

- s 75K** ins 2002 SL No. 109 s 8
 amd 2002 SL No. 232 s 5
 om 2005 SL No. 308 s 47

Division 5—Workers

div 5 (s 75L) ins 2002 SL No. 109 s 8
om 2005 SL No. 308 s 47

PART 12—UNDERWATER DIVING WORK

pt hdg sub 2005 SL No. 70 s 5

Division 1—Definitions for part 12

div hdg sub 2005 SL No. 70 s 5

Meaning of “underwater diving work”

s 76 amd 2001 SL No. 166 s 4; 2002 SL No. 261 s 4; 2003 SL No. 169 s 6; 2004
SL No. 142 s 9
sub 2005 SL No. 70 s 5

Meaning of “construction diving work”

s 77 sub 2005 SL No. 70 s 5
amd 2008 SL No. 74 s 18

Division 2—All underwater diving work—medical fitness to dive

div hdg sub 1999 SL No. 233 s 3; 2005 SL No. 70 s 5

Requirements about certificate of medical fitness to dive

s 78 amd 2001 SL No. 166 s 5
sub 2005 SL No. 70 s 5
amd 2005 SL No. 308 s 17 sch

Contents of certificate of medical fitness to dive

s 79 amd 2001 SL No. 166 s 6; 2003 SL No. 169 s 7
sub 2005 SL No. 70 s 5

Division 3—Underwater diving work other than conducting recreational diving or recreational technical diving

div hdg sub 2005 SL No. 70 s 5

Subdivision 1—Preliminary

sdiv hdg ins 2002 SL No. 261 s 5
sub 2005 SL No. 70 s 5

Meaning of “competent person” for subdiv 2

s 79A ins 2002 SL No. 261 s 5
om 2005 SL No. 70 s 5

Work that is not construction diving work if process carried out

s 79B ins 2002 SL No. 261 s 5
om 2005 SL No. 70 s 5

Process to be carried out each time there is a significant change

s 79C ins 2002 SL No. 261 s 5
om 2005 SL No. 70 s 5

Employer not to allow worker to start or restart work unless worker has done certain things about record of process

s 79D ins 2002 SL No. 261 s 5
om 2005 SL No. 70 s 5

Record to be kept for each time process is carried out

- s 79E ins 2002 SL No. 261 s 5
 amd 2003 SL No. 169 s 8
 om 2005 SL No. 70 s 5

Control measure to be in place and monitored and reviewed

- s 79F ins 2002 SL No. 261 s 5
 om 2005 SL No. 70 s 5

Application of div 3

- s 80 amd 2001 SL No. 166 s 7
 sub 2005 SL No. 70 s 5

Meaning of “competent person” for construction diving work

- s 81 amd 2001 SL No. 166 s 8
 sub 2005 SL No. 70 s 5

Meaning of “competent person” for other underwater diving work

- s 82 amd 2001 SL No. 166 s 9
 sub 2005 SL No. 70 s 5
 (1)(e) and (3) exp 31 October 2008 (see s 82(3))

Competent person for s 82—holder of ADAS diving certificate for the diving

- s 83 amd 2001 SL No. 166 s 10; 2003 SL No. 169 s 9
 sub 2005 SL No. 70 s 5

Competent person for s 82—holder of certification under Australian Qualifications Framework

- s 84 amd 2001 SL No. 166 s 11; 2003 SL No. 169 s 10
 sub 2005 SL No. 70 s 5

Competent person for s 82—holder of certificate for AS 4005.2 subject areas

- s 85 sub 2005 SL No. 70 s 5

Competent person for s 82—person doing underwater diving work on no more than 28 days in the last 6 months

- s 86 sub 2005 SL No. 70 s 5
 amd 2007 SL No. 115 s 30

Competent person for s 82—someone who has spent at least 15 hours doing the same type of work as the underwater diving work

- s 86AA ins 2005 SL No. 70 s 5
 amd 2007 SL No. 115 s 31
exp 31 October 2008 (see s 86AA(2))

Subdivision 2—Proof of competency for underwater diving work other than construction diving work

- sdiv hdg ins 2002 SL No. 261 s 5
 sub 2005 SL No. 70 s 5

Proof of competency

- s 86AB ins 2005 SL No. 70 s 5

Subdivision 3—Risk assessment and control measure process at particular stages

sdiv hdg ins 2002 SL No. 261 s 5
sub 2005 SL No. 70 s 5

Process to be carried out before work starts

s 86AC ins 2005 SL No. 70 s 5

Process to be carried out each time there is a significant change

s 86AD ins 2005 SL No. 70 s 5

Work not to start or restart unless diver has read, understood and signed record of process

s 86AE ins 2005 SL No. 70 s 5

Record to be kept for each time process is carried out

s 86AF ins 2005 SL No. 70 s 5

Control measure to be in place and monitored and reviewed

s 86AG ins 2005 SL No. 70 s 5

Subdivision 4—Dive safety log

sdiv 4 (ss 86AH–86AL) ins 2005 SL No. 70 s 5

Subdivision 5—Provisions relating only to construction diving work

sdiv 5 (ss 86AM–86AS) ins 2005 SL No. 70 s 5

Division 4—Conducting recreational diving or recreational technical diving

div hdg ins 1999 SL No. 233 s 4
sub 2001 SL No. 166 s 12; 2002 SL No. 261 s 6

Ways to prevent or minimise risks prescribed

s 86A ins 1999 SL No. 233 s 4
amd 2001 SL No. 166 s 13

Count of all persons on board to be made and recorded

s 86B ins 1999 SL No. 233 s 4
amd 2001 SL No. 166 s 14; 2004 SL No. 142 s 10

Medical conditions of resort divers

s 86C ins 1999 SL No. 233 s 4

Lookout and rescuer

s 86D ins 1999 SL No. 233 s 4
amd 2001 SL No. 166 s 15

Supervision of resort divers

s 86E ins 1999 SL No. 233 s 4

Dive safety log

s 86F ins 1999 SL No. 233 s 4
amd 2001 SL No. 166 s 16; 2004 SL No. 142 s 11

PART 12A—CONDUCTING RECREATIONAL SNORKELLING

pt hdg ins 1999 SL No. 233 s 4

Ways to prevent or minimise risks prescribed

s 86G ins 1999 SL No. 233 s 4

Count of all persons on board to be made and recorded

s 86H ins 1999 SL No. 233 s 4
amd 2004 SL No. 142 s 12

Advice about medical conditions

s 86I ins 1999 SL No. 233 s 4

Lookout, guide and rescuer

s 86J ins 1999 SL No. 233 s 4

PART 13—HAZARDOUS SUBSTANCES**Preparing, amending and reviewing MSDS**

s 90 amd 2005 SL No. 308 s 17 sch

Providing MSDS

s 91 amd 2005 SL No. 308 s 17 sch

Disclosing ingredient's chemical name

s 93 amd 2005 SL No. 308 s 17 sch

Providing NICNAS summary report and other information

s 94 amd 2005 SL No. 308 s 17 sch

Providing MSDS

s 97 amd 2005 SL No. 308 s 17 sch

Labelling containers

s 98 amd 1999 SL No. 276 s 3; 2005 SL No. 308 s 17 sch

Division 4—Relevant persons

div hdg sub 2005 SL No. 308 s 17 sch

Who division applies to

s 99 amd 2005 SL No. 308 s 17 sch

Meaning of “hazardous substance” for division

s 100 def “hazardous substance” amd 2005 SL No. 308 s 17 sch

Obtaining MSDS

s 101 amd 2005 SL No. 308 s 17 sch

Recording and displaying MSDS

s 102 amd 2005 SL No. 308 s 17 sch

Labelling containers

s 103 amd 1999 SL No. 276 s 4; 2005 SL No. 308 s 17 sch

Hazardous substances in enclosed systems

s 104 amd 2005 SL No. 308 s 17 sch

Risk assessments

s 105 amd 2005 SL No. 308 s 17 sch

Risk assessment records

s 106 amd 2005 SL No. 308 s 17 sch

Controlling exposure

s 107 amd 1999 SL No. 110 s 12(1); 2005 SL No. 308 s 17 sch

Monitoring

s 108 amd 2005 SL No. 308 s 17 sch

Health surveillance

s 109 amd 2005 SL No. 308 s 17 sch

Confidentiality of worker's medical record

s 110 amd 2005 SL No. 308 s 17 sch

Keeping register

s 111 sub 2003 SL No. 235 s 6
amd 2005 SL No. 308 s 17 sch

Keeping records

s 112 amd 2005 SL No. 308 s 17 sch (amdt 18 could not be given effect); 2007 SL No. 115 s 32

Induction and training about hazardous substances

s 113 amd 2005 SL No. 308 s 17 sch

Prohibited substances and asbestos products

prov hdg sub 2003 SL No. 235 s 7

s 114 amd 2003 SL No. 235 s 7
om 2005 SL No. 308 s 48

Division 5—Spray painting with hazardous substances

div hdg ins 1999 SL No. 110 s 12(2)

Ways to prevent or minimise risk prescribed

s 115A ins 1999 SL No. 110 s 12(2)
amd 1999 SL No. 110 s 12(3); 2005 SL No. 308 s 17 sch

Manufacturing or importing a spray painting booth

s 115B ins 1999 SL No. 110 s 12(2)
amd 2005 SL No. 308 s 17 sch

Supplying a spray painting booth

s 115C ins 1999 SL No. 110 s 12(2)

Protecting persons from spray painting

s 115D ins 1999 SL No. 110 s 12(2)
amd 2005 SL No. 308 s 17 sch

Spray painting to be done in spray painting booth

s 115E ins 1999 SL No. 110 s 12(2)
amd 2005 SL No. 308 s 17 sch

Controlling exposure from spray painting

s 115F ins 1999 SL No. 110 s 12(2)
amd 2005 SL No. 308 s 17 sch

Maintaining a spray painting booth

s 115G ins 1999 SL No. 110 s 12(2)
amd 2005 SL No. 308 s 17 sch

Minimum air movement for booths

s 115H ins 1999 SL No. 110 s 12(4)
amd 2005 SL No. 308 s 17 sch

PART 14—LEAD**Preparing, amending and reviewing MSDS**

s 119 amd 2005 SL No. 308 s 17 sch

Providing MSDS

s 120 amd 2005 SL No. 308 s 17 sch

Providing NICNAS summary report and other information

s 121 amd 2005 SL No. 308 s 17 sch

Providing MSDS

s 123 amd 2005 SL No. 308 s 17 sch

Labelling containers

s 124 amd 2005 SL No. 308 s 17 sch

Division 4—Relevant persons

div hdg sub 2005 SL No. 308 s 17 sch

Who division applies to

s 125 amd 2005 SL No. 308 s 17 sch

Obtaining MSDS

s 126 amd 2005 SL No. 308 s 17 sch

Keeping registers

s 127 amd 2005 SL No. 308 s 17 sch

Labelling containers

s 128 amd 2005 SL No. 308 s 17 sch

Risk assessment

s 129 amd 2005 SL No. 308 s 17 sch

Risk assessment records

s 130 amd 2005 SL No. 308 s 17 sch

Controlling exposure

s 131 amd 2005 SL No. 308 s 17 sch

Atmospheric monitoring

s 132 amd 2005 SL No. 308 s 17 sch

Health surveillance

s 133 amd 2005 SL No. 308 s 17 sch

Reviewing control measures

s 134 amd 2005 SL No. 308 s 17 sch

Removal of worker from a lead-risk job

s 135 sub 2005 SL No. 308 s 49

Removal of relevant person from a lead-risk job

s 135A ins 2005 SL No. 308 s 49
amd 2007 SL No. 115 s 33

Return to a lead-risk job

s 136 amd 2005 SL No. 308 s 17 sch

Confidentiality of worker's medical record

s 137 amd 2005 SL No. 308 s 17 sch

Induction and training about lead

s 138 amd 2005 SL No. 308 s 17 sch

Keeping records

s 139 amd 2005 SL No. 308 s 17 sch

Health surveillance

s 141 amd 2005 SL No. 308 s 17 sch

Advising of pregnancy or breast feeding

s 142 amd 2005 SL No. 308 s 17 sch

Designing, manufacturing or supplying a confined space

s 143 amd 2002 SL No. 182 s 3; 2003 SL No. 169 s 11; 2005 SL No. 308 s 17 sch

Modifying a confined space

s 144 amd 2002 SL No. 182 s 4; 2003 SL No. 169 s 12; 2005 SL No. 308 s 17 sch

Using a confined space

s 145 amd 2002 SL No. 182 s 5; 2002 SL No. 260 s 235 sch 7; 2003 SL No. 169 s 13; 2005 SL No. 308 s 17 sch

PART 16—ROLL-OVER PROTECTIVE STRUCTURES FOR WHEELED TRACTORS

pt hdg prev pt 16 hdg ins 1999 SL No. 110 s 13
om 2002 SL No. 260 s 235 sch 7
pres pt 16 hdg ins 2003 SL No. 68 s 4

Division 1—Interpretation

div hdg prev div 1 hdg ins 1999 SL No. 110 s 13
om 2002 SL No. 260 s 235 sch 7
pres div 1 hdg ins 2003 SL No. 68 s 4

Definitions for pt 16

s 146 prev s 146 ins 1999 SL No. 110 s 13
om 2002 SL No. 260 s 235 sch 7
pres s 146 ins 2003 SL No. 68 s 4
def “**exempt tractor**” amd 2004 SL No. 142 s 13(2)
def “**historical activity**” ins 2004 SL No. 142 s 13(1)

Meaning of “tractor”

s 147 prev s 147 ins 1999 SL No. 110 s 13
om 2002 SL No. 260 s 235 sch 7
pres s 147 ins 2003 SL No. 68 s 4

Demonstrator tractor is taken to be new

- s 148** prev s 148 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 148 ins 2003 SL No. 68 s 4

Division 2—Ways to prevent or minimise risk from wheeled tractor rolling over

- div hdg** prev div 2 hdg ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres div 2 hdg ins 2003 SL No. 68 s 4

Ways to prevent or minimise risk prescribed

- s 149** prev s 149 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 149 ins 2003 SL No. 68 s 4

Roll-over protective structure to be fitted to wheeled tractor used by relevant person

- prov hdg** amd 2005 SL No. 308 s 17 sch
s 150 prev s 150 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 150 ins 2003 SL No. 68 s 4
 amd 2005 SL No. 308 s 17 sch

Roll-over protective structure to be fitted to wheeled tractor used by worker

- s 151** prev s 151 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 151 ins 2003 SL No. 68 s 4
 amd 2005 SL No. 308 s 17 sch

Roll-over protective structure to be fitted to wheeled tractor used for business or undertaking

- s 152** prev s 152 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 152 ins 2003 SL No. 68 s 4
 om 2005 SL No. 308 s 17 sch

Roll-over protective structure to be fitted to wheeled tractor hired, leased or borrowed

- s 153** prev s 153 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 153 ins 2003 SL No. 68 s 4
 amd 2005 SL No. 308 s 17 sch

Division 3—Obligation of prospective supplier of wheeled tractor not fitted with a roll-over protective structure

- div hdg** prev div 3 hdg ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres div 3 hdg ins 2003 SL No. 68 s 4

Obligation of prospective supplier of wheeled tractor not fitted with a roll-over protective structure

- s 154** prev s 154 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7; 2004 SL No. 142 s 14

pres s 154 ins 2003 SL No. 68 s 4
amd 2004 SL No. 142 s 14

Division 4—Class 2 work

div hdg ins 1999 SL No. 110 s 13 (incl in orig pt 16)
om 2002 SL No. 260 s 235 sch 7

Division 5—Class 3 or 4 work

div hdg ins 1999 SL No. 110 s 13 (incl in orig pt 16)
om 2002 SL No. 260 s 235 sch 7

Division 6—Hire electrical equipment

div hdg ins 1999 SL No. 110 s 13 (incl in orig pt 16)
om 2002 SL No. 260 s 235 sch 7

PART 17—CONSTRUCTION WORK

pt hdg ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Division 1—Interpretation

div hdg ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Definitions for pt 17

s 155 prev s 155 ins 1999 SL No. 110 s 13
om 2002 SL No. 260 s 235 sch 7
pres s 155 ins 2005 SL No. 308 s 50

Meaning of “high risk construction activity”

s 156 prev s 156 ins 1999 SL No. 110 s 13
om 2002 SL No. 260 s 235 sch 7
pres s 156 ins 2005 SL No. 308 s 50

Meaning of “work method statement” for high risk construction activity other than prescribed activity

s 157 prev s 157 ins 1999 SL No. 110 s 13
om 2002 SL No. 260 s 235 sch 7
pres s 157 ins 2005 SL No. 308 s 50
amd 2007 SL No. 115 s 46

Meaning of “work method statement” for high risk construction activity that is prescribed activity

s 158 prev s 158 ins 1999 SL No. 110 s 13
om 2002 SL No. 260 s 235 sch 7
pres s 158 ins 2005 SL No. 308 s 50
amd 2007 SL No. 115 s 34

Division 2—Principal contractors

div hdg ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Subdivision 1—Preliminary

sdiv hdg ins 2005 SL No. 308 s 50

Application of div 2

- s 159** prev s 159 ins 1999 SL No. 110 s 13
 amd 2002 SL No. 39 s 3
 om 2002 SL No. 260 s 235 sch 7
 pres s 159 ins 2005 SL No. 308 s 50

Subdivision 2—Obligation to prepare construction safety plan

sdiv hdg ins 2005 SL No. 308 s 50

Principal contractor must prepare construction safety plan

- s 160** prev s 160 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 160 ins 2005 SL No. 308 s 50

When principal contractor not to allow relevant person to start housing construction work

- s 161** prev s 161 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 161 ins 2005 SL No. 308 s 50

When principal contractor not to allow relevant person to start construction work, other than housing construction work

- s 162** prev s 162 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 162 ins 2005 SL No. 308 s 50

Availability of current construction safety plan

- s 163** prev s 163 ins 1999 SL No. 110 s 13
 amd 2002 SL No. 39 s 4
 om 2002 SL No. 260 s 235 sch 7
 pres s 163 ins 2005 SL No. 308 s 50

Amendment of construction safety plan

- s 164** prev s 164 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 164 ins 2005 SL No. 308 s 50

Subdivision 3—Principal contractor's obligation for work method statements

sdiv hdg ins 2005 SL No. 308 s 50

Principal contractor not to allow relevant person to start high risk construction activity unless work method statement prepared

- s 165** prev s 165 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 165 ins 2005 SL No. 308 s 50

Work method statement or amended work method statement to be kept with construction safety plan

- s 166** prev s 166 ins 1999 SL No. 110 s 13
 om 2002 SL No. 260 s 235 sch 7
 pres s 166 ins 2005 SL No. 308 s 50

Principal contractor not to allow person to perform prescribed activity unless in compliance with work method statement

- s 167** sub 2002 SL No. 109 s 10
 amd 2004 SL No. 142 s 15
 sub 2005 SL No. 308 s 50

Principal contractor to monitor use of work method statement

- s 168** sub 2002 SL No. 109 s 10
 amd 2004 SL No. 289 s 28
 sub 2005 SL No. 308 s 50

Subdivision 4—Principal contractor's obligation to sight induction evidence and conduct site-specific workplace health and safety inductions

sdiv hdg ins 2005 SL No. 308 s 50

Principal contractor to sight general induction evidence before construction work starts

- s 169** prev s 169 ins 1999 SL No. 276 s 5
 exp 1 February 2000 (see s 169(2))
 pres s 169 ins 2002 SL No. 109 s 10
 sub 2005 SL No. 308 s 50

Site-specific induction to be given

- s 170** ins 2002 SL No. 109 s 10
 amd 2002 SL No. 232 s 6
 sub 2005 SL No. 308 s 50

Subdivision 5—Principal contractor's obligation for others

sdiv hdg ins 2005 SL No. 308 s 50
 sub 2007 SL no. 115 s 47

Authority to perform work for prescribed activities, work in an earthmoving or particular crane occupation or high risk work

- s 171** ins 2002 SL No. 109 s 10
 sub 2005 SL No. 308 s 50; 2007 SL No. 115 s 47

Subdivision 6—Principal contractor's obligation to erect signs

sdiv hdg ins 2005 SL No. 308 s 50

Signs

- s 172** ins 2002 SL No. 109 s 10
 sub 2005 SL No. 308 s 50

Subdivision 7—Principal contractor's obligation about safe housekeeping practices

sdiv hdg ins 2005 SL No. 308 s 50

Purpose of sdiv 7

- s 173** ins 2002 SL No. 109 s 10
 sub 2005 SL No. 308 s 50

Safe housekeeping practices

- s 174** ins 2002 SL No. 109 s 10
 sub 2005 SL No. 308 s 50

Subdivision 8—Principal contractor’s obligation for common plant**sdiv hdg** ins 2005 SL No. 308 s 50**Common plant****s 175** ins 2002 SL No. 109 s 10
amd 2002 SL No. 232 s 7
sub 2005 SL No. 308 s 50**Subdivision 9—Principal contractor’s obligation for hazardous substances****sdiv hdg** ins 2005 SL No. 308 s 50**Register of hazardous substances****s 176** ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50**Subdivision 10—Principal contractor’s obligation for underground services****sdiv hdg** ins 2005 SL No. 308 s 50**Information about underground services****s 177** ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50**Subdivision 11—Principal contractor’s obligation for falling objects****sdiv hdg** ins 2005 SL No. 308 s 50**Application of sdiv 11****s 178** ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50**What is “mesh” for sdiv 11****s 179** ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50**Risk assessment and control measures for civil construction work and housing construction work****s 180** ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50**Control measures for construction work that is not civil construction work or housing construction work****s 181** ins 2002 SL No. 109 s 10
amd 2002 SL No. 232 s 8; 2004 SL No. 142 s 16; 2004 SL No. 289 s 29
sub 2005 SL No. 308 s 50**Additional control measures if measured angle is 75° or more, other than for demolition work or work erecting or dismantling formwork****s 182** ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50**Control measures for demolition work or work erecting or dismantling formwork****prov hdg** sub 2004 SL No. 142 s 17(1)
s 183 ins 2002 SL No. 109 s 10
amd 2003 SL No. 102 s 23; 2004 SL No. 142 s 17
sub 2005 SL No. 308 s 50

Perimeter containment screening as control measure

- prov hdg** amd 2002 SL No. 232 s 9
 sub 2004 SL No. 142 s 18(1)
- s 184** ins 2002 SL No. 109 s 10
 amd 2003 SL No. 102 s 24; 2004 SL No. 142 s 18
 sub 2005 SL No. 308 s 50

Catch platform as control measure

- s 185** ins 2002 SL No. 109 s 10
 amd 2002 SL No. 232 s 10; 2004 SL No. 142 s 19
 sub 2005 SL No. 308 s 50

Chief executive may ask general manager of Queensland Building Services Authority for relevant information

- s 185A** ins 2004 SL No. 256 s 3
 om 2005 SL No. 308 s 50

Gantry as control measure

- s 186** ins 2002 SL No. 109 s 10
 sub 2005 SL No. 308 s 50

Load lifted over adjoining area

- s 187** ins 2002 SL No. 109 s 10
 sub 2005 SL No. 308 s 50

Fall arresting platform

- s 187A** ins 2004 SL No. 142 s 20
 om 2005 SL No. 308 s 50

Closure of part or all of adjoining area

- s 188** ins 2002 SL No. 109 s 10
 amd 2002 SL No. 232 s 11; 2004 SL No. 142 s 21
 sub 2005 SL No. 308 s 50

Subdivision 12—Principal contractor's obligation for amenities

- sdiv hdg** ins 2005 SL No. 308 s 50

Amenities

- s 189** ins 2002 SL No. 109 s 10
 amd 2004 SL No. 142 s 22
 sub 2005 SL No. 308 s 50

Division 3—Relevant persons

- div hdg** ins 2002 SL No. 109 s 10
 sub 2005 SL No. 308 s 50

Subdivision 1—Preliminary

- sdiv hdg** ins 2002 SL No. 109 s 10
 sub 2005 SL No. 308 s 50

Application of div 3

- s 190** ins 2002 SL No. 109 s 10
 amd 2003 SL No. 102 s 25
 sub 2005 SL No. 308 s 50

Subdivision 2—Relevant person's obligation for work method statements

sdiv hdg ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Relevant person to prepare work method statement before starting high risk construction activity

s 191 ins 2002 SL No. 109 s 10
amd 2003 SL No. 102 s 26
sub 2005 SL No. 308 s 50

When relevant person not to allow another relevant person to start prescribed activity

s 192 ins 2002 SL No. 109 s 10
amd 2003 SL No. 102 s 27; 2004 SL No. 142 s 23
sub 2005 SL No. 308 s 50

When relevant person who is employer not to allow worker to start high risk construction activity

s 193 ins 2002 SL No. 109 s 10
amd 2003 SL No. 102 s 28; 2004 SL No. 142 s 24
sub 2005 SL No. 308 s 50

High risk construction activity not to be performed unless in compliance with work method statement

s 194 ins 2002 SL No. 109 s 10
amd 2003 SL No. 102 s 29
sub 2005 SL No. 308 s 50

Amendment of work method statement

s 195 ins 2002 SL No. 109 s 10
amd 2002 SL No. 232 s 12; 2003 SL No. 102 s 30
sub 2005 SL No. 308 s 50

Availability and review of work method statement

s 196 ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Subdivision 3—Relevant person's obligation for general induction evidence

sdiv hdg ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Definition for sdiv 3

s 197 ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Relevant person to hold general induction evidence before starting construction work

s 198 ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Relevant person who is employer to ensure worker holds general induction evidence before worker starts construction work

s 199 ins 2002 SL No. 109 s 10
amd 2002 SL No. 232 s 13; 2004 SL No. 142 s 25
sub 2005 SL No. 308 s 50

Meaning of “mesh”

s 199A ins 2004 SL No. 142 s 26
om 2005 SL No. 308 s 50

Subdivision 4—Relevant person’s obligation for safe housekeeping practices

sdiv hdg ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Safe housekeeping practices

s 200 ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Subdivision 5—Relevant person’s obligation for common plant

sdiv hdg ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Common plant

prov hdg amd 2003 SL No. 102 s 32(1)
s 201 ins 2002 SL No. 109 s 10
amd 2003 SL No. 102 s 32(2)–(3)
sub 2005 SL No. 308 s 50

Subdivision 6—Relevant person’s obligation for hazardous substances

sdiv hdg ins 2005 SL No. 308 s 50

Relevant person to give principal contractor details of hazardous substances to be used

s 202 ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Subdivision 7—Relevant person’s obligation for underground services

sdiv hdg ins 2005 SL No. 308 s 50

Risk from contact with underground services—construction work for which there is principal contractor

s 203 ins 2002 SL No. 109 s 10
amd 2003 SL No. 102 s 33
sub 2005 SL No. 308 s 50

Risk from contact with underground services—construction work for which there is no principal contractor

prov hdg amd 2002 SL No. 232 s 14(1)
s 204 ins 2002 SL No. 109 s 10
amd 2002 SL No. 232 s 14(2); 2004 SL No. 142 s 27
sub 2005 SL No. 308 s 50

Subdivision 8—Relevant person’s obligation for excavation work that could reduce the stability of a structure

sdiv hdg ins 2005 SL No. 308 s 50

Obligation before excavation work starts

s 205 ins 2002 SL No. 109 s 10
sub 2002 SL No. 232 s 15
amd 2004 SL No. 142 s 28
sub 2005 SL No. 308 s 50

Perimeter containment screening

s 205A ins 2004 SL No. 142 s 29
om 2005 SL No. 308 s 50

Obligation during excavation work

s 206 ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Subdivision 9—Relevant person’s obligation for risk from excavations

sdiv hdg ins 2005 SL No. 308 s 50

Meaning of “competent person” for sdiv 9

s 207 ins 2002 SL No. 109 s 10
amd 2002 SL No. 232 s 16
sub 2005 SL No. 308 s 50

Risk from all excavations

s 208 ins 2002 SL No. 109 s 10
amd 2002 SL No. 232 s 17; 2003 SL No. 102 s 34; 2004 SL No. 142 s 30
sub 2005 SL No. 308 s 50

Risk from working in trench at least 1m deep

s 209 ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Risk from working in trench more than 1.5m deep

s 210 ins 2002 SL No. 109 s 10
amd 2003 SL No. 102 s 36
sub 2005 SL No. 308 s 50

Access by ladders to trench more than 1.5m deep

s 211 ins 2002 SL No. 109 s 10
amd 2002 SL No. 232 s 18; 2003 SL No. 102 s 37; 2004 SL No. 142 s 31
sub 2005 SL No. 308 s 50

PART 18—CONSTRUCTION WORK WHERE THERE IS A RISK A PERSON COULD FALL

pt hdg ins 2002 SL No. 109 s 10
amd 2003 SL No. 102 s 22
om 2005 SL No. 308 s 50

Division 1—Interpretation

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 18)
om 2005 SL No. 308 s 50

Division 2—Ways for employers and self-employed persons to prevent or minimise risk prescribed

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 18)
om 2005 SL No. 308 s 50

Division 3—Risk of fall in particular circumstances

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 18)
om 2005 SL No. 308 s 50

Division 4—Requirements about particular control measures

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 18)
om 2005 SL No. 308 s 50

Division 5—Ladders

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 18)
om 2005 SL No. 308 s 50

Division 6—Platforms supported by trestle ladders

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 18)
om 2005 SL No. 308 s 50

Division 7—Scaffolding

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 18)
om 2005 SL No. 308 s 50

PART 19—OBJECTS THAT COULD FALL ON OR OTHERWISE HIT MEMBERS OF THE PUBLIC

pt hdg ins 2002 SL No. 109 s 10
om 2005 SL No. 308 s 50

Division 1—Interpretation

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 19)
om 2005 SL No. 308 s 50

Division 2—Building work, other than housing construction work, and demolition work

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 19)
sub 2003 SL No. 102 s 31
om 2005 SL No. 308 s 50

Division 3—Housing construction work and civil construction work

div hdg ins 2002 SL No. 109 s 10 (incl in orig pt 19)
sub 2003 SL No. 102 s 35
om 2005 SL No. 308 s 50

PART 20—GENERAL PROVISIONS FOR PTS 17–19

pt hdg ins 2002 SL No. 109 s 10
om 2005 SL No. 308 s 50

Events in trench more than 1.5m deep that is not shored, benched or battered

s 212 ins 2002 SL No. 109 s 10
sub 2002 SL No. 232 s 19; 2005 SL No. 308 s 50

Subdivision 10—Relevant person's obligation for risk of a person falling

sdiv hdg ins 2005 SL No. 308 s 50

Definition for sdiv 10

s 213 ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Risk of fall less than 3m in housing construction work or less than 2m in other construction work or construction work on roof with slope not over 26°

s 214 ins 2002 SL No. 109 s 10
sub 2005 SL No. 308 s 50

Risk of fall of at least 3m in housing construction work or at least 2m in other construction work or construction work on roof with a slope over 26°

s 215 ins 2002 SL No. 109 s 10
amd 2004 SL No. 142 s 32
sub 2005 SL No. 308 s 50

Edge protection as control measure

s 216 prev s 216 ins 2002 SL No. 201 s 4
 sub 2004 SL No. 290 s 6
 om 2005 SL No. 308 s 51
 pres s 216 ins 2005 SL No. 308 s 50

Fall protection cover as control measure

s 217 prev s 217 ins 2002 SL No. 201 s 4
 sub 2004 SL No. 290 s 6
 om 2005 SL No. 308 s 51
 pres s 217 ins 2005 SL No. 308 s 50

Travel restraint system as control measure

s 217A ins 2005 SL No. 308 s 50

Fall arresting platform as control measure

s 217B ins 2005 SL No. 308 s 50

Fall-arrest harness system as control measure

s 217C ins 2005 SL No. 308 s 50

Industrial safety net as control measure

s 217D ins 2005 SL No. 308 s 50

Subdivision 11—Relevant person's obligation for ladders

sdiv 11 (ss 217E–217G) ins 2005 SL No. 308 s 50

Subdivision 12—Relevant person's obligation for platforms supported by trestle ladders

sdiv 12 (ss 217H–217I) ins 2005 SL No. 308 s 50

Subdivision 13—Relevant person's obligation for scaffolding

sdiv 13 (ss 217J–217L) ins 2005 SL No. 308 s 50

Subdivision 14—Relevant person's obligation for falling objects

sdiv 14 (ss 217M–217N) ins 2005 SL No. 308 s 50

Subdivision 15—Relevant person's obligation for first aid

sdiv 15 (s 217O) ins 2005 SL No. 308 s 50

Division 4—Workers

div 4 (ss 217P–217Q) ins 2005 SL No. 308 s 50

Division 5—General provisions about control measures and plant for pt 17

div 5 (ss 217R–217U) ins 2005 SL No. 308 s 50

Division 6—Chief executive may ask for information from Queensland Building Services Authority

div 6 (ss 217V–217W) ins 2005 SL No. 308 s 50

PART 21—AMENITIES—WORK THAT IS NOT CONSTRUCTION WORK

pt hdg sub 2004 SL No. 290 s 6; 2005 SL No. 308 s 17 sch

Amenities for rural industry work

s 218 ins 2002 SL No. 201 s 4
 sub 2004 SL No. 290 s 6

Amenities for work that is not construction work or rural industry work

s 219 ins 2002 SL No. 201 s 4
sub 2004 SL No. 290 s 6

Maintenance of amenities

s 220 ins 2002 SL No. 201 s 4
sub 2004 SL No. 290 s 6
amd 2005 SL No. 308 s 52

Division 1—Definition for pt 21

div hdg ins 2002 SL No. 201 s 4 (incl in orig pt 21)
sub 2004 SL No. 290 s 6
om 2005 SL No. 308 s 51

Division 2—Principal contractors

div hdg ins 2002 SL No. 201 s 4 (incl in orig pt 21)
sub 2004 SL No. 290 s 6
om 2005 SL No. 308 s 51

Division 3—Employers

div hdg ins 2004 SL No. 290 s 6 (incl in orig pt 21)
om 2005 SL No. 308 s 17 sch

Division 4—Principal contractors and employers—maintenance of particular amenities

div hdg ins 2004 SL No. 290 s 6 (incl in orig pt 21)
om 2005 SL No. 308 s 17 sch

PART 21A—EMPLOYERS—REQUIREMENTS FOR BUILDING PROVIDED FOR WORKER TO OCCUPY WHEN PERFORMING WORK THAT IS NOT CONSTRUCTION WORK OR RURAL INDUSTRY WORK

pt hdg ins 2004 SL No. 290 s 6

Ventilation, lighting, floor area and air space for building

s 221 ins 2002 SL No. 201 s 4
sub 2004 SL No. 290 s 6

PART 21B—EMPLOYERS—ATMOSPHERIC CONTAMINANTS

pt hdg ins 2004 SL No. 290 s 6

Level of atmospheric contaminants

s 222 ins 2002 SL No. 201 s 4
sub 2004 SL No. 290 s 6

PART 21C—FIRST AID

pt hdg ins 2004 SL No. 290 s 6
amd 2005 SL No. 308 s 17 sch

note prec s 223 om 2005 SL No. 308 s 17 sch

Employers—work other than construction work

prov hdg sub 2005 SL No. 308 s 53(1)
s 223 ins 2002 SL No. 201 s 4
sub 2004 SL No. 290 s 6
amd 2005 SL No. 308 s 53

Employers—workers performing rural industry work

s 224 ins 2002 SL No. 201 s 4
sub 2004 SL No. 290 s 6

Self-employed persons performing construction work

s 225 ins 2002 SL No. 201 s 4
sub 2004 SL No. 290 s 6
om 2005 SL No. 308 s 17 sch

PART 21D—WORKPLACE HEALTH AND SAFETY CONTRIBUTIONS

pt hdg ins 2005 SL No. 308 s 54

Purpose of pt 21D

s 226 prev s 226 ins 2002 SL No. 201 s 4
om 2004 SL No. 290 s 6
pres s 226 ins 2005 SL No. 308 s 54

Amount of workplace health and safety contribution

s 227 prev s 227 ins 2002 SL No. 201 s 4
om 2004 SL No. 290 s 6
pres s 227 ins 2005 SL No. 308 s 54

First aid

s 228 ins 2002 SL No. 201 s 4
om 2004 SL No. 290 s 6

PART 22—MISCELLANEOUS

pt hdg (prev pt 17 hdg (orig pt 16 hdg)) renum 1999 SL No. 110 s 14(1); 2002 SL No. 109 s 9(1)

Rural industry exemption

s 229 (prev s 167 (orig s 146)) renum 1999 SL No. 110 s 14(2)
amd 2001 SL No. 100 s 5
renum 2002 SL No. 109 s 9(2)
amd 2002 SL No. 201 s 5; 2003 SL No. 68 s 5; 2005 SL No. 308 s 55

Time for giving workplace health and safety undertaking

s 229A ins 2004 SL No. 289 s 30

Workplace health and safety representative training course

s 229B ins 2007 SL No. 75 s 3

Appeal against decision of Authority

s 230 (prev s 168 (orig s 147)) renum 1999 SL No. 110 s 14(2); 2002 SL No. 109 s 9(2)

PART 23—TRANSITIONAL PROVISIONS

pt hdg ins 2002 SL No. 109 s 11

Division 1—Pc's workplace plan and pc's demolition work plan

div hdg ins 2004 SL No. 290 s 7

Transitional provision for pc's workplace plan and pc's demolition work plan

s 231 ins 2002 SL No. 109 s 11

Division 2—Induction for specified work**div hdg** ins 2004 SL No. 290 s 8**Transitional provision for Workplace Health and Safety induction for specified work****s 232** ins 2002 SL No. 109 s 11**Division 3—Certificates of registration of registrable plant design****div hdg** ins 2004 SL No. 290 s 9**Transitional provision for Workplace Health and Safety Amendment Regulation (No. 1) 2004—applications for certificate of registration of registrable plant design****s 233** ins 2004 SL No. 142 s 33**Transitional provision for Workplace Health and Safety Amendment Regulation (No. 1) 2004—certificates of registration of registrable plant design****s 234** ins 2004 SL No. 142 s 33**Division 4—Certain amenities complying, or leased or acquired, immediately before 1 January 2005****div 4 (ss 235–239)** ins 2004 SL No. 290 s 10**Division 5—Transitional provisions for Workers' Compensation and Rehabilitation and Other Legislation Amendment Regulation (No. 1) 2005****div hdg** ins 2005 SL No. 308 s 56**Certificates to work in prescribed occupation—self-erecting tower cranes****s 240** ins 2005 SL No. 308 s 56
amd 2007 SL No. 12 s 7 (retro)
om 2007 SL No. 115 s 48**Construction work—construction safety plans****s 241** ins 2005 SL No. 308 s 56**Construction work—general induction evidence before 1 January 2006****s 242** ins 2005 SL No. 308 s 56**Construction work—general induction evidence from 1 January 2006****s 243** ins 2005 SL No. 308 s 56
amd 2006 SL No. 312 s 4**Division 6—Transitional provisions for Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2007, part 2, division 2****div 6 (ss 244–249)** ins 2007 SL No. 115 s 35**Division 7—Transitional provision for Workplace Health and Safety Legislation Amendment Regulation (No. 1) 2007****div 7 (s 250)** ins 2007 SL No. 310 s 7**Division 8—Transitional provisions for Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2007, part 2, division 3****div 8 (ss 251–252)** ins 2007 SL No. 115 s 49 (amd 2007 SL No. 310 s 11)**Division 9—Transitional provision for Workplace Health and Safety and Other Legislation Amendment Regulation (No. 1) 2008****div 9 (s 253)** ins 2008 SL No. 189 s 30

SCHEDULE 1—FEES

sch 1 sub 1999 SL No. 110 s 15; 2000 SL No. 313 s 4; 2002 SL No. 313 s 4; 2003 SL No. 235 s 8; 2004 SL No. 289 s 31; 2005 SL No. 308 s 57; 2006 SL No. 312 s 5; 2007 SL No. 310 s 8

Notification of building and construction work

s 1 sub 1999 SL No. 110 s 15; 2000 SL No. 313 s 4
 amd 2001 SL No. 219 s 4(1)
 sub 2002 SL No. 313 s 4; 2003 SL No. 235 s 8; 2004 SL No. 289 s 31; 2005 SL No. 308 s 57; 2006 SL No. 312 s 5; 2007 SL No. 310 s 8

Registration, or renewal of certificate of registration, of registrable plant

s 2 amd 1998 SL No. 318 s 6
 sub 1999 SL No. 110 s 15; 2000 SL No. 313 s 4; 2002 SL No. 313 s 4; 2003 SL No. 235 s 8; 2004 SL No. 289 s 31; 2005 SL No. 308 s 57; 2006 SL No. 312 s 5; 2007 SL No. 310 s 8

Application for certificate of registration of registrable plant design

s 3 sub 1999 SL No. 110 s 15; 2000 SL No. 313 s 4
 amd 2001 SL No. 219 s 4(2)
 sub 2002 SL No. 313 s 4; 2003 SL No. 235 s 8
 amd 2004 SL No. 142 s 34(1)–(2)
 sub 2004 SL No. 289 s 31; 2005 SL No. 308 s 57; 2006 SL No. 312 s 5; 2007 SL No. 310 s 8

Certificates of authority of appointment of a workplace health and safety officer

s 4 sub 1999 SL No. 110 s 15; 2000 SL No. 313 s 4
 amd 2001 SL No. 219 s 4(3)
 sub 2002 SL No. 313 s 4; 2003 SL No. 235 s 8; 2004 SL No. 142 s 34(3);
 2004 SL No. 289 s 31; 2005 SL No. 308 s 57; 2006 SL No. 312 s 5; 2007 SL No. 310 s 8; 2007 SL No. 115 s 50 (amd 2007 SL No. 310 s 12)

Earthmoving or particular crane work certificates

s 4A ins 2007 SL No. 115 s 50 (amd 2007 SL No. 310 s 12)

Licences to perform a class of high risk work

s 4B ins 2007 SL No. 115 s 50 (amd 2007 SL No. 310 s 12)
 amd 2008 SL No. 189 s 31

Conversion to renewable licence to perform a class of high risk work

s 4C ins 2007 SL No. 115 s 50 (amd 2007 SL No. 310 s 12)

Certificates—prescribed activities

s 5 sub 1999 SL No. 110 s 15; 2000 SL No. 313 s 4
 amd 2001 SL No. 219 s 4(4)
 sub 2002 SL No. 313 s 4; 2003 SL No. 235 s 8; 2004 SL No. 289 s 31; 2005 SL No. 308 s 57; 2006 SL No. 312 s 5; 2007 SL No. 310 s 8

Certificates—prescribed activities

s 5A ins 2000 SL No. 288 s 12
 om 2002 SL No. 313 s 4

Certificate of appointment as an accredited provider

- s 6** sub 1999 SL No. 110 s 15 (amd 1999 SL No. 276 s 8); 2000 SL No. 288 s 12;
 2000 SL No. 313 s 4
 amd 2001 SL No. 219 s 4(5)
 sub 2002 SL No. 313 s 4; 2003 SL No. 235 s 8; 2004 SL No. 289 s 31; 2005
 SL No. 308 s 57; 2006 SL No. 312 s 5; 2007 SL No. 310 s 8

Bonded asbestos removal certificate

- s 6A** ins 2007 SL No. 115 s 36
 om 2007 SL No. 310 s 8

Bonded asbestos removal certificate

- s 7** ins 2000 SL No. 288 s 12 (amd 1999 SL No. 276 s 8)
 sub 1999 SL No. 216 s 3; 2000 SL No. 313 s 4
 amd 2001 SL No. 219 s 4(6)
 sub 2002 SL No. 313 s 4; 2003 SL No. 235 s 8; 2004 SL No. 289 s 31; 2005
 SL No. 308 s 57; 2006 SL No. 312 s 5; 2007 SL No. 310 s 8

Report about occupational health and safety performance for Workers' Compensation Act

- prov hdg** prev prov hdg amd 2003 SL No. 119 s 121 sch 7
s 8 prev s 8 ins 2000 SL No. 313 s 4
 amd 2001 SL No. 219 s 4(7)
 sub 2002 SL No. 313 s 4
 amd 2003 SL No. 119 s 121 sch 7
 sub 2003 SL No. 235 s 8
 om 2004 SL No. 289 s 31
 pres s 8 ins 2007 SL No. 310 s 8

SCHEDULE 2—ACCREDITED COURSES

- om 2004 SL No. 289 s 31
 ins 2005 SL No. 308 s 58
 amd 2007 SL No. 12 s 8

SCHEDULE 2A—WORKPLACE HEALTH AND SAFETY REPRESENTATIVES TRAINING COURSE

- ins 2007 SL No. 75 s 4

SCHEDULE 3—REGISTRABLE PLANT

- sch hdg** amd 2007 SL No. 115 s 37
sch 3 amd 2003 SL No. 169 s 14; 2004 SL No. 142 s 35
 sub 2004 SL No. 289 s 31
 amd 2005 SL No. 308 s 59

SCHEDULE 4—REGISTRABLE PLANT DESIGN

- sch hdg** sub 2005 SL No. 308 s 60(1)
sch 4 sub 2004 SL No. 142 s 36
 amd 2004 SL No. 289 s 32; 2005 SL No. 308 s 60(2)

SCHEDULE 5—CLASSES OF HIGH RISK WORK AND UNITS OF COMPETENCY FOR THE CLASSES

sch 5 amd 2000 SL No. 288 s 13; 2000 SL No. 288 s 19; 2002 SL No. 232 s 20;
2004 SL No. 142 s 37; 2005 SL No. 308 s 61
sub 2007 SL No. 115 s 38; 2007 SL No. 115 s 51

Bridge and gantry crane (open)

prov hdg amd 2008 SL No. 189 s 32(1)

s 12 amd 2008 SL No. 189 s 32(1)

Slewing mobile crane with a capacity of 20t or less

s 15 amd 2008 SL No. 189 s 32(2)

Slewing mobile crane with a capacity of 60t or less

s 16 amd 2008 SL No. 189 s 32(3)

Slewing mobile crane with a capacity of 100t or less

s 17 amd 2008 SL No. 189 s 32(4)

Slewing mobile crane with a capacity of more than 100t

s 18 amd 2008 SL No. 189 s 32(5)

Materials and personnel hoist

prov hdg amd 2008 SL No. 189 s 32(6)

s 20 amd 2008 SL No. 189 s 32(6)

SCHEDULE 5A—EARTHMOVING OR PARTICULAR CRANE OCCUPATIONS AND UNITS OF COMPETENCY FOR THE OCCUPATIONS

sch 5A prev sch 5A ins 2000 SL No. 288 s 14
om 2005 SL No. 308 s 17 sch
pres sch 5A ins 2007 SL No. 115 s 51

Bridge and gantry crane (remote control only)

prov hdg amd 2008 SL No. 189 s 33

s 1 amd 2008 SL No. 189 s 33

SCHEDULE 5B—PARTICULAR WORK ENCOMPASSED IN LICENCE CLASSES

ins 2008 SL No. 189 s 34

SCHEDULE 7—PROHIBITED SUBSTANCES, PROHIBITED ACM AND PROHIBITED PURPOSES

sub 2003 SL No. 235 s 9; 2005 SL No. 308 s 62

SCHEDULE 8A—PRINCIPAL CONTRACTORS—PARTICULAR AMENITIES FOR CONSTRUCTION WORK

sch hdg ins 2004 SL No. 290 s 11

sch 8A amd 2005 SL No. 308 s 17 sch

note prec pt 1 om 2005 SL No. 308 s 17 sch

PART 1—DEFINITION FOR SCH 8A

pt hdg ins 2004 SL No. 290 s 11

Definition

- s 1** ins 2004 SL No. 290 s 11
def “**construction person**” sub 2005 SL No. 308 s 17 sch

PART 2—TOILETS

- pt hdg** ins 2004 SL No. 290 s 11

Toilets

- s 2** ins 2004 SL No. 290 s 11
amd 2005 SL No. 308 s 17 sch

When toilet must be connected toilet or portable toilet

- s 3** ins 2004 SL No. 290 s 11

Privacy, ventilation and toilet paper

- s 4** ins 2004 SL No. 290 s 11

PART 3—OTHER AMENITIES

- pt hdg** ins 2004 SL No. 290 s 11

Room, or sheltered area, to eat meals in

- s 5** ins 2004 SL No. 290 s 11
amd 2005 SL No. 308 s 17 sch

Hands and face washing facilities

- s 6** ins 2004 SL No. 290 s 11
amd 2005 SL No. 308 s 17 sch

Drinking water

- s 7** ins 2004 SL No. 290 s 11
amd 2005 SL No. 308 s 17 sch

SCHEDULE 8B—EMPLOYERS—PARTICULAR AMENITIES FOR RURAL INDUSTRY WORK

- sch hdg** ins 2004 SL No. 290 s 11

note prec pt 1 om 2005 SL No. 308 s 17 sch

PART 1—TOILETS FOR WORKERS AND EMPLOYER

- pt hdg** ins 2004 SL No. 290 s 11

Toilets

- s 1** ins 2004 SL No. 290 s 11
amd 2005 SL No. 308 s 17 sch

PART 2—OTHER AMENITIES FOR WORKERS

- pt 2 (ss 2–5)** ins 2004 SL No. 290 s 11

SCHEDULE 8C—EMPLOYERS—PARTICULAR AMENITIES FOR WORK THAT IS NOT CONSTRUCTION WORK OR RURAL INDUSTRY WORK

- sch hdg** ins 2004 SL No. 290 s 11

note prec pt 1 om 2005 SL No. 308 s 17 sch

PART 1—APPLICATION OF SCH 8C

- pt 1 (s 1)** ins 2004 SL No. 290 s 11

PART 2—EXPLANATION OF APPLIED BCA PROVISIONS OR APPLIED QDC PROVISIONS USED FOR PT 3 OR SCH 8D**pt hdg** ins 2004 SL No. 290 s 11**Definitions for pt 2****s 2** ins 2004 SL No. 290 s 11def “**Building Code of Australia**” amd 2006 SL No. 227 s 81(1)def “**Queensland Development Code**” sub 2006 SL No. 227 s 81(2)**Purpose of applied BCA or applied QDC provisions****s 3** ins 2004 SL No. 290 s 11**Changes to the text of BCA or QDC in modified provision****s 4** ins 2004 SL No. 290 s 11**Interpretation of applied BCA or applied QDC provisions****s 5** ins 2004 SL No. 290 s 11**PART 3—IF WORKER IS AT WORKPLACE WHERE EMPLOYER PROVIDES NON-CLASS 10 BUILDING FOR WORKERS TO OCCUPY****pt hdg** ins 2004 SL No. 290 s 11**Division 1—Application of pt 3****div 1 (s 6)** ins 2004 SL No. 290 s 11**Division 2—Toilets, and hands and face washing facilities****div hdg** ins 2004 SL No. 290 s 11**Subdivision 1—If the building is a class 1b building or employer’s domestic premises****sdiv 1 (ss 7–8)** ins 2004 SL No. 290 s 11**Subdivision 2—If the building is a particular class of building and not employer’s domestic premises****sdiv hdg** ins 2004 SL No. 290 s 11**Application of sdiv 2****prov hdg** amd 2007 SL No. 115 s 39(1)**s 9** ins 2004 SL No. 290 s 11**Toilets, and hands and face washing facilities****s 10** ins 2004 SL No. 290 s 11
amd 2005 SL No. 308 s 17 sch**Performance requirements to be complied with****s 11** ins 2004 SL No. 290 s 11
amd 2007 SL No. 115 s 39(2)**How to comply with performance requirements****s 12** ins 2004 SL No. 290 s 11**Location of toilet****s 13** ins 2004 SL No. 290 s 11
amd 2005 SL No. 308 s 17 sch**Toilet paper and disposal of female sanitary items****s 14** ins 2004 SL No. 290 s 11

Hands and face washing facilities to include soap, water and hands drying facilities
s 15 ins 2004 SL No. 290 s 11

Division 3—Dining facilities

div 3 (ss 16–19) ins 2004 SL No. 290 s 11

Division 4—Dressing room facilities

div 4 (ss 20–21) ins 2004 SL No. 290 s 11

Division 5—Drinking Water

div 5 (ss 22–23) ins 2004 SL No. 290 s 11

Division 6—Other amenities

div 6 (ss 24–25) ins 2004 SL No. 290 s 11

PART 4—IF WORKER IS NOT AT WORKPLACE WHERE EMPLOYER PROVIDES NON-CLASS 10 BUILDING FOR WORKERS TO OCCUPY

pt hdg ins 2004 SL No. 290 s 11

Application of pt 4

s 26 ins 2004 SL No. 290 s 11

Toilets

s 27 ins 2004 SL No. 290 s 11
 amd 2005 SL No. 308 s 17 sch

Sheltered area to eat meals in

s 28 ins 2004 SL No. 290 s 11
 amd 2005 SL No. 308 s 17 sch

Drinking water

s 29 ins 2004 SL No. 290 s 11

Hands washing facilities

s 30 ins 2004 SL No. 290 s 11

Showers

s 31 ins 2004 SL No. 290 s 11

SCHEDULE 8D—EMPLOYERS—REQUIREMENTS FOR BUILDING PROVIDED FOR WORKER TO OCCUPY WHEN PERFORMING WORK THAT IS NOT CONSTRUCTION WORK OR RURAL INDUSTRY WORK

sch hdg ins 2004 SL No. 290 s 11

PART 1—APPLICATION OF SCH 8D

pt hdg ins 2004 SL No. 290 s 11

Application of sch 8D

s 1 ins 2004 SL No. 290 s 11
 amd 2005 SL No. 308 s 17 sch

PART 2—VENTILATION

pt hdg ins 2004 SL No. 290 s 11

Ventilation

s 2 ins 2004 SL No. 290 s 11

How to comply with performance requirements

s 3 ins 2004 SL No. 290 s 11
amd 2007 SL No. 115 s 40

PART 3—LIGHTING

pt hdg ins 2004 SL No. 290 s 11

Lighting

s 4 ins 2004 SL No. 290 s 11

PART 4—FLOOR AREA AND AIR SPACE

pt hdg ins 2004 SL No. 290 s 11

Floor area and air space

s 5 ins 2004 SL No. 290 s 11

SCHEDULE 8E—APPLIED BCA PROVISIONS

ins 2004 SL No. 290 s 11
amd 2006 SL No. 246 s 90(2) sch 2; 2007 SL No. 115 s 41

SCHEDULE 8F—APPLIED QDC PROVISIONS

ins 2004 SL No. 290 s 11

SCHEDULE 9—DICTIONARY

def “**accredited course**” ins 2007 SL No. 115 s 42(2)
def “**ACM**” ins 2005 SL No. 308 s 63(3)
def “**advanced scaffolder**” amd 2008 SL No. 189 s 35(3)
def “**agreement**” ins 2004 SL No. 290 s 12
def “**anchorage point**” ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
def “**application for training approval**” ins 2008 SL No. 189 s 35(2)
def “**applied BCA provision**” ins 2004 SL No. 290 s 12
def “**applied QDC provision**” ins 2004 SL No. 290 s 12
def “**appropriately qualified person**” ins 2000 SL No. 249 s 10
om 2005 SL No. 308 s 63(2)
def “**approved criteria**” sub 1999 SL No. 276 s 6
def “**asbestos**” om 2005 SL No. 308 s 63(1)
def “**asbestos fibre**” om 2005 SL No. 308 s 63(2)
def “**asbestos management code**” ins 2005 SL No. 308 s 63(3)
def “**asbestos materials**” om 2005 SL No. 308 s 63(1)
def “**asbestos product**” om 2005 SL No. 308 s 63(2)
def “**asbestos removal area**” om 2005 SL No. 308 s 63(2)
def “**asbestos removal code**” ins 2005 SL No. 308 s 63(3)
def “**asbestos removalist**” sub 2000 SL No. 288 s 20; 2005 SL No. 308 s 63(2)–(3)
def “**asbestos removal site**” om 2005 SL No. 308 s 63(2)
def “**asbestos removal work**” om 2005 SL No. 308 s 63(1)
def “**AS**” or “**AS/NZS**” om 2001 SL No. 100 s 6(1)
def “**AS/NZS**” ins 2001 SL No. 100 s 6(2)
def “**assessment**” ins 2007 SL No. 115 s 42(2)
amd 2008 SL No. 189 s 35(4)
def “**assessment instrument**” ins 2008 SL No. 189 s 35(2)
def “**assessment summary**” ins 2007 SL No. 115 s 42(2)

- def **“Australian Qualifications Framework”** ins 2005 SL No. 70 s 6(2)
- def **“Australian Quality Training Framework”** ins 2002 SL No. 109 s 12(2)
 - om 2005 SL No. 308 s 63(2)
- def **“barricade”** ins 2002 SL No. 109 s 12(2)
 - om 2007 SL No. 115 s 42(1)
- def **“barricade”**, for part 17, ins 2005 SL No. 308 s 63(3)
- def **“basic scaffolder”** amd 2008 SL No. 189 s 35(3)
- def **“BCA”** ins 2004 SL No. 290 s 12
- def **“biological monitoring”** amd 2004 SL No. 142 s 38(3)
- def **“boiler”** ins 2004 SL No. 289 s 33(2)
- def **“boom-type elevating work platform”** ins 2004 SL No. 142 s 38(2)
- def **“bottom mix”** ins 2001 SL No. 166 s 17(1)
- def **“bottom time”** ins 2001 SL No. 166 s 17(1)
- def **“bridge crane”** ins 2004 SL No. 142 s 38(2)
- def **“building”** ins 2004 SL No. 290 s 12
 - amd 2006 SL No. 227 s 82
 - sub 2007 SL No. 115 s 42(1)–(2)
- def **“Building Code of Australia”** ins 2004 SL No. 290 s 12
- def **“building maintenance unit”** sub 2004 SL No. 142 s 37(1)–(2)
- def **“caisson”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“catch platform”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“certificate”** ins 2007 SL No. 115 s 42(2)
- def **“certificate of registration of a mobile crane or tower crane”** ins 2007 SL No. 310 s 9
- def **“civil construction work”** ins 2005 SL No. 308 s 63(3)
- def **“class”** ins 2004 SL No. 290 s 12
- def **“class of high risk work”** ins 2007 SL No. 115 s 52(2)
- def **“cofferdam”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“common plant”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“competency”** ins 2007 SL No. 115 s 42(2)
- def **“competency standard”** om 2007 SL No. 115 s 42(1)
- def **“competent person”** sub 1999 SL No. 110 s 16(2); 2002 SL No. 260 s 235 sch 7
 - amd 2002 SL No. 261 s 7(2)
 - sub 2003 SL No. 102 s 38; 2005 SL No. 70 s 6(1)–(2)
 - amd 2005 SL No. 308 s 63(4)
- def **“competent person”**, for parts 17 and 18, ins 2002 SL No. 109 s 12(2)
 - om 2002 SL No. 260 s 235 sch 7
- def **“confined space”** sub 2002 SL No. 182 s 6
- def **“construction diving work”** ins 2005 SL No. 70 s 6(2)
- def **“construction person”** ins 2004 SL No. 290 s 12
- def **“construction safety plan”** ins 2005 SL No. 308 s 63(3)
- def **“construction-type work”** ins 2002 SL No. 109 s 12(2)
 - om 2003 SL No. 102 s 38(1)

- def **“construction wiring”** ins 1999 SL No. 110 s 16(1)
om 2002 SL No. 260 s 235 sch 7
- def **“construction work”** ins 2002 SL No. 109 s 12(2)
om 2003 SL No. 102 s 38(1)
- def **“construction workplace”** om 2005 SL No. 308 s 63(1)
- def **“construction workplace plan”** ins 2002 SL No. 109 s 12(2)
om 2005 SL No. 308 s 63(2)
- def **“containment barrier”** om 2005 SL No. 308 s 63(2)
- def **“containment device”** om 2005 SL No. 308 s 63(1)
- def **“control measure”** ins 2005 SL No. 308 s 63(3)
- def **“control measures”** om 2002 SL No. 109 s 12(1)
- def **“cord extension set”** ins 1999 SL No. 110 s 16(1)
om 2002 SL No. 260 s 235 sch 7
- def **“corresponding authority”** ins 2007 SL No. 115 s 52(2)
- def **“corresponding law”** ins 2004 SL No. 142 s 38(2)
- def **“crane”** sub 2004 SL No. 142 s 38(1)–(2)
- def **“current”** om 2005 SL No. 70 s 6(1)
- def **“C-weighted”** ins 2005 SL No. 308 s 63(3)
- def **“dangerous goods”** ins 2004 SL No. 142 s 38(2)
- def **“dB(C)”** ins 2002 SL No. 7 s 5(2)
- def **“dB(lin)”** om 2002 SL No. 7 s 5(1)
- def **“decompression diving”** ins 2001 SL No. 166 s 17(1)
- def **“directly supervise”** ins 2007 SL No. 115 s 52(2)
sub 2008 SL No. 189 s 35(1)–(2)
- def **“designated doctor”** amd 2002 SL No. 31 s 16 sch 4; 2002 SL No. 80 s 10 sch 3
- def **“designated hazardous substance”** sub 1999 SL No. 276 s 6
- def **“design verification statement”** ins 2004 SL No. 142 s 38(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“design verifier”** ins 2007 SL No. 115 s 42(2)
- def **“dismantle”** ins 2000 SL No. 249 s 10
om 2005 SL No. 308 s 63(2)
- def **“dive supervisor”** ins 2005 SL No. 70 s 6(2)
- def **“dive time”** ins 2001 SL No. 166 s 17(1)
- def **“EANx”** ins 2001 SL No. 166 s 17(1)
- def **“earthmoving or particular crane occupation”** ins 2007 SL No. 115 s 52(2)
- def **“earthmoving or particular crane work certificate”** ins 2007 SL No. 115 s 52(2)
- def **“edge protection”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“electrical equipment”** ins 1999 SL No. 110 s 16(1)
om 2002 SL No. 260 s 235 sch 7
- def **“electrical work”** ins 1999 SL No. 110 s 16(1)
om 2002 SL No. 260 s 235 sch 7
- def **“electrical worker”** ins 1999 SL No. 110 s 16(1)
om 2002 SL No. 260 s 235 sch 7
- def **“electricity entity”** ins 1999 SL No. 110 s 16(1)
om 2002 SL No. 260 s 235 sch 7

- def **“engineer”** ins 2002 SL No. 109 s 12(2)
amd 2004 SL No. 142 s 38(4)
- def **“engineering principles”** ins 2004 SL No. 142 s 38(2)
sub 2005 SL No. 308 s 63(2)–(3)
amd 2007 SL No. 115 s 42(3)
- def **“essential plant”** ins 2000 SL No. 249 s 10
om 2005 SL No. 308 s 63(2)
- def **“excavation”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“excavation work”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“excessive noise”** amd 2007 SL No. 115 s 42(4)
- def **“exempt tractor”** ins 2003 SL No. 68 s 6
- def **“exposed”** amd 2005 SL No. 308 s 17 sch
- def **“fall-arrest harness system”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“fall arresting platform”** ins 2005 SL No. 308 s 63(3)
- def **“fall protection cover”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“fired heater”** ins 2004 SL No. 289 s 33(2)
- def **“formal training”** ins 2008 SL No. 189 s 35(2)
- def **“formerly complying amenity”** ins 2004 SL No. 290 s 12
- def **“formerly complying dressing room”** ins 2004 SL No. 290 s 12
- def **“formerly complying lunch room”** ins 2004 SL No. 290 s 12
- def **“formerly complying toilet”** ins 2004 SL No. 290 s 12
- def **“free fall”** ins 2002 SL No. 109 s 12(2)
om 2005 SL No. 308 s 63(2)
- def **“gantry”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“gantry crane”** ins 2004 SL No. 142 s 38(2)
- def **“general induction card”** ins 2002 SL No. 109 s 12(2)
sub 2002 SL No. 232 s 21(1)
amd 2004 SL No. 142 s 38(5)
- def **“general induction evidence”** ins 2002 SL No. 109 s 12(2)
amd 2002 SL No. 232 s 21(2); 2004 SL No. 142 s 38(5); 2005 SL No. 308 s 17 sch
- def **“general induction training course”** ins 2002 SL No. 109 s 12(2)
amd 2004 SL No. 142 s 38(6)
- def **“geo-technical engineer”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“hazardous service”** om 2005 SL No. 308 s 63(2)
- def **“hazardous substance”** sub 2005 SL No. 308 s 63(2)–(3)
- def **“high risk construction activity”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“high risk work”** ins 2007 SL No. 115 s 52(2)
- def **“historical activity”** ins 2004 SL No. 142 s 38(2)
- def **“hoarding”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
- def **“housing construction work”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)

- def **“informal learning”** ins 2008 SL No. 189 s 35(2)
- def **“intermediate scaffold”** ins 2008 SL No. 189 s 35(3)
- def **“ladder”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“lead process”** amd 2007 SL No. 115 s 42(5)
- def **“licence”** ins 2007 SL No. 115 s 52(2)
- def **“licence class”** ins 2007 SL No. 115 s 52(2)
- def **“licence to perform a class of high risk work”** ins 2007 SL No. 115 s 52(2)
- def **“light work”** ins 2002 SL No. 109 s 12(2)
 - amd 2002 SL No. 232 s 21(3)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“limited free fall”** ins 2002 SL No. 109 s 12(2)
 - om 2005 SL No. 308 s 63(2)
- def **“low voltage supply”** ins 1999 SL No. 110 s 16(1)
 - om 2002 SL No. 260 s 235 sch 7
- def **“mast climbing work platform”** ins 2004 SL No. 142 s 38(2)
- def **“master”** ins 2001 SL No. 166 s 17(1)
- def **“maximum operating depth”** ins 2001 SL No. 166 s 17(1)
- def **“mesh”** ins 2004 SL No. 142 s 38(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“minimum operating depth”** ins 2001 SL No. 166 s 17(1)
- def **“mixed gas”** ins 2001 SL No. 166 s 17(1)
- def **“mobile crane”** ins 2004 SL No. 289 s 33(2)
- def **“national standard”** sub 2003 SL No. 102 s 38
 - om 2007 SL No. 115 s 42(1)
- def **“NICNAS summary report”** amd 2001 SL No. 166 s 17(2)
- def **“notice of refusal”** ins 2007 SL No. 115 s 42(2)
 - sub 2007 SL No. 115 s 52(1)–(2)
- def **“object”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“overhead platform”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“owner”** ins 2000 SL No. 249 s 10
 - om 2005 SL No. 308 s 63(1)
- def **“people mover”** amd 2004 SL No. 289 s 33(3)
- def **“perimeter containment screening”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“permitted work”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“personnel hoist”** ins 2004 SL No. 142 s 38(2)
 - amd 2005 SL No. 308 s 17 sch
- def **“platform”** ins 2002 SL No. 109 s 12(2)
 - om 2005 SL No. 308 s 63(1)
- def **“plug”** ins 1999 SL No. 110 s 16(1)
 - sub 2002 SL No. 39 s 5(1)
 - om 2002 SL No. 260 s 235 sch 7
- def **“portable generator”** ins 1999 SL No. 110 s 16(1)
 - om 2002 SL No. 260 s 235 sch 7

- def **“portable outlet device”** ins 1999 SL No. 110 s 16(1)
 - sub 2002 SL No. 39 s 5(1)
 - om 2002 SL No. 260 s 235 sch 7
- def **“powered operation”** ins 2008 SL No. 189 s 35(2)
- def **“prefabricated scaffolding”** ins 2004 SL No. 142 s 38(2)
- def **“prescribed activity”** ins 2000 SL No. 288 s 15(2)
 - om 2005 SL No. 308 s 63(1)
- def **“prescribed information”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“prescribed occupation”** sub 2000 SL No. 288 s 15
 - om 2007 SL No. 115 s 52(1)
- def **“pressure piping”** ins 2004 SL No. 289 s 33(2)
- def **“pressure vessel”** ins 2004 SL No. 289 s 33(2)
- def **“process”** ins 2002 SL No. 261 s 7(1)
 - sub 2005 SL No. 70 s 6(1)–(2)
- def **“proposed action”** ins 2007 SL No. 115 s 52(2)
- def **“QDC”** ins 2004 SL No. 290 s 12
- def **“Queensland Development Code”** ins 2004 SL No. 290 s 12
- def **“reasonably available”** ins 2004 SL No. 290 s 12
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“rebreather”** ins 2001 SL No. 166 s 17(1)
- def **“recognised official”** sub 2007 SL No. 115 s 52(1)–(2)
- def **“recreational diving”** ins 1999 SL No. 233 s 5
 - amd 2001 SL No. 166 s 17(3)
- def **“recreational snorkelling”** ins 1999 SL No. 233 s 5
- def **“recreational technical diving”** ins 2001 SL No. 166 s 17(1)
- def **“refillable gas cylinder”** ins 2004 SL No. 142 s 38(2)
- def **“registered training organisation”** ins 2005 SL No. 70 s 6(2)
- def **“registrable plant design”** sub 2004 SL No. 142 s 38(1)–(2)
 - amd 2004 SL No. 289 s 33(4)
 - sub 2005 SL No. 308 ss 63(1), 17 sch
- def **“registrable workplace”** om 2004 SL No. 289 s 33(1)
- def **“relevant authority”** ins 1999 SL No. 110 s 16(1)
- def **“relevant person”** ins 2005 SL No. 308 s 63(3)
- def **“repetitive dive group”** ins 2001 SL No. 166 s 17(1)
- def **“residual nitrogen”** ins 2001 SL No. 166 s 17(1)
- def **“resort diving”** ins 1999 SL No. 233 s 5
 - amd 2001 SL No. 166 s 17(4)
- def **“retraining”** ins 2007 SL No. 115 s 52(2)
- def **“roll-over protective structure”** ins 2003 SL No. 68 s 6
- def **“rural industry”** amd 2007 SL No. 115 s 42(6)–(7)
- def **“scaffolding”** sub 2002 SL No. 232 s 21(4)
- def **“scope of registration”** ins 2005 SL No. 70 s 6(2)
- def **“self-erecting tower crane”** ins 2005 SL No. 308 s 63(3)
- def **“show cause notice”** ins 2007 SL No. 115 s 52(2)
- def **“site-specific induction”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“socket outlet”** ins 1999 SL No. 110 s 16(1)
 - sub 2002 SL No. 39 s 5(1)
 - om 2002 SL No. 260 s 235 sch 7

- def **“specified amusement device”** ins 2004 SL No. 142 s 38(2)
- def **“specified electrical equipment”** ins 1999 SL No. 110 s 16(1)
 - amd 2002 SL No. 39 s 5(2)
 - om 2002 SL No. 260 s 235 sch 7
- def **“specified work”** om 2002 SL No. 109 s 12(1)
- def **“spray painting”** ins 1999 SL No. 110 s 16(1)
 - amd 2007 SL No. 115 s 42(8)
- def **“spray painting booth”** ins 1999 SL No. 110 s 16(1)
- def **“stand-by diver”** ins 2005 SL No. 70 s 6(2)
- def **“statement of attainment”** ins 2005 SL No. 70 s 6(2)
- def **“static line”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“surface”** ins 2002 SL No. 109 s 12(2)
 - om 2005 SL No. 308 s 63(1)
- def **“technical standard”** ins 2004 SL No. 142 s 38(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
 - amd 2007 SL No. 115 s 42(9)
- def **“time in”** ins 2001 SL No. 166 s 17(1)
- def **“time out”** ins 2001 SL No. 166 s 17(1)
- def **“toe board”** ins 2002 SL No. 109 s 12(2)
 - om 2005 SL No. 308 s 63(2)
- def **“tower crane”** ins 2004 SL No. 142 s 38(2)
- def **“tractor”** ins 2003 SL No. 68 s 6
- def **“trainee”** sub 2007 SL No. 115 s 52(1)–(2); 2008 SL No. 189 s 35(1)–(2)
- def **“training approval”** ins 2008 SL No. 189 s 35(2)
- def **“travel restraint system”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“trench”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“truck-mounted concrete placing unit with boom”** ins 2004 SL No. 289 s 33(2)
- def **“type 1 portable residual current device”** ins 1999 SL No. 110 s 16(1)
 - om 2002 SL No. 260 s 235 sch 7
- def **“type 1 residual current device”** ins 1999 SL No. 110 s 16(1)
 - om 2002 SL No. 260 s 235 sch 7
- def **“type 2 portable residual current device”** ins 1999 SL No. 110 s 16(1)
 - om 2002 SL No. 260 s 235 sch 7
- def **“type 2 residual current device”** ins 1999 SL No. 110 s 16(1)
 - om 2002 SL No. 260 s 235 sch 7
- def **“underground service”** ins 2002 SL No. 109 s 12(2)
 - sub 2005 SL No. 308 s 63(2)–(3)
- def **“underwater diving work”** ins 2005 SL No. 70 s 6(2)
- def **“unit of competency”** ins 2007 SL No. 115 s 42(2)
 - sub 2007 SL No. 115 s 52(1)–(2); 2008 SL No. 189 s 35(1)–(2)
- def **“unweighted”** om 2002 SL No. 7 s 5(1)
- def **“variation of a licence”** ins 2007 SL No. 115 s 52(2)
- def **“vehicle hoist”** ins 2004 SL No. 142 s 38(2)
- def **“vertical containment sheeting”** ins 2002 SL No. 109 s 12(2)
 - om 2004 SL No. 142 s 38(1)
- def **“welder certificate no. 1”** om 2000 SL No. 288 s 15(1)

def **“welder certificate no. 1E”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 2”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 3”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 3E”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 4”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 5”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 6”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 7”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 8F”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 8G”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 9”** om 2000 SL No. 288 s 15(1)
def **“welder certificate no. 10”** om 2000 SL No. 288 s 15(1)
def **“work activity performer”** ins 2005 SL No. 70 s 6(2)
def **“work box”** ins 2004 SL No. 142 s 38(2)
def **“Workers’ Compensation Act”** ins 2005 SL No. 308 s 63(3)
def **“work method statement”** ins 2002 SL No. 109 s 12(2)
sub 2005 SL No. 308 s 63(2)–(3)
def **“workplace health and safety plan”** om 2002 SL No. 109 s 12(1)
def **“work requiring a decompression stop”** amd 2003 SL No. 169 s 15

8 Information about retrospectivity

Retrospective amendments that have been consolidated are noted in the list of legislation and list of annotations. Any retrospective amendment that has not been consolidated is noted in footnotes to the text.